SENTINEL HOLDING
INSTITUT

SHI PRODUCT PASSPORT

Find products. Certify buildings.

SHI Product Passport No.:

1776-10-1050

ALUJET Jetfoam

Product group: Underlay

ALUJET GmbH
Ahornstraße 16
82291 Mammendorf

Product qualities:

- **SHI** Product Assessment 2024
- **QNG** Qualitätssiegel Nachhaltiges Gebäude
- **DGNB** NEW CONSTRUCTION 2023.2
- **DGNB** NEW CONSTRUCTION 2023
- **DGNB** NEW CONSTRUCTION 2018
- **BNB-BN** NEUBAU V2015
- **EU** TAXONOMY
- **BREEAM** DE NEUBAU 2018
- **LEED** v4.1 (outside US)

CERTIFIED SUSTAINABLE PRODUCT
SHI PRODUCT PASSPORT
SENTINEL HOLDING INSTITUT
www.sentinel-holding.eu

Köttner

Helmut Köttner
Scientific Director
Freiburg, 26 August 2026

Product:
ALUJET Jetfoam

SHI Product Passport no.:
1776-10-1050

Contents

SHI Product Assessment 2024	1
QNG - Qualitätssiegel Nachhaltiges Gebäude	2
DGNB New Construction 2023.2	3
DGNB New Construction 2023	4
DGNB New Construction 2018	5
BNB-BN Neubau V2015	6
EU taxonomy	7
BREEAM DE Neubau 2018	8
LEED v4.1	9
Product labels	10
Legal notices	11
Technical data sheet/attachments	12

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar

SENTINEL HOLDING
INSTITUT

Product:
ALUJET Jetfoam

SHI Product Passport no.:
1776-10-1050

SHI Product Assessment 2024

Since 2008, Sentinel Holding Institut GmbH (SHI) has been establishing a unique standard for products that support healthy indoor air. Experts carry out independent product assessments based on clear and transparent criteria. In addition, the independent testing company SGS regularly audits the processes and data accuracy.

Criteria	Product category	Harmful substance limit	Assessment
SHI Product Assessment	Other products	TVOC ≤ 300 µg/m^3 Formaldehyd ≤ 24 µg/m^3	Indoor Air Quality Certified
Valid untill: 20 December 2029			

SENTINEL HOLDING
INSTITUT

Product:
ALUJET Jetfoam

SHI Product Passport no.:
1776-10-1050

QNG - Qualitätssiegel Nachhaltiges Gebäude

The Qualitätssiegel Nachhaltiges Gebäude (Quality Seal for Sustainable Buildings), developed by the German Federal Ministry for Housing, Urban Development and Building (BMWSB), defines requirements for the ecological, socio-cultural, and economic quality of buildings. The Sentinel Holding Institut evaluates construction products in accordance with QNG requirements for certification and awards the QNG ready label. Compliance with the QNG standard is a prerequisite for eligibility for the KfW funding programme. For certain product groups, the QNG currently has no specific requirements defined. Although classified as not assessment-relevant, these products remain suitable for QNG-certified projects.

Criteria	Pos. / product group	Considered substances	QNG assessment
3.1.3 Schadstoffvermeidung in Baumaterialien	2.4 Underlays for floor coverings	VOC/ emissions / hazardous substances / polycyclic aromatic hydrocarbons (PAH) / nitrosamines	QNG ready
Verification: EMICODE EC1+ Zertifikat vom 20.12.2024 (Nr. 19996/13.02.23).			

Product:
ALUJET Jetfoam

SHI Product Passport no.:
1776-10-1050

DGNB New Construction 2023.2

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact			Not relevant for assessment

SENTINEL HOLDING
INSTITUT

Product:
ALUJET Jetfoam

SHI Product Passport no.:
1776-10-1050

DGNB New Construction 2023

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings. The 2023 version sets high standards for ecological, economic, socio-cultural, and functional aspects throughout the entire life cycle of a building.

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 03.05.2024 (3rd edition)			Not relevant for assessment

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 29.05.2025 (4th edition)	not applicable		Not relevant for assessment

SENTINEL HOLDING
INSTITUT

Product:
ALUJET Jetfoam

SHI Product Passport no.:
1776-10-1050

DGNB New Construction 2018

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings.

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact			Not relevant for assessment

SENTINEL HOLDING
INSTITUT

Product:
ALUJET Jetfoam

SHI Product Passport no.:
1776-10-1050

BNB-BN Neubau V2015

The Bewertungssystem Nachhaltiges Bauen (Assessment System for Sustainable Building) is a tool for evaluating public office and administrative buildings, educational facilities, laboratory buildings, and outdoor areas in Germany. The BNB was developed by the former Federal Ministry for the Environment, Nature Conservation, Building and Nuclear Safety (BMUB) and is now overseen by the Federal Ministry for Housing, Urban Development and Building (BMWSB).

Criteria	Pos. / product type	Considered substance group	Quality level
1.1.6 Risiken für die lokale Umwelt	32b Rubber-like insulation products based on rubber and PP/PE/EPDM for interior use	Individual hazardous substances	Quality level 5
Verification: Herstellererklärung vom 11.02.2025			

SENTINEL HOLDING
INSTITUT

Product:
ALUJET Jetfoam

SHI Product Passport no.:
1776-10-1050

EU taxonomy

The EU Taxonomy classifies economic activities and products according to their environmental impact. At the product level, the EU regulation defines clear requirements for harmful substances, formaldehyde and volatile organic compounds (VOCs). The Sentinel Holding Institut GmbH labels qualified products that meet this standard.

Criteria	Product type	Considered substances	Assessment
DNSH - Pollution prevention and control	Sonstige	Stoffe nach Anlage C	compliant

Verification: EMICODE EC1+ Zertifikat vom 20.12.2024 (Nr. 19996/13.02.23).

SENTINEL HOLDING
INSTITUT

Product:
ALUJET Jetfoam

SHI Product Passport no.:
1776-10-1050

BREEAM DE Neubau 2018

BREEAM (Building Research Establishment Environmental Assessment Methodology) is a UK-based building assessment system that evaluates the sustainability of new constructions, refurbishments, and conversions. Developed by the Building Research Establishment (BRE), the system aims to assess and improve the environmental, economic, and social performance of buildings.

Criteria	Product category	Considered substances	Quality level
Hea 02 Indoor Air Quality	Ceiling, wall, and acoustic and thermal insulation materials	Emissions: Formaldehyde, TVOC, TSVOC, carcinogens	Exemplary quality
Verification: EMICODE EC1+ Zertifikat vom 20.12.2024 (Nr. 19996/13.02.23).			

SENTINEL HOLDING
INSTITUT

Product:
ALUJET Jetfoam

SHI Product Passport no.:
1776-10-1050

LEED v4.1

LEED (Leadership in Energy and Environmental Design) is an internationally recognised building certification system developed by the U.S. Green Building Council. It is one of the most widely used sustainability standards for buildings worldwide and is particularly applied in internationally oriented projects. LEED assesses buildings holistically across categories such as energy efficiency, resource conservation, material selection, indoor environmental quality and site sustainability. Depending on the number of points achieved, projects are awarded one of the certification levels: LEED Certified, Silver, Gold or Platinum.

Criteria	Product category	Considered substances	Assessment
EQ Credit: Low-Emitting Materials	Dämmstoffe	Emissionen: Formaldehyd, VOC, Krebserregende Stoffe	compliant
Verification: EMICODE EC1+ Zertifikat vom 20.12.2024 (Nr. 19996/13.02.23).			

SENTINEL HOLDING
INSTITUT

Product:
ALUJET Jetfoam

SHI Product Passport no.:
1776-10-1050

Product labels

In the construction industry, high-quality materials are crucial for a building's indoor air quality and sustainability. Product labels and certificates offer guidance to meet these requirements. However, the evaluation criteria of these labels vary, and it is important to carefully assess them to ensure products align with the specific needs of a construction project.

Products bearing the Sentinel Holding Institute QNG-ready seal are suitable for projects aiming to achieve the "Qualitätssiegel Nachhaltiges Gebäude" (Quality Seal for Sustainable Buildings). QNG-ready products meet the requirements of QNG Appendix Document 3.1.3, "Avoidance of Harmful Substances in Building Materials." The KfW loan program Climate-Friendly New Construction with QNG may allow for additional funding.

This product is SHI Indoor Air Quality certified and recommended by Sentinel Holding Institut. Indoor-air-focused construction, renovation, and operation of buildings is made possible by transparent and verifiable criteria thanks to the Sentinel Holding concept.

The EMICODE® label, awarded by the German manufacturers' association "GEV – Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e. V.", is primarily relevant for flooring installation materials. The EMICODE® EC1^{PLUS} label, as the premium class, sets significantly stricter emission limits than the other label variants.

Product:
ALUJET Jetfoam

SHI Product Passport no.:
1776-10-1050

Legal notices

(*) These criteria apply to the construction project as a whole. While individual products can positively contribute to the overall building score through proper planning, the evaluation is always conducted at the building level. The information was provided entirely by the manufacturer.

Find our criteria here: https://www.sentinel-holding.eu/de/Themenwelten/Pr%C3%BCfkriterien%20f%C3%BCr%20Produkte

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar

Publisher

Sentinel Holding Institut GmbH
Bötzinger Str. 38
79111 Freiburg im Breisgau
Germany
Tel.: +49 761 590 481-70
info@sentinel-holding.eu
www.sentinel-holding.eu

ALUJET Jetfoam

Produkt-beschreibung

Der ALUJET Jetfoam wird in den Stärken von 2-10 mm produziert und wird eingesetzt als Unterlage unter Laminat und Parkett zur Reduzierung des Trittschalls. Hierfür werden die Stärken 2 und 3 mm verwendet. Die 5 mm starke Bahn dient zum Einsatz unter Estrich um den Trittschall zu vermindern. In Verbindung mit den Randstreifen ALUJET Jetfoam RS / RSL bieten wir ein Komplettdämmsystem im Bereich Estrich.




Abb. 1: ALUJET Jetfoam

Vorteile

Recyclebar; geringes Gewicht; hoher Wärmeschutz; hohe Trittschalldämpfung; bis 1.500 mm Breite möglich; Weitere Abmessungen auf Anfrage.

Technische Daten

Prüfung	Norm	Einheit	Wert
Wärmeleitfähigkeit		W/(m·K)	0,045
Brandschutzklasse	DIN 4102		B2

Spezifikation

Stärke:	2 mm	5 mm	5 mm
Abmessung	1.000 mm x 25 m	1.500 mm x 75 m	1.000 mm x 12,5 m
Sackinhalt:	4 Rollen	1 Rolle	4 Rollen

Weitere Abmessungen bitten wir Sie anzufragen

Lagerung

Ohne Einwirkung von UV-Strahlung.

Verarbeitung

Den Untergrund reinigen und von Unebenheiten, spitzen und scharfkantigen Teilen befreien. Die Matte entlang der Wand ausrollen. Stirnseitig wird der ALUJET Jetfoam bündig zur angrenzenden Wand abgeschnitten (Um Schallbrücken zu vermeiden wird im Wandbereich mit dem ALUJET Jetfoam RS bzw. RSL gearbeitet). Die nächsten Bahnen werden im Bereich der Längsverbindung und Querverbindung an die vorherige Bahn herangeführt, dass eine Stoß-an-Stoß-Verbindung des Schaumes gegeben ist. Der ALUJET Jetfoam ist mit einer Abdeckung nach DIN 18560 Teil 2 abzudecken.

Hinweise

Unsere Gebrauchsanweisungen, Verarbeitungsrichtlinien, Produkt- oder Leistungsangaben und sonstigen technischen Aussagen sind nur allgemeine Richtlinien; sie beschreiben nur die Beschaffenheit unserer Produkte (Werteangaben / -ermittlung zum Produktionszeitpunkt) und Leistungen und stellen keine Garantie im Sinne des §443 BGB dar. Wegen der Vielfalt der Verwendungszwecke des einzelnen Produkts und der jeweiligen besonderen Gegebenheiten (z.B. Verarbeitungsparameter, Materialeigenschaften etc.)obliegt dem Anwender die eigene Erprobung; unsere kostenlose anwendungstechnische Beratung in Wort, Schrift und Versuch ist unverbindlicher Art..

ALUJET GmbH, Ahornstraße 16, D-82291 Mammendorf

Sentinel Holding Institut GmbH
Frau Jadwiga Seidenberger
Bötzingerstr. 38
79100 Freiburg i. Br.

Zentrale Mammendorf
Oliver Krieger
Marketingleiter
Telefon: +49 8145 921 205
oliver.krieger@alujet.de

Mammendorf, den 11.02.25

Bestätigung / Herstellererklärung

Sehr geehrter Herr Muhlke,

hiermit bestätigen wir, dass die Produkte

ALUJET Jetfoam
ALUJET Jetfoam RS
ALUJET Jetfoam RSL

- Keine besonders besorgniserregende Stoffe (SVHC's) in einer Konzentration > 0,1%
- Frei von halogenierten Treibmitteln (FCKW & HFCKW)
- Frei von fluorierten Treibhausgase (F-Gase)
- Frei von Altreifengranulat
- Keine Chlorparrafine und PBDE in einer Konzentration > 0,1%
- Frei von Blei- und Zinnorganische Verbindungen
- Frei von Polybromierte Biphenyle

Enthalten. Wir hoffen Ihnen mit dieser Information geholfen zu haben, stehen für weitere Fragen jedoch gerne zur Verfügung.

Mit freundlichen Grüßen

ALUJET GmbH

ppa.

Oliver Krieger

Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e.V.

GEV EMICODE®

Lizenzerteilung zur Führung des EMICODE

Lizenzierungs-Nummer:	19996/13.02.23
Für den Artikel	ALUJET Jetfoam
der Firma	ALUJET GmbH
wird auf Antrag vom	20.12.2024

unter Bezugnahme auf die Einstufung gemäß den nach § 10 der GEV-Zeichensatzung festgelegten Richtlinien

namens der Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e.V. für den oben genannten Artikel nach § 5 Abs. 4 der GEV-Zeichensatzung die Lizenz zur Führung des GEV-Zeichens

GEV-EMICODE® EC 1 PLUS sehr emissionsarm

erteilt. Damit erfüllt dieser Artikel die rückseitig aufgeführten Kriterien.
Die Firma ist ordentliches Mitglied der GEV.

OM240 20.12.2024
gültig bis 20.12.2029

Der Geschäftsführer
Gemeinschaft Emissionskontrollierte Verlegewerkstoffe,
Klebstoffe und Bauprodukte e.V.
Völklinger Straße 4 · D-40219 Düsseldorf

Hinweise zu den Voraussetzungen über die Vergabe der Lizenz für den EMICODE

Das gemäß vorseitiger Lizenz eingestufte Produkt hat nach der Satzung und den Richtlinien des Technischen Beirats der GEV u.a. den folgenden Kriterien zu genügen:

- Das Produkt entspricht allen gesetzlichen Bestimmungen, insbesondere denen des Chemikalienrechtes und seiner Verordnungen.
- Das Produkt ist nach der Definition der TRGS 610 lösemittelfrei, sofern es sich nicht um ein Oberflächenprodukt handelt. Soweit es einer Produktgruppe nach GISCODE zuzuordnen ist, wird diese angegeben.
- Für das Produkt wird ein Sicherheitsdatenblatt nach lokalem Recht in der jeweils aktuellen Fassung erstellt.
- Krebserregende, erbgutverändernde oder fruchtschädigende Stoffe der Klassen 1A und 1B werden dem Produkt bei der Herstellung nicht zugesetzt.
- Die Prüfung des Produktes erfolgt nach der definierten „GEV-Prüfmethode“. Die VOC-Bestimmung wird dabei in einer Prüfkammer nach dem Tenax-Thermodesorptions-Verfahren mit nachgeschalteter GC/MS-Analyse durchgeführt.
- Die Einstufung in EMICODE-Klassen erfolgt entsprechend den nachstehenden Bezeichnungen und TVOC/TSVOC-Konzentrationsbereichen. Zur Produktkennzeichnung ist die zutreffende EMICODE-Klasse zu verwenden:

1) Verlegewerkstoffe, Klebstoffe und Bauprodukte

Parameter	EC 1 PLUS	EC 1	EC 2
	max. zulässige Konzentration [µg/m³]		
TVOC nach 3 Tagen	≤ 750	≤ 1000	≤ 3000
TVOC nach 28 Tagen	≤ 60	≤ 100	≤ 300
TSVOC nach 28 Tagen	≤ 40	≤ 50	≤ 100
R-Wert basierend auf AgBB-NIK-Werten nach 28 Tagen	≤ 1	-	-
Summe der nicht bewertbaren VOC	≤ 40	-	-
Formaldehyd nach 3 Tagen	≤ 50	≤ 50	≤ 50
Acetaldehyd nach 3 Tagen	≤ 50	≤ 50	≤ 50
Summe von Form- und Acetaldehyd	≤ 0,05 ppm	≤ 0,05 ppm	≤ 0,05 ppm
Summe von flüchtigen K1A/K1B Stoffen nach 3 Tagen	< 10	< 10	< 10
Jeder flüchtige K1A/K1B Stoff nach 28 Tagen	< 1	< 1	< 1

2) Oberflächenbehandlungsmittel für Parkett, mineralische Böden und elastische Bodenbeläge

Parameter	EC 1 PLUS	EC 1	EC 2
	max. zulässige Konzentration [µg/m³]		
Summe TVOC + TSVOC nach 28 Tagen	≤ 100 davon max. 40 SVOC	≤ 150 davon max. 50 SVOC	≤ 400 davon max. 100 SVOC
Formaldehyd nach 3 Tagen	≤ 50	≤ 50	≤ 50
Acetaldehyd nach 3 Tagen	≤ 50	≤ 50	≤ 50
Jeder flüchtige K1A/K1B Stoff nach 3 Tagen	< 10	< 10	< 10
Jeder flüchtige K1A/K1B Stoff nach 28 Tagen	< 1	< 1	< 1