SENTINEL HOLDING
INSTITUT

SHI PRODUCT PASSPORT

Find products. Certify buildings.

SHI Product Passport No.:

1776-10-1084

ALUJET Anschlussstreifen SPEED

Product group: Accessories & Tools - Adhesive tapes / Joint sealing tapes

ALUJET GmbH
Ahornstraße 16
82291 Mammendorf

Product qualities:

- SHI Product Assessment 2024
- QNG Qualitätssiegel Nachhaltiges Gebäude
- DGNB NEW CONSTRUCTION 2023
- DGNB NEW CONSTRUCTION 2018
- BNB-BN NEUBAU V2015
- EU taxonomy
- BREEAM DE NEUBAU 2018
- LEED v4.1 (outside US)

CERTIFIED SUSTAINABLE PRODUCT – SHI PRODUCT PASSPORT – SENTINEL HOLDING INSTITUT – www.sentinel-holding.eu

Köttner

Helmut Köttner
Scientific Director
Freiburg, 03 April 2026

SENTINEL HOLDING
INSTITUT

Product:
ALUJET Anschlussstreifen SPEED

SHI Product Passport no.:
1776-10-1084

Contents

SHI Product Assessment 2024	1
QNG - Qualitätssiegel Nachhaltiges Gebäude	2
DGNB New Construction 2023	3
DGNB New Construction 2018	5
BNB-BN Neubau V2015	6
EU taxonomy	7
BREEAM DE Neubau 2018	8
LEED v4.1	9
Product labels	10
Legal notices	11
Technical data sheet/attachments	11

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar

SENTINEL HOLDING
INSTITUT

Product:
ALUJET Anschlussstreifen SPEED

SHI Product Passport no.:
1776-10-1084

SHI Product Assessment 2024

Since 2008, Sentinel Holding Institut GmbH (SHI) has been establishing a unique standard for products that support healthy indoor air. Experts carry out independent product assessments based on clear and transparent criteria. In addition, the independent testing company SGS regularly audits the processes and data accuracy.

Criteria	Product category	Harmful substance limit	Assessment
SHI Product Assessment	Other products	TVOC ≤ 300 µg/m³ Formaldehyd ≤ 24 µg/m³	Indoor Air Quality Certified
Valid untill: 31 January 2027			

SENTINEL HOLDING
INSTITUT

Product:
ALUJET Anschlussstreifen SPEED

SHI Product Passport no.:
1776-10-1084

QNG - Qualitätssiegel Nachhaltiges Gebäude

The Qualitätssiegel Nachhaltiges Gebäude (Quality Seal for Sustainable Buildings), developed by the German Federal Ministry for Housing, Urban Development and Building (BMWSB), defines requirements for the ecological, socio-cultural, and economic quality of buildings. The Sentinel Holding Institut evaluates construction products in accordance with QNG requirements for certification and awards the QNG ready label. Compliance with the QNG standard is a prerequisite for eligibility for the KfW funding programme. For certain product groups, the QNG currently has no specific requirements defined. Although classified as not assessment-relevant, these products remain suitable for QNG-certified projects.

Criteria	Pos. / product group	Considered substances	QNG assessment
3.1.3 Schadstoffvermeidung in Baumaterialien			QNG ready - Not relevant for assessment

SENTINEL HOLDING
INSTITUT

Product:
ALUJET Anschlussstreifen SPEED

SHI Product Passport no.:
1776-10-1084

DGNB New Construction 2023

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings. The 2023 version sets high standards for ecological, economic, socio-cultural, and functional aspects throughout the entire life cycle of a building.

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 03.05.2024 (3rd edition)	not applicable		Not relevant for assessment

Criteria	Assessment
SOC1.2 Indoor air quality (*)	May positively contribute to the overall building score
Verification: SHI Schadstoffgeprüft	

Criteria	Assessment
ECO1.1 Life cycle cost (*)	May positively contribute to the overall building score

Criteria	Assessment
ECO2.6 Climate resilience (*)	May positively contribute to the overall building score

Criteria	Assessment
ENV1.1 Climate action and energy (*)	May positively contribute to the overall building score

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 29.05.2025 (4th edition)	not applicable		Not relevant for assessment

SENTINEL HOLDING
INSTITUT

Product:
ALUJET Anschlussstreifen SPEED

SHI Product Passport no.:
1776-10-1084

DGNB New Construction 2018

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings.

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact	not applicable	not applicable	Not relevant for assessment

SENTINEL HOLDING
INSTITUT

Product:
ALUJET Anschlussstreifen SPEED

SHI Product Passport no.:
1776-10-1084

BNB-BN Neubau V2015

The Bewertungssystem Nachhaltiges Bauen (Assessment System for Sustainable Building) is a tool for evaluating public office and administrative buildings, educational facilities, laboratory buildings, and outdoor areas in Germany. The BNB was developed by the former Federal Ministry for the Environment, Nature Conservation, Building and Nuclear Safety (BMUB) and is now overseen by the Federal Ministry for Housing, Urban Development and Building (BMWSB).

Criteria	Pos. / product type	Considered substance group	Quality level
1.1.6 Risiken für die lokale Umwelt			Not relevant for assessment

SENTINEL HOLDING
INSTITUT

Product:
ALUJET Anschlussstreifen SPEED

SHI Product Passport no.:
1776-10-1084

EU taxonomy

The EU Taxonomy classifies economic activities and products according to their environmental impact. At the product level, the EU regulation defines clear requirements for harmful substances, formaldehyde and volatile organic compounds (VOCs). The Sentinel Holding Institut GmbH labels qualified products that meet this standard.

Criteria	Product type	Considered substances	Assessment
DNSH - Pollution prevention and control		Substances according to Annex C	EU taxonomy compliant
Verification: Zertifikat des eco-INSTITUTs vom 10.02.2025			

SENTINEL HOLDING
INSTITUT

Product:
ALUJET Anschlussstreifen SPEED

SHI Product Passport no.:
1776-10-1084

BREEAM DE Neubau 2018

BREEAM (Building Research Establishment Environmental Assessment Methodology) is a UK-based building assessment system that evaluates the sustainability of new constructions, refurbishments, and conversions. Developed by the Building Research Establishment (BRE), the system aims to assess and improve the environmental, economic, and social performance of buildings.

Criteria	Product category	Considered substances	Quality level
Hea 02 Indoor Air Quality			Not relevant for assessment

SENTINEL HOLDING
INSTITUT

Product:
ALUJET Anschlussstreifen SPEED

SHI Product Passport no.:
1776-10-1084

LEED v4.1

LEED (Leadership in Energy and Environmental Design) is an internationally recognised building certification system developed by the U.S. Green Building Council. It is one of the most widely used sustainability standards for buildings worldwide and is particularly applied in internationally oriented projects. LEED assesses buildings holistically across categories such as energy efficiency, resource conservation, material selection, indoor environmental quality and site sustainability. Depending on the number of points achieved, projects are awarded one of the certification levels: LEED Certified, Silver, Gold or Platinum.

Criteria	Product category	Assessment
EQ Credit: Low-Emitting Materials		Not relevant for assessment

SENTINEL HOLDING
INSTITUT

Product:
ALUJET Anschlussstreifen SPEED

SHI Product Passport no.:
1776-10-1084

Product labels

In the construction industry, high-quality materials are crucial for a building's indoor air quality and sustainability. Product labels and certificates offer guidance to meet these requirements. However, the evaluation criteria of these labels vary, and it is important to carefully assess them to ensure products align with the specific needs of a construction project.

eco INSTITUT
TESTED PRODUCT
ID 0808 - 47110 - 001

The privately owned eco-INSTITUT certifies low-emission, low-odour and low-pollutant construction and cleaning products, furnishings and furniture on the basis of its strict test criteria and precisely documented certification conditions.

GEPRÜFT NACHHALTIGES PRODUKT
SENTINEL HOLDING INSTITUT

This product is SHI Indoor Air Quality certified and recommended by Sentinel Holding Institut. Indoor-air-focused construction, renovation, and operation of buildings is made possible by transparent and verifiable criteria thanks to the Sentinel Holding concept.

GEPRÜFT NACHHALTIGES PRODUKT
QNG READY
SENTINEL HOLDING INSTITUT

Products bearing the Sentinel Holding Institute QNG-ready seal are suitable for projects aiming to achieve the "Qualitätssiegel Nachhaltiges Gebäude" (Quality Seal for Sustainable Buildings). QNG-ready products meet the requirements of QNG Appendix Document 3.1.3, "Avoidance of Harmful Substances in Building Materials." The KfW loan program Climate-Friendly New Construction with QNG may allow for additional funding.

SENTINEL HOLDING
INSTITUT

Product:
ALUJET Anschlussstreifen SPEED

SHI Product Passport no.:
1776-10-1084

Legal notices

(*) These criteria apply to the construction project as a whole. While individual products can positively contribute to the overall building score through proper planning, the evaluation is always conducted at the building level. The information was provided entirely by the manufacturer.

Find our criteria here: https://www.sentinel-holding.eu/de/Themenwelten/Pr%C3%BCfkriterien%20f%C3%BCr%20Produkte

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar

Publisher

Sentinel Holding Institut GmbH
Bötzinger Str. 38
79111 Freiburg im Breisgau
Germany
Tel.: +49 761 590 481-70
info@sentinel-holding.eu
www.sentinel-holding.eu

ALUJET Anschlussstreifen SPEED

Produkt-beschreibung

Der ALUJET Anschlussstreifen SPEED ist ein 5-lagiges vollflächig selbstklebendes Verbundmaterial für den Einsatz als Systemkomponente der ALUJET Walljet ALU und der ALUJET Floorjet SPEED.



Abb. 1: ALUJET Anschlussstreifen SPEED



Abb. 2: ALUJET Anschlussstreifen SPEED

Vorteile

Frei von Bitumen und PVC; vollflächig selbstklebend; extreme Klebkraft; Hohe Anfangsklebkraft; geprüfte Klebkraft in Verbindung mit der ALUJET Floorjet SPEED und ALUJET Walljet ALU; geschlitzter Trennliner bei 500mm-Ausführung.

Einsatzgebiet

Zur Verklebung der Querstöße bei der ALUJET Floorjet SPEED als auch zum Anschluss an aufgehende Bauteile und an bitumenfreie Mauersperrbahnen. Zur Stoßverklebung der ALUJET Walljet ALU bei Überlappungen unter 200 mm. Des Weiteren zur Abdichtung gegen Spritz- und Sickerwasser und Bodenfeuchte am Wandsockel (DIN 18533 Teil 1 und 2: W4-E). Im An- und Abschlussbereich an Durchdringungen und aufgehende Bauteile (Wände, Wandsockel, Tür- und Fensterrahmen etc.) übernimmt der ALUJET Anschlussstreifen SPEED auch die Dichtfunktion.

Technische Daten

Art	Norm	Einheit	Wert
Klebeschicht:	---		Vollflächig
Trägermaterial	---		Aluminiumverbund
Trennliner	---		Polyethylen
Klebstoff	---		Modifizierte Acrylat Dispersion
Verarbeitungstemperatur	---	°C	ab -10
Verarbeitungstemperatur auf mineralischen Untergründen (z.B. Wandsockelabdichtung)	---	°!C	ab +5

Verarbeitung

Die Untergründe müssen tragfähig, trocken, staubfrei, fettfrei sein und dürfen keine klebstoffabweisenden Substanzen beinhalten. Gegebenenfalls sind die Untergründe zu Primern (z.B. mit ALUJET Sprühfixx). Es ist darauf zu achten, dass keine Fehlklebungen, Falten und Wellen bei der Verklebung auftreten.

Verklebung Querstöße / Anschluss an Mauersperrbahn
Die ALUJET Floorjet SPEED bzw. ALUJET Walljet ALU wird Stoß an Stoß verlegt. Den ALUJET Anschlussstreifen SPEED in der benötigten Länge abschneiden, dann den Trennliner etwas vom ALUJET Anschlussstreifen SPEED lösen, den Anschlussstreifen ausrichten und mittig auf den Stoß aufkleben. Den Trennliner langsam zwischen Abdichtungsbahn und Anschlusstreifen herausziehen und mit der Hand auf dem Stoß fixieren. Die Verklebung jetzt noch stark andrücken (z. B. mit einer Anpressrolle).

Anschluss an bestehende Bauteile
Sofern das Heranführen, Überlappen, bzw. Verkleben mit der eingebrachten Mauersperrbahn nicht möglich ist, bzw. keine Mauersperrbahn vorhanden ist, besteht folgende Möglichkeit um eine korrekte Verklebung mit der ALUJET Floorjet SPEED zu gewährleisten: dazu sollte der ALUJET Anschlussstreifen SPEED zuerst auf der ALUJET Floorjet SPEED verklebt werden. Anschließend wird der ALUJET Anschlussstreifen SPEED am bestehenden Bauteil bis Oberkante Fußbodenaufbau nach oben geführt und durch Druck auf dem Untergrund fixiert.

Abdichtung im Wandsockel
Im Bereich des Wandsockels besteht die Möglichkeit, dass der ALUJET Anschlussstreifen SPEED (Mindestbreite 20 cm) auch die Aufgabe der Flächenabdichtung übernimmt. Hierzu ist der ALUJET Anschlussstreifen SPEED vollflächig auf dem Untergrund zu verkleben.

Vertikale Stöße: Die Ausführung findet ohne Überdeckung (Stoß an Stoß) statt. Die Stoßbereiche sind unter Verwendung eines ALUJET Anschlussstreifen SPEED, bei mittig angeordnetem Stoßbereich, zu überkleben.

Horizontale Überlappungsverklebung: Die horizontale Überlappungsverklebung des ALUJET Anschlussstreifen SPEED wird unter Verwendung eines ALUJET Anschlussstreifen SPEED mit einer Überdeckung von mindestens 10 cm hergestellt.

Beschädigungen
Kleinere Beschädigungen der ALUJET Walljet ALU und der ALUJET Floorjet SPEED können mit dem ALUJET Anschlussstreifen SPEED überklebt werden.

Spezifikation

ALUJET Anschlussstreifen SPEED

Breite:	200 mm	200 mm	350 mm	500 mm
Länge:	30 m	32,5 m	32,5 m	32,5 m
Verpackungseinheit:	1 Rolle	1 Rolle	1 Rolle	1 Rolle
Liner geschlitzt	nein	ja	ja	ja

ALUJET Reparaturband SPEED

Breite:	50 mm
Länge:	30 m
Verpackungseinheit:	6 Rollen
Im abP enthalten?	Nein

Lagerung

12 Monate; bei mind. +5°C bis +25°C; UV-geschützt

DGNB

Das Produkt qualifiziert sich für den Einsatz in allen DGNB-Neubauprojekten bis zur höchsten Auszeichnungsstufe "Platin“. Dies wird durch das unabhängige Sentinel Haus Institut bestätigt, welches das Produkt gemäß den Anforderungen des DGNB Steckbriefs ENV1.2 "Risiken für die lokale Umwelt" (Version 2023) geprüft hat. Aufgrund der sehr guten Produkteigenschaften hinsichtlich des Schadstoffgehalts sind für die DGNB-Zertifizierung keine zusätzlichen Nachweisdokumente erforderlich.

Hinweise

Unsere Gebrauchsanweisungen, Verarbeitungsrichtlinien, Produkt- oder Leistungsangaben und sonstigen technischen Aussagen sind nur allgemeine Richtlinien; sie beschreiben nur die Beschaffenheit unserer Produkte (Werteangaben / -ermittlung zum Produktionszeitpunkt) und Leistungen und stellen keine Garantie im Sinne des §443 BGB dar. Wegen der Vielfalt der Verwendungszwecke des einzelnen Produkts und der jeweiligen besonderen Gegebenheiten (z.B. Verarbeitungsparameter, Materialeigenschaften etc.)obliegt dem Anwender die eigene Erprobung; unsere kostenlose anwendungstechnische Beratung in Wort, Schrift und Versuch ist unverbindlicher Art..

ZERTIFIKAT / CERTIFICATE

Zertifizierte Produkte Certified products	**ALUJET Floorjet SPEED** **ALUJET Anschlussstreifen SPEED** **ALUJET Anschlussstreifen SPEED - Innenecke** **ALUJET Anschlussstreifen SPEED - Außenecke**
Produktart Product type	**Abdichtungsbahn auf Bodenplatte Aluminiumverbundfolie;** **Aluminiumverbund mit modifizierter Acrylat Dispersion**
Hersteller / Vertrieb Manufacturer / Distributor	**ALUJET GmbH** **Ahornstraße 16** **82291 Mammendorf**
Zertifizierungsnummer Certification number	**0117-33679-001**
Prüfberichtsnummer Number of test report	**59596-A001-A002-L** **59596-A001-A002-eIL-G**
Prüfumfang Test program	Laborprüfung auf gesundheitlich bedenkliche Emissionen und Inhaltsstoffe. Tested on hazardous emissions and components.
Prüfergebnis Test result	Die untersuchten Produkte erfüllen die Anforderungen des eco-INSTITUT-Label-Programms sowie der Prüfkriterien eIL 01.01 (03/2024) Dichtstoffe und Dichtungsbahnen. Einzelheiten siehe zugehöriges Gutachten. The products tested meet the requirements of the eco-INSTITUT-Label programme and the test criteria eIL 01.01 (03/2024) Sealants and sealing sheets. For further details see the respective report.
Gültigkeit / Überwachung bis Validity / Monitoring until	**01/2027**

Köln, 28.01.2026

eco-INSTITUT Germany GmbH
Schanzenstr. 6-20
Carlswerk 1.19
D-51063 Köln

Dr. Frank Kuebart

Marc-Anton Dobaj
M.Sc. Crystalline Materials

eco INSTITUT
TESTED PRODUCT
ID 0117 - 33679 - 001

eco-institut.de
eco-institut-label.de

INFORMATION ZUM ZERTIFIKAT

Die wichtigsten Fakten zum eco-INSTITUT-Label

- **Anerkanntes Qualitätssiegel** für Bau- und Einrichtungsprodukte, Möbel, Reinigungsmittel, Matratzen und Bettwaren
- **Empfohlen** von führenden unabhängigen Verbrauchermedien (z. B. WDR Haushalts-Check, Magazin ÖKO-TEST, label-online.de)
- Kennzeichnet Produkte, die **besonders schadstoff- und emissionsarm** sind
- Prüfumfang: **1. Dokumentenprüfung** (Volldeklaration), **2. Laborprüfung** (umfangreiche Untersuchungen auf Emissionen, Inhaltsstoffe und Geruch)
- **Gültigkeit: 2 Jahre**; jährliche Konformitätsprüfung; zur Verlängerung nach 2 Jahren komplette Neuprüfung erforderlich
- **Transparenz** beim Prüfablauf, bei den Prüfkriterien und den Kosten (weiterführende Informationen unter **www.eco-institut-label.de**)

Was deckt das Label ab bzw. wo wird es anerkannt?

Das Hauptmerkmal der eco-INSTITUT-Label-Kriterien ist die **ausführliche Liste von VOC-Emissionsanforderungen** für kritische Substanzgruppen und Einzelsubstanzen. Diese basiert unter anderem auf der jeweils aktuellen NIK-Wert-Liste des AgBB, umfasst aber auch die deutschen Innenraumrichtwerte RW I.

Die Emissionsprüfungen erfolgen gemäß EN 16516 i. d. R. nach 3 und 28 Tagen. Durch die strengen eco-INSTITUT-Label-Kriterien werden die Emissionsanforderungen an Produkte bei anderen **nationalen und internationalen Bewertungsprogrammen** abgedeckt bzw. anerkannt, wie z. B. ...

✓ **AgBB Schema Deutschland**
Ausschuss für die gesundheitliche Bewertung von Bauprodukten

✓ **Landesbauordnungen/MVV TB Deutschland:**
Anforderungen an bauliche Anlagen bezüglich des Gesundheitsschutzes (ABG)

✓ **Belgische VOC-Verordnung**

✓ **Französische VOC-Verordnung**
Klasse A sowie
französische KMR-Verordnung

✓ **BREEAM**
Hea 02 / Hea 04 (v7) Indoor air quality, VOC emissions

✓ **BVB Schweden**
Byggvaru® Bedömningen: VOC emissions

✓ **Danish Indoor Climate Labelling**
Emissions by chemical analysis

✓ **DGNB International**
ENV1.2 – Risiken für die lokale Umwelt; Emissionsnachweise der Zeilen 8, 9, 11, 13, 20, 47a, 48 (Neubau, Innenräume Anlage 1 v2018); 1, 2 (Innenräume Anlage 2 v2018)

✓ **eco-bau Schweiz**
Kriterium Lösemittel

✓ **EGGbi Europäische Gesellschaft für gesundes Bauen und Innenraumhygiene**
(Zitat: „[...] umfangreichsten und völlig transparenten Kriterienkatalog aller Gütezeichen [...]"

✓ **EU Taxonomieverordnung (EU) 2023/2486**
3.1 Neubau, 3.2 Gebäuderenovierung, 3.5 Verwendung von Beton: 5) Vermeidung und Verminderung der Umweltverschmutzung, Formaldehyd und krebserzeugende VOC

✓ **GOLS Global Organic Latex Standard**

✓ **Italienisches Green Public Procurement**
I Criteri ambientali minimi – CAM

✓ **LEED v4.1** Option 2 und **LEED v4** for projects outside the U.S.; EQ credit low-emitting materials: VOC emissions requirements (bei Formaldehyd-emissionen nach 28 Tagen < 10 µg/m³)

✓ **QNG Qualitätssiegel Nachhaltiges Gebäude**
3.1.3 Schadstoffvermeidung in Baumaterialien: Teil- oder Komplettanforderungen an SVHC, VOC-Emissionen und Inhaltsstoffe Pos. 1, 2, 3.1, 3.2, 4.1, 4.2, 4.3, 4.5, 5.3, 5.5, 5.6, 5.7, 5.8, 5.10, 6, 7.5, 9, 11.1, 12.4

✓ **SINTEF Environmental certificate**
4.3 Emission requirements

✓ **WELL International**
(International WELL Building Institute)

Die Liste ist nicht abschließend.
Stand: Oktober2025

INFORMATION ON THE CERTIFICATE

The most important facts about the eco-INSTITUT-Label

- **Recognised quality seal** for construction and furnishing products, furniture, cleaning products, mattresses and bedding
- **Recommended** by leading independent consumer media (e.g. WDR Haushalts-Check, ÖKO-TEST Magazine, label-online.de)
- Identifies products that are particularly **low in pollutants and emissions**
- Test scope: **1. Document inspection** (full declaration), **2. Laboratory testing** (extensive tests for emissions, substances and odour)
- **Validity: 2 years**; annual conformity test; complete reassessment required for renewal after 2 years
- **Transparency** in the test sequence, the test criteria and the costs (further information at **www.eco-institut-label.de**)

What does the label cover and where is it recognised?

The main feature of the eco-INSTITUT-Label criteria is the **detailed list of VOC emission requirements** for critical substance groups and individual substances. This is based, among other things, on the current list of NIK values from the AgBB, but also includes the German Indoor Guide Values RW I.

Emission tests are usually carried out after 3 and 28 days in accordance with EN 16516. Due to the strict eco-INSTITUT-Label criteria, emission requirements for products are covered or recognised in other **national and international evaluation programmes**, such as …

✓ **AgBB scheme Germany**
Committee for Health-related Evaluation of Building Products

✓ **State Building Codes/MVV TB Germany:**
Requirements for structural installations regarding health protection (ABG)

✓ **Belgian VOC regulation**

✓ **French VOC regulation**
Class A and
French CMR regulation

✓ **BREEAM**
Hea 02 / Hea 04 (v7) Indoor air quality, Emission criteria

✓ **BVB Sweden**
Byggvaru® Bedömningen: VOC emissions

✓ **Danish Indoor Climate Labelling**
Emissions by chemical analysis

✓ **DGNB International**
ENV1.2 – Risks to the local environment; emission evidence from rows 8, 9, 11, 13, 20, 47a, 48 (new buildings, interiors Annex 1 v2018); 1, 2 (interiors Annex 2 v2018)

✓ **eco-bau Switzerland**
Criterion: Solvents

✓ **EGGbi European Society for Healthy Building and Indoor Hygiene**
(quote: „[…] most comprehensive and completely transparent catalogue of criteria of all quality labels […]")

✓ **EU Taxonomy Regulation (EU) Standard 2023/2486**
3.1 New construction, 3.2 Building renovation, 3.5 Use of concrete: 5) Avoidance and reduction of environmental pollution, formaldehyde and carcinogenic VOCs

✓ **GOLS Global Organic Latex Standard**

✓ **Italian Green Public Procurement**
I Criteri ambientali minimi – CAM

✓ **LEED v4.1** Option 2 and **LEED v4** for projects outside the U.S.; EQ credit low-emitting materials: VOC emissions requirements (formaldehyde emissions after 28 days < 10 µg/m³)

✓ **QNG German Quality label Sustainable Building**
3.1.3 Avoidance of harmful substances in building materials: Partial or complete requirements for SVHC, VOC emissions and Content Pos. 1, 2, 3.1, 3.2, 4.1, 4.2, 4.3, 4.5, 5.3, 5.5, 5.6, 5.7, 5.8, 5.10, 6, 7.5, 9, 11.1, 12.4

✓ **SINTEF Environmental certificate**
4.3 Emission requirements

✓ **WELL International**
International WELL Building Institute

The list is not exhaustive.
Last updated: October 2025

ALUJET GmbH, Ahornstraße 16, D-82291 Mammendorf

Sentinel Haus Institut GmbH
Frau Lina Hug
Merzhauser Straße 74
79100 Freiburg i. Br.

Zentrale Mammendorf
Oliver Krieger
Marketingleiter
Telefon: +49 8145 921 205
oliver.krieger@alujet.de

Mammendorf, den 11.02.26

Bestätigung / Herstellererklärung

Sehr geehrte Frau Hug,

Konformitätserklärung gemäß REACH-Verordnung Stand 11/2025 Besonders besorgniserregende Stoffe nach Art. 33 der REACH-Verordnung bestätigen wir, dass unsere Produkte (Erzeugnisse)

ALUJET Basic
ALUJET Climajet SD2
ALUJET Climajet SD DUO
ALUJET Difujet BLU
ALUJET Master
ALUJET Professional
ALUJET Anschlussstreifen SPEED – Innenecke
ALUJET Anschlussstreifen SPEED – Außenecke

den von Ihnen angefragten Schwellenwert von 0,1 Gew.-% gemäß REACH für SVHC nicht überschreiten. Chlorparaffine, TCEP, PBB und PBDE von $\leq$ 0,10 % werden eingehalten. Wir hoffen Ihnen mit dieser Information geholfen zu haben, stehen für weitere Fragen jedoch gerne zur Verfügung.

Mit freundlichen Grüßen

ALUJET GmbH

ppa.
Oliver Krieger