SENTINEL HOLDING
INSTITUT

SHI-PRODUKTPASS

Produkte finden - Gebäude zertifizieren

SHI-Produktpass-Nr.:

13373-10-1073

ASSY Schrauben

Warengruppe: Befestigungstechnik - Schrauben

WÜRTH

Adolf Würth GmbH & Co. KG
Reinhold-Würth-Straße 12-17
74653 Künzelsau-Gaisbach

Produktqualitäten:

- SHI-Produkt bewertung 2024
- QNG Qualitätssiegel Nachhaltiges Gebäude
- DGNB NEUBAU 2023
- DGNB NEUBAU 2018
- BNB-BN NEUBAU V2015
- EU-Taxonomie
- BREEAM DE NEUBAU 2018
- LEED v4.1 (outside US)

GEPRÜFT NACHHALTIGES PRODUKT
SHI PRODUKT PASS
SENTINEL HOLDING INSTITUT
www.sentinel-holding.eu

Köttner

Helmut Köttner
Wissenschaftlicher Leiter
Freiburg, den 19.05.2026

Produkt:
ASSY Schrauben

SHI Produktpass-Nr.:
13373-10-1073

WÜRTH

Inhalt

SHI-Produktbewertung 2024	1
QNG - Qualitätssiegel Nachhaltiges Gebäude	2
DGNB Neubau 2023	3
DGNB Neubau 2018	4
BNB-BN Neubau V2015	5
EU-Taxonomie	6
BREEAM DE Neubau 2018	7
LEED v4.1	8
Produktsiegel	9
Rechtliche Hinweise	10
Technisches Datenblatt/Anhänge	11

Wir sind stolz darauf, dass die SHI-Datenbank, die erste und einzige Datenbank für Bauprodukte ist, die ihre umfassenden Prozesse sowie die Aktualität regelmäßig von dem unabhängigen Prüfunternehmen SGS-TÜV Saar überprüfen lässt.

SGS TÜV SAAR

SENTINEL HOLDING
INSTITUT

Produkt:
ASSY Schrauben

SHI Produktpass-Nr.:
13373-10-1073

WÜRTH

SHI-Produktbewertung 2024

Seit 2008 etabliert die Sentinel Holding Institut GmbH (SHI) einen einzigartigen Standard für schadstoffgeprüfte Produkte. Experten führen unabhängige Produktprüfungen nach klaren und transparenten Kriterien durch. Zusätzlich überprüft das unabhängige Prüfunternehmen SGS-TÜV Saar regelmäßig die Prozesse und Aktualität.

Kriterium	Produktkategorie	Schadstoffgrenzwert	Bewertung
SHI-Produktbewertung	sonstige Produkte	TVOC ≤ 300 µg/m³ Formaldehyd ≤ 24 µg/m³	Emissionsneutral

SENTINEL HOLDING
INSTITUT

Produkt:
ASSY Schrauben

SHI Produktpass-Nr.:
13373-10-1073

WÜRTH

QNG - Qualitätssiegel Nachhaltiges Gebäude

Das Qualitätssiegel Nachhaltiges Gebäude, entwickelt durch das Bundesministerium für Wohnen, Stadtentwicklung und Bauwesen (BMWSB), legt Anforderungen an die ökologische, soziokulturelle und ökonomische Qualität von Gebäuden fest. Das Sentinel Holding Institut prüft Bauprodukte gemäß den QNG-Anforderungen für eine Zertifizierung und vergibt das QNG-ready Siegel. Das Einhalten des QNG-Standards ist Voraussetzung für den KfW-Förderkredit. Für bestimmte Produktgruppen hat das QNG derzeit keine spezifischen Anforderungen definiert. Diese Produkte sind als nicht bewertungsrelevant eingestuft, können jedoch in QNG-Projekten genutzt werden.

Kriterium	Pos. / Bauproduktgruppe	Betrachtete Stoffe	QNG Freigabe
3.1.3 Schadstoffvermeidung in Baumaterialien			QNG-ready nicht bewertungsrelevant

SENTINEL HOLDING
INSTITUT

Produkt:
ASSY Schrauben

SHI Produktpass-Nr.:
13373-10-1073

WÜRTH

DGNB Neubau 2023

Das DGNB-System (Deutsche Gesellschaft für Nachhaltiges Bauen) bewertet die Nachhaltigkeit von Gebäuden verschiedener Art. Das System ist sowohl anwendbar für private und gewerbliche Großprojekte als auch für kleinere Wohngebäude. Die Version 2023 setzt hohe Standards für ökologische, ökonomische, soziokulturelle und funktionale Aspekte während des gesamten Lebenszyklus eines Gebäudes.

Kriterium	Pos. / Relevante Bauteile / Bau-Materialien / Flächen	Betrachtete Stoffe / Aspekte	Qualitätsstufe
ENV 1.2 Risiken für die lokale Umwelt, 03.05.2024 (3. Auflage)	nicht zutreffend		nicht bewertungsrelevant

Kriterium	Bewertung
ENV 1.1 Klimaschutz und Energie (*)	Kann Gesamtbewertung positiv beeinflussen
Nachweis: EPD; Rückbaubar, Gradle to grave.	

Kriterium	Pos. / Relevante Bauteile / Bau-Materialien / Flächen	Betrachtete Stoffe / Aspekte	Qualitätsstufe
ENV 1.2 Risiken für die lokale Umwelt, 29.05.2025 (4. Auflage)	nicht zutreffend		nicht bewertungsrelevant

SENTINEL HOLDING
INSTITUT

Produkt:
ASSY Schrauben

SHI Produktpass-Nr.:
13373-10-1073

WÜRTH

DGNB Neubau 2018

Das DGNB-System (Deutsche Gesellschaft für Nachhaltiges Bauen) bewertet die Nachhaltigkeit von Gebäuden verschiedener Art. Das System ist sowohl anwendbar für private und gewerbliche Großprojekte als auch für kleinere Wohngebäude.

Kriterium	Pos. / Relevante Bauteile / Bau-Materialien / Flächen	Betrachtete Stoffe / Aspekte	Qualitätsstufe
ENV 1.2 Risiken für die lokale Umwelt	nicht zutreffend	nicht zutreffend	nicht bewertungsrelevant

SENTINEL HOLDING
INSTITUT

Produkt:
ASSY Schrauben

SHI Produktpass-Nr.:
13373-10-1073

WÜRTH

BNB-BN Neubau V2015

Das Bewertungssystem Nachhaltiges Bauen ist ein Instrument zur Bewertung von Büro- und Verwaltungsgebäuden, Unterrichtsgebäuden, Laborgebäuden sowie Außenanlagen in Deutschland. Das BNB wurde vom damaligen Bundesministerium für Umwelt, Naturschutz, Bau und Reaktorsicherheit (BMUB) entwickelt und unterliegt heute dem Bundesministerium für Wohnen, Stadtentwicklung und Bauwesen.

Kriterium	Pos. / Bauprodukttyp	Betrachtete Schadstoffgruppe	Qualitätsniveau
1.1.6 Risiken für die lokale Umwelt			nicht bewertungsrelevant

SENTINEL HOLDING
INSTITUT

Produkt:
ASSY Schrauben

SHI Produktpass-Nr.:
13373-10-1073

WÜRTH

EU-Taxonomie

Die EU-Taxonomie klassifiziert wirtschaftliche Aktivitäten und Produkte nach ihren Umweltauswirkungen. Auf der Produktebene gibt es gemäß der EU-Verordnung klare Anforderungen zu Formaldehyd und flüchtigen organischen Verbindungen (VOC). Die Sentinel Holding Institut GmbH kennzeichnet qualifizierte Produkte, die diesen Standard erfüllen.

Kriterium	Produkttyp	Betrachtete Stoffe	Bewertung
DNSH - Vermeidung und Verminderung der Umweltverschmutzung			nicht bewertungsrelevant

SENTINEL HOLDING
INSTITUT

Produkt:
ASSY Schrauben

SHI Produktpass-Nr.:
13373-10-1073

WÜRTH

BREEAM DE Neubau 2018

BREEAM (Building Research Establishment Environmental Assessment Methodology) ist ein britisches Gebäudebewertungssystem, welches die Nachhaltigkeit von Neubauten, Sanierungsprojekten und Umbauten einstuft. Das Bewertungssystem wurde vom Building Research Establishment (BRE) entwickelt und zielt darauf ab, ökologische, ökonomische und soziale Auswirkungen von Gebäuden zu bewerten und zu verbessern.

Kriterium	Produktkategorie	Betrachtete Stoffe	Qualitätsstufe
Hea 02 Qualität der Innenraumluft			nicht bewertungsrelevant

SENTINEL HOLDING
INSTITUT

Produkt:
ASSY Schrauben

SHI Produktpass-Nr.:
13373-10-1073

WÜRTH

LEED v4.1

LEED (Leadership in Energy and Environmental Design) ist ein international anerkanntes Gebäudezertifizierungssystem des U.S. Green Building Council. Es zählt zu den weltweit am weitesten verbreiteten Nachhaltigkeitsstandards für Gebäude und wird insbesondere bei international ausgerichteten Projekten eingesetzt. LEED bewertet Gebäude ganzheitlich in Kategorien wie Energieeffizienz, Ressourcenschonung, Materialauswahl, Innenraumqualität und Standortqualität. Je nach erreichter Punktzahl werden die Zertifizierungsstufen LEED Certified, Silver, Gold oder Platinum vergeben.

Kriterium	Produktkategorie	Betrachtete Stoffe	Bewertung
EQ Credit: Low-Emitting Materials			nicht bewertungsrelevant

Produkt:
ASSY Schrauben

SHI Produktpass-Nr.:
13373-10-1073

WÜRTH

Produktsiegel

In der Baubranche spielt die Auswahl qualitativ hochwertiger Materialien eine zentrale Rolle für die Gesundheit in Gebäuden und deren Nachhaltigkeit. Produktlabels und Zertifikate bieten Orientierung, um diesen Anforderungen gerecht zu werden. Allerdings besitzt jedes Zertifikat und Label eigene Prüfkriterien, die genau betrachtet werden sollten, um sicherzustellen, dass sie den spezifischen Bedürfnissen eines Bauvorhabens entsprechen.

Produkte mit dem QNG-ready Siegel des Sentinel Holding Instituts eignen sich für Projekte, für welche das Qualitätssiegel Nachhaltiges Gebäude (QNG) angestrebt wird. QNG-ready Produkte erfüllen die Anforderungen des QNG Anhangdokument 3.1.3 "Schadstoffvermeidung in Baumaterialien". Das KfW-Kreditprogramm Klimafreundlicher Neubau mit QNG kann eine höhere Fördersumme ermöglichen.

Das IBU ("Institut Bauen und Umwelt e.V.") ist eine Initiative von Bauprodukt- und Baukomponentenherstellern, die sich dem Leitbild der Nachhaltigkeit im Bauwesen verpflichten. IBU ist Programmbetreiber für Umwelt-Produktdeklarationen (Environmental Product Declaration, kurz: EPD) nach der Norm EN 15804. Das IBU-EPD-Programm steht für umfassende Ökobilanzen und Umweltwirkungen von Bauprodukten und eine unabhängige Überprüfung durch Dritte.

Produkt:
ASSY Schrauben

SHI Produktpass-Nr.:
13373-10-1073

WÜRTH

Rechtliche Hinweise

(*) Die Kriterien dieses Steckbriefs beziehen sich auf das gesamte Bauobjekt. Die Bewertung erfolgt auf der Ebene des Gebäudes. Im Rahmen einer sachgemäßen Planung und fachgerechten Installation können einzelne Produkte einen positiven Beitrag zum Gesamtergebnis der Bewertung leisten. Das Sentinel Holding Institut stützt sich einzig auf die Angaben des Herstellers.

Alle Kriterien finden Sie unter:
https://www.sentinel-holding.eu/de/Themenwelten/Pr%C3%BCfkriterien%20f%C3%BCr%20Produkte

Wir sind stolz darauf, dass die SHI-Datenbank, die erste und einzige Datenbank für Bauprodukte ist, die ihre umfassenden Prozesse sowie die Aktualität regelmäßig von dem unabhängigen Prüfunternehmen SGS-TÜV Saar überprüfen lässt.

SGS TÜV SAAR

Herausgeber

Sentinel Holding Institut GmbH
Bötzinger Str. 38
79111 Freiburg im Breisgau
Tel.: +49 761 590 481-70
info@sentinel-holding.eu
www.sentinel-holding.eu

ENVIRONMENTAL PRODUCT DECLARATION

as per *ISO 14025* and *EN 15804+A2*

Owner of the Declaration	Würth Group / Adolf Würth GmbH & Co. KG
Publisher	Institut Bauen und Umwelt e.V. (IBU)
Programme holder	Institut Bauen und Umwelt e.V. (IBU)
Declaration number	EPD-AWU-20230569-CBA1-EN
Issue date	21.03.2024
Valid to	20.03.2029

Stainless Steel screws

Adolf Würth GmbH & Co. KG

Institut Bauen und Umwelt e.V.

ECO PLATFORM EPD VERIFIED

www.ibu-epd.com | https://epd-online.com



General Information

Adolf Würth GmbH & Co. KG

Programme holder

IBU – Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

Declaration number

EPD-AWU-20230569-CBA1-EN

This declaration is based on the product category rules:

Screws, 01.06.2023
(PCR checked and approved by the SVR)

Issue date

21.03.2024

Valid to

20.03.2029



Dipl.-Ing. Hans Peters
(Chairman of Institut Bauen und Umwelt e.V.)



Florian Pronold
(Managing Director Institut Bauen und Umwelt e.V.)

Stainless Steel screws

Owner of the declaration

Würth Group / Adolf Würth GmbH & Co. KG
Reinhold-Würth Str. 12-17
74653 Künzelsau
Germany

Declared product / declared unit

1 kg weighted average of dowel-type fasteners with thread.

Scope:

This EPD relates to timber screws, chipboard screws, drilling and tapping screws, screws for plastics, metric screws and dowel-type fasteners with thread made of steel or stainless steel. Depending on the type of screw, these products are generally used for fastening two or more components made of wood, steel or plastic.

The declared environmental data related to 1 kg of stainless steel are based on a weighted average stainless steel screws in a Würth manufacturing plant, SWG Schraubenwerk Gaisbach GmbH and internationalized with generic data. The holder of the declaration shall be liable for the underlying information and supporting documents; any liability of IBU (Institut Bauen und Umwelt e. V.) with regard to manufacturer information, life cycle assessment data and supporting documents is hereby excluded. The EPD (Environmental Product Declaration) was created in accordance with EN 15804 + A2: 2022-03. In the following, the standard is referred to in simplified form as EN 15804.

The owner of the declaration shall be liable for the underlying information and evidence; the IBU shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

The EPD was created according to the specifications of EN 15804+A2. In the following, the standard will be simplified as *EN 15804*.

Verification

The standard EN 15804 serves as the core PCR
Independent verification of the declaration and data according to ISO 14025:2011
☐ internally ☒ externally



Dr.-Ing. Nikolay Minkov,
(Independent verifier)

Product

Product description/Product definition
Dowel-type fasteners with thread, e.g. screws made of stainless steel, are fasteners that can predominantly be used for fastening two or more components. The materials to be fastened or screw-in surfaces can be made of wood, wood materials, plastic, aluminium, steel, stainless steel or other metals.

Pin-shaped connectors, such as screws, are generally manufactured from a wire (stainless steel) and provided with a head on one component side to be tightened. Depending on the application, it can have different shapes, e.g. countersunk head, round head, hexagon head or washer head. For anchoring the pin-shaped connectors, a thread is formed on the opposite side. The thread shape (e.g. wood thread or metric thread) is matched to the screw-in surface and can be designed differently in terms of thread height, thread angle or thread pitch. The point design of the dowel-type fasteners with thread is matched to the application, e.g. wooden tip, drill tip or blunt shape. For protection against corrosion or e.g. for setting a sliding friction, the pin-shaped connectors can be provided with different coatings, for example, anti-skid coating.

Depending on the application, the additional use of suitable steel or stainless steel seals as well as EPDM seals (ethylene-propylene-diene rubber), washers or nuts is provided. Depending on the application, the dowel-type fasteners with thread can be subject to legal national or European requirements such as the Construction Products Regulation. For example, the following documentation possibilities may be available:

Product according to CPR with hEN:
Regulation (EU) No 305/2011 (CPR) shall apply to the placing of the product on the market in the EU/EFTA states (with the exception of Switzerland). The product requires a declaration of performance taking into account the respective EN.

The CE marking shall be applied to the product in compliance with the proof of its conformity with the following harmonized standards based on the mentioned harmonization legislation:

- *EN 14592:2008-04*; timber structures - dowel-type fasteners

The use shall be subject to the respective national provisions.

Product according to CPR with ETA:
Regulation (EU) No 305/2011 (CPR) shall apply to the placing of the product on the market in the the European Union/European/Free Trade Association (EU/EFTA) states (with the exception of Switzerland). The product needs a declaration of performance taking into account the respective *ETA* such as *ETA-10/0184, ETA-13/0210 or ETA-11/0190* and CE marking.

The use shall be subject to the respective national provisions.

Product that is not subject to EU harmonization legislation:
The national regulations of the place of use apply to the use of the product. In Germany, for example, the building codes of the respective countries and the technical building regulations based on these codes apply.

Application
Timber screws, chipboard screws, drilling and tapping screws, plastic screws and dowel-type fasteners with thread made of stainless steel are used when fastening two or more components. Depending on the type of screw, these products are generally used for fastening components made of wood, steel or plastic. Possible application examples include timber construction, steel construction, indoor/outdoor use, furniture applications or window construction. Examples of Würth product groups are ASSY, Pias and Piasta screws.

Technical Data
Structural data for the respective dowel-type fasteners with thread are provided in the corresponding approvals and technical drawings, as shown below in an excerpt from *ETA 11/0190 (ASSY)* for wood screws.

Constructional data
Data based on ASSY plus VG:

Name	Value	Unit
Screw diameter	8	mm
Usage category as per ETA	11/0190	-
Characteristic tension resistance	20	kN
Screw length (+1.0/-0.5)	450 - 480	mm
Material	carbon steel	

Product according to CPR with hEN:

- Performance values of the product in accordance with the declaration of performance in relation to its essential characteristics according to applicable hEN such as *EN 15048-1:2016 and EN 14399-1:2015*.

Product according to CPR with ETA:

- Performance values of the product according to the declaration of performance with respect to its essential characteristics in accordance with applicable ETA.

Product that is not subject to EU harmonization legislation:

- Performance values of the product in relation to its characteristics according to the applicable technical regulation (no CE marking).

All approvals can be downloaded from the Würth Online Shop homepage under the Documents tab for the respective products.

Base materials/Ancillary materials
Dowel-type fasteners with thread are made of stainless steel. As explained in the product description (2.1), depending on the type of application and material, the fasteners are provided with, for example, galvanic and/or mechanical galvanizing and, if appropriate, with anti-friction coating. Depending on the application, the fasteners are also equipped with a corresponding sealing washer made of steel, stainless steel or aluminium and EPDM sealing rubber.

Stainless steel
The designation stainless steel (according to *DIN EN 10020*) refers to alloyed or unalloyed steels with a special degree of purity, such as steels in which the sulfur and phosphorus content (also known as an iron companion) does not exceed 0.025%. Often, additional heat treatments (such as quenching and tempering) are planned.

EPDM
EPDM is an abbreviation for ethylene-propylene diene (monomer) rubber and is a terpolymer elastomer (rubber). It thus belongs to the group of synthetic rubbers. In the context of the rubber classification, seals made of this sealing material are therefore assigned to the group of non-polar saturated rubbers. This material is a high-quality rubber-elastic synthetic elastomer

of ethylene, propylene and dienes of high-molecular weight. The saturated basic molecular base structure of EPDM offers properties such as high weathering resistance, ozone resistance and high heat resistance.

Electrogalvanizing
Galvanization (also electroplating technology) is a surface and coating technology process for the electrochemical separation of metals on metallic or metallized surfaces using an electrolyte and direct current. Functional electroplating protects against corrosion and wear, catalyzes, improves conductivity, and reduces frictional forces. The ductility and formability of workpieces can also be influenced by electroplating.

Anti-friction coating
Aqueous suspensions, emulsions and dispersions are used as lubricants. Depending on the application, these include kerosenes, polymers and waxes. A lubricious coating is applied to the screw by means of an immersion bath or drum coating. It lies on the screw as a dry transparent film. Some lubricating coatings contain small amounts of alcohol. Type 6 work clothing, safety goggles, face protection and chemical-resistant gloves are worn as safety measures to protect human contact during coating. An annual safety briefing is carried out and extraction systems are used.

Reference service life
Given the wide range of applications, no specific information on the recommended useful life is provided. The actual service life of screws generally depends on their intended use, installation environment and proper installation. External influences can have a significant impact on the useful life. According to the European Technical Approval, the average useful life of screws is > 25 years. The indication of the useful life cannot be understood as a guarantee by the manufacturer. It must be ensured that the use of the dowel-type fasteners with thread complies with the applicable technical regulations.

LCA: Calculation rules

Declared Unit
1 kg average screws made of stainless steel:

Declared unit and mass reference

Name	Value	Unit
Declared unit	1	kg
Gross density	7900	kg/m^3

The exact weight of the screw is provided digitally.

System boundary
Type of the EPD: cradle-to-gate - with options, modules C1-C4 and module D (A1-A3 + C + D and additional modules: A4, A5).

Production Stage (A1-A3): The Product stage includes:
· A1 Raw material supply and processing (mainly steel),
· A2 Transport of raw materials to the manufacturer,
· A3 Production of Stainless steel screws (incl. energy provision, treatment of production waste, production of packaging materials).

Construction stage (A4-A5): The construction process stage includes:
· A4 transport to the construction site 100 km by truck,
· A5 Disposal of the packaging and installation of the Stainless steel screw.

End-of-life stage (C1-C4): The end-of-life stage includes:
· C1 machine-assisted de- construction (Hand-screwdriver; battery operated)
· C2 transport to waste processing; 50 km with truck Transport distance can be adjusted at building level if necessary (e.g., for 100 km actual transport distance: multiply LCA values by factor 2)
· C3 waste processing for recycling of Stainless steel.
· C4 no components of the product are landfilled.

Benefits and loads beyond the System Boundary (D):
Module D includes:
Material recovery potentials from metal recycling and energy recovery potentials from the
thermal recovery of Packaging.

Geographic Representativeness
Land or region, in which the declared product system is manufactured, used or handled at the end of the product´s lifespan: Europe

Comparability
Basically, a comparison or an evaluation of EPD data is only possible if all the data sets to be compared were created according to *EN 15804* and the building context, respectively the product-specific characteristics of performance, are taken into account. The underlying database is *LCA FE (GaBi)* 2023, version 2023.1

LCA: Scenarios and additional technical information

Characteristic product properties of biogenic carbon

Information on describing the biogenic carbon content at factory gate
Note: 1 kg of biogenic carbon is equivalent to 44/12 kg of CO2

Name	Value	Unit
Biogenic carbon content in product	-	kg C
Biogenic carbon content in accompanying packaging	0.0228	kg C

Transport from the gate to the site (A4)

Name	Value	Unit
Litres of fuel (per kg transported goods)	0.0018	l/100km
Transport distance	100	km
Capacity utilisation (including empty runs)	61	%
Mass for Transportation	1	kg

Assembly (A5)

Name	Value	Unit
Electricity consumption	0.0281	kWh
Material loss	-	kg
Output substances following waste treatment on site (Packaging)	0.051	kg

End of life (C1-C4)

Name	Value	Unit
Energy consumption for dismantling	0.0281	kWh
Collected separately waste type waste type	1	kg
Collected as mixed construction waste	-	kg
Reuse	-	kg
Recycling	1	kg
Energy recovery	-	kg

Reuse, recovery and/or recycling potentials (D), relevant scenario information

Name	Value	Unit
collection rate	100	%

The results of the scenario (100%) can be scaled on building level according to the applied collection rate.

LCA: Results

DESCRIPTION OF THE SYSTEM BOUNDARY (X = INCLUDED IN LCA; MND = MODULE OR INDICATOR NOT DECLARED; MNR = MODULE NOT RELEVANT)

Product stage			Construction process stage		Use stage							End of life stage				Benefits and loads beyond the system boundaries
Raw material supply	Transport	Manufacturing	Transport from the gate to the site	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	X	X	MND	MND	MNR	MNR	MNR	MND	MND	X	X	X	X	X

RESULTS OF THE LCA - ENVIRONMENTAL IMPACT according to EN 15804+A2: 1 kg Stainless steel fasteners with thread

Parameter	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
GWP-total	kg CO_2 eq	6.88E+00	6.69E-03	1.2E-01	4.26E-02	4.34E-03	0	0	-4.31E+00
GWP-fossil	kg CO_2 eq	6.94E+00	6.61E-03	4.5E-02	4.26E-02	4.29E-03	0	0	-4.32E+00
GWP-biogenic	kg CO_2 eq	-7.44E-02	1.95E-05	7.55E-02	2.12E-05	1.27E-05	0	0	1.98E-02
GWP-luluc	kg CO_2 eq	1.52E-02	6.13E-05	4.29E-06	3.9E-06	3.98E-05	0	0	-1.14E-02
ODP	kg CFC11 eq	6.76E-12	8.61E-16	4.28E-13	4.19E-13	5.59E-16	0	0	-1.76E-13
AP	mol H^+ eq	3.92E-02	9.86E-06	8.37E-05	6.49E-05	6.4E-06	0	0	-2.63E-02
EP-freshwater	kg P eq	1.43E-05	2.42E-08	4.48E-08	4.21E-08	1.57E-08	0	0	-6.21E-06
EP-marine	kg N eq	6.88E-03	3.6E-06	2.52E-05	1.83E-05	2.34E-06	0	0	-3.78E-03
EP-terrestrial	mol N eq	7.46E-02	4.25E-05	2.79E-04	1.93E-04	2.76E-05	0	0	-4.09E-02
POCP	kg NMVOC eq	1.99E-02	8.66E-06	6.87E-05	5.06E-05	5.62E-06	0	0	-1.15E-02
ADPE	kg Sb eq	2.34E-04	4.36E-10	2.14E-09	2.06E-09	2.83E-10	0	0	-6.3E-06
ADPF	MJ	7.45E+01	9.01E-02	9.58E-01	9.36E-01	5.85E-02	0	0	-5.27E+01
WDP	m^3 world eq deprived	2.26E+00	7.99E-05	1.21E-02	3.58E-03	5.19E-05	0	0	-1.75E+00

GWP = Global warming potential; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential of land and water; EP = Eutrophication potential; POCP = Formation potential of tropospheric ozone photochemical oxidants; ADPE = Abiotic depletion potential for non-fossil resources; ADPF = Abiotic depletion potential for fossil resources; WDP = Water (user) deprivation potential)

RESULTS OF THE LCA - INDICATORS TO DESCRIBE RESOURCE USE according to EN 15804+A2: 1 kg Stainless steel fasteners with thread

Parameter	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
PERE	MJ	1.37E+01	6.56E-03	9.97E-01	1.28E-01	4.26E-03	0	0	-9.94E+00
PERM	MJ	8.64E-01	0	-8.64E-01	0	0	0	0	0
PERT	MJ	1.45E+01	6.56E-03	1.33E-01	1.28E-01	4.26E-03	0	0	-9.94E+00
PENRE	MJ	7.46E+01	9.04E-02	9.72E-01	9.36E-01	5.87E-02	0	0	-5.28E+01
PENRM	MJ	1.38E-02	0	-1.38E-02	0	0	0	0	0
PENRT	MJ	7.46E+01	9.04E-02	9.58E-01	9.36E-01	5.87E-02	0	0	-5.28E+01
SM	kg	2.49E-01	0	0	0	0	0	0	7.61E-01
RSF	MJ	0	0	0	0	0	0	0	0
NRSF	MJ	0	0	0	0	0	0	0	0
FW	m^3	8.19E-02	7.18E-06	4.15E-04	2.15E-04	4.66E-06	0	0	-7.17E-02

PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water

RESULTS OF THE LCA – WASTE CATEGORIES AND OUTPUT FLOWS according to EN 15804+A2: 1 kg Stainless steel fasteners with thread

Parameter	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
HWD	kg	1.76E-06	2.8E-13	5.49E-11	5.43E-11	1.82E-13	0	0	-4.8E-04
NHWD	kg	3.65E+00	1.38E-05	2.41E-03	2.06E-04	8.95E-06	0	0	4.68E-02
RWD	kg	1.08E-03	1.69E-07	1.47E-04	1.46E-04	1.1E-07	0	0	-3.73E-04
CRU	kg	0	0	0	0	0	0	0	0
MFR	kg	1.02E-02	0	0	0	0	1E+00	0	0
MER	kg	0	0	0	0	0	0	0	0
EEE	MJ	0	0	1.04E-01	0	0	0	0	0

EET	MJ	0	0	1.89E-01	0	0	0	0	0

HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported electrical energy; EET = Exported thermal energy

RESULTS OF THE LCA – additional impact categories according to EN 15804+A2-optional:
1 kg Stainless steel fasteners with thread

Parameter	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
PM	Disease incidence	6.13E-07	8.16E-11	6.9E-10	5.87E-10	5.3E-11	0	0	-5.68E-07
IR	kBq U235 eq	1.1E-01	2.52E-05	2.21E-02	2.19E-02	1.64E-05	0	0	-4.19E-02
ETP-fw	CTUe	2.32E+01	6.4E-02	2.78E-01	2.68E-01	4.16E-02	0	0	-3.15E+01
HTP-c	CTUh	1.34E-06	1.31E-12	5.41E-12	4.84E-12	8.5E-13	0	0	-6.4E-08
HTP-nc	CTUh	1.46E-07	6.98E-11	2.71E-10	2.48E-10	4.53E-11	0	0	-3.26E-08
SQP	SQP	3.43E+01	3.76E-02	1.33E-01	1.27E-01	2.44E-02	0	0	-7.26E+00

PM = Potential incidence of disease due to PM emissions; IR = Potential Human exposure efficiency relative to U235; ETP-fw = Potential comparative Toxic Unit for ecosystems; HTP-c = Potential comparative Toxic Unit for humans (cancerogenic); HTP-nc = Potential comparative Toxic Unit for humans (not cancerogenic); SQP = Potential soil quality index

Disclaimer 1 – for the indicator “Potential Human exposure efficiency relative to U235”. This impact category deals mainly with the eventual impact of low-dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure or radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, radon and from some construction materials is also not measured by this indicator.

Disclaimer 2 – for the indicators “abiotic depletion potential for non-fossil resources”, “abiotic depletion potential for fossil resources”, “water (user) deprivation potential, deprivation-weighted water consumption”, “potential comparative toxic unit for ecosystems”, “potential comparative toxic unit for humans – cancerogenic”, “Potential comparative toxic unit for humans - not cancerogenic”, “potential soil quality index”. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high as there is limited experience with the indicator.

References

Standards:

EN 15804
EN 15804:2012+A1 2013, Sustainability of construction works — Environmental Product Declarations — Core rules for the product category of construction products.

EN 15804
EN 15804:2012+A2:2019+AC:2021, Sustainability of construction works — Environmental Product Declarations — Core rules for the product category of construction products.

EN 14592
EN 14592:2008-04, Timberstructures– Dowel-typefasteners– Requirements

ISO 14025
EN ISO 14025:2011, Environmental labels and declarations — Type III environmental declarations — Principles and procedures.

DIN EN 10020
DIN EN 10020:2000, Definition and classification of grades of steel

Literature:

LCAFE (GaBI) software
Sphera Solutions GmbH
LCAFE (GaBI) Software
System and Database for Life Cycle Engineering
CUP Version: 2023.1
University of Stuttgart
Leinfelden Echterdingen

GaBi documentation
LCAFE (GaBI) life cycle inventory data documentation (http://www.gabi-software.com/international/databases/gabi-data-search/)

IBU 2021
Institut Bauen und Umwelt e.V.: General Programme Instructions
for the Preparation of EPDs at the Institut Bauen und Umwelt e.V., version 2.0., Berlin: Institut Bauen und Umwelt e.V., 2021, http://www.ibu-epd.com

PCR Part A
Calculation Rules for the Life Cycle Assessment and Requirements on the Project
Report,Berlin: Institut Bauen und Umwelt e.V., www.ibu-epd.com, Version 1.3, 2021

PCR Part B
Requirements on the EPD for Screws ,
version 8, Institut Bauen und Umwelt e.V., www.bau-umwelt.com, 2023
ETA-11/0190 (ASSY)

ETA-10/0184

ETA-13/0210

Regulation (EU) No 305/2011 (CRB)

Publisher

Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

+49 (0)30 3087748- 0
info@ibu-epd.com
www.ibu-epd.com

Programme holder

Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

+49 (0)30 3087748- 0
info@ibu-epd.com
www.ibu-epd.com

Author of the Life Cycle Assessment

Sphera Solutions GmbH
Hauptstraße 111- 113
70771 Leinfelden-Echterdingen
Germany

+49 711 341817-0
info@sphera.com
www.sphera.com

Owner of the Declaration

Würth Group / Adolf Würth GmbH & Co. KG
Reinhold-Würth Str. 12-17
74653 Künzelsau
Germany

+49 7940 15-0
info@wuerth.com
www.wuerth.com

Adolf Würth GmbH & Co. KG
Reinhold-Würth-Str. 12-17
74653 Künzelsau
Germany

+49 7940/15-0
info@wuerth.com
www.wuerth.de

Würth Industrie Service GmbH & Co. KG
Industriepark Würth, Drillberg -
97980 Bad Mergentheim
Germany

+49 7931 91-0
info@wuerth-industrie.com
www.wuerth-industrie.com