SENTINEL HOLDING
INSTITUT

SHI PRODUCT PASSPORT

Find products. Certify buildings.

SHI Product Passport No.:

13373-10-1001

Anschlussklebstoff All-in-One

Product group: Glues

WÜRTH

Adolf Würth GmbH & Co. KG
Reinhold-Würth-Straße 12-17
74653 Künzelsau-Gaisbach

Product qualities:

- SHI Product Assessment 2024
- QNG Qualitätssiegel Nachhaltiges Gebäude
- DGNB NEW CONSTRUCTION 2023
- DGNB NEW CONSTRUCTION 2018
- BNB-BN NEUBAU V2015
- EU taxonomy
- BREEAM DE NEUBAU 2018
- LEED v4.1 (outside US)

CERTIFIED SUSTAINABLE PRODUCT
SHI PRODUCT PASSPORT
SENTINEL HOLDING INSTITUT
www.sentinel-holding.eu

Köttner

Helmut Köttner
Scientific Director
Freiburg, 31 March 2026

SENTINEL HOLDING
INSTITUT

Product:
Anschlussklebstoff All-in-One

SHI Product Passport no.:
13373-10-1001

WÜRTH

Contents

SHI Product Assessment 2024	1
QNG - Qualitätssiegel Nachhaltiges Gebäude	2
DGNB New Construction 2023	3
DGNB New Construction 2018	4
BNB-BN Neubau V2015	5
EU taxonomy	6
BREEAM DE Neubau 2018	7
LEED v4.1	8
Product labels	9
Legal notices	10
Technical data sheet/attachments	11

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar

SGS

SGS TÜV SAAR

SENTINEL HOLDING
INSTITUT

Product:
Anschlussklebstoff All-in-One

SHI Product Passport no.:
13373-10-1001

WÜRTH

SHI Product Assessment 2024

Since 2008, Sentinel Holding Institut GmbH (SHI) has been establishing a unique standard for products that support healthy indoor air. Experts carry out independent product assessments based on clear and transparent criteria. In addition, the independent testing company SGS regularly audits the processes and data accuracy.

Criteria	Product category	Harmful substance limit	Assessment	Notice
SHI Product Assessment	Sealants and adhesives	TVOC ≤ 300 µg/m^3 Formaldehyd ≤ 24 µg/m^3	Indoor Air Quality Certified (Advisory Note)	Achtung, enthält Isothiazolinone zur Topfkonservierung. Kann Allergien auslösen.
Valid untill: 14 June 2027				

Product:
Anschlussklebstoff All-in-One

SHI Product Passport no.:
13373-10-1001

WÜRTH

QNG - Qualitätssiegel Nachhaltiges Gebäude

The Qualitätssiegel Nachhaltiges Gebäude (Quality Seal for Sustainable Buildings), developed by the German Federal Ministry for Housing, Urban Development and Building (BMWSB), defines requirements for the ecological, socio-cultural, and economic quality of buildings. The Sentinel Holding Institut evaluates construction products in accordance with QNG requirements for certification and awards the QNG ready label. Compliance with the QNG standard is a prerequisite for eligibility for the KfW funding programme. For certain product groups, the QNG currently has no specific requirements defined. Although classified as not assessment-relevant, these products remain suitable for QNG-certified projects.

Criteria	Pos. / product group	Considered substances	QNG assessment
3.1.3 Schadstoffvermeidung in Baumaterialien	4.3 Adhesives and sealants based on PU, PU-hybrid	VOC (volatile organic compounds) / chlorinated paraffins / polybrominated biphenyls (PBB) / polybrominated diphenyl ethers (PBDE) / SVHC	QNG ready
Verification: Herstellererklärungen 01.26			

Product:
Anschlussklebstoff All-in-One

SHI Product Passport no.:
13373-10-1001

WÜRTH

DGNB New Construction 2023

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings. The 2023 version sets high standards for ecological, economic, socio-cultural, and functional aspects throughout the entire life cycle of a building.

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 03.05.2024 (3rd edition)	13 Assembly adhesives and sealants on the façade	VVOCs, VOC, SVOC emissions and content of hazardous substances	Quality level 4
Verification: Herstellererklärung 01.26, EMICODE EC1 Plus Zertifikat (8154/01.01.11) 14.06.2022			

Criteria	Assessment
SOC1.2 Indoor air quality (*)	May positively contribute to the overall building score
Verification: SHI-Schadstoffgeprüft	

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 29.05.2025 (4th edition)	13 Assembly adhesives and sealants	VVOCs, VOC, SVOC emissions and content of hazardous substances	Quality level 4
Verification: Herstellererklärung 01.26, EMICODE EC1 Plus Zertifikat (8154/01.01.11) 14.06.2022			

Product:
Anschlussklebstoff All-in-One

SHI Product Passport no.:
13373-10-1001

WÜRTH

DGNB New Construction 2018

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings.

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact	13 Installation adhesives and sealants on the façade	Halogenated propellants, chlorinated paraffins and emissions	Quality level 4
Verification: Herstellererklärung 01.26, EMICODE EC1 Plus Zertifikat (8154/01.01.11) 14.06.2022			

Product:
Anschlussklebstoff All-in-One

SHI Product Passport no.:
13373-10-1001

WÜRTH

BNB-BN Neubau V2015

The Bewertungssystem Nachhaltiges Bauen (Assessment System for Sustainable Building) is a tool for evaluating public office and administrative buildings, educational facilities, laboratory buildings, and outdoor areas in Germany. The BNB was developed by the former Federal Ministry for the Environment, Nature Conservation, Building and Nuclear Safety (BMUB) and is now overseen by the Federal Ministry for Housing, Urban Development and Building (BMWSB).

Criteria	Pos. / product type	Considered substance group	Quality level
1.1.6 Risiken für die lokale Umwelt	9 Adhesives and sealants for creating airtightness on facades, both interior and exterior: e.g. PU, PU-hybrid, MS polymer, SMP, or similar	VOC / hazardous substances	Quality level 5
Verification: Herstellererklärung 01.26, EMICODE EC1 Plus Zertifikat (8154/01.01.11) 14.06.2022			

Product:
Anschlussklebstoff All-in-One

SHI Product Passport no.:
13373-10-1001

WÜRTH

EU taxonomy

The EU Taxonomy classifies economic activities and products according to their environmental impact. At the product level, the EU regulation defines clear requirements for harmful substances, formaldehyde and volatile organic compounds (VOCs). The Sentinel Holding Institut GmbH labels qualified products that meet this standard.

Criteria	Product type	Considered substances	Assessment
DNSH - Pollution prevention and control		Substances according to Annex C	EU taxonomy compliant
Verification: EMICODE EC1 Plus Zertifikat (8154/01.01.11) 14.06.2022			

Product:
Anschlussklebstoff All-in-One

SHI Product Passport no.:
13373-10-1001

WÜRTH

BREEAM DE Neubau 2018

BREEAM (Building Research Establishment Environmental Assessment Methodology) is a UK-based building assessment system that evaluates the sustainability of new constructions, refurbishments, and conversions. Developed by the Building Research Establishment (BRE), the system aims to assess and improve the environmental, economic, and social performance of buildings.

Criteria	Product category	Considered substances	Quality level
Hea 02 Indoor Air Quality	Interior adhesives and sealants (including flooring adhesives)	Emissions: Formaldehyde, TVOC, carcinogens	Exemplary quality
Verification: erfüllt durch EC1+ Zertifikat vom 14.06.2022 Nr. 8154/01.01.11.			

Product:
Anschlussklebstoff All-in-One

SHI Product Passport no.:
13373-10-1001

WÜRTH

LEED v4.1

LEED (Leadership in Energy and Environmental Design) is an internationally recognised building certification system developed by the U.S. Green Building Council. It is one of the most widely used sustainability standards for buildings worldwide and is particularly applied in internationally oriented projects. LEED assesses buildings holistically across categories such as energy efficiency, resource conservation, material selection, indoor environmental quality and site sustainability. Depending on the number of points achieved, projects are awarded one of the certification levels: LEED Certified, Silver, Gold or Platinum.

Criteria	Product category	Assessment
EQ Credit: Low-Emitting Materials	Kleb- und Dichtstoffe	compliant
Verification: erfüllt durch EC1+ Zertifikat vom 14.06.2022 Nr. 8154/01.01.11.		

Product:
Anschlussklebstoff All-in-One

SHI Product Passport no.:
13373-10-1001

WÜRTH

Product labels

In the construction industry, high-quality materials are crucial for a building's indoor air quality and sustainability. Product labels and certificates offer guidance to meet these requirements. However, the evaluation criteria of these labels vary, and it is important to carefully assess them to ensure products align with the specific needs of a construction project.

The EMICODE® label, awarded by the German manufacturers' association "GEV – Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e. V.", is primarily relevant for flooring installation materials. The EMICODE® EC1^{PLUS} label, as the premium class, sets significantly stricter emission limits than the other label variants.

Products bearing the Sentinel Holding Institute QNG-ready seal are suitable for projects aiming to achieve the "Qualitätssiegel Nachhaltiges Gebäude" (Quality Seal for Sustainable Buildings). QNG-ready products meet the requirements of QNG Appendix Document 3.1.3, "Avoidance of Harmful Substances in Building Materials." The KfW loan program Climate-Friendly New Construction with QNG may allow for additional funding.

This product is SHI Indoor Air Quality certified and recommended by Sentinel Holding Institut. Indoor-air-focused construction, renovation, and operation of buildings is made possible by transparent and verifiable criteria thanks to the Sentinel Holding concept.

The IBU ("Institut Bauen und Umwelt e.V.") is an initiative of building product manufacturers committed to sustainability in construction. It serves as the programme operator for Environmental Product Declarations (EPDs) in accordance with the EN 15804 standard. The IBU EPD programme provides comprehensive life cycle assessments and environmental impact data for construction products, supported by independent third-party verification.

Product:
Anschlussklebstoff All-in-One

SHI Product Passport no.:
13373-10-1001

WÜRTH

Legal notices

(*) These criteria apply to the construction project as a whole. While individual products can positively contribute to the overall building score through proper planning, the evaluation is always conducted at the building level. The information was provided entirely by the manufacturer.

Find our criteria here: https://www.sentinel-holding.eu/de/Themenwelten/Pr%C3%BCfkriterien%20f%C3%BCr%20Produkte

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar

SGS TÜV SAAR

Publisher

Sentinel Holding Institut GmbH
Bötzinger Str. 38
79111 Freiburg im Breisgau
Germany
Tel.: +49 761 590 481-70
info@sentinel-holding.eu
www.sentinel-holding.eu

TECHNICAL DATA SHEET

Connection adhesive ALL-IN-ONE


Art. no. 0893 700 111
P. Qty.: 1 / 12



For the permanent sealing of all connection joints to ensure that they are air-tight and windproof and for fitting indoor and outdoor windows and doors.

Construction surfaces such as masonry and brickwork, stone, concrete, wood, plaster, screed, gypsum fibre and gypsum plasterboard panels, copper, zinc, aluminium and zinc-plated metal.

Container	Cartridge
Chemical basis	Acrylate polymer dispersion
Colour	Light blue
Density/conditions	1.02 g/cm³/at 20 °C, EN 542
Min. final strength	48 h
Min./max. processing temperature	-5 to 40 °C
Min./max. processing temperature for cartridge	10 to 35 °C
Min./max. temperature resistance	-30 to +120 °C
Shelf life from production/conditions	24 Month/cool and dry storage area, no exposure to sunlight, 15 °C to 25 °C
Weight of content	316 g
Solvent-free	Yes
Contents	310 ml
Silicone-free	Yes
Sustainability	Pollutants/Emissions



PR01_0893700111, TDB, Rev: 0.50, State: 20. 09. 2024

TECHNICAL DATA SHEET

ECO LINE

Application area

Permanently elastic, airtight joint, component connection and impact overlap bonding/sealing of vapour barriers, vapour retarders, sealing films in dry construction (except for swimming pool areas) and all WÜTOP non-breathable membranes, breathable membranes, façade membranes and WÜTOP thermal membranes to be used only on the non-woven side.
Permanently elastic, airtight joint, component connection and impact overlap bonding/sealing of vapour barriers, vapour retarders, sealing films in dry construction (except for swimming pool areas) and all WÜTOP non-breathable membranes, breathable membranes, façade membranes and WÜTOP thermal membranes to be used only on the non-woven side in accordance with the German Buildings Energy Act.
Bonding/sealing of water-vapour-impermeable and permeable sealing tapes when installing windows and doors on absorbent surfaces.

Examples for the material humidity of the building materials as orientation values:	
Construction material	**Vol. %**
Clay bricks	≤ 2.5
Plaster	≤ 5
Drywall panels	≤ 5
Concrete	≤ 5
Aerated concrete	≤ 8
Wood	≤ 12

Application quantity/adhesive yield		
Adhesive bead diameter	**310 ml cartridge**	**600 ml bag**
4 mm	24.7 rm	47.7 rm
5 mm	15.8 rm	30.6 rm
6 mm	11.0 rm	21.2 rm
7 mm	8.1 rm	16.6 rm
8 mm	6.2 rm	11.9 rm

Application information

The application surfaces must be solid, clean, dry and free of grease and oil. On highly absorbent surfaces such as aerated concrete, gypsum plasterboard or sandstone, the EURASOL® Primer plus SK (art. no. 0893 992 710) should be used.
The adhesive is applied on one side (as a 4–8 mm thick bead) to the film or the load-bearing construction material (can also be applied to slightly damp, dusty or absorbent surfaces).

The film is then bonded with a discharge loop for strain relief while the adhesive bead is still wet and pressed lightly to fix it in place (do not press the bead flat; the bead should retain a thickness of ≥1 mm).
Detached compounds can be joined together once again due to the self-adhesive properties of the adhesive.

Dispersion adhesives harden by giving off moisture (physical drying); the construction material must be sufficiently absorbent to guarantee curing of the ALL-IN-ONE connection adhesive. Alternatively, adhesion on non-absorbent surfaces can be achieved

PRO1_0893700111, TDB, Rev: 0.50, State: 20. 09. 2024

TECHNICAL DATA SHEET

by leaving the adhesive to dry for a certain amount of time (16-20 h in a dust-free environment) in a contact bonding procedure.

In individual cases, suitable material preparations (e.g. heating, pre-drying of the bonding surfaces/adhesive) must be made; ensure sufficient room ventilation.
The curing time (drying process) varies according to temperature and humidity.
Uncured adhesive is cleaned from the tools with water. Clean cured adhesive with a Type 60 cleaning agent (item no. 0892130030).

Proof of performance

EMICODE EC1plus: Very low emissions: The EMICODE classification system distinguishes the environmental and health compatibility of construction products. The lowest-emission products bear the EC1plus mark.



Notice

- Please refer to the processing instructions of the system warranty.
- When adhering films and strips in outdoor applications, despite the largely favourable „resistance to rain immediately after application of the ALL-IN-ONE connection adhesive", it must be ensured that intensive moisture exposure, e.g. through continual rain, moisture run-off, is excluded.
- Cured ALL-IN-ONE connection adhesive has good water resistance; nevertheless, applications where there is a constantly increased level of humidity, e.g. swimming pools or other wet areas (due to the aggressive chlorine-containing moist air, among other factors), should be avoided. Not suitable for bonding pool linings.
- The time parameters specified here can only be determined precisely by in-house tests, as they are greatly affected by material, temperature, application quantity, humidity, material humidity, adhesive film thickness, press pressure and other criteria. As a rule, corresponding safety margins are provided for the reference values.

The usage instructions are recommendations based on the tests we have conducted and on our experience; carry out your own tests before each application. Due to the large number of applications and storage and processing conditions, we do not assume any liability for a specific application result. Insofar as our free customer service provides technical information or acts as an advisory service, no responsibility is assumed by this service except where the advice or information given falls within the scope of our specified, contractually agreed service or the advisor was acting deliberately. We guarantee the consistent quality of our products. We reserve the right to make technical changes and further develop products. Please observe the technical data sheet!

PR01_0893700111, TDB, Rev: 0.50, State: 20. 09. 2024

SICHERHEITSDATENBLATT

gemäß der Verordnung (EG) Nr. 1907/2006, geändert durch die Verordnung (EU) 2020/878 der Kommission

ANSCHLUSSKLEBSTOFF ALL-IN-ONE - 310 ML / 310 G

Version	Überarbeitet am:	SDB-Nummer:	Datum der letzten Ausgabe: 31.10.2024
6.2	04.06.2025	10781711-00015	Datum der ersten Ausgabe: 10.07.2017

ABSCHNITT 1: Bezeichnung des Stoffs beziehungsweise des Gemischs und des Unternehmens

1.1 Produktidentifikator

Handelsname	:	ANSCHLUSSKLEBSTOFF ALL-IN-ONE - 310 ML / 310 G
Produktnummer	:	0893700111

1.2 Relevante identifizierte Verwendungen des Stoffs oder Gemischs und Verwendungen, von denen abgeraten wird

Verwendung des Stoffs/des Gemisches	:	Klebstoffe und/ oder Dichtstoffe Produkt zur professionellen Verwendung
Empfohlene Einschränkungen der Anwendung	:	Nicht anwendbar

1.3 Einzelheiten zum Lieferanten, der das Sicherheitsdatenblatt bereitstellt

Firma	:	Adolf Wuerth GmbH & Co. KG Reinhold-Würth-Str. 12-17 74653 Künzelsau
Telefon	:	+49 794015 0
Telefax	:	+49 794015 10 00
E-Mailadresse der für SDB verantwortlichen Person	:	isi@wuerth.com

1.4 Notrufnummer

+49 (0)6132 – 84463

ABSCHNITT 2: Mögliche Gefahren

2.1 Einstufung des Stoffs oder Gemischs

Einstufung (VERORDNUNG (EG) Nr. 1272/2008)

Keine gefährliche Substanz oder Mischung.

2.2 Kennzeichnungselemente

Kennzeichnung (VERORDNUNG (EG) Nr. 1272/2008)

Kein Gefahrenpiktogramm, kein Signalwort, kein(e) Gefahrenhinweis(e), kein(e) Sicherheitshinweis(e) erforderlich.

Zusätzliche Kennzeichnung

EUH210 Sicherheitsdatenblatt auf Anfrage erhältlich.

EUH208 Enthält Reaktionsmasse von: 5-Chlor-2-methyl-2H-isothiazol-3-on [EG Nr. 247-500-7] und 2-Methyl-2H-isothiazol-3-on [EG Nr. 220-239-6] (3:1), 1,2-Benzisothiazol-3(2H)-on. Kann allergische Reaktionen hervorrufen.

2.3 Sonstige Gefahren

Dieser Stoff/diese Mischung enthält keine Komponenten in Konzentrationen von 0,1 % oder höher, die entweder als persistent, bioakkumulierbar und toxisch (PBT) oder sehr persistent und sehr bioakkumulierbar (vPvB) eingestuft sind.

Umweltbezogene Angaben: Der Stoff/dieses Gemisch enthält keine Bestandteile, die gemäß REACH Artikel 57(f) oder der delegierten Verordnung (EU) 2017/2100 der Kommission oder der delegierten Verordnung (EU) 2018/605 der Kommission in Mengen von 0,1 % oder mehr endokrinschädliche Eigenschaften aufweisen.

Toxikologische Angaben: Der Stoff/dieses Gemisch enthält keine Bestandteile, die gemäß REACH Artikel 57(f) oder der delegierten Verordnung (EU) 2017/2100 der Kommission oder der delegierten Verordnung (EU) 2018/605 der Kommission in Mengen von 0,1 % oder mehr endokrinschädliche Eigenschaften aufweisen.

ABSCHNITT 3: Zusammensetzung/Angaben zu Bestandteilen

3.2 Gemische

Inhaltsstoffe

Chemische Bezeichnung	CAS-Nr. EG-Nr. INDEX-Nr. Registrierungsnummer	Einstufung	Konzentration (% w/w)
1,2-Benzisothiazol-3(2H)-on	2634-33-5 220-120-9 613-088-00-6	Acute Tox. 4; H302 Acute Tox. 2; H330 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 --- M-Faktor (Akute aquatische Toxizität): 1 M-Faktor (Chronische aquatische Toxizität): 1	>= 0,025 - < 0,036

		Spezifische Konzentrationsgrenzwerte Skin Sens. 1A; H317 >= 0,036 % Schätzwert Akuter Toxizität Akute orale Toxizität: 450 mg/kg Akute inhalative Toxizität (Staub/Nebel): 0,21 mg/l	
Reaktionsmasse von: 5-Chlor-2-methyl-2H-isothiazol-3-on [EG Nr. 247-500-7] und 2-Methyl-2H-isothiazol-3-on [EG Nr. 220-239-6] (3:1)	55965-84-9 613-167-00-5	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 2; H310 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071 M-Faktor (Akute aquatische Toxizität): 100 M-Faktor (Chronische aquatische Toxizität): 100 Spezifische Konzentrationsgrenzwerte Skin Corr. 1C; H314 >= 0,6 % Skin Irrit. 2; H315 0,06 - < 0,6 % Eye Irrit. 2; H319 0,06 - < 0,6 % Skin Sens. 1A; H317 >= 0,0015 % Eye Dam. 1; H318 >= 0,6 %	>= 0,0002 - < 0,0015

		EUH071 >= 0,6 % Schätzwert Akuter Toxizität Akute orale Toxizität: 64 mg/kg Akute inhalative Toxizität (Staub/Nebel): 0,171 mg/l Akute dermale Toxizität: 87,12 mg/kg	

Die Erklärung der Abkürzungen finden Sie unter Abschnitt 16.

Alternative CAS-Nummern für einige Regionen

Chemische Bezeichnung	Alternative CAS-Nummer(n)
Reaktionsmasse von: 5-Chlor-2-methyl-2H-isothiazol-3-on [EG Nr. 247-500-7] und 2-Methyl-2H-isothiazol-3-on [EG Nr. 220-239-6] (3:1)	2682-20-4, 26172-55-4

ABSCHNITT 4: Erste-Hilfe-Maßnahmen

4.1 Beschreibung der Erste-Hilfe-Maßnahmen

Schutz der Ersthelfer : Es sind keine speziellen Vorsichtsmaßnahmen für Ersthelfer erforderlich.

Nach Einatmen : Bei Inhalation, an die frische Luft bringen.
Bei Auftreten von Symptomen, ärztliche Betreuung aufsuchen.

Nach Hautkontakt : Vorsorglich mit Wasser und Seife waschen.
Bei Auftreten von Symptomen, ärztliche Betreuung aufsuchen.

Nach Augenkontakt : Augen vorsorglich mit Wasser ausspülen.
Bei Auftreten einer andauernden Reizung, ärztliche Betreuung aufsuchen.

Nach Verschlucken : Bei Verschlucken, KEIN Erbrechen hervorrufen.
Bei Auftreten von Symptomen, ärztliche Betreuung aufsuchen.
Mund gründlich mit Wasser ausspülen.

4.2 Wichtigste akute und verzögert auftretende Symptome und Wirkungen

Keine bekannt.

4.3 Hinweise auf ärztliche Soforthilfe oder Spezialbehandlung

Behandlung	:	Symptomatisch und unterstützend behandeln.

ABSCHNITT 5: Maßnahmen zur Brandbekämpfung

5.1 Löschmittel

Geeignete Löschmittel	:	Nicht anwendbar Brennt nicht
Ungeeignete Löschmittel	:	Nicht anwendbar Brennt nicht

5.2 Besondere vom Stoff oder Gemisch ausgehende Gefahren

Besondere Gefahren bei der Brandbekämpfung	:	Kontakt mit Verbrennungsprodukten kann gesundheitsgefährdend sein.
Gefährliche Verbrennungsprodukte	:	Kohlenstoffoxide

5.3 Hinweise für die Brandbekämpfung

Besondere Schutzausrüstung für die Brandbekämpfung	:	Im Brandfall, wenn nötig, umgebungsluftunabhängiges Atemschutzgerät tragen. Persönliche Schutzausrüstung verwenden.
Spezifische Löschmethoden	:	Löschmaßnahmen auf die Umgebung abstimmen. Zur Kühlung geschlossener Behälter Wassersprühstrahl einsetzen. Entfernen Sie unbeschädigte Behälter aus dem Brandbereich, wenn dies sicher ist. Umgebung räumen.

ABSCHNITT 6: Maßnahmen bei unbeabsichtigter Freisetzung

6.1 Personenbezogene Vorsichtsmaßnahmen, Schutzausrüstungen und in Notfällen anzuwendende Verfahren

Personenbezogene Vorsichtsmaßnahmen	:	Empfehlungen zur sicheren Handhabung (siehe Abschnitt 7) und zur persönlichen Schutzausrüstung befolgen (siehe Abschnitt 8).

6.2 Umweltschutzmaßnahmen

Umweltschutzmaßnahmen	:	Freisetzung in die Umwelt vermeiden. Weiteres Auslaufen oder Verschütten verhindern, wenn dies ohne Gefahr möglich ist. Ausbreitung über große Flächen verhindern (z.B. durch Eindämmen oder Ölsperren). Verunreinigtes Waschwasser zurückhalten und entsorgen. Wenn größere Mengen verschütteten Materials nicht eingedämmt werden können, sollen die lokalen Behörden

benachrichtigt werden.

6.3 Methoden und Material für Rückhaltung und Reinigung

Reinigungsverfahren	:	Mit inertem Aufsaugmittel aufnehmen. Bei großflächiger Verschmutzung, mit Gräben oder anderen Eindämmungsmaßnahmen weitere Verbreitung des Stoffes verhindern. Wenn Material aus den Gräben abgepumpt werden kann, dieses Material in geeigneten Behältern lagern. Restliches Material aus der verschmutzten Zone mit geeignetem Bindemittel beseitigen. Lokale oder nationale Richtlinien können für Freisetzung und Entsorgung des Stoffes gelten, ebenso für die bei der Beseitigung von freigesetztem Material verwendeten Stoffe und Gegenstände. Man muss ermitteln, welche dieser Richtlinien anzuwenden sind. Abschnitt 13 und 15 dieses SDBs liefern Informationen bezüglich bestimmter lokaler oder nationaler Vorschriften.

6.4 Verweis auf andere Abschnitte

Siehe Abschnitte: 7, 8, 11, 12 und 13.

ABSCHNITT 7: Handhabung und Lagerung

7.1 Schutzmaßnahmen zur sicheren Handhabung

Technische Maßnahmen	:	Siehe technische Maßnahmen im Abschnitt "Begrenzung und Überwachung der Exposition/Persönliche Schutzausrüstungen".
Lokale Belüftung / Volllüftung	:	Nur mit ausreichender Belüftung verwenden.
Hinweise zum sicheren Umgang	:	Basierend auf den Ergebnissen der Bewertung der Exposition am Arbeitsplatz gemäß den üblichen industriellen Hygiene- und Sicherheitspraktiken handhaben Massnahmen zu Vermeidung von Abfällen/unkontrolliertem Eintrag in die Umwelt sollten getroffen werden.
Hygienemaßnahmen	:	Wenn eine Exposition gegenüber Chemikalien während des normalen Gebrauchs wahrscheinlich ist, sind Augen- und Notduschen nahe dem Arbeitsplatz vorzusehen. Bei der Arbeit nicht essen, trinken, rauchen. Beschmutzte Kleidung vor Wiedergebrauch waschen.

7.2 Bedingungen zur sicheren Lagerung unter Berücksichtigung von Unverträglichkeiten

Anforderungen an Lagerräume und Behälter	:	In korrekt beschrifteten Behältern aufbewahren. In Übereinstimmung mit den besonderen nationalen gesetzlichen Vorschriften lagern.
Zusammenlagerungshinweise	:	Keine besonderen Beschränkungen zur Zusammenlagerung mit anderen Produkten.
Lagerklasse (TRGS 510)	:	12

7.3 Spezifische Endanwendungen

Bestimmte Verwendung(en) : Keine Daten verfügbar

ABSCHNITT 8: Begrenzung und Überwachung der Exposition/Persönliche Schutzausrüstungen

8.1 Zu überwachende Parameter

Arbeitsplatzgrenzwerte

Enthält keine Stoffe mit Arbeitsplatzgrenzwerten.

Abgeleitete Expositionshöhe ohne Beeinträchtigung (DNEL) gemäß Verordnung (EG) Nr. 1907/2006

Stoffname	Anwendungsbereich	Expositionsweg e	Mögliche Gesundheitsschäden	Wert
1,2-Benzisothiazol-3(2H)-on	Arbeitnehmer	Einatmung	Langzeit - systemische Effekte	6,81 mg/m³
	Arbeitnehmer	Hautkontakt	Langzeit - systemische Effekte	0,966 mg/kg Körpergewicht /Tag
	Verbraucher	Einatmung	Langzeit - systemische Effekte	1,2 mg/m³
	Verbraucher	Hautkontakt	Langzeit - systemische Effekte	0,345 mg/kg Körpergewicht /Tag

Abgeschätzte Nicht-Effekt-Konzentration (PNEC) gemäß Verordnung (EG) Nr. 1907/2006

Stoffname	Umweltkompartiment	Wert
1,2-Benzisothiazol-3(2H)-on	Süßwasser	11 µg/l
	Zeitweise Verwendung/Freisetzung	0,403 µg/l
	Meerwasser	1,1 µg/l
	Zeitweise Verwendung/Freisetzung	0,0403 µg/l
	Abwasserkläranlage	1,03 mg/l
	Süßwassersediment	0,0499 mg/kg Trockengewicht (TW)
	Meeressediment	0,00499 mg/kg Trockengewicht (TW)
	Boden	3 mg/kg Trockengewicht (TW)

8.2 Begrenzung und Überwachung der Exposition

Technische Schutzmaßnahmen

Für ausreichende Belüftung sorgen, besonders in geschlossenen Räumen.
Expositionskonzentrationen am Arbeitsplatz minimieren.

Persönliche Schutzausrüstung

Augen-/Gesichtsschutz	:	Bitte befolgen Sie bei der Auswahl der Schutzmaßnahmen für einen spezifischen Arbeitsplatz alle anwendbaren lokalen/nationalen Anforderungen. Folgende persönliche Schutzausrüstung tragen: Sicherheitsbrille Tragen Sie immer einen Augenschutz, wenn ein versehentlicher Augenkontakt mit dem Produkt nicht ausgeschlossen werden kann. Die Ausrüstung sollte DIN EN 166 entsprechen
Handschutz		
Material	:	Nitrilkautschuk
Durchbruchzeit	:	>= 480 min
Handschuhdicke	:	>= 0,35 mm
Richtlinie	:	Die Ausrüstung sollte DIN EN 374 entsprechen
Tragedauer	:	>= 240 min
Anmerkungen	:	Chemikalienschutzhandschuhe sind in ihrer Ausführung in Abhängigkeit von Gefahrstoffkonzentration und -menge arbeitsplatzspezifisch auszuwählen. Es wird empfohlen, die Chemikalienbeständigkeit der oben genannten Schutzhandschuhe für spezielle Anwendungen mit dem Handschuhhersteller abzuklären. Vor den Pausen und bei Arbeitsende Hände waschen.
Haut- und Körperschutz	:	Nach Kontakt Hautflächen gründlich waschen.
Atemschutz	:	Normalerweise kein persönlicher Atemschutz notwendig.

ABSCHNITT 9: Physikalische und chemische Eigenschaften

9.1 Angaben zu den grundlegenden physikalischen und chemischen Eigenschaften

Aggregatzustand	:	Paste
Farbe	:	farbig
Geruch	:	charakteristisch
Geruchsschwelle	:	Keine Daten verfügbar
Schmelzpunkt/Gefrierpunkt	:	Keine Daten verfügbar
Siedebeginn und Siedebereich	:	Keine Daten verfügbar
Entzündbarkeit (fest, gasförmig)	:	Nicht anwendbar
Entzündbarkeit (Flüssigkeiten)	:	Keine Daten verfügbar
Obere Explosionsgrenze / Obere Entzündbarkeitsgrenze	:	Keine Daten verfügbar

Untere Explosionsgrenze / Untere Entzündbarkeitsgrenze	:	Keine Daten verfügbar
Flammpunkt	:	Nicht anwendbar
Zündtemperatur	:	Keine Daten verfügbar
Zersetzungstemperatur	:	Keine Daten verfügbar
pH-Wert	:	7,5 - 8,5
Viskosität		
Viskosität, dynamisch	:	ca. 67.000 mPa.s
Viskosität, kinematisch	:	Keine Daten verfügbar
Löslichkeit(en)		
Wasserlöslichkeit	:	Keine Daten verfügbar
Verteilungskoeffizient: n-Octanol/Wasser	:	Nicht anwendbar
Dampfdruck	:	Keine Daten verfügbar
Dichte	:	ca. 1,02 g/cm³ (20 °C)
Relative Dampfdichte	:	Keine Daten verfügbar
Partikeleigenschaften		
Partikelgröße	:	Nicht anwendbar

9.2 Sonstige Angaben

Explosive Stoffe/Gemische	:	Nicht explosiv
Oxidierende Eigenschaften	:	Der Stoff oder das Gemisch ist nicht eingestuft als oxidierend.
Verdampfungsgeschwindigkeit	:	Keine Daten verfügbar

ABSCHNITT 10: Stabilität und Reaktivität

10.1 Reaktivität

Nicht als reaktionsgefährlich eingestuft.

10.2 Chemische Stabilität

Stabil unter normalen Bedingungen.

10.3 Möglichkeit gefährlicher Reaktionen

Gefährliche Reaktionen : Keine bekannt.

10.4 Zu vermeidende Bedingungen

Zu vermeidende Bedingungen : Keine bekannt.

10.5 Unverträgliche Materialien

Zu vermeidende Stoffe : Kein(e,er).

10.6 Gefährliche Zersetzungsprodukte

Es sind keine gefährlichen Zersetzungsprodukte bekannt.

ABSCHNITT 11: Toxikologische Angaben

11.1 Angaben zu den Gefahrenklassen im Sinne der Verordnung (EG) Nr. 1272/2008

Angaben zu wahrscheinlichen Expositionswegen : Einatmung
Hautkontakt
Verschlucken
Augenkontakt

Akute Toxizität

Nicht klassifiziert nach den vorliegenden Informationen.

Inhaltsstoffe:

1,2-Benzisothiazol-3(2H)-on:

Akute orale Toxizität : LD50 (Ratte, männlich): 450 mg/kg
Methode: OECD Prüfrichtlinie 401

Akute inhalative Toxizität : LC50 (Ratte, männlich): 0,21 mg/l
Expositionszeit: 4 h
Testatmosphäre: Staub/Nebel
Methode: OECD Prüfrichtlinie 403

Akute dermale Toxizität : LD50 (Ratte): > 2.000 mg/kg
Methode: OECD Prüfrichtlinie 402
Bewertung: Der Stoff oder das Gemisch besitzt keine akute dermale Toxizität

Reaktionsmasse von: 5-Chlor-2-methyl-2H-isothiazol-3-on [EG Nr. 247-500-7] und 2-Methyl-2H-isothiazol-3-on [EG Nr. 220-239-6] (3:1):

Akute orale Toxizität : LD50 (Ratte): 64 mg/kg

Akute inhalative Toxizität : LC50 (Ratte): 0,171 mg/l
Expositionszeit: 4 h

Testatmosphäre: Staub/Nebel
Bewertung: Wirkt ätzend auf die Atemwege.

Akute dermale Toxizität : LD50 (Kaninchen): 87,12 mg/kg

Ätz-/Reizwirkung auf die Haut

Nicht klassifiziert nach den vorliegenden Informationen.

Inhaltsstoffe:

1,2-Benzisothiazol-3(2H)-on:

Ergebnis : Hautreizung

Reaktionsmasse von: 5-Chlor-2-methyl-2H-isothiazol-3-on [EG Nr. 247-500-7] und 2-Methyl-2H-isothiazol-3-on [EG Nr. 220-239-6] (3:1):

Spezies : Kaninchen
Methode : OECD Prüfrichtlinie 404
Ergebnis : Ätzend nach 1-4 Stunden Exposition

Schwere Augenschädigung/-reizung

Nicht klassifiziert nach den vorliegenden Informationen.

Inhaltsstoffe:

1,2-Benzisothiazol-3(2H)-on:

Spezies : Kaninchen
Ergebnis : Irreversible Schädigung der Augen

Reaktionsmasse von: 5-Chlor-2-methyl-2H-isothiazol-3-on [EG Nr. 247-500-7] und 2-Methyl-2H-isothiazol-3-on [EG Nr. 220-239-6] (3:1):

Ergebnis : Irreversible Schädigung der Augen
Anmerkungen : Basierend auf der Hautkorrosivität.

Sensibilisierung der Atemwege/Haut

Sensibilisierung durch Hautkontakt

Nicht klassifiziert nach den vorliegenden Informationen.

Sensibilisierung durch Einatmen

Nicht klassifiziert nach den vorliegenden Informationen.

Inhaltsstoffe:

1,2-Benzisothiazol-3(2H)-on:

Art des Testes : Maximierungstest
Expositionswege : Hautkontakt
Spezies : Meerschweinchen
Methode : OECD Prüfrichtlinie 406
Ergebnis : positiv

Bewertung	:	Hohe Sensibilisierungsrate der Haut beim Menschen wahrscheinlich oder bewiesen

Reaktionsmasse von: 5-Chlor-2-methyl-2H-isothiazol-3-on [EG Nr. 247-500-7] und 2-Methyl-2H-isothiazol-3-on [EG Nr. 220-239-6] (3:1):

Art des Testes	:	Buehler Test
Expositionswege	:	Hautkontakt
Spezies	:	Meerschweinchen
Ergebnis	:	positiv
Bewertung	:	Hohe Sensibilisierungsrate der Haut beim Menschen wahrscheinlich oder bewiesen

Keimzell-Mutagenität

Nicht klassifiziert nach den vorliegenden Informationen.

Inhaltsstoffe:

1,2-Benzisothiazol-3(2H)-on:

Gentoxizität in vitro	:	Art des Testes: Bakterieller Rückmutationstest (AMES) Methode: OECD Prüfrichtlinie 471 Ergebnis: negativ Art des Testes: In-Vitro-Genmutationstest an Säugetierzellen Methode: OECD Prüfrichtlinie 476 Ergebnis: negativ Art des Testes: Chromosomenaberrationstest in vitro Methode: OECD Prüfrichtlinie 473 Ergebnis: positiv
Gentoxizität in vivo	:	Art des Testes: In-vivo-Test zur unplanmäßigen DNA-Synthese (UDS) in Säugetierleberzellen Spezies: Ratte Applikationsweg: Verschlucken Methode: OECD Prüfrichtlinie 486 Ergebnis: negativ

Karzinogenität

Nicht klassifiziert nach den vorliegenden Informationen.

Reproduktionstoxizität

Nicht klassifiziert nach den vorliegenden Informationen.

Inhaltsstoffe:

1,2-Benzisothiazol-3(2H)-on:

Wirkung auf die Fruchtbarkeit	:	Art des Testes: Fruchtbarkeit / frühe Embryonalentwicklung Spezies: Ratte Applikationsweg: Verschlucken Methode: OPPTS 870.3800

Ergebnis: negativ

Spezifische Zielorgan-Toxizität bei einmaliger Exposition
Nicht klassifiziert nach den vorliegenden Informationen.

Spezifische Zielorgan-Toxizität bei wiederholter Exposition
Nicht klassifiziert nach den vorliegenden Informationen.

Inhaltsstoffe:

1,2-Benzisothiazol-3(2H)-on:

Bewertung	:	Keine signifikanten gesundheitlichen Effekte bei Tieren in Konzentrationen von 100 mg/kg bw oder weniger.

Toxizität bei wiederholter Verabreichung

Inhaltsstoffe:

1,2-Benzisothiazol-3(2H)-on:

Spezies	:	Hund
NOAEL	:	5 mg/kg
LOAEL	:	20 mg/kg
Applikationsweg	:	Verschlucken
Expositionszeit	:	90 Tage
Methode	:	Richtlinie 67/548/EWG, Anhang V, B.27.

Aspirationstoxizität
Nicht klassifiziert nach den vorliegenden Informationen.

11.2 Angaben über sonstige Gefahren

Endokrinschädliche Eigenschaften
Nicht klassifiziert nach den vorliegenden Informationen.

Produkt:

Bewertung	:	Der Stoff/dieses Gemisch enthält keine Bestandteile, die gemäß REACH Artikel 57(f) oder der delegierten Verordnung (EU) 2017/2100 der Kommission oder der delegierten Verordnung (EU) 2018/605 der Kommission in Mengen von 0,1 % oder mehr endokrinschädliche Eigenschaften aufweisen.

ABSCHNITT 12: Umweltbezogene Angaben

12.1 Toxizität

Inhaltsstoffe:

1,2-Benzisothiazol-3(2H)-on:

Toxizität gegenüber Fischen	:	LC50 (Oncorhynchus mykiss (Regenbogenforelle)): 0,74 mg/l

Expositionszeit: 96 h

Toxizität gegenüber Daphnien und anderen wirbellosen Wassertieren	:	EC50 (Daphnia magna (Großer Wasserfloh)): 2,24 mg/l Expositionszeit: 48 h
Toxizität gegenüber Algen/Wasserpflanzen	:	ErC50 (Pseudokirchneriella subcapitata (Grünalge)): 0,1087 mg/l Expositionszeit: 24 h EC10 (Pseudokirchneriella subcapitata (Grünalge)): 0,0268 mg/l Expositionszeit: 24 h
M-Faktor (Akute aquatische Toxizität)	:	1
Toxizität bei Mikroorganismen	:	NOEC : 10,3 mg/l Expositionszeit: 3 h Methode: OECD- Prüfrichtlinie 209
Toxizität gegenüber Fischen (Chronische Toxizität)	:	NOEC: 0,28 mg/l Expositionszeit: 33 d Spezies: Pimephales promelas (fettköpfige Elritze) Methode: OECD- Prüfrichtlinie 210
Toxizität gegenüber Daphnien und anderen wirbellosen Wassertieren (Chronische Toxizität)	:	NOEC: 0,91 mg/l Expositionszeit: 21 d Spezies: Daphnia magna (Großer Wasserfloh) Methode: OECD- Prüfrichtlinie 211
M-Faktor (Chronische aquatische Toxizität)	:	1

Reaktionsmasse von: 5-Chlor-2-methyl-2H-isothiazol-3-on [EG Nr. 247-500-7] und 2-Methyl-2H-isothiazol-3-on [EG Nr. 220-239-6] (3:1):

Toxizität gegenüber Fischen	:	LC50 (Oncorhynchus mykiss (Regenbogenforelle)): 0,19 mg/l Expositionszeit: 96 h
Toxizität gegenüber Daphnien und anderen wirbellosen Wassertieren	:	EC50 (Daphnia magna (Großer Wasserfloh)): 0,16 mg/l Expositionszeit: 48 h
Toxizität gegenüber Algen/Wasserpflanzen	:	ErC50 (Skeletonema costatum (Kieselalge)): 0,0052 mg/l Expositionszeit: 48 h NOEC (Skeletonema costatum (Kieselalge)): 0,00049 mg/l Expositionszeit: 48 h
M-Faktor (Akute aquatische Toxizität)	:	100
Toxizität gegenüber Fischen (Chronische Toxizität)	:	NOEC: 0,02 mg/l Expositionszeit: 36 d

Spezies: Pimephales promelas (fettköpfige Elritze)

Toxizität gegenüber Daphnien und anderen wirbellosen Wassertieren (Chronische Toxizität)	:	NOEC: 0,10 mg/l Expositionszeit: 21 d Spezies: Daphnia magna (Großer Wasserfloh)
M-Faktor (Chronische aquatische Toxizität)	:	100

12.2 Persistenz und Abbaubarkeit

Inhaltsstoffe:

Reaktionsmasse von: 5-Chlor-2-methyl-2H-isothiazol-3-on [EG Nr. 247-500-7] und 2-Methyl-2H-isothiazol-3-on [EG Nr. 220-239-6] (3:1):

Biologische Abbaubarkeit	:	Ergebnis: Nicht leicht biologisch abbaubar. Biologischer Abbau: 62 % Expositionszeit: 28 d Methode: OECD Prüfrichtlinie 301B

12.3 Bioakkumulationspotenzial

Inhaltsstoffe:

1,2-Benzisothiazol-3(2H)-on:

Bioakkumulation	:	Spezies: Lepomis macrochirus (Blauer Sonnenbarsch) Biokonzentrationsfaktor (BCF): 6,62
Verteilungskoeffizient: n-Octanol/Wasser	:	log Pow: 0,7

Reaktionsmasse von: 5-Chlor-2-methyl-2H-isothiazol-3-on [EG Nr. 247-500-7] und 2-Methyl-2H-isothiazol-3-on [EG Nr. 220-239-6] (3:1):

Verteilungskoeffizient: n-Octanol/Wasser	:	log Pow: < 1

12.4 Mobilität im Boden

Keine Daten verfügbar

12.5 Ergebnisse der PBT- und vPvB-Beurteilung

Produkt:

Bewertung	:	Dieser Stoff/diese Mischung enthält keine Komponenten in Konzentrationen von 0,1 % oder höher, die entweder als persistent, bioakkumulierbar und toxisch (PBT) oder sehr persistent und sehr bioakkumulierbar (vPvB) eingestuft sind.

12.6 Endokrinschädliche Eigenschaften

Produkt:

Bewertung	:	Der Stoff/dieses Gemisch enthält keine Bestandteile, die gemäß REACH Artikel 57(f) oder der delegierten Verordnung

(EU) 2017/2100 der Kommission oder der delegierten Verordnung (EU) 2018/605 der Kommission in Mengen von 0,1 % oder mehr endokrinschädliche Eigenschaften aufweisen.

12.7 Andere schädliche Wirkungen

Keine Daten verfügbar

ABSCHNITT 13: Hinweise zur Entsorgung

13.1 Verfahren der Abfallbehandlung

Produkt	:	Unter Beachtung der örtlichen behördlichen Bestimmungen beseitigen. Gemäß europäischem Abfallkatalog (EAK) sind Abfallschlüsselnummern nicht produkt- sondern anwendungsbezogen. Abfallschlüsselnummern sollen vom Verbraucher, möglichst in Absprache mit den Abfallentsorgungsbehörden, ausgestellt werden. Abfälle nicht in den Ausguss schütten.
Verunreinigte Verpackungen	:	Leere Behälter einer anerkannten Abfallentsorgungsanlage zuführen zwecks Wiedergewinnung oder Entsorgung. Falls nicht anders angegeben: Entsorgung als unbenutztes Produkt.
Abfallschlüssel-Nr.	:	Die folgenden Abfallschlüsselnummern sind nur als Empfehlung gedacht: gebrauchtes Produkt 08 04 10, Klebstoff- und Dichtmassenabfälle mit Ausnahme derjenigen, die unter 08 04 09 fallen nicht gebrauchtes Produkt 08 04 10, Klebstoff- und Dichtmassenabfälle mit Ausnahme derjenigen, die unter 08 04 09 fallen ungereinigte Verpackung 15 01 06, gemischte Verpackungen Gem. Verpackungsgesetz restentleerte Verpackungen: Restentleerte, nicht kontaminierte Verpackungen nicht schadstoffhaltiger Füllgüter können den Erfassungssystemen für Verkaufsverpackungen zur Verwertung zugeführt werden.

ABSCHNITT 14: Angaben zum Transport

14.1 UN-Nummer oder ID-Nummer

ADN	:	Nicht als Gefahrgut eingestuft

ADR	:	Nicht als Gefahrgut eingestuft
RID	:	Nicht als Gefahrgut eingestuft
IMDG	:	Nicht als Gefahrgut eingestuft
IATA	:	Nicht als Gefahrgut eingestuft

14.2 Ordnungsgemäße UN-Versandbezeichnung

ADN	:	Nicht als Gefahrgut eingestuft
ADR	:	Nicht als Gefahrgut eingestuft
RID	:	Nicht als Gefahrgut eingestuft
IMDG	:	Nicht als Gefahrgut eingestuft
IATA	:	Nicht als Gefahrgut eingestuft

14.3 Transportgefahrenklassen

ADN	:	Nicht als Gefahrgut eingestuft
ADR	:	Nicht als Gefahrgut eingestuft
RID	:	Nicht als Gefahrgut eingestuft
IMDG	:	Nicht als Gefahrgut eingestuft
IATA	:	Nicht als Gefahrgut eingestuft

14.4 Verpackungsgruppe

ADN	:	Nicht als Gefahrgut eingestuft
ADR	:	Nicht als Gefahrgut eingestuft
RID	:	Nicht als Gefahrgut eingestuft
IMDG	:	Nicht als Gefahrgut eingestuft
IATA (Fracht)	:	Nicht als Gefahrgut eingestuft
IATA (Passagier)	:	Nicht als Gefahrgut eingestuft

14.5 Umweltgefahren

Nicht als Gefahrgut eingestuft

14.6 Besondere Vorsichtsmaßnahmen für den Verwender

Nicht anwendbar

14.7 Massengutbeförderung auf dem Seeweg gemäß IMO-Instrumenten

Anmerkungen : Auf Produkt im Lieferzustand nicht zutreffend.

ABSCHNITT 15: Rechtsvorschriften

15.1 Vorschriften zu Sicherheit, Gesundheits- und Umweltschutz/spezifische Rechtsvorschriften für den Stoff oder das Gemisch

REACH - Beschränkungen der Herstellung, des Inverkehrbringens und der Verwendung bestimmter gefährlicher Stoffe, Gemische und Erzeugnisse (Anhang XVII) :

Stoff(e) oder Gemisch(e) werden hier entsprechend ihrem Vorkommen in der Verordnung aufgeführt, unabhängig von ihrer Verwendung/ihrem Zweck oder den Bedingungen der Beschränkung. Bitte beachten Sie die Bedingungen in der entsprechenden Verordnung, um festzustellen, ob ein Eintrag für das Inverkehrbringen relevant ist oder nicht.
Die Beschränkungsbedingungen für folgende Einträge sollten berücksichtigt werden:
Nummer in der Liste 75: Wenn Sie beabsichtigen, dieses Produkt als Tätowiertinte zu verwenden, wenden Sie sich bitte an Ihren Verkäufer.

REACH - Liste der für eine Zulassung in Frage kommenden besonders besorgniserregenden Stoffe (Artikel 59).	:	Nicht anwendbar
Verordnung (EG) Nr. 2024/590 über Stoffe, die zum Abbau der Ozonschicht führen	:	Nicht anwendbar
Verordnung (EU) 2019/1021 über persistente organische Schadstoffe (Neufassung)	:	Nicht anwendbar
Verordnung (EU) Nr. 649/2012 des Europäischen Parlaments und des Rates über die Aus- und Einfuhr gefährlicher Chemikalien	:	Nicht anwendbar
REACH - Verzeichnis der zulassungspflichtigen Stoffe (Anhang XIV)	:	Nicht anwendbar

Die behandelte Ware enthält Biozidprodukte

Wirkstoffe	:	Reaktionsmasse von: 5-Chlor-2-methyl-2H-isothiazol-3-on [EG Nr. 247-500-7] und 2-Methyl-2H-isothiazol-3-on [EG Nr. 220-239-6] (3:1)

Seveso III: Richtlinie 2012/18/EU des Europäischen Parlaments und des Rates zur Beherrschung der Gefahren schwerer Unfälle mit gefährlichen Stoffen.
Nicht anwendbar

Wassergefährdungsklasse	:	WGK 1 schwach wassergefährdend Einstufung nach AwSV, Anlage 1 (5.2)

TA Luft	:	5.2.5: Organische Stoffe: Klasse 1: Ethylacrylat
Flüchtige organische Verbindungen	:	Richtlinie 2010/75/EU des Europäischen Parlaments und des Rates vom 24. November 2010 über Emissionen aus Industrie und Tierhaltung (integrierte Vermeidung und Verminderung der Umweltverschmutzung) Gehalt flüchtiger organischer Verbindungen (VOC): 0 %

15.2 Stoffsicherheitsbeurteilung

Eine Stoffsicherheitsbewertung wurde nicht durchgeführt.

ABSCHNITT 16: Sonstige Angaben

Sonstige Angaben	:	Positionen, bei denen Veränderungen gegenüber der vorherigen Fassung vorgenommen wurden, sind im Textkörper durch zwei vertikale Linien hervorgehoben.

Volltext der H-Sätze

H301	:	Giftig bei Verschlucken.
H302	:	Gesundheitsschädlich bei Verschlucken.
H310	:	Lebensgefahr bei Hautkontakt.
H314	:	Verursacht schwere Verätzungen der Haut und schwere Augenschäden.
H315	:	Verursacht Hautreizungen.
H317	:	Kann allergische Hautreaktionen verursachen.
H318	:	Verursacht schwere Augenschäden.
H330	:	Lebensgefahr bei Einatmen.
H400	:	Sehr giftig für Wasserorganismen.
H410	:	Sehr giftig für Wasserorganismen, mit langfristiger Wirkung.
EUH071	:	Wirkt ätzend auf die Atemwege.

Volltext anderer Abkürzungen

Acute Tox.	:	Akute Toxizität
Aquatic Acute	:	Kurzfristig (akut) gewässergefährdend
Aquatic Chronic	:	Langfristig (chronisch) gewässergefährdend
Eye Dam.	:	Schwere Augenschädigung
Skin Corr.	:	Ätzwirkung auf die Haut
Skin Irrit.	:	Reizwirkung auf die Haut
Skin Sens.	:	Sensibilisierung durch Hautkontakt

ADN - Europäisches Übereinkommen über die internationale Beförderung gefährlicher Güter auf Binnenwasserstrassen; ADR - Übereinkommen über die internationale Beförderung gefährlicher Güter auf der Straße; AIIC - Australisches Verzeichnis von Industriechemikalien; ASTM - Amerikanische Gesellschaft für Werkstoffprüfung; bw - Körpergewicht; CLP - Verordnung über die Einstufung, Kennzeichnung und Verpackung von Stoffen, Verordnung (EG) Nr 1272/2008; CMR - Karzinogener, mutagener oder reproduktiver Giftstoff; DIN - Norm des Deutschen Instituts

für Normung; DSL - Liste heimischer Substanzen (Kanada); ECHA - Europäische Chemikalienbehörde; EC-Number - Nummer der Europäischen Gemeinschaft; ECx - Konzentration verbunden mit x % Reaktion; ELx - Beladungsrate verbunden mit x % Reaktion; EmS - Notfallplan; ENCS - Vorhandene und neue chemische Substanzen (Japan); ErCx - Konzentration verbunden mit x % Wachstumsgeschwindigkeit; GHS - Global harmonisiertes System; GLP - Gute Laborpraxis; IARC - Internationale Krebsforschungsagentur; IATA - Internationale Luftverkehrs-Vereinigung; IBC - Internationaler Code für den Bau und die Ausrüstung von Schiffen zur Beförderung gefährlicher Chemikalien als Massengut; IC50 - Halbmaximale Hemmstoffkonzentration; ICAO - Internationale Zivilluftfahrt-Organisation; IECSC - Verzeichnis der in China vorhandenen chemischen Substanzen; IMDG - Code – Internationaler Code für die Beförderung gefährlicher Güter mit Seeschiffen; IMO - Internationale Seeschifffahrtsorganisation; ISHL - Gesetz- über Sicherheit und Gesundheitsschutz am Arbeitsplatz (Japan); ISO - Internationale Organisation für Normung; KECI - Verzeichnis der in Korea vorhandenen Chemikalien; LC50 - Lethale Konzentration für 50 % einer Versuchspopulation; LD50 - Lethale Dosis für 50 % einer Versuchspopulation (mittlere lethale Dosis); MARPOL - Internationales Übereinkommen zur Verhütung der Meeresverschmutzung durch Schiffe; n.o.s. - nicht anderweitig genannt; NO(A)EC - Konzentration, bei der keine (schädliche) Wirkung erkennbar ist; NO(A)EL - Dosis, bei der keine (schädliche) Wirkung erkennbar ist; NOELR - Keine erkennbare Effektladung; NZIoC - Neuseeländisches Chemikalienverzeichnis; OECD - Organisation für wirtschaftliche Zusammenarbeit und Entwicklung; OPPTS - Büro für chemische Sicherheit und Verschmutzungsverhütung (OSCPP); PBT - Persistente, bioakkumulierbare und toxische Substanzen; PICCS - Verzeichnis der auf den Philippinen vorhandenen Chemikalien und chemischen Substanzen; (Q)SAR - (Quantitative) Struktur-Wirkungsbeziehung; REACH - Verordnung (EG) Nr. 1907/2006 des Europäischen Parliaments und des Rats bezüglich der Registrierung, Bewertung, Genehmigung und Restriktion von Chemikalien; RID - Regelung zur internationalen Beförderung gefährlicher Güter im Schienenverkehr; SADT - Selbstbeschleunigende Zersetzungstemperatur; SDS - Sicherheitsdatenblatt; SVHC - besonders besorgniserregender Stoff; TCSI - Verzeichnis der in Taiwan vorhandenen chemischen Substanzen; TECI - Thailand Lagerbestand Vorhandener Chemikalien; TRGS - Technischen Regeln für Gefahrstoffe; TSCA - Gesetz zur Kontrolle giftiger Stoffe (Vereinigte Staaten); UN - Vereinte Nationen; vPvB - Sehr persistent und sehr bioakkumulierbar

Weitere Information

Quellen der wichtigsten Daten, die zur Erstellung des Datenblatts verwendet wurden	:	Interne technische Daten, Rohstoffdaten von den SDB, Suchergebnisse des OECD eChem Portals und der Europäischen Chemikalienagentur, http://echa.europa.eu/

Die in diesem Sicherheitsdatenblatt enthaltenenen Informationen sind nach bestem Wissen und Gewissen erstellt worden und basieren auf dem Wissensstand zum Zeitpunkt der Veröffentlichung. Die Informationen dienen lediglich als Richtlinie für eine sichere Handhabung, Verwendung, Verarbeitung, Lagerung, Transport, Entsorgung und Freisetzung und stellen keine Gewährleistung oder Qualitätsspezifikation dar. Die vorliegenden Informationen beziehen sich nur auf den oben in diesem SDB bezeichneten Stoff und gelten nicht bei Verwendung des im SDB angegebenen Stoffes in Kombination mit anderen Stoffen oder in anderen Verfahren, sofern nicht anders im Text angegeben ist. Anwender des Stoffes sollten die Informationen und Empfehlungen im konkreten Einzelfall der vorgesehenen Handhabung, Verwendung, Verarbeitung und Lagerung, einschließlich gegebenenfalls einer Beurteilung der Angemessenheit des im SDB bezeichneten Stoffes im Endprodukt des Anwenders, überprüfen.

DE / DE

HERSTELLERERKLÄRUNG

Firma	Adolf Würth GmbH & Co. KG
Artikelnummer	0893700111, 0893700112
Produktbezeichnung	Anschlussklebstoff All-in-One
Anwendung/ Beschreibung	Zur dauerhaften Abdichtung aller Anschlussfugen im Luft- und Winddichtbereich und bei der Fenster- und Türenmontage im Innen – und Außenbereich.

Anforderungen	Erfüllt	Bemerkung
SVHC	Ja	s. SDB* (Abschnitt 3.2)
VOC-Gehalt	Ja	s. SDB* (Abschnitt 15.1)
CMR-Stoffe der Kategorie 1A/1B < 0,10%	Ja	
Chlorparaffine SCCPs < 0,10 %	Ja	
Chlorparaffine MCCPs < 0,10 %	Ja	
Chlorparaffine LCCPs < 0,10 %	Ja	
TCEP < 0,10 %	Ja	
PBB < 0,10 %	Ja	
PBDE < 0,10 %	Ja	
halogenierte Treibmittel < 0,10 %	Ja	

Vorhandene Dokumente

Sicherheitsdatenblatt (SDB*)	s. Onlineshop
Prüfzeugnisse Sonstiges	EC1+

01/26

Dieses Dokument ist ohne Unterschrift gültig.

Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e.V.

GEV EMICODE®

Lizenzerteilung zur Führung des EMICODE

Lizenzierungs-Nummer: 8154/01.01.11

Für den Artikel Anschlussklebstoff ALL-IN-ONE

wird auf Antrag vom 14.06.2017

unter Bezugnahme auf die Einstufung gemäß den nach § 10 der GEV-Zeichensatzung festgelegten Richtlinien

namens der Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e.V. für den oben genannten Artikel nach § 5 Abs. 4 der GEV-Zeichensatzung die Lizenz zur Führung des GEV-Zeichens

GEV-EMICODE® EC 1 PLUS sehr emissionsarm

erteilt. Damit erfüllt dieser Artikel die rückseitig aufgeführten Kriterien.
Die Firma ist ordentliches Mitglied der GEV.

OM071 14.06.2022
gültig bis 14.06.2027

Der Geschäftsführer
Gemeinschaft Emissionskontrollierte Verlegewerkstoffe,
Klebstoffe und Bauprodukte e.V.
Völklinger Straße 4 · D-40219 Düsseldorf

Hinweise zu den Voraussetzungen über die Vergabe der Lizenz für den EMICODE

Das gemäß vorseitiger Lizenz eingestufte Produkt hat nach der Satzung und den Richtlinien des Technischen Beirats der GEV u.a. den folgenden Kriterien zu genügen:

- Das Produkt entspricht allen gesetzlichen Bestimmungen, insbesondere denen des Chemikalienrechtes und seiner Verordnungen.
- Das Produkt ist nach der Definition der TRGS 610 lösemittelfrei, sofern es sich nicht um ein Oberflächenprodukt handelt. Soweit es einer Produktgruppe nach GISCODE zuzuordnen ist, wird diese angegeben.
- Für das Produkt wird ein Sicherheitsdatenblatt nach lokalem Recht in der jeweils aktuellen Fassung erstellt.
- Krebserregende, erbgutverändernde oder fruchtschädigende Stoffe der Klassen 1A und 1B werden dem Produkt bei der Herstellung nicht zugesetzt.
- Die Prüfung des Produktes erfolgt nach der definierten „GEV-Prüfmethode“. Die VOC-Bestimmung wird dabei in einer Prüfkammer nach dem Tenax-Thermodesorptions-Verfahren mit nachgeschalteter GC/MS-Analyse durchgeführt.
- Die Einstufung in EMICODE-Klassen erfolgt entsprechend den nachstehenden Bezeichnungen und TVOC/TSVOC-Konzentrationsbereichen. Zur Produktkennzeichnung ist die zutreffende EMICODE-Klasse zu verwenden:

1) Verlegewerkstoffe, Klebstoffe und Bauprodukte

Parameter	EC 1 PLUS	EC 1	EC 2
	max. zulässige Konzentration [µg/m³]		
TVOC nach 3 Tagen	≤ 750	≤ 1000	≤ 3000
TVOC nach 28 Tagen	≤ 60	≤ 100	≤ 300
TSVOC nach 28 Tagen	≤ 40	≤ 50	≤ 100
R-Wert basierend auf AgBB-NIK-Werten nach 28 Tagen	1	-	-
Summe der nicht bewertbaren VOC	≤ 40	-	-
Formaldehyd nach 3 Tagen	≤ 50	≤ 50	≤ 50
Acetaldehyd nach 3 Tagen	≤ 50	≤ 50	≤ 50
Summe von Form- und Acetaldehyd	≤ 0,05 ppm	≤ 0,05 ppm	≤ 0,05 ppm
Summe von flüchtigen K1A/K1B Stoffen nach 3 Tagen	≤ 10	≤ 10	≤ 10
Jeder flüchtige K1A/K1B Stoff nach 28 Tagen	≤ 1	≤ 1	≤ 1

2) Oberflächenbehandlungsmittel für Parkett, mineralische Böden und elastische Bodenbeläge

Parameter	EC 1 PLUS	EC 1	EC 2
	max. zulässige Konzentration [µg/m³]		
Summe TVOC + TSVOC nach 28 Tagen	≤ 100 davon max. 40 SVOC	≤ 150 davon max. 50 SVOC	≤ 450 davon max. 100 SVOC
Formaldehyd nach 3 Tagen	≤ 50	≤ 50	≤ 50
Acetaldehyd nach 3 Tagen	≤ 50	≤ 50	≤ 50
Jeder flüchtige K1A/K1B Stoff nach 3 Tagen	≤ 10	≤ 10	≤ 10
Jeder flüchtige K1A/K1B Stoff nach 28 Tagen	≤ 1	≤ 1	≤ 1

STATEMENT OF CONFORMITY

Adolf Würth GmbH & Co. KG confirms that the following products are compliant with Model EPD:

Declaration number:	EPD-DBC-20220147-IBF1-EN
Würth Compliant Product Numbers:	0893700111, 0893700112
EPD-Name:	Dispersion-based products, group 2

In collaboration, the Deutsche Bauchemie e.V. (DBC), the Association of the European Adhesive and Sealant Industry (FEICA), the Industrieverband Klebstoffe e.V. (IVK), and the European Federation for Construction Chemicals (EFFCC) have developed model Environmental Product Declarations for a variety of construction chemical products. These declarations have been verified and published by the IBU (Institut Bauen und Umwelt).

This declaration confirms the compliance of above mentioned product with the specific model EPD.

07.08.2025

ENVIRONMENTAL PRODUCT DECLARATION

as per *ISO 14025* and *EN 15804+A2*

Owner of the Declaration	DBC, EFCC, FEICA, IVK
Programme holder	Institut Bauen und Umwelt e.V. (IBU)
Publisher	Institut Bauen und Umwelt e.V. (IBU)
Declaration number	EPD-DBC-20220147-IBF1-EN
Issue date	08.06.2022
Valid to	07.06.2027

Dispersion-based products, group 2

DBC - Deutsche Bauchemie e.V.

EFCC - European Federation for Construction Chemicals

FEICA - Association of the European Adhesive and Sealant Industry

IVK - Industrieverband Klebstoffe e.V.

Institut Bauen und Umwelt e.V.

www.ibu-epd.com | https://epd-online.com

ECO PLATFORM EPD VERIFIED



1. General Information

DBC - Deutsche Bauchemie e.V.
EFCC - European Federation for Construction Chemicals
FEICA - Association of the European Adhesive and Sealant Industry
IVK - Industrieverband Klebstoffe e.V.

Dispersion-based products, group 2

Programme holder
IBU – Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

Owner of the declaration
DBC, Mainzer Landstr. 55, D-60329 Frankfurt a.M.
EFCC, 172 Boulevard du Triomphe, B-1160 Brussels
FEICA, Rue Belliard 40, B-1040 Brussels
IVK, Völklingerstr. 4, D-40219 Düsseldorf

Declaration number
EPD-DBC-20220147-IBF1-EN

Declared product / declared unit
1 kg / 1 kg; density 1,000 - 1,500 kg/m³

This declaration is based on the product category rules:
Dispersion adhesives and primers for floor coverings, 01.2019
(PCR checked and approved by the SVR)

Scope:
This verified EPD entitles the holder to bear the symbol of the Institut Bauen und Umwelt e.V. It exclusively applies for products produced in Europe and for a period of five years from the date of issue. This EPD may be used by members of DBC, EFCC, FEICA and IVK and their members provided it has been proven that the respective product can be represented by this EPD. For this purpose, a guideline is available at the secretariats of the four associations. The members of the associations are listed on the respective websites.

Issue date
08.06.2022

Valid to
07.06.2027

The owner of the declaration shall be liable for the underlying information and evidence; the IBU shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.
The EPD was created according to the specifications of *EN 15804+A2*. In the following, the standard will be simplified as *EN 15804*.

Verification

The standard *EN 15804* serves as the core PCR
Independent verification of the declaration and data according to *ISO 14025:2011*
☐ internally ☒ externally

Dipl. Ing. Hans Peters
(chairman of Institut Bauen und Umwelt e.V.)

Dr. Alexander Röder
(Managing Director Institut Bauen und Umwelt e.V.))

Matthias Schulz
(Independent verifier)

2. Product

2.1 Product description/Product definition

This EPD comprises dispersion-based products with a Volatile Organic Compound (VOC) content ≤1 % (VOC definition according to *Decopaint Directive*). The products typically consist of organic binding agents based on synthetic and/or natural resins, mineral fillers such as chalk as well as water and smaller volumes of auxiliaries (thickening agents, defoaming agents, surface-active agents, preservatives etc.). They dry physically through evaporation of the water contained therein. They comply with manifold, often specific, functions in the construction, furnishing and repair of buildings. Using dispersion-based products decisively improves the fitness for use of structures and extends their life expectancy. The product displaying the highest environmental impacts within the class of dispersion-based products considered was used as a representative product for calculating the Life Cycle Assessment results (worst-case approach).

For the placing on the market in the European Union/European Free Trade Association (EU/EFTA) with the exception of Switzerland) products falling under the Regulation (EU) No 305/2011 (*CPR*) need a Declaration of Performance taking into consideration either the relevant harmonised European standard or the European Technical Assessment and the CE

marking. For the application and use of the products the respective national provisions apply.

2.2 Application

Dispersion-based products are used for the following applications:

Module 1: Dispersion adhesives, fixatives, precoatings and primers for floor coverings and parquet flooring
Adhesives for, e.g. tufted carpets with various backings, woven textile coverings, fibre-bonded and natural fibre coverings, resilient coverings (PVC, rubber, PVC-free luxury vinyl tiles), linoleum, insulating bases and underlays, parquet, laminate and wood blocks on surfaces ready for laying. The products are suitable for normal wear in residential and commercial areas, also on heated floor constructions.

Module 2: Dispersion-based tile adhesive
Products for bonding ceramic tiles and paving as well as natural stone for internal and external installations on walls, floors and ceilings

Module 3: *Dispersion-based adhesives and sealants*
As structural adhesives and sealants: structural and repair adhesives, dispersion filler compounds, joint sealants

Module 4: Dispersion-based products for waterproofing of buildings
Products for waterproofing floors and/or walls in wet rooms inside buildings

Module 5: Dispersion-based primers and bonding agents for concrete and floor screeds
Products to improve the adhesion of e.g. self-levelling compounds or repair mortars on absorbent cement and calcium sulphate screeds, concrete, dry construction boards

Module 6: Dispersion-based products for surface protection of concrete
To increase the durability of concrete and reinforced steel structures as well as for new concrete and for maintenance and repair work (for areas without vehicle traffic)

Module 7: Dispersion-based primers and barrier coatings
Products to protect a substrate from e.g. the immersion of water, thus preventing degradation, corrosion or damage

2.3 Technical Data

The density of the products is between 1,00 and 1,50 g/cm³, other relevant technical data can be found in the manufacturer’s technical documentation.

Module 1: Dispersion adhesives, fixatives, precoatings and primers for floor coverings and parquet flooring
Dispersion adhesives for floor coverings have to comply with the requirements of the *EN ISO 22636*. The mechanical requirements of *EN ISO 22636* don’t apply to fixatives; their strengths are lower in accordance with their specifications. The performance characteristics of precoatings and primers are subject to the manufacturer's technical documentation / declaration of performance. Dispersion adhesives for parquet: The test procedures and requirements of the *EN ISO 17178* have to be fulfilled.

Module 2: Dispersion-based tile adhesive
The requirements on essential characteristics according to *EN 12004*, must be maintained. These are:
Tensile adhesion strength after dry storage (*EN 12004-2*)
-Tensile adhesion strength after water immersion (*EN 12004-2*)
-Tensile adhesion strength after heat ageing (*EN 12004*)
-Tensile adhesion strength after freeze/thaw cycles (*EN 12004-2*)
-Open time: Tensile strength (*EN 12004-2*)
Further essential characteristics in accordance with the manufacturer's technical documentation

Module 3: Dispersion-based adhesives and sealants
Performance characteristics in accordance with the manufacturer's technical documentation / declaration of performance

Module 4: Dispersion-based products for waterproofing of buildings
The minimum requirement of *EAD 030352-00-0503* - Liquid applied watertight covering kits for wet room floors and/or walls- must be maintained. The essential characteristics are to be specified in accordance with the European technical assessment (ETA, specification no.).

Module 5: Dispersion-based primers and bonding agents for concrete and floor screeds
Performance characteristics in accordance with the manufacturer's technical documentation

Module 6: Dispersion-based products for surface protection of concrete
The requirements on essential characteristics for all intended uses in accordance with *EN 1504-2*, Tables 1 and 5, must be maintained. These are:
- Permeability to CO_2 (*EN 1062-6*)
- Water vapour permeability (*EN ISO 7783-1/-2*)
- Capillary absorption and permeability to water (*EN 1062-3*)
- Adhesion strength by pull-off test (*EN 1542*)

Further essential characteristics in accordance with the manufacturer's technical documentation / declaration of performance

Module 7: Dispersion-based primers and barrier coatings
The requirements of the *Decopaint Directive* must be maintained.
Essential characteristics in accordance with the manufacturer's technical documentation / declaration of performance.

2.4 Delivery status

Liquid or pasty in containers made of plastic or metal. Typical container sizes contain 1 to 30 kg, usually 10 to 20 kg of product on pallets. For larger applications, vats with approx. volumes of 200 kg (litres) or IBCs

(intermediate bulk containers) with a capacity of 1 tonne (m³) or more are also used. A plastic container was modelled for the Life Cycle Assessment.

2.5 Base materials/Ancillary materials

Dispersion-based products usually comprise at least one synthetic resin dispersion, natural or synthetic resins dispersed in water, mineral fillers (e.g. chalk) and/or pigments. Auxiliaries such as thickening agents, defoaming agents, surface-active and dispersing agents as well as preservatives are used to fine-tune the product features. **Typically**, the products covered by this EPD contain the following range of base materials and auxiliaries (% by mass):

- Synthetic polymer dispersion (solids portion): 5 - 65
- Natural resins, natural resin derivatives: 0 - 25
- Mineral fillers: 0 - 60
- Pigments: 0 - 35
- Water: 15 - 95
- Auxiliaries: 1 - 5
- Thickening agents: < 3
- Dispersing agents / Emulsifying agents: < 2
- Wetting agent: 2
- Other: 0 - 2
- VOC according to *Decopaint Directive*: <1 % **(mandatory)**

These ranges are average values and the composition of products complying with the EPD can deviate from these concentration levels in individual cases. More detailed information is available in the respective manufacturer's documentation (e.g. product data sheets).

Note: For companies to declare their products within the scope of this EPD it is not sufficient to simply comply with the product composition shown above. The application of this EPD is only possible for member companies of DBC, EFCC, FEICA, and IVK member associations and only for specific formulations with a total score below the declared maximum score for a product group according to the associated guidance document.

1. substances from the "Candidate List of Substances of Very High Concern for Authorisation" (SVHC)

If this product contains substances listed in the *candidate list* (latest version) exceeding 0.1 percentage by mass, the relevant information can be found in the safety data sheet of the relevant product covered by this model EPD.

2. CMR substances in categories 1A and 1B

If this product contains other carcinogenic, mutagenic, reprotoxic (CMR) substances in categories 1A or 1B which are not on the *candidate list*, exceeding 0.1 percentage by mass, the relevant information can be found in the safety data sheet of the relevant product covered by this model EPD.

3. Biocide products added to the construction product

If this construction product contains biocide products, the active substances, information on the concentration and/or concentration range, the product type together with information on their hazardous properties are listed in the safety data sheet of the respective product.

2.6 Manufacture

Dispersion-based products are usually mixed discontinuously in batch mode, i.e. in individual batches or a series of individual batches, and filled into the delivery containers.

2.7 Environment and health during manufacturing

As a general rule, no particular environmental or health protection measures other than those specified by law are necessary.

2.8 Product processing/Installation

Dispersion based products are processed on site using suitable tools, usually by hand. The products are applied by trowelling/knife-coating, painting, rolling or spraying. Precautions for safe handling and storage (e.g. air exchange, exhaust ventilation, personal protective measures, conditions for safe storage) must be observed in accordance with the information on the safety data sheet.

Depending on the application and product specifications, between 50 and 1,500 g/m² are applied.

2.9 Packaging

A detailed description of packaging is provided in section 2.4. Empty containers and clean foils can be recycled.

2.10 Condition of use

During the use phase, dispersion-based products are existent as hardened film. They are long-lasting products which protect our buildings in the form of adhesives, primers, coatings or sealants as well as make an essential contribution towards their appearance, function and sustainability.

2.11 Environment and health during use

Option 1 – Products for applications outside indoor areas with permanent stays by people

No risks are known for water, air and soil if the products are used as designated.

Option 2 – Products for applications inside indoor areas with permanent stays by people

When used in indoor areas with permanent stays by people, evidence of the emission performance of construction products in contact with indoor air must be submitted according to national requirements (see chapter 7). No further influences by emissions on the environment and health are known.

2.12 Reference service life

Dispersion-based products fulfill manifold, often specific, functions in the construction or refurbishment of building structures. They decisively improve the usability of building structures and significantly extend their original service lives. The anticipated reference service life depends on the specific installation situation and the exposure associated with the product. It can be influenced by weathering as well as mechanical or chemical load.

2.13 Extraordinary effects

Fire

In terms of the volumes applied, dispersion based products have no or only a marginal influence on the fire performance characteristics of the building structure in which they have been installed.

Water

Dispersion-based products are water-resistant only to a certain degree and their strength can deteriorate when exposed to water for longer periods (of time); detaching from the surface is possible in a worst-case scenario. The components of dispersion-based products are not hazardous to water or only slightly hazardous to water. Owing to the overall low volumes of dispersion-based products used on buildings, no relevant contribution towards environmental damage can be anticipated by buildings featuring dispersion-based products in the event of extraordinary exposure to water.

Mechanical destruction
The mechanical destruction of dispersion-based products does not lead to any decomposition products which are harmful to the environment or health.

2.14 Re-use phase
According to present knowledge, no environmentally hazardous effects in terms of landfilling are to be generally anticipated through dismantling and recycling components to which dispersion-based products have been applied and on which they have dried.

2.15 Disposal
The low amounts of a dispersion-based product applied to a construction product will not interfere with the disposal/recycling of this.
Hardened product residue mechanically removed from substrates must be disposed of as commercial/construction waste. The following waste codes according to the European List of Waste (*2000/532/EC*) can apply:
Hardened product residue:
080112 Paint and varnish waste with the exception of that covered by 08 01 11
080410 Adhesive and sealant compound waste with the exception of that covered by 08 04 09

2.16 Further information
More information is available on the manufacturer's product or safety data sheets and is available on the manufacturer's websites or on request. Valuable technical information is also available on the associations' websites.

3. LCA: Calculation rules

3.1 Declared Unit
This EPD refers to the declared unit of 1 kg of dispersion-based product, group 2; applied into the building with a density of 1,000 - 1,500 kg/m^3 in accordance with the *IBU PCR* part B for dispersion adhesives and primers for floor coverings.
The results of the Life Cycle Assessment provided in this declaration have been selected from the product with the highest environmental impact (worst-case scenario).
Depending on the application, a corresponding conversion factor such as the density to convert volumetric use to mass must be taken into consideration.

The Declaration type is according to *EN 15804*: Cradle to gate with options, modules C1–C3, and module D (A1–A3, C, D) and additional modules (A4-A5).

Declared unit

Name	Value	Unit
Declared unit	1	kg
Gross density	1,000-1,500	kg/m^3

3.2 System boundary
Modules A1, A2 and A3 are taken into consideration in the LCA:
- A1 Production of preliminary products
- A2 Transport to the plant
- A3 Production incl. provision of energy, production of packaging as well as auxiliaries and consumables and waste treatment
- A4 Transport to site
- A5 Installation, product applied into the building during A5 phase operations and packaging disposal. The end of life for the packaging material considered is described below:
  -Incineration, for materials like plastic and wood.
-C1-C2-C3-D

The building deconstruction (demolition process) takes place in the C1 module which considers energy production and consumption in terms of diesel and all the emissions connected with the fuel-burning process to run the machines. After the demolition, the product is transported to the end-of-life processing (C2 module) where all the impacts related to the transport processes are considered. For precautionary principle and as a worst-case scenario, thermal treatment is the only end of life scenario considered. This is modelled by the incineration process (module C3) where the product ends its life cycle.
Module D accounts for potential benefits that are beyond the defined system boundaries. Credits are generated during the incineration of wastes and related electricity produced that are occurring in the A5 module.

3.3 Estimates and assumptions
For this EPD formulation and production data defined and collected by FEICA were considered. Production waste was assumed to be disposed of by incineration without credits as a worst case.
An average of plastic containers and wooden pallets was considered in the LCA.

3.4 Cut-off criteria
All raw materials submitted for the formulations and production data were taken into consideration.
The manufacture of machinery, plant and other infrastructure required for the production of the products under review was not taken into consideration in the LCA.
Transport of packaging materials is excluded.

3.5 Background data
Data from the *GaBi* database SP40 (2020) was used as background data.

3.6 Data quality
Representative products were applied for this EPD and the product in the group displaying the highest environmental impact was selected for calculating the

LCA results. The background datasets used are less than 4 years old.
Production data and packaging are based on details provided by the manufacturer. The formulation used for evaluation refers to a specific product.
The data quality of the background data is considered to be good.

3.7 Period under review
Representative formulations are valid for 2021.

3.8 Allocation
Mass allocation has been applied when primary data have been used and implemented into the LCA model.

3.9 Comparability
Basically, a comparison or an evaluation of EPD data is only possible if all the data sets to be compared were created according to *EN 15804* and the building context, respectively the product-specific characteristics of performance, are taken into account.

The *GaBi* database SP40 (2020) was used.

4. LCA: Scenarios and additional technical information

Characteristic product properties
Information on biogenic Carbon
The packaging material contains biogenic carbon content which is presented below.

Information on describing the biogenic Carbon Content at factory gate

Name	Value	Unit
Biogenic carbon content in product	-	kg C
Biogenic carbon content in accompanying packaging	0.016	kg C

For the preparation of building life cycle assessments, it must be taken into account that in module A5 (installation in the building) the biogenic amount of CO_2 (0.016 kg C *3.67 = 0.059 kg CO_2-eq.) of the packaging bound in module A1-A3 is mathematically booked out.

Transport to the building site (A4)

Name	Value	Unit
Transport distance	1000	km
Gross weight	34 - 40	t
Payload capacity	27	t

Installation into the building (A5)

Name	Value	Unit
Other resources for packaging material	0.067	kg
Material loss	0.01	kg

Material loss regards the amount of product not used during the application phase into the building. This amount is 1% of the product, impacts related to the production of this part are charged to the A5 module. This percentage is considered as waste to disposal and impacts of its end of life have been considered in the LCA model and declared in A5.

End of life (C1-C3)

Name	Value	Unit
Collected as mixed construction waste	1	kg
Incineration	1	kg

5. LCA: Results

DESCRIPTION OF THE SYSTEM BOUNDARY (X = INCLUDED IN LCA; ND = MODULE OR INDICATOR NOT DECLARED; MNR = MODULE NOT RELEVANT)

PRODUCT STAGE			CONSTRUCTION PROCESS STAGE		USE STAGE							END OF LIFE STAGE				BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARIES
Raw material supply	Transport	Manufacturing	Transport from the gate to the site	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	X	X	ND	ND	MNR	MNR	MNR	ND	ND	X	X	X	ND	X

RESULTS OF THE LCA - ENVIRONMENTAL IMPACT according to EN 15804+A2: 1 kg of dispersion-based product, group 2

Core Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	D
GWP-total	[kg CO_2-Eq.]	2.00E+0	5.11E-2	1.80E-1	2.79E-4	1.24E-2	9.45E-1	-3.98E-1
GWP-fossil	[kg CO_2-Eq.]	2.05E+0	5.06E-2	9.49E-2	2.66E-4	1.18E-2	4.29E-1	-3.97E-1
GWP-biogenic	[kg CO_2-Eq.]	-3.96E-2	1.48E-4	8.54E-2	1.24E-5	5.42E-4	5.15E-1	-8.96E-4
GWP-luluc	[kg CO_2-Eq.]	8.17E-4	4.10E-4	9.68E-6	6.39E-9	2.79E-7	3.50E-5	-2.51E-4
ODP	[kg CFC11-Eq.]	3.53E-14	6.08E-18	3.70E-16	2.84E-20	1.24E-18	3.02E-16	-3.72E-15
AP	[mol H^+-Eq.]	8.99E-3	1.52E-4	1.14E-4	3.60E-6	3.73E-5	5.25E-4	-5.26E-4
EP-freshwater	[kg P-Eq.]	2.85E-5	1.54E-7	2.88E-7	5.75E-11	2.51E-9	1.04E-7	-4.62E-7
EP-marine	[kg N-Eq.]	1.70E-3	6.75E-5	2.42E-5	1.63E-6	1.72E-5	2.01E-4	-1.39E-4
EP-terrestrial	[mol N-Eq.]	1.95E-2	7.56E-4	3.08E-4	1.79E-5	1.89E-4	2.52E-3	-1.49E-3
POCP	[kg NMVOC-Eq.]	6.25E-3	1.33E-4	8.24E-5	4.91E-6	3.39E-5	5.22E-4	-4.02E-4
ADPE	[kg Sb-Eq.]	7.32E-7	3.63E-9	7.60E-9	8.06E-12	3.52E-10	4.62E-9	-6.06E-8
ADPF	[MJ]	4.44E+1	6.73E-1	4.75E-1	3.81E-3	1.66E-1	5.52E-1	-6.70E+0
WDP	[m^3 world-Eq deprived]	6.36E-2	4.52E-4	1.70E-2	5.27E-7	2.30E-5	1.57E-1	-3.70E-2

Caption	GWP = Global warming potential; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential of land and water; EP = Eutrophication potential; POCP = Formation potential of tropospheric ozone photochemical oxidants; ADPE = Abiotic depletion potential for non-fossil resources; ADPF = Abiotic depletion potential for fossil resources; WDP = Water (user) deprivation potential

RESULTS OF THE LCA - INDICATORS TO DESCRIBE RESOURCE USE according to EN 15804+A2: 1 kg of dispersion-based product, group 2

Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	D
PERE	[MJ]	6.19E+0	3.79E-2	6.58E-1	1.20E-5	5.25E-4	9.36E-2	-1.32E+0
PERM	[MJ]	5.85E-1	0.00E+0	-5.85E-1	0.00E+0	0.00E+0	0.00E+0	0.00E+0
PERT	[MJ]	6.77E+0	3.79E-2	7.35E-2	1.20E-5	5.25E-4	9.36E-2	-1.32E+0
PENRE	[MJ]	2.93E+1	6.74E-1	1.43E+0	3.81E-3	1.67E-1	1.48E+1	-6.70E+0
PENRM	[MJ]	1.52E+1	0.00E+0	-9.53E-1	0.00E+0	0.00E+0	-1.42E+1	0.00E+0
PENRT	[MJ]	4.44E+1	6.74E-1	4.76E-1	3.81E-3	1.67E-1	5.52E-1	-6.70E+0
SM	[kg]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
RSF	[MJ]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
NRSF	[MJ]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
FW	[m^3]	1.54E-2	4.38E-5	5.38E-4	2.16E-8	9.41E-7	3.70E-3	-1.53E-3

Caption	PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water

RESULTS OF THE LCA – WASTE CATEGORIES AND OUTPUT FLOWS according to EN 15804+A2: 1 kg of dispersion-based product, group 2

Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	D
HWD	[kg]	1.51E-8	3.14E-8	1.87E-10	3.70E-13	1.62E-11	1.77E-9	-2.66E-9
NHWD	[kg]	2.75E-1	1.03E-4	4.97E-3	3.90E-7	1.70E-5	1.36E-1	-2.94E-3
RWD	[kg]	1.09E-3	8.34E-7	1.27E-5	4.09E-9	1.79E-7	2.51E-5	-4.51E-4
CRU	[kg]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
MFR	[kg]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
MER	[kg]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
EEE	[MJ]	0.00E+0	0.00E+0	2.77E-1	0.00E+0	0.00E+0	0.00E+0	0.00E+0
EET	[MJ]	0.00E+0	0.00E+0	5.01E-1	0.00E+0	0.00E+0	0.00E+0	0.00E+0

Caption	HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported electrical energy; EET = Exported thermal energy

RESULTS OF THE LCA – additional impact categories according to EN 15804+A2-optional: 1 kg of dispersion-based product, group 2

Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	D
PM	[Disease Incidence]	ND	ND	ND	ND	ND	ND	ND
IRP	[kBq U235-Eq.]	ND	ND	ND	ND	ND	ND	ND
ETP-fw	[CTUe]	ND	ND	ND	ND	ND	ND	ND
HTP-c	[CTUh]	ND	ND	ND	ND	ND	ND	ND
HTP-nc	[CTUh]	ND	ND	ND	ND	ND	ND	ND
SQP	[-]	ND	ND	ND	ND	ND	ND	ND

Caption	PM = Potential incidence of disease due to PM emissions; IR = Potential Human exposure efficiency relative to U235; ETP-fw = Potential comparative Toxic Unit for ecosystems; HTP-c = Potential comparative Toxic Unit for humans (cancerogenic); HTP-nc = Potential comparative Toxic Unit for humans (not cancerogenic); SQP = Potential soil quality index

Potential Human exposure efficiency relative to U235, Disclaimer 1 – This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure or radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, radon and (from) some construction materials, is also not measured by this indicator.

ADP minerals & metals, ADP fossil, WDP, ETF-fw, HTP-c, HTP-nc, SQP, Disclaimer 2 – The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experience with the indicator.

Additional environmental impact indicators (suggested by *EN15804*, table 4) are not declared in the EPD. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high and as there is limited experience with the indicator (see ILCD classification in *EN 15804*, table 5). For this reason, results based on these indicators are not considered suitable for a decision-making process and are thus not declared in the EPD.

6. LCA: Interpretation

The majority of impacts are associated with the production phase (A1-A3). The most significant contribution to the production phase impacts is the upstream production of raw materials as the main driver. Another contributor in the production phase, in the category of Photochemical ozone formation (POCP), is the plastic used as a packaging material. Emissions associated with the manufacturing of products also have some influence on Ozone Depletion Potential (ODP) in the production phase. In all EPDs, CO_2 is the most important contributor to Global Warming Potential (GWP). For the Acidification Potential (AP), NOx and SO_2 contribute the largest share.
The majority of life cycle energy consumption takes place during the production phase (A1-A3). Significant contributions to Primary Energy Demand – Non-renewable (PENRT) come from the energy resources used in the production of raw materials. The largest contributor to Primary Energy Demand – Renewable (PERT) impacts comes from the consumption of renewable energy resources required for the generation and supply of electricity. It should be noted that Primary Energy Demand – Renewable (PERT) generally represents a small percentage of the production phase primary energy demand with the bulk of the demand coming from non-renewable energy resources.
Transportation to the construction site (A4) and the installation process (A5) make a low contribution to all impacts. Climate change from land-use change is the only indicator influenced by transport processes, due to the diesel production used as fuel because part of this diesel has been produced from bio-based raw materials.
The installation phase influence mainly climate change indicators, due to the impact related to the incineration processes used for packaging waste treatment and residual product treatment (1 % of the total mass).
The end-of-life phases influence climate change indicators, due to the thermal treatment process of the dispersion-based product occurring in the C3 module.

7. Requisite evidence

VOC
Special tests and evidence have not been carried out or provided within the framework of drawing up this Model EPD. Some member states require special documentation on VOC emissions into indoor air for specific areas of application. This documentation, as well as documentation for voluntary VOC labelling, has to be provided separately and is specific to the product in question.

Evidence pertaining to VOC emissions shall show
- either an attestation of compliance with,
- or documentation of test data that are required in any of the existing regulations or in any of the existing voluntary labelling programs for low-emitting products, as far as these

(1) include limits for the parameters TVOC, TSVOC, carcinogens, formaldehyde, acetaldehyde, LCI limits for individual substances (including but not limited to the European list of harmonized LCIs), and the R-value;
(2) base their test methods on *EN 16516*;
(3) perform testing and apply the limits after 28 days of storage in a ventilated test chamber, under the conditions specified in *EN 16516*; some regulations and programs also have limits after 3 days, on top of the 28 days limits;

(4) express the test results as air concentrations in the European Reference Room, as specified in *EN 16516*.

Examples of such regulations are the *Belgian Royal Decree C-2014/24239*, or the *German AgBB/* ABG. Examples of such voluntary labelling programs are *EMICODE*, *Blue Angel* or *Indoor Air Comfort*.

Relevant test results shall be produced either by an *ISO 17025* accredited commercial test lab or by a qualified internal test lab of the manufacturer.
Examples for the applied limits after 28 days of storage in a ventilated test chamber are:

- TVOC: 1000 µg/m³
- TSVOC: 100 µg/m³
- Each carcinogen: 1 µg/m³
- Formaldehyde: 100 µg/m³
- LCI: different per substance involved
- R-value: 1 (meaning that, in total, 100 % of the combined LCI values must not be exceeded).

Informative Annexes (2 tables):
Table 1 shown below is an overview of the most relevant regulations and specifications as of October 2021, as regards requirements after 3 days of storage in a ventilated test chamber.
Table 2 provides an overview of the most relevant regulations and specifications as of October 2021, as regards requirements after 28 days of storage in a ventilated test chamber. Some details may be missing in the table due to lack of space. Values given represent maximum values/limits.

	TVOC µg/m³	Sum of carcinogens. C1A,CA2 µg/m³	Formaldehyde µg/m³	Acetaldehyde µg/m³	Sum of Form- and Acetaldehyde
German AgBB/ABG regulation	10 000	10	-/-	-/-	-/-
Belgian regulation	10 000	10	-/-	-/-	-/-
EMICODE EC1	1 000	10	50	50	50 ppb
EMICODE EC1 *PLUS*	750	10	50	50	50 ppb

	TVOC µg/m³	TSVOC µg/m³	Each carcinogen C1A,CA2 µg/m³	Formalde-hyde µg/m³	Acetalde-hyde µg/m³	LCI	R value	Specials	Sum of non-LCI & non-identified µg/m³
Belgian regulation	1000	100	1	100	200	Belgian list	1	Toluene 300 µg/m³	-/-
French regulations class A+	1000	-/-	-/-	10	200	-/-	-/-	List of 8 VOCs, 4 CMR	-/-
French regulations class A	1500	-/-	-/-	60	300	-/-	-/-	List of 8 VOCs, 4 CMR	-/-
French regulations class B	2000	-/-	-/-	120	400	-/-	-/-	List of 8 VOCs, 4 CMR	-/-
French regulations class C	>2000	-/-	-/-	>120	>400	-/-	-/-	List of 8 VOCs, 4 CMR	-/-
German DIBt/AgBB regulation	1000	100	1	100	300	German AgBB list	1	-/-	100
EMICODE EC1	100	50	1	(after 3 days)	(after 3 days)	-/-	-/-	-/-	-/-
EMICODE EC1 *PLUS*	60	40	1	(after 3 days)	(after 3 days)	German AgBB list	1	-/-	40
Finnish M1, sealants	20	-/-	1	10	300	EU LCI list	-/-	Ammonia, odour	-/-
Finnish M1, adhesives	200 µg/m²h	-/-	5 µg/m²h	50 µg/m²h	300	EU LCI list	-/-	Ammonia, odour	-/-

8. References

EN 1062-3
EN 1062-3:2008-04, Paints and varnishes - Coating materials and coating systems for exterior masonry and concrete - Part 3: Determination of liquid water permeability

EN 1062-6
EN 1062-6:2002-10, Paints and varnishes - Coating materials and coating systems for exterior masonry

and concrete - Part 6: Determination of carbon dioxide permeability

EN 1504-2
EN 1504-2:2004-10, Products and systems for the protection and repair of concrete structures - Definitions, requirements, quality control and evaluation of conformity - Part 2: Surface protection systems for concrete

EN 1542
EN 1542:1999-07, Products and systems for the protection and repair of concrete structures - Test methods - Measurement of bond strength by pull-off

EN ISO 7783-1/-2
EN ISO 7783-1/-2:2019-02, Paints and varnishes - Determination of water-vapour transmission properties - Cup method

EN 12004
EN12004:2012, Adhesives for ceramic tiles

EN 12004-2
EN 12004-2:2017, Adhesives for ceramic tiles - Part 2: Test methods

ISO 14025
DIN EN ISO 14025:2011-10, Environmental labels and declarations — Type III environmental declarations — Principles and procedures

EN 15804
EN 15804:2019+A2+AC, Sustainability of construction works — Environmental Product Declarations — Core rules for the product category of construction products.

EN 16516
EN 16516:2017
Construction products - Assessment of release of dangerous substances - Determination of emissions into indoor air

EN ISO 17025
EN ISO 17025: 2018-03
General requirements for the competence of testing and calibration laboratories

EN ISO 17178
EN ISO 17178:2020, Adhesives - Adhesives for bonding parquet to subfloor - Test methods and minimum requirements

EN ISO 22636
EN ISO 22636:2020, Adhesives - Adhesives for floor coverings - Requirements for mechanical and electrical performance

EAD 030352-00-0503
EAD 030352-00-0503:2019-01, Watertight covering kits for wet room floors and or walls Part 1: Liquid Applied Coverings with or without wearing surface Part 2: Kits based on flexible sheets Part 3: Kits based on inherently watertight boards

(EU) No 528/2012
Biocidal Products Regulation (EU) No 528/2012 of the European Parliament and of the Council of 22 May 2012 concerning the making available on the market and use of biocidal products (current consolidated version: 2021-06)

2000/532/EC
Commission decision dated 3 May 2000 replacing decision 94/3/EC on a waste directory in accordance with Article 1 a) of Council Directive 75/442/EEC on waste and Council decision 94/904/EC on a directory of hazardous waste in terms of Article 1, paragraph 4 of Directive 91/689/EEC on hazardous waste

Belgian Royal Decree C-2014/24239
Belgisch Staatsblad 8 MEI 2014, p. 60603. — Koninklijk besluit tot vaststelling van de drempelniveaus voor de emissies naar het binnenmilieu van bouwproducten voor bepaalde geoogde gebruiken

Blue Angel
Environmental label organised by the federal government of Germany www.blauer-engel.de

Candidate list
Candidate List of substances of very high concern for Authorisation, published in accordance with Article 59(10) of the REACH Regulation, ECHA, www.echa.europa.eu/candidate-list-table

CPR
CPR Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 laying down harmonised conditions for the marketing of construction products and repealing Council Directive 89/106/EEC

Decopaint Directive
Directive 2004/42/CE of the European Parliament and the council of 21 April 2004 on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products and amending Directive 1999/13/EC

EMICODE
EMICODE, GEV – Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e. V. (pub.).www.emicode.de

GaBi 10 software & documentation
Data base for Life Cycle Engineering LBP, University of Stuttgart and Sphera, documentation of GaBi 10 data sets http://documentation.gabi-software.com/, 2020

German AgBB
Committee for Health-related Evaluation of Building Products: health-related evaluation of emissions of volatile organic compounds (VOC and SVOC) from building products; status: June 2012 www.umweltbundesamt.de/produkte/bauprodukte/agbb.htm

IBU 2021
Institut Bauen und Umwelt e.V.: General Instructions for the EPD programme of Institut Bauen und Umwelt e.V. EPD programme. Version 2.0. Berlin: Institut Bauen und Umwelt e.V., 2021
www.ibu-epd.com

Indoor Air Comfort
Product certification by Eurofins, Hamburg, Germany www.eurofins.com .

PCR Part A
Product Category Rules for Building-Related Products and Services, Part A: Calculation Rules for the Life Cycle Assessment and Requirements on the Project report, Version 1.1, Institut Bauen und Umwelt e.V., 2021-01

PCR Part B
Product Category Rules for Construction Products. Part B: Dispersion adhesives and primers for floor coverings, Version 1.7, 2019.

REACH
Directive (EG) No. 1907/2006 of the European Parliament and of the Council dated 18 December 2006 on the registration, evaluation, approval and restriction of chemical substances (REACH), for establishing a European Agency for chemical substances, for amending Directive 1999/45/EC and for annulment of Directive (EEC) No. 793/93 of the Council, Directive (EC) No. 1488/94 of the Commission, Guideline 76/769/EEC of the Council and Guidelines 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC of the Commission.

Publisher
Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

Tel +49 (0)30 3087748- 0
Fax +49 (0)30 3087748- 29
Mail info@ibu-epd.com
Web **www.ibu-epd.com**

Programme holder
Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

Tel +49 (0)30 - 3087748- 0
Fax +49 (0)30 – 3087748 - 29
Mail info@ibu-epd.com
Web **www.ibu-epd.com**

Author of the Life Cycle Assessment
Sphera Solutions GmbH
Hauptstraße 111- 113
70771 Leinfelden-Echterdingen
Germany

Tel +49 711 341817-0
Fax +49 711 341817-25
Mail info@sphera.com
Web **www.sphera.com**

Owner of the Declaration
EFCC - European Federation for Construction Chemicals
Boulevard du Triomphe 172
1160 Brussels
Belgium

Tel +32289720-39
Fax +32289720-37
Mail info@efcc.be
Web **www.efcc.eu**

Deutsche Bauchemie e.V.
Mainzer Landstr. 55
60329 Frankfurt
Germany

Tel +49 (0)69 2556-1318
Fax +49 (0)69 2556-1319
Mail info@deutsche-bauchemie.de
Web **www.deutsche-bauchemie.de**

FEICA - Association of the European Adhesive and Sealant Industry
Rue Belliard 40 box 10
1040 Brussels
Belgium

Tel +32 (0)267 673 20
Fax +32 (0)267 673 99
Mail info@feica.eu
Web **www.feica.eu**

Industrieverband Klebstoffe e.V
Völklinger Straße 4
40219 Düsseldorf
Germany

Tel +49 (0)211 67931-10
Fax +49 (0)211 67931-33
Mail info@klebstoffe.com
Web **www.klebstoffe.com**