SENTINEL HOLDING
INSTITUT

SHI PRODUCT PASSPORT

Find products. Certify buildings.

SHI Product Passport No.:

13373-10-1041

Bodenausgleichsmasse CERAfix 201-2

Product group: Leveling compound

WÜRTH

Adolf Würth GmbH & Co. KG
Reinhold-Würth-Straße 12-17
74653 Künzelsau-Gaisbach

Product qualities:

- SHI Product Assessment 2024
- QNG Qualitätssiegel Nachhaltiges Gebäude
- DGNB NEW CONSTRUCTION 2023
- DGNB NEW CONSTRUCTION 2018
- BNB-BN NEUBAU V2015
- EU taxonomy
- BREEAM DE NEUBAU 2018
- LEED v4.1 (outside US)

CERTIFIED SUSTAINABLE PRODUCT
SHI PRODUCT PASSPORT
SENTINEL HOLDING INSTITUT
www.sentinel-holding.eu

Köttner

Helmut Köttner
Scientific Director
Freiburg, 31 March 2026

Product:
Bodenausgleichsmasse CERAfix 201-2

SHI Product Passport no.:
13373-10-1041

WÜRTH

Contents

SHI Product Assessment 2024	1
QNG - Qualitätssiegel Nachhaltiges Gebäude	2
DGNB New Construction 2023	3
DGNB New Construction 2018	4
BNB-BN Neubau V2015	5
EU taxonomy	6
BREEAM DE Neubau 2018	7
LEED v4.1	8
Product labels	9
Legal notices	10
Technical data sheet/attachments	11

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar

SENTINEL HOLDING
INSTITUT

Product:
Bodenausgleichsmasse CERAfix 201-2

SHI Product Passport no.:
13373-10-1041

WÜRTH

SHI Product Assessment 2024

Since 2008, Sentinel Holding Institut GmbH (SHI) has been establishing a unique standard for products that support healthy indoor air. Experts carry out independent product assessments based on clear and transparent criteria. In addition, the independent testing company SGS regularly audits the processes and data accuracy.

Criteria	Product category	Assessment
SHI Product Assessment		Indoor Air Quality Certified
Valid untill: 05 October 2026		

Product:
Bodenausgleichsmasse CERAfix 201-2

SHI Product Passport no.:
13373-10-1041

WÜRTH

QNG - Qualitätssiegel Nachhaltiges Gebäude

The Qualitätssiegel Nachhaltiges Gebäude (Quality Seal for Sustainable Buildings), developed by the German Federal Ministry for Housing, Urban Development and Building (BMWSB), defines requirements for the ecological, socio-cultural, and economic quality of buildings. The Sentinel Holding Institut evaluates construction products in accordance with QNG requirements for certification and awards the QNG ready label. Compliance with the QNG standard is a prerequisite for eligibility for the KfW funding programme. For certain product groups, the QNG currently has no specific requirements defined. Although classified as not assessment-relevant, these products remain suitable for QNG-certified projects.

Criteria	Pos. / product group	Considered substances	QNG assessment
3.1.3 Schadstoffvermeidung in Baumaterialien	3.2 Installation materials for ceramic tiles, natural stone, and concrete stone on walls and floors	VOC / Emissions / hazardous substances / plasticizers / biocides	QNG ready
Verification: EMICODE EC1 Plus-Zertifikat (4631/01.01.05) 05.10.2021			

Product:
Bodenausgleichsmasse CERAfix 201-2

SHI Product Passport no.:
13373-10-1041

WÜRTH

DGNB New Construction 2023

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings. The 2023 version sets high standards for ecological, economic, socio-cultural, and functional aspects throughout the entire life cycle of a building.

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 03.05.2024 (3rd edition)	8 Primers, undercoats, fillers and adhesives under wall	VVOCs, VOC, SVOC emissions and content of hazardous substances	Quality level 4
Verification: Herstellererklärung 01.26, EMICODE EC1 Plus Zertifikat (4631/01.01.05) 05.10.2021			

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 29.05.2025 (4th edition)	8 Primers, undercoats, fillers and adhesives under wall and floor coverings	VVOCs, VOC, SVOC emissions and content of hazardous substances	Quality level 4
Verification: Herstellererklärung 01.26, EMICODE EC1 Plus Zertifikat (4631/01.01.05) 05.10.2021			

Product:
Bodenausgleichsmasse CERAfix 201-2

SHI Product Passport no.:
13373-10-1041

WÜRTH

DGNB New Construction 2018

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings.

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact	8 Primers, precoats, fillers and adhesives under wall and floor coverings	VOC	Quality level 4
Verification: Herstellererklärung 01.26, EMICODE EC1 Plus Zertifikat (4631/01.01.05) 05.10.2021			

Product:
Bodenausgleichsmasse CERAfix 201-2

SHI Product Passport no.:
13373-10-1041

WÜRTH

BNB-BN Neubau V2015

The Bewertungssystem Nachhaltiges Bauen (Assessment System for Sustainable Building) is a tool for evaluating public office and administrative buildings, educational facilities, laboratory buildings, and outdoor areas in Germany. The BNB was developed by the former Federal Ministry for the Environment, Nature Conservation, Building and Nuclear Safety (BMUB) and is now overseen by the Federal Ministry for Housing, Urban Development and Building (BMWSB).

Criteria	Pos. / product type	Considered substance group	Quality level
1.1.6 Risiken für die lokale Umwelt	10a Laying materials for ceramic wall and floor tiles and slabs	VOC / hazardous substances / biocides	Quality level 5
Verification: EMICODE EC1 Plus Zertifikat (4631/01.01.05) 05.10.2021			

Product:
Bodenausgleichsmasse CERAfix 201-2

SHI Product Passport no.:
13373-10-1041

WÜRTH

EU taxonomy

The EU Taxonomy classifies economic activities and products according to their environmental impact. At the product level, the EU regulation defines clear requirements for harmful substances, formaldehyde and volatile organic compounds (VOCs). The Sentinel Holding Institut GmbH labels qualified products that meet this standard.

Criteria	Product type	Considered substances	Assessment
DNSH - Pollution prevention and control		Substances according to Annex C	EU taxonomy compliant
Verification: EMICODE EC1 Plus Zertifikat (4631/01.01.05) 05.10.2021			

Product:
Bodenausgleichsmasse CERAfix 201-2

SHI Product Passport no.:
13373-10-1041

WÜRTH

BREEAM DE Neubau 2018

BREEAM (Building Research Establishment Environmental Assessment Methodology) is a UK-based building assessment system that evaluates the sustainability of new constructions, refurbishments, and conversions. Developed by the Building Research Establishment (BRE), the system aims to assess and improve the environmental, economic, and social performance of buildings.

Criteria	Product category	Considered substances	Quality level
Hea 02 Indoor Air Quality			Not relevant for assessment

Product:
Bodenausgleichsmasse CERAfix 201-2

SHI Product Passport no.:
13373-10-1041

WÜRTH

LEED v4.1

LEED (Leadership in Energy and Environmental Design) is an internationally recognised building certification system developed by the U.S. Green Building Council. It is one of the most widely used sustainability standards for buildings worldwide and is particularly applied in internationally oriented projects. LEED assesses buildings holistically across categories such as energy efficiency, resource conservation, material selection, indoor environmental quality and site sustainability. Depending on the number of points achieved, projects are awarded one of the certification levels: LEED Certified, Silver, Gold or Platinum.

Criteria	Product category	Assessment
EQ Credit: Low-Emitting Materials		Not relevant for assessment

Product:
Bodenausgleichsmasse CERAfix 201-2

SHI Product Passport no.:
13373-10-1041

WÜRTH

Product labels

In the construction industry, high-quality materials are crucial for a building's indoor air quality and sustainability. Product labels and certificates offer guidance to meet these requirements. However, the evaluation criteria of these labels vary, and it is important to carefully assess them to ensure products align with the specific needs of a construction project.

The EMICODE® label, awarded by the German manufacturers' association "GEV – Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e. V.", is primarily relevant for flooring installation materials. The EMICODE® EC1^{PLUS} label, as the premium class, sets significantly stricter emission limits than the other label variants.

This product is SHI Indoor Air Quality certified and recommended by Sentinel Holding Institut. Indoor-air-focused construction, renovation, and operation of buildings is made possible by transparent and verifiable criteria thanks to the Sentinel Holding concept.

Products bearing the Sentinel Holding Institute QNG-ready seal are suitable for projects aiming to achieve the "Qualitätssiegel Nachhaltiges Gebäude" (Quality Seal for Sustainable Buildings). QNG-ready products meet the requirements of QNG Appendix Document 3.1.3, "Avoidance of Harmful Substances in Building Materials." The KfW loan program Climate-Friendly New Construction with QNG may allow for additional funding.

The IBU ("Institut Bauen und Umwelt e.V.") is an initiative of building product manufacturers committed to sustainability in construction. It serves as the programme operator for Environmental Product Declarations (EPDs) in accordance with the EN 15804 standard. The IBU EPD programme provides comprehensive life cycle assessments and environmental impact data for construction products, supported by independent third-party verification.

Product:
Bodenausgleichsmasse CERAfix 201-2

SHI Product Passport no.:
13373-10-1041

WÜRTH

Legal notices

(*) These criteria apply to the construction project as a whole. While individual products can positively contribute to the overall building score through proper planning, the evaluation is always conducted at the building level. The information was provided entirely by the manufacturer.

Find our criteria here: https://www.sentinel-holding.eu/de/Themenwelten/Pr%C3%BCfkriterien%20f%C3%BCr%20Produkte

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar

SGS TÜV SAAR

Publisher

Sentinel Holding Institut GmbH
Bötzinger Str. 38
79111 Freiburg im Breisgau
Germany
Tel.: +49 761 590 481-70
info@sentinel-holding.eu
www.sentinel-holding.eu

TECHNISCHES DATENBLATT

Bodenausgleichsmasse CERAfix® 201-2

Art.-Nr. 5875 200 201
VE: 1 / 24 / 42



Spannungsarmer selbstverlaufender Zement-fließspachtel für Schichtdicken von 2 – 40 mm

- Staubreduziert
- EC1-Plus
- Spannungsarm
- Hydraulisch abbindend
- Schnell begehbar und nutzbar
- Gute Verlaufseigenschaften
- Pumpfähig
- In einem Arbeitsgang von 2 – 30 mm, gestreckt von 20 – 40 mm Schichtdicke verarbeitbar
- Hohe Oberflächenhärte durch Kunststoffmodifizierung
- Für Fußbodenheizungen geeignet

Chemische Basis	Zement, mineralische Zuschläge, hochwertige Additive (Kunststoffvergütet)
Farbe	Grau
Mischungsverhältnis	4,5 - 4,75 l Wasser für 25 kg
Verarbeitungstemperatur min./max.	5 bis 25 °C
Verarbeitungszeit max.	20 min
Abbindezeit	30 min
Begehbarkeit nach max.	3 h
Begehbarkeit Bedingung	bei 20°C und 50% relative Luftfeuchtigkeit
Belegbar nach max.	24 h
Vollbelastbarkeit	14 d
Vollbelastbarkeit Bedingung	bei 20°C und 50% relative Luftfeuchtigkeit
Verarbeitungstemperatur min.	5 °C
Verarbeitungstemperatur max.	25 °C
Auftragsmenge in Gewicht/Fläche	1,6 kg/m^2
Druckfestigkeit min.	21 N/mm^2
Druckfestigkeit Bedingung	nach 7 Tagen, DIN EN 196-1
Baustoffklasse	A2 fl s1 - Nicht brennbar
Inhaltsgewicht	25 kg
Inhalt	25 l
Gebinde	Papiersack
Lagerfähigkeit ab Herstellung	9 Monate
Lagerfähigkeit ab Herstellung Bedingung	kühle und trockene Lagerung
Nachhaltigkeit	Schadstoffe/Emissionen

PR01_5875200201, TDB, Rev. 0.36, Stand: 20. 09. 2024

TECHNISCHES DATENBLATT

Anwendungsgebiet

Zum Ausgleichen von unebenen Bodenflächen im Innenbereich vor der Verlegung von Keramik-, Marmor-, Naturstein- und PVC-Belägen, Teppichböden, schwimmend verlegtem Parkett und Laminat, u.a.
Geeignet auf Rohbetondecken, Betonsohlen, beheizte und unbeheizte Zementestriche gemäß DIN 18560, alte fest haftende Fliesenbelägen und Zementschnellestriche sowie als Nutzschicht in Kellern und auf Dachböden.

Untergrund	Mögliche Schichtdicke
Zementäre Untergründe	Ungestreckt 2 – 30 mm Gestreckt* bis 40 mm
Anhydridgebundene Untergründe	2 – 20 mm
Gussasphalt	2 – 10 mm

Anwendungsinformationen

Der Untergrund muss fest, tragfähig, sauber, trocken, sowie frei von Rissen und trennenden Substanzen sein. Es gelten folgende Grenzwerte (max. Feuchtigkeitsgehalt) für den Untergrund von:

- Z-ementgebunden 2 CM-Gew. %
- Calciumsulfatestrich 0,5 CM-Gew. %
- Beheizte Calciumsulfatestriche 0,3 CM-Gew.%

An Wandanschlüssen, Stützen usw. sind Randstreifen anzubringen. Die Fläche ist mit einer geeigneten Grundierung vorzustreichen.

In einem sauberen Gefäß die Nivelliermasse (25kg) mit 4,5 bis 4,75 Liter sauberem, kaltem Leitungswasser klumpenfrei anmischen. Empfohlen wird ein Rührgerät mit 600 U / Minute mit Doppelscheibenrührer. Nach einer Reifezeit von ca. 3 Minuten nochmals gründlich durchmischen. Anschließend den Frischmörtel auf den vorbereiteten Untergrund gießen und in der erforderlichen Schichtdicke mit Glättkelle oder Rakel verteilen. Um die gewünschte Höhenlage bereits im frischen Zustand kontrollieren zu können ist es vorteilhaft Niveaupunkte zu setzen. Das noch flüssige Material mit einer Stachelwalze oder einem anderen geeigneten Werkzeug entlüften und zum Fließen anregen. Dadurch werden die Oberfläche und Verlauf entscheidend verbessert. Zur Verarbeitung mit Pumpen eignen sich handelsübliche Schnecken-, Kolben- und durchlaufend arbeitende Mischpumpen, die für Körnungen bis 2mm geeignet sind.

Leistungsnachweis

Geprüft nach EN 13813

- Brandverhalten: A2 fl
- Freisetzung korrosiver Substanzen: CT
- Druckfestigkeit: C25
- Biegezugfestigkeit: F5

EMICODE EC1plus: Sehr emissionsarm - Das Klassifizierungssystem EMICODE zeichnet die Umwelt- und Gesundheitsverträglich-

PR01_5875200201, TDB, Rev. 0.36, Stand: 20. 09. 2024

TECHNISCHES DATENBLATT

keit von Bauprodukten aus. Die emissionsärmsten Produkte tragen das Zeichen EC1plus.

PR01_5875200201, TDB, Rev: 0.36, Stand: 20. 09. 2024

TECHNISCHES DATENBLATT

Hinweis

- Das abbindende Produkt vor Sonneneinstrahlung, Zugluft, Schlagregen, Frost und zu hohen Temperaturen (≥ +25°C) schützt.
- Bereits abbindendes Material darf mit Wasser nicht nachträglich verdünnt werden.
- Das Produkt reagiert mit Feuchtigkeit alkalisch.
- Dieses Produkt ist chromatarm gemäß RL 2003/53/EG-GISCODE ZP 1

Die Verarbeitungsangaben sind Empfehlungen, die auf unseren Versuchen und Erfahrungen beruhen; vor jedem Anwendungsfall sind Eigenversuche durchzuführen. Aufgrund der Vielzahl der Anwendungen sowie der Lagerungs- und Verarbeitungsbedingungen übernehmen wir keine Gewährleistung für ein bestimmtes Verarbeitungsergebnis. Soweit unser kostenloser Kundendienst technische Auskünfte gibt bzw. beratend tätig wird, erfolgt dies unter Ausschluss jeglicher Haftung, es sei denn, die Beratung bzw. Auskunft gehört zu unserem geschuldeten, vertraglich vereinbarten Leistungsumfang oder der Berater handelte vorsätzlich. Wir gewährleisten gleich bleibende Qualität unserer Produkte, technische Änderungen und Weiterentwicklungen behalten wir uns vor. Weitere Informationen siehe Technisches Datenblatt!

PR01_5875200201, TDB, Rev: 0.36, Stand: 20. 09. 2024

SICHERHEITSDATENBLATT

gemäß der Verordnung (EG) Nr. 1907/2006, geändert durch die Verordnung (EU) 2020/878 der Kommission

BODENAUSGLEICHSMASSE CERAfix 201-2 - 25 KG

Version	Überarbeitet am:	SDB-Nummer:	Datum der letzten Ausgabe: 26.11.2024
5.2	24.06.2025	10845004-00007	Datum der ersten Ausgabe: 25.06.2013

ABSCHNITT 1: Bezeichnung des Stoffs beziehungsweise des Gemischs und des Unternehmens

1.1 Produktidentifikator

Handelsname	:	BODENAUSGLEICHSMASSE CERAfix 201-2 - 25 KG
Produktnummer	:	5875200201
Eindeutiger Rezepturidentifikator (UFI)	:	QM5D-50D0-800G-2V90

1.2 Relevante identifizierte Verwendungen des Stoffs oder Gemischs und Verwendungen, von denen abgeraten wird

Verwendung des Stoffs/des Gemisches	:	Baustoff Produkt zur professionellen Verwendung
Empfohlene Einschränkungen der Anwendung	:	Nicht anwendbar

1.3 Einzelheiten zum Lieferanten, der das Sicherheitsdatenblatt bereitstellt

Firma	:	Adolf Wuerth GmbH & Co. KG Reinhold-Würth-Str. 12-17 74653 Künzelsau
Telefon	:	+49 794015 0
Telefax	:	+49 794015 10 00
E-Mailadresse der für SDB verantwortlichen Person	:	isi@wuerth.com

1.4 Notrufnummer

+49 (0)6132 – 84463

ABSCHNITT 2: Mögliche Gefahren

2.1 Einstufung des Stoffs oder Gemischs

Einstufung (VERORDNUNG (EG) Nr. 1272/2008)

Schwere Augenschädigung, Kategorie 1	H318: Verursacht schwere Augenschäden.
Sensibilisierung durch Hautkontakt, Kategorie 1	H317: Kann allergische Hautreaktionen verursachen.

2.2 Kennzeichnungselemente

Kennzeichnung (VERORDNUNG (EG) Nr. 1272/2008)

Gefahrenpiktogramme :



Signalwort : Gefahr

Gefahrenhinweise :

H317	Kann allergische Hautreaktionen verursachen.
H318	Verursacht schwere Augenschäden.

Sicherheitshinweise :

Prävention:

P261	Einatmen von Staub vermeiden.
P272	Kontaminierte Arbeitskleidung nicht außerhalb des Arbeitsplatzes tragen.
P280	Schutzhandschuhe/ Augenschutz/ Gesichtsschutz tragen.

Reaktion:

P305 + P351 + P338 + P310	BEI KONTAKT MIT DEN AUGEN: Einige Minuten lang behutsam mit Wasser spülen. Eventuell vorhandene Kontaktlinsen nach Möglichkeit entfernen. Weiter spülen. Sofort GIFTINFORMATIONSZENTRUM/ Arzt anrufen.
P333 + P313	Bei Hautreizung oder -ausschlag: Ärztlichen Rat einholen/ ärztliche Hilfe hinzuziehen.
P362 + P364	Kontaminierte Kleidung ausziehen und vor erneutem Tragen waschen.

Gefahrenbestimmende Komponente(n) zur Etikettierung:

Zement, Portland-, Chemikalien
Kaminstaub, Portlandzement

2.3 Sonstige Gefahren

Dieser Stoff/diese Mischung enthält keine Komponenten in Konzentrationen von 0,1 % oder höher, die entweder als persistent, bioakkumulierbar und toxisch (PBT) oder sehr persistent und sehr bioakkumulierbar (vPvB) eingestuft sind.

Umweltbezogene Angaben: Der Stoff/dieses Gemisch enthält keine Bestandteile, die gemäß REACH Artikel 57(f) oder der delegierten Verordnung (EU) 2017/2100 der Kommission oder der delegierten Verordnung (EU) 2018/605 der Kommission in Mengen von 0,1 % oder mehr endokrinschädliche Eigenschaften aufweisen.

Toxikologische Angaben: Der Stoff/dieses Gemisch enthält keine Bestandteile, die gemäß REACH Artikel 57(f) oder der delegierten Verordnung (EU) 2017/2100 der Kommission oder der delegierten Verordnung (EU) 2018/605 der Kommission in Mengen von 0,1 % oder mehr endokrinschädliche Eigenschaften aufweisen.

ABSCHNITT 3: Zusammensetzung/Angaben zu Bestandteilen

3.2 Gemische

Inhaltsstoffe

Chemische Bezeichnung	CAS-Nr. EG-Nr. INDEX-Nr. Registrierungsnummer	Einstufung	Konzentration (% w/w)
Zement, Aluminiumoxid-, Chemikalien	65997-16-2 266-045-5	Eye Irrit. 2; H319	>= 10 - < 20
Zement, Portland-, Chemikalien	65997-15-1 266-043-4	Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1B; H317 STOT SE 3; H335	>= 3 - < 10
Kaminstaub, Portlandzement	68475-76-3 270-659-9	Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 STOT SE 3; H335	>= 0,1 - < 1

Die Erklärung der Abkürzungen finden Sie unter Abschnitt 16.

ABSCHNITT 4: Erste-Hilfe-Maßnahmen

4.1 Beschreibung der Erste-Hilfe-Maßnahmen

Allgemeine Hinweise : Bei Unfall oder Unwohlsein sofort Arzt zuziehen.
Wenn die Symptome anhalten oder falls irgendein Zweifel besteht, ärztlichen Rat einholen.

Schutz der Ersthelfer : Erstversorger sollten auf Selbstschutz achten und die empfohlene persönliche Schutzkleidung verwenden, wenn ein Expositionsrisiko besteht (siehe Abschnitt 8).

Nach Einatmen : Bei Inhalation, an die frische Luft bringen.
Bei Auftreten von Symptomen, ärztliche Betreuung aufsuchen.

Nach Hautkontakt : Bei Kontakt, Haut sofort mit viel Wasser abspülen.
Verunreinigte Kleidung und Schuhe ausziehen.
Arzt hinzuziehen.
Beschmutzte Kleidung vor Wiedergebrauch waschen.
Schuhe vor der Wiederverwendung gründlich reinigen.

Nach Augenkontakt : Bei Kontakt, Augen sofort mit viel Wasser während mindestens 15 Minuten ausspülen.
Vorhandene Kontaktlinsen, wenn möglich, entfernen.
Sofort Arzt hinzuziehen.

Nach Verschlucken : Bei Verschlucken, KEIN Erbrechen hervorrufen.
Bei Auftreten von Symptomen, ärztliche Betreuung aufsuchen.

Mund gründlich mit Wasser ausspülen.

4.2 Wichtigste akute und verzögert auftretende Symptome und Wirkungen

Risiken : Kann allergische Hautreaktionen verursachen.
Verursacht schwere Augenschäden.

4.3 Hinweise auf ärztliche Soforthilfe oder Spezialbehandlung

Behandlung : Symptomatisch und unterstützend behandeln.

ABSCHNITT 5: Maßnahmen zur Brandbekämpfung

5.1 Löschmittel

Geeignete Löschmittel : Nicht anwendbar
Brennt nicht

Ungeeignete Löschmittel : Nicht anwendbar
Brennt nicht

5.2 Besondere vom Stoff oder Gemisch ausgehende Gefahren

Besondere Gefahren bei der Brandbekämpfung : Kontakt mit Verbrennungsprodukten kann gesundheitsgefährdend sein.

Gefährliche Verbrennungsprodukte : Metalloxide
Siliziumoxide
Kohlenstoffoxide
Schwefeloxide

5.3 Hinweise für die Brandbekämpfung

Besondere Schutzausrüstung für die Brandbekämpfung : Im Brandfall umgebungsluftunabhängiges Atemschutzgerät tragen. Persönliche Schutzausrüstung verwenden.

Spezifische Löschmethoden : Löschmaßnahmen auf die Umgebung abstimmen.
Zur Kühlung geschlossener Behälter Wassersprühstrahl einsetzen.
Entfernen Sie unbeschädigte Behälter aus dem Brandbereich, wenn dies sicher ist.
Umgebung räumen.

ABSCHNITT 6: Maßnahmen bei unbeabsichtigter Freisetzung

6.1 Personenbezogene Vorsichtsmaßnahmen, Schutzausrüstungen und in Notfällen anzuwendende Verfahren

Personenbezogene Vorsichtsmaßnahmen : Persönliche Schutzausrüstung verwenden.
Empfehlungen zur sicheren Handhabung (siehe Abschnitt 7) und zur persönlichen Schutzausrüstung befolgen (siehe

Abschnitt 8).

6.2 Umweltschutzmaßnahmen

Umweltschutzmaßnahmen	:	Freisetzung in die Umwelt vermeiden. Weiteres Auslaufen oder Verschütten verhindern, wenn dies ohne Gefahr möglich ist. Verunreinigtes Waschwasser zurückhalten und entsorgen. Wenn größere Mengen verschütteten Materials nicht eingedämmt werden können, sollen die lokalen Behörden benachrichtigt werden.

6.3 Methoden und Material für Rückhaltung und Reinigung

Reinigungsverfahren	:	Verschüttetes Material aufkehren oder aufsaugen und in geeigneten Behälter zur Entsorgung geben. Staubaufwirbelung in der Luft vermeiden (z.B. Reinigen von staubigen Oberflächen mit Druckluft). Lokale oder nationale Richtlinien können für Freisetzung und Entsorgung des Stoffes gelten, ebenso für die bei der Beseitigung von freigesetztem Material verwendeten Stoffe und Gegenstände. Man muss ermitteln, welche dieser Richtlinien anzuwenden sind. Abschnitt 13 und 15 dieses SDBs liefern Informationen bezüglich bestimmter lokaler oder nationaler Vorschriften.

6.4 Verweis auf andere Abschnitte

Siehe Abschnitte: 7, 8, 11, 12 und 13.

ABSCHNITT 7: Handhabung und Lagerung

7.1 Schutzmaßnahmen zur sicheren Handhabung

Technische Maßnahmen	:	Siehe technische Maßnahmen im Abschnitt "Begrenzung und Überwachung der Exposition/Persönliche Schutzausrüstungen".
Lokale Belüftung / Volllüftung	:	Nur mit ausreichender Belüftung verwenden.
Hinweise zum sicheren Umgang	:	Nicht auf die Haut oder die Kleidung gelangen lassen. Einatmen von Staub vermeiden. Nicht verschlucken. Berührung mit den Augen vermeiden. Basierend auf den Ergebnissen der Bewertung der Exposition am Arbeitsplatz gemäß den üblichen industriellen Hygiene- und Sicherheitspraktiken handhaben Behälter dicht verschlossen halten. Stauberzeugung und -ansammlung so klein wie möglich halten. Behälter verschlossen halten, wenn dieser nicht in Gebrauch ist. Massnahmen zu Vermeidung von Abfällen/unkontrolliertem Eintrag in die Umwelt sollten getroffen werden.
Hygienemaßnahmen	:	Wenn eine Exposition gegenüber Chemikalien während des

normalen Gebrauchs wahrscheinlich ist, sind Augen- und Notduschen nahe dem Arbeitsplatz vorzusehen. Bei der Arbeit nicht essen, trinken, rauchen. Kontaminierte Arbeitskleidung nicht außerhalb des Arbeitsplatzes tragen. Beschmutzte Kleidung vor Wiedergebrauch waschen.

7.2 Bedingungen zur sicheren Lagerung unter Berücksichtigung von Unverträglichkeiten

Anforderungen an Lagerräume und Behälter	:	In korrekt beschrifteten Behältern aufbewahren. Dicht verschlossen halten. In Übereinstimmung mit den besonderen nationalen gesetzlichen Vorschriften lagern.
Zusammenlagerungshinweise	:	Keine besonderen Beschränkungen zur Zusammenlagerung mit anderen Produkten.
Lagerklasse (TRGS 510)	:	13

7.3 Spezifische Endanwendungen

Bestimmte Verwendung(en)	:	Keine Daten verfügbar

ABSCHNITT 8: Begrenzung und Überwachung der Exposition/Persönliche Schutzausrüstungen

8.1 Zu überwachende Parameter

Arbeitsplatzgrenzwerte

Allgemeiner Staubgrenzwert	10 mg/m³ Spitzenbegrenzung: Überschreitungsfaktor (Kategorie): 2;(II) Werttyp (Art der Exposition): AGW (Einatembare Fraktion) Grundlage: DE TRGS 900 Weitere Information: Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden 1,25 mg/m³ Spitzenbegrenzung: Überschreitungsfaktor (Kategorie): 2;(II) Werttyp (Art der Exposition): AGW (Alveolengängige Fraktion) Grundlage: DE TRGS 900 Weitere Information: Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden
Stäube	Grundlage: DE DFG MAK
Allgemeiner Staubgrenzwert	0,3 mg/m³ Spitzenbegrenzung: Überschreitungsfaktor (Kategorie): 8; II Werttyp (Art der Exposition): MAK (gemessen als alveolengängige Fraktion) Grundlage: DE DFG MAK Weitere Information: Stoffe, die bei Tier oder Mensch Krebs erzeugen oder als krebserzeugend für den Menschen anzusehen

sind und für die ein MAK-Wert abgeleitet werden kann., Eine fruchtschädigende Wirkung ist bei Einhaltung des MAK- und BATWertes nicht anzunehmen

4 mg/m³
Spitzenbegrenzung: Überschreitungsfaktor (Kategorie): 8; II
Werttyp (Art der Exposition): MAK (einatembarer Anteil)
Grundlage: DE DFG MAK
Weitere Information: Stoffe, die bei Tier oder Mensch Krebs erzeugen oder als krebserzeugend für den Menschen anzusehen sind und für die ein MAK-Wert abgeleitet werden kann., Eine fruchtschädigende Wirkung ist bei Einhaltung des MAK- und BATWertes nicht anzunehmen

Inhaltsstoffe	CAS-Nr.	Werttyp (Art der Exposition)	Zu überwachende Parameter	Grundlage
Calciumsulfat	7778-18-9	MAK (einatembarer Anteil)	4 mg/m³	DE DFG MAK
	Weitere Information: Eine fruchtschädigende Wirkung ist bei Einhaltung des MAK- und BATWertes nicht anzunehmen			

Abgeleitete Expositionshöhe ohne Beeinträchtigung (DNEL) gemäß Verordnung (EG) Nr. 1907/2006

Stoffname	Anwendungsbereich	Expositionsweg e	Mögliche Gesundheitsschäden	Wert
Zement, Aluminiumoxid-, Chemikalien	Arbeitnehmer	Einatmung	Langzeit - systemische Effekte	2,5 mg/m³
	Arbeitnehmer	Einatmung	Akut - systemische Effekte	5 mg/m³
Calciumsulfat	Verbraucher	Verschlucken	Langzeit - systemische Effekte	1,52 mg/kg Körpergewicht /Tag
	Verbraucher	Einatmung	Langzeit - systemische Effekte	5,29 mg/m³
	Verbraucher	Verschlucken	Akut - systemische Effekte	11,4 mg/kg Körpergewicht /Tag
	Verbraucher	Einatmung	Akut - systemische Effekte	3811 mg/m³
	Arbeitnehmer	Einatmung	Langzeit - systemische Effekte	21,17 mg/m³
	Arbeitnehmer	Einatmung	Akut - systemische Effekte	5082 mg/m³
Kaminstaub, Portlandzement	Arbeitnehmer	Einatmung	Langzeit - lokale Effekte	1 mg/m³
	Arbeitnehmer	Einatmung	Akut - lokale Effekte	4 mg/m³
	Verbraucher	Einatmung	Langzeit - lokale Effekte	1 mg/m³

	Verbraucher	Einatmung	Akut - lokale Effekte	4 mg/m³

Abgeschätzte Nicht-Effekt-Konzentration (PNEC) gemäß Verordnung (EG) Nr. 1907/2006

Stoffname	Umweltkompartiment	Wert
Zement, Aluminiumoxid-, Chemikalien	Süßwasser	260 mg/l
	Zeitweise Verwendung/Freisetzung	260 mg/l
	Abwasserkläranlage	10 mg/l
Calciumsulfat	Abwasserkläranlage	100 mg/l
Kaminstaub, Portlandzement	Süßwasser	0,028 mg/l
	Meerwasser	0,003 mg/l
	Zeitweise Verwendung/Freisetzung	0,282 mg/l
	Süßwassersediment	0,875 mg/kg
	Meeressediment	0,088 mg/kg
	Abwasserkläranlage	6 mg/l
	Boden	5 mg/kg

8.2 Begrenzung und Überwachung der Exposition

Technische Schutzmaßnahmen

Für ausreichende Belüftung sorgen, besonders in geschlossenen Räumen.
Expositionskonzentrationen am Arbeitsplatz minimieren.
Sicherstellen dass Behandlungssysteme von Staub (wie Abluftkanäle, Staubfänger, Gefäße und Verarbeitungsgeräte) so konzipiert sind, dass kein Staub in den Arbeitsbereich gelangen kann (z.B. keine Undichtigkeit der Ausrüstung).

Persönliche Schutzausrüstung

Augen-/Gesichtsschutz : Folgende persönliche Schutzausrüstung tragen:
Chemikalienbeständige Schutzbrillen müssen getragen werden.
Falls Spritzer möglich sind, Folgendes tragen:
Gesichtsschutzschild
Die Ausrüstung sollte DIN EN 166 entsprechen

Handschutz
- Material : Nitrilgetränkte Baumwollhandschuhe
- Durchbruchzeit : 480 min
- Handschuhdicke : 0,15 mm

- Anmerkungen : Chemikalienschutzhandschuhe sind in ihrer Ausführung in Abhängigkeit von Gefahrstoffkonzentration und -menge arbeitsplatzspezifisch auszuwählen. Es wird empfohlen, die Chemikalienbeständigkeit der oben genannten Schutzhandschuhe für spezielle Anwendungen mit dem Handschuhhersteller abzuklären. Vor den Pausen und bei Arbeitsende Hände waschen.

Haut- und Körperschutz : Angemessene Schutzkleidung basierend auf den Angaben zur chemischen Beständigkeit und einer Bewertung der potenziellen Exposition vor Ort wählen.
Hautkontakt mittels undurchdringlicher Schutzkleidung vermeiden (Handschuhe, Schürzen, Stiefel etc.).

Atemschutz : Bei Nichtverfügbarkeit einer lokalen Entlüftung oder wenn die

		Expositionsbewertung Expositionen außerhalb der empfohlenen Richtlinien ergibt, ist ein Atemschutz zu verwenden. Die Ausrüstung sollte DIN EN 143 entsprechen
Filtertyp	:	Typ Partikel (P)

ABSCHNITT 9: Physikalische und chemische Eigenschaften

9.1 Angaben zu den grundlegenden physikalischen und chemischen Eigenschaften

Aggregatzustand	:	Pulver
Farbe	:	grau
Geruch	:	geruchlos
Geruchsschwelle	:	Keine Daten verfügbar
Schmelzpunkt/Gefrierpunkt	:	> 1.000 °C
Siedebeginn und Siedebereich	:	Keine Daten verfügbar
Entzündbarkeit (fest, gasförmig)	:	Brennt nicht, Bildung explosiver Staub-/Luft-Gemische nicht zu erwarten.
Obere Explosionsgrenze / Obere Entzündbarkeitsgrenze	:	Nicht anwendbar
Untere Explosionsgrenze / Untere Entzündbarkeitsgrenze	:	Nicht anwendbar
Flammpunkt	:	Nicht anwendbar
Zündtemperatur	:	nicht entzündlich
Zersetzungstemperatur	:	Keine Daten verfügbar
pH-Wert	:	12,5 - 13,5 Konzentration: 66,7 % (wässrige Suspension)
Viskosität		
Viskosität, kinematisch	:	Nicht anwendbar
Löslichkeit(en)		
Wasserlöslichkeit	:	< 2 g/l (20 °C) (für einen Bestandteil dieser Mischung)

Verteilungskoeffizient: n-Octanol/Wasser	:	Nicht anwendbar
Dampfdruck	:	Nicht anwendbar
Dichte	:	2,7 - 3,0 g/cm³ (20 °C)
Schüttdichte	:	ca. 1,2 - 1,4 kg/m³
Relative Dampfdichte	:	Nicht anwendbar
Partikeleigenschaften Partikelgröße	:	2 mm

9.2 Sonstige Angaben

Explosive Stoffe/Gemische	:	Nicht explosiv
Oxidierende Eigenschaften	:	Der Stoff oder das Gemisch ist nicht eingestuft als oxidierend.
Verdampfungsgeschwindigkeit	:	Nicht anwendbar

ABSCHNITT 10: Stabilität und Reaktivität

10.1 Reaktivität

Nicht als reaktionsgefährlich eingestuft.

10.2 Chemische Stabilität

Stabil unter normalen Bedingungen.

10.3 Möglichkeit gefährlicher Reaktionen

Gefährliche Reaktionen : Keine bekannt.

10.4 Zu vermeidende Bedingungen

Zu vermeidende Bedingungen : Keine bekannt.

10.5 Unverträgliche Materialien

Zu vermeidende Stoffe : Säuren

10.6 Gefährliche Zersetzungsprodukte

Es sind keine gefährlichen Zersetzungsprodukte bekannt.

ABSCHNITT 11: Toxikologische Angaben

11.1 Angaben zu den Gefahrenklassen im Sinne der Verordnung (EG) Nr. 1272/2008

Angaben zu : Einatmung

wahrscheinlichen Expositionswegen	Hautkontakt Verschlucken Augenkontakt

Akute Toxizität

Nicht klassifiziert nach den vorliegenden Informationen.

Inhaltsstoffe:

Zement, Aluminiumoxid-, Chemikalien:

Akute orale Toxizität	:	LD50 (Ratte): > 2.000 mg/kg Methode: OECD Prüfrichtlinie 423
Akute dermale Toxizität	:	LD50 (Ratte): > 2.000 mg/kg Methode: OECD Prüfrichtlinie 402 Anmerkungen: Basierend auf Testdaten von ähnlichen Materialien

Zement, Portland-, Chemikalien:

Akute orale Toxizität	:	LD50 (Ratte): > 1.848 mg/kg Anmerkungen: Basierend auf Testdaten von ähnlichen Materialien
Akute inhalative Toxizität	:	LC50 (Ratte): > 6,04 mg/l Expositionszeit: 4 h Testatmosphäre: Staub/Nebel Methode: OECD Prüfrichtlinie 436 Bewertung: Der Stoff oder das Gemisch besitzt keine akute Atmungstoxizität Anmerkungen: Basierend auf Testdaten von ähnlichen Materialien
Akute dermale Toxizität	:	LD50 (Ratte): > 2.000 mg/kg Methode: OECD Prüfrichtlinie 402 Bewertung: Der Stoff oder das Gemisch besitzt keine akute dermale Toxizität Anmerkungen: Basierend auf Testdaten von ähnlichen Materialien

Kaminstaub, Portlandzement:

Akute inhalative Toxizität	:	LC50 (Ratte): > 6,04 mg/l Expositionszeit: 4 h Testatmosphäre: Staub/Nebel Methode: OECD Prüfrichtlinie 436
Akute dermale Toxizität	:	LD50 (Ratte): > 2.000 mg/kg Methode: OECD Prüfrichtlinie 402

Ätz-/Reizwirkung auf die Haut

Nicht klassifiziert nach den vorliegenden Informationen.

Inhaltsstoffe:

Zement, Aluminiumoxid-, Chemikalien:

Spezies	:	Kaninchen
Methode	:	OECD Prüfrichtlinie 404
Ergebnis	:	Keine Hautreizung

Zement, Portland-, Chemikalien:

Spezies	:	rekonstruierte menschliche Epidermis
Methode	:	OECD Prüfrichtlinie 431
Ergebnis	:	Hautreizung
Anmerkungen	:	Basierend auf Testdaten von ähnlichen Materialien

Kaminstaub, Portlandzement:

Ergebnis	:	Hautreizung

Schwere Augenschädigung/-reizung

Verursacht schwere Augenschäden.

Inhaltsstoffe:

Zement, Aluminiumoxid-, Chemikalien:

Spezies	:	Kaninchen
Ergebnis	:	Augenreizend, reversibel innerhalb 21 Tagen

Zement, Portland-, Chemikalien:

Spezies	:	Kaninchen
Methode	:	OECD Prüfrichtlinie 405
Ergebnis	:	Irreversible Schädigung der Augen
Anmerkungen	:	Basierend auf Testdaten von ähnlichen Materialien

Kaminstaub, Portlandzement:

Spezies	:	Kaninchen
Methode	:	OECD Prüfrichtlinie 405
Ergebnis	:	Irreversible Schädigung der Augen
Anmerkungen	:	Basierend auf Testdaten von ähnlichen Materialien

Sensibilisierung der Atemwege/Haut

Sensibilisierung durch Hautkontakt

Kann allergische Hautreaktionen verursachen.

Sensibilisierung durch Einatmen

Nicht klassifiziert nach den vorliegenden Informationen.

Inhaltsstoffe:

Zement, Aluminiumoxid-, Chemikalien:

Art des Testes	:	Maximierungstest
Expositionswege	:	Hautkontakt
Spezies	:	Meerschweinchen
Methode	:	OECD Prüfrichtlinie 406
Ergebnis	:	negativ
Anmerkungen	:	Basierend auf Testdaten von ähnlichen Materialien

Zement, Portland-, Chemikalien:

Expositionswege	:	Hautkontakt
Spezies	:	Menschen
Ergebnis	:	positiv
Bewertung	:	Geringe oder moderate Sensibilisierungsrate der Haut beim Menschen wahrscheinlich oder bewiesen.

Kaminstaub, Portlandzement:

Expositionswege	:	Hautkontakt
Spezies	:	Menschen
Ergebnis	:	positiv
Anmerkungen	:	Basierend auf Testdaten von ähnlichen Materialien
Bewertung	:	Sensibilisierung der Haut beim Menschen wahrscheinlich oder bewiesen

Keimzell-Mutagenität

Nicht klassifiziert nach den vorliegenden Informationen.

Inhaltsstoffe:

Zement, Aluminiumoxid-, Chemikalien:

Gentoxizität in vitro	:	Art des Testes: Bakterieller Rückmutationstest (AMES) Methode: OECD Prüfrichtlinie 471 Ergebnis: negativ Art des Testes: Chromosomenaberrationstest in vitro Methode: OECD Prüfrichtlinie 473 Ergebnis: negativ Art des Testes: In-Vitro-Genmutationstest an Säugetierzellen Methode: OECD Prüfrichtlinie 476 Ergebnis: negativ Anmerkungen: Basierend auf Testdaten von ähnlichen Materialien

Zement, Portland-, Chemikalien:

Gentoxizität in vitro	:	Art des Testes: In-vitro-Mikrokerntest Ergebnis: negativ Anmerkungen: Basierend auf Testdaten von ähnlichen Materialien

Kaminstaub, Portlandzement:

Gentoxizität in vitro : Art des Testes: In-vitro-Mikrokerntest
Methode: OECD Prüfrichtlinie 487
Ergebnis: positiv

Karzinogenität

Nicht klassifiziert nach den vorliegenden Informationen.

Reproduktionstoxizität

Nicht klassifiziert nach den vorliegenden Informationen.

Inhaltsstoffe:

Zement, Portland-, Chemikalien:

Wirkung auf die Fruchtbarkeit : Art des Testes: Toxizitätsstudie mit kombinierten wiederholten Dosen mit Screeningtest auf Reproduktions-/Entwicklungstoxizität
Spezies: Ratte
Applikationsweg: Verschlucken
Methode: OECD Prüfrichtlinie 422
Ergebnis: negativ
Anmerkungen: Basierend auf Testdaten von ähnlichen Materialien

Effekte auf die Fötusentwicklung : Art des Testes: Toxizitätsstudie mit kombinierten wiederholten Dosen mit Screeningtest auf Reproduktions-/Entwicklungstoxizität
Spezies: Ratte
Applikationsweg: Verschlucken
Methode: OECD Prüfrichtlinie 422
Ergebnis: negativ
Anmerkungen: Basierend auf Testdaten von ähnlichen Materialien

Kaminstaub, Portlandzement:

Wirkung auf die Fruchtbarkeit : Art des Testes: Toxizitätsstudie mit kombinierten wiederholten Dosen mit Screeningtest auf Reproduktions-/Entwicklungstoxizität
Spezies: Ratte
Applikationsweg: Verschlucken
Methode: OECD Prüfrichtlinie 422
Ergebnis: negativ

Spezifische Zielorgan-Toxizität bei einmaliger Exposition

Nicht klassifiziert nach den vorliegenden Informationen.

Inhaltsstoffe:

Zement, Portland-, Chemikalien:

Bewertung : Kann die Atemwege reizen.

Kaminstaub, Portlandzement:

Bewertung : Kann die Atemwege reizen.

Spezifische Zielorgan-Toxizität bei wiederholter Exposition

Nicht klassifiziert nach den vorliegenden Informationen.

Toxizität bei wiederholter Verabreichung

Inhaltsstoffe:

Zement, Portland-, Chemikalien:

Spezies	:	Ratte
NOAEL	:	374 mg/kg
Applikationsweg	:	Verschlucken
Expositionszeit	:	28 Tage
Methode	:	OECD Prüfrichtlinie 422
Anmerkungen	:	Basierend auf Testdaten von ähnlichen Materialien

Kaminstaub, Portlandzement:

Spezies	:	Ratte
NOAEL	:	374 mg/kg
Applikationsweg	:	Verschlucken
Expositionszeit	:	6 - 7 Wochen
Methode	:	OECD Prüfrichtlinie 422

Aspirationstoxizität

Nicht klassifiziert nach den vorliegenden Informationen.

11.2 Angaben über sonstige Gefahren

Endokrinschädliche Eigenschaften

Nicht klassifiziert nach den vorliegenden Informationen.

Produkt:

Bewertung : Der Stoff/dieses Gemisch enthält keine Bestandteile, die gemäß REACH Artikel 57(f) oder der delegierten Verordnung (EU) 2017/2100 der Kommission oder der delegierten Verordnung (EU) 2018/605 der Kommission in Mengen von 0,1 % oder mehr endokrinschädliche Eigenschaften aufweisen.

ABSCHNITT 12: Umweltbezogene Angaben

12.1 Toxizität

Inhaltsstoffe:

Zement, Aluminiumoxid-, Chemikalien:

Toxizität gegenüber Fischen	:	LC50 (Danio rerio (Zebrabärbling)): > 100 mg/l Expositionszeit: 96 h Methode: OECD Prüfrichtlinie 203
Toxizität gegenüber Daphnien und anderen wirbellosen Wassertieren	:	EC50 (Daphnia magna (Großer Wasserfloh)): 5,4 mg/l Expositionszeit: 48 h Methode: OECD- Prüfrichtlinie 202
Toxizität gegenüber Algen/Wasserpflanzen	:	ErC50 (Desmodesmus subspicatus (Grünalge)): 3,6 mg/l Expositionszeit: 72 h Methode: OECD- Prüfrichtlinie 201 NOEC (Desmodesmus subspicatus (Grünalge)): 2,2 mg/l Expositionszeit: 72 h Methode: OECD- Prüfrichtlinie 201

Zement, Portland-, Chemikalien:

Toxizität gegenüber Daphnien und anderen wirbellosen Wassertieren	:	EC50 (Daphnia magna (Großer Wasserfloh)): > 100 mg/l Expositionszeit: 48 h Testsubstanz: Wasserlösliche Anteile Methode: OECD- Prüfrichtlinie 202 Anmerkungen: Basierend auf Testdaten von ähnlichen Materialien
Toxizität gegenüber Algen/Wasserpflanzen	:	EC50 (Desmodesmus subspicatus (Grünalge)): 28,2 mg/l Expositionszeit: 72 h Testsubstanz: Wasserlösliche Anteile Methode: OECD- Prüfrichtlinie 201 Anmerkungen: Keine Toxizität an der Löslichkeitsgrenze Basierend auf Testdaten von ähnlichen Materialien NOEC (Desmodesmus subspicatus (Grünalge)): 6,25 mg/l Expositionszeit: 72 h Testsubstanz: Wasserlösliche Anteile Methode: OECD- Prüfrichtlinie 201 Anmerkungen: Basierend auf Testdaten von ähnlichen Materialien
Toxizität bei Mikroorganismen	:	EC50 : 743 mg/l Expositionszeit: 3 h Anmerkungen: Basierend auf Testdaten von ähnlichen Materialien

Toxizität gegenüber Daphnien und anderen wirbellosen Wassertieren (Chronische Toxizität)	:	NOEC: 50 mg/l Expositionszeit: 21 d Spezies: Daphnia magna (Großer Wasserfloh) Methode: OECD- Prüfrichtlinie 211 Anmerkungen: Basierend auf Testdaten von ähnlichen Materialien

Kaminstaub, Portlandzement:

Toxizität gegenüber Fischen	:	NOEC (Danio rerio (Zebrabärbling)): 11,1 mg/l Expositionszeit: 96 h Methode: OECD Prüfrichtlinie 203
Toxizität gegenüber Daphnien und anderen wirbellosen Wassertieren	:	EL50 (Daphnia magna (Großer Wasserfloh)): > 100 mg/l Expositionszeit: 48 h Testsubstanz: Wasserlösliche Anteile Methode: OECD- Prüfrichtlinie 202
Toxizität gegenüber Daphnien und anderen wirbellosen Wassertieren (Chronische Toxizität)	:	NOELR: 50 mg/l Spezies: Daphnia magna (Großer Wasserfloh) Testsubstanz: Wasserlösliche Anteile Methode: OECD- Prüfrichtlinie 211

12.2 Persistenz und Abbaubarkeit

Keine Daten verfügbar

12.3 Bioakkumulationspotenzial

Keine Daten verfügbar

12.4 Mobilität im Boden

Keine Daten verfügbar

12.5 Ergebnisse der PBT- und vPvB-Beurteilung

Produkt:

Bewertung	:	Dieser Stoff/diese Mischung enthält keine Komponenten in Konzentrationen von 0,1 % oder höher, die entweder als persistent, bioakkumulierbar und toxisch (PBT) oder sehr persistent und sehr bioakkumulierbar (vPvB) eingestuft sind.

12.6 Endokrinschädliche Eigenschaften

Produkt:

Bewertung	:	Der Stoff/dieses Gemisch enthält keine Bestandteile, die gemäß REACH Artikel 57(f) oder der delegierten Verordnung (EU) 2017/2100 der Kommission oder der delegierten Verordnung (EU) 2018/605 der Kommission in Mengen von 0,1 % oder mehr endokrinschädliche Eigenschaften aufweisen.

12.7 Andere schädliche Wirkungen

Keine Daten verfügbar

ABSCHNITT 13: Hinweise zur Entsorgung

13.1 Verfahren der Abfallbehandlung

Produkt	:	Unter Beachtung der örtlichen behördlichen Bestimmungen beseitigen. Gemäß europäischem Abfallkatalog (EAK) sind Abfallschlüsselnummern nicht produkt- sondern anwendungsbezogen. Abfallschlüsselnummern sollen vom Verbraucher, möglichst in Absprache mit den Abfallentsorgungsbehörden, ausgestellt werden. Abfälle nicht in den Ausguss schütten.
Verunreinigte Verpackungen	:	Leere Behälter einer anerkannten Abfallentsorgungsanlage zuführen zwecks Wiedergewinnung oder Entsorgung. Falls nicht anders angegeben: Entsorgung als unbenutztes Produkt.
Abfallschlüssel-Nr.	:	Die folgenden Abfallschlüsselnummern sind nur als Empfehlung gedacht: gebrauchtes Produkt 17 01 01, Beton nicht gebrauchtes Produkt 17 01 01, Beton ungereinigte Verpackung 15 01 05, Verbundverpackungen Gem. Verpackungsgesetz restentleerte Verpackungen: Restentleerte, nicht kontaminierte Verpackungen nicht schadstoffhaltiger Füllgüter können den Erfassungssystemen für Verkaufsverpackungen zur Verwertung zugeführt werden.

ABSCHNITT 14: Angaben zum Transport

14.1 UN-Nummer oder ID-Nummer

ADN	:	Nicht als Gefahrgut eingestuft
ADR	:	Nicht als Gefahrgut eingestuft
RID	:	Nicht als Gefahrgut eingestuft
IMDG	:	Nicht als Gefahrgut eingestuft
IATA	:	Nicht als Gefahrgut eingestuft

14.2 Ordnungsgemäße UN-Versandbezeichnung

ADN	:	Nicht als Gefahrgut eingestuft
ADR	:	Nicht als Gefahrgut eingestuft
RID	:	Nicht als Gefahrgut eingestuft
IMDG	:	Nicht als Gefahrgut eingestuft
IATA	:	Nicht als Gefahrgut eingestuft

14.3 Transportgefahrenklassen

ADN	:	Nicht als Gefahrgut eingestuft
ADR	:	Nicht als Gefahrgut eingestuft
RID	:	Nicht als Gefahrgut eingestuft
IMDG	:	Nicht als Gefahrgut eingestuft
IATA	:	Nicht als Gefahrgut eingestuft

14.4 Verpackungsgruppe

ADN	:	Nicht als Gefahrgut eingestuft
ADR	:	Nicht als Gefahrgut eingestuft
RID	:	Nicht als Gefahrgut eingestuft
IMDG	:	Nicht als Gefahrgut eingestuft
IATA (Fracht)	:	Nicht als Gefahrgut eingestuft
IATA (Passagier)	:	Nicht als Gefahrgut eingestuft

14.5 Umweltgefahren

Nicht als Gefahrgut eingestuft

14.6 Besondere Vorsichtsmaßnahmen für den Verwender

Nicht anwendbar

14.7 Massengutbeförderung auf dem Seeweg gemäß IMO-Instrumenten

Anmerkungen : Auf Produkt im Lieferzustand nicht zutreffend.

ABSCHNITT 15: Rechtsvorschriften

15.1 Vorschriften zu Sicherheit, Gesundheits- und Umweltschutz/spezifische Rechtsvorschriften für den Stoff oder das Gemisch

REACH - Beschränkungen der Herstellung, des Inverkehrbringens und der Verwendung bestimmter gefährlicher Stoffe, Gemische und Erzeugnisse (Anhang XVII)	:	Nicht anwendbar
REACH - Liste der für eine Zulassung in Frage kommenden besonders besorgniserregenden Stoffe (Artikel 59).	:	Nicht anwendbar

Verordnung (EG) Nr. 2024/590 über Stoffe, die zum Abbau der Ozonschicht führen	:	Nicht anwendbar
Verordnung (EU) 2019/1021 über persistente organische Schadstoffe (Neufassung)	:	Nicht anwendbar
Verordnung (EU) Nr. 649/2012 des Europäischen Parlaments und des Rates über die Aus- und Einfuhr gefährlicher Chemikalien	:	Nicht anwendbar
REACH - Verzeichnis der zulassungspflichtigen Stoffe (Anhang XIV)	:	Nicht anwendbar

Seveso III: Richtlinie 2012/18/EU des Europäischen Parlaments und des Rates zur Beherrschung der Gefahren schwerer Unfälle mit gefährlichen Stoffen.
Nicht anwendbar

Wassergefährdungsklasse	:	WGK 1 schwach wassergefährdend Einstufung nach AwSV, Anlage 1 (5.2)
Flüchtige organische Verbindungen	:	Richtlinie 2010/75/EU des Europäischen Parlaments und des Rates vom 24. November 2010 über Emissionen aus Industrie und Tierhaltung (integrierte Vermeidung und Verminderung der Umweltverschmutzung) Gehalt flüchtiger organischer Verbindungen (VOC): 0 %, 0 g/l Anmerkungen: VOC(flüchtige organische Verbindung)-Gehalt abzüglich Wasser

Sonstige Vorschriften:

Beschäftigungsbeschränkungen gemäß Richtlinie 94/33/EG über den Jugendarbeitsschutz oder verschärfenden nationalen Bestimmungen beachten, soweit zutreffend.

15.2 Stoffsicherheitsbeurteilung

Eine Stoffsicherheitsbewertung wurde nicht durchgeführt.

ABSCHNITT 16: Sonstige Angaben

Sonstige Angaben	:	Positionen, bei denen Veränderungen gegenüber der vorherigen Fassung vorgenommen wurden, sind im Textkörper durch zwei vertikale Linien hervorgehoben.

Volltext der H-Sätze

H315	:	Verursacht Hautreizungen.
H317	:	Kann allergische Hautreaktionen verursachen.
H318	:	Verursacht schwere Augenschäden.
H319	:	Verursacht schwere Augenreizung.
H335	:	Kann die Atemwege reizen.

Volltext anderer Abkürzungen

Eye Dam.	:	Schwere Augenschädigung
Eye Irrit.	:	Augenreizung
Skin Irrit.	:	Reizwirkung auf die Haut
Skin Sens.	:	Sensibilisierung durch Hautkontakt
STOT SE	:	Spezifische Zielorgan-Toxizität - einmalige Exposition

DE DFG MAK	:	Deutschland. MAK- und BAT Anhang IIa
DE TRGS 900	:	Deutschland. TRGS 900 - Arbeitsplatzgrenzwerte
DE DFG MAK / MAK	:	MAK-Wert

ADN - Europäisches Übereinkommen über die internationale Beförderung gefährlicher Güter auf Binnenwasserstrassen; ADR - Übereinkommen über die internationale Beförderung gefährlicher Güter auf der Straße; AIIC - Australisches Verzeichnis von Industriechemikalien; ASTM - Amerikanische Gesellschaft für Werkstoffprüfung; bw - Körpergewicht; CLP - Verordnung über die Einstufung, Kennzeichnung und Verpackung von Stoffen, Verordnung (EG) Nr 1272/2008; CMR - Karzinogener, mutagener oder reproduktiver Giftstoff; DIN - Norm des Deutschen Instituts für Normung; DSL - Liste heimischer Substanzen (Kanada); ECHA - Europäische Chemikalienbehörde; EC-Number - Nummer der Europäischen Gemeinschaft; ECx - Konzentration verbunden mit x % Reaktion; ELx - Beladungsrate verbunden mit x % Reaktion; EmS - Notfallplan; ENCS - Vorhandene und neue chemische Substanzen (Japan); ErCx - Konzentration verbunden mit x % Wachstumsgeschwindigkeit; GHS - Global harmonisiertes System; GLP - Gute Laborpraxis; IARC - Internationale Krebsforschungsagentur; IATA - Internationale Luftverkehrs-Vereinigung; IBC - Internationaler Code für den Bau und die Ausrüstung von Schiffen zur Beförderung gefährlicher Chemikalien als Massengut; IC50 - Halbmaximale Hemmstoffkonzentration; ICAO - Internationale Zivilluftfahrt-Organisation; IECSC - Verzeichnis der in China vorhandenen chemischen Substanzen; IMDG - Code – Internationaler Code für die Beförderung gefährlicher Güter mit Seeschiffen; IMO - Internationale Seeschifffahrtsorganisation; ISHL - Gesetz- über Sicherheit und Gesundheitsschutz am Arbeitsplatz (Japan); ISO - Internationale Organisation für Normung; KECI - Verzeichnis der in Korea vorhandenen Chemikalien; LC50 - Lethale Konzentration für 50 % einer Versuchspopulation; LD50 - Lethale Dosis für 50 % einer Versuchspopulation (mittlere lethale Dosis); MARPOL - Internationales Übereinkommen zur Verhütung der Meeresverschmutzung durch Schiffe; n.o.s. - nicht anderweitig genannt; NO(A)EC - Konzentration, bei der keine (schädliche) Wirkung erkennbar ist; NO(A)EL - Dosis, bei der keine (schädliche) Wirkung erkennbar ist; NOELR - Keine erkennbare Effektladung; NZIoC - Neuseeländisches Chemikalienverzeichnis; OECD - Organisation für wirtschaftliche Zusammenarbeit und Entwicklung; OPPTS - Büro für chemische Sicherheit und Verschmutzungsverhütung (OSCPP); PBT - Persistente, bioakkumulierbare und toxische Substanzen; PICCS - Verzeichnis der auf den Philippinen vorhandenen Chemikalien und chemischen Substanzen; (Q)SAR - (Quantitative) Struktur-Wirkungsbeziehung; REACH - Verordnung (EG) Nr. 1907/2006 des Europäischen Parliaments und des Rats bezüglich der Registrierung, Bewertung, Genehmigung und Restriktion von Chemikalien; RID - Regelung zur internationalen Beförderung gefährlicher Güter im Schienenverkehr; SADT - Selbstbeschleunigende Zersetzungstemperatur; SDS - Sicherheitsdatenblatt; SVHC - besonders besorgniserregender Stoff; TCSI - Verzeichnis der in Taiwan vorhandenen chemischen Substanzen; TECI - Thailand Lagerbestand Vorhandener Chemikalien; TRGS - Technischen Regeln für Gefahrstoffe; TSCA - Gesetz zur Kontrolle giftiger Stoffe (Vereinigte Staaten); UN - Vereinte Nationen; vPvB - Sehr persistent und sehr bioakkumulierbar

Weitere Information

Quellen der wichtigsten Daten, die zur Erstellung des Datenblatts verwendet wurden	:	Interne technische Daten, Rohstoffdaten von den SDB, Suchergebnisse des OECD eChem Portals und der Europäischen Chemikalienagentur, http://echa.europa.eu/

Einstufung des Gemisches:		**Einstufungsverfahren:**
Eye Dam. 1	H318	Rechenmethode

Skin Sens. 1	H317	Rechenmethode

Die in diesem Sicherheitsdatenblatt enthaltenenen Informationen sind nach bestem Wissen und Gewissen erstellt worden und basieren auf dem Wissensstand zum Zeitpunkt der Veröffentlichung. Die Informationen dienen lediglich als Richtlinie für eine sichere Handhabung, Verwendung, Verarbeitung, Lagerung, Transport, Entsorgung und Freisetzung und stellen keine Gewährleistung oder Qualitätsspezifikation dar. Die vorliegenden Informationen beziehen sich nur auf den oben in diesem SDB bezeichneten Stoff und gelten nicht bei Verwendung des im SDB angegebenen Stoffes in Kombination mit anderen Stoffen oder in anderen Verfahren, sofern nicht anders im Text angegeben ist. Anwender des Stoffes sollten die Informationen und Empfehlungen im konkreten Einzelfall der vorgesehenen Handhabung, Verwendung, Verarbeitung und Lagerung, einschließlich gegebenenfalls einer Beurteilung der Angemessenheit des im SDB bezeichneten Stoffes im Endprodukt des Anwenders, überprüfen.

DE / DE

HERSTELLERERKLÄRUNG

Firma	Adolf Würth GmbH & Co. KG
Artikelnummer	5875200201
Produktbezeichnung	Bodenausgleichsmasse CERAfix 201-2
Anwendung/ Beschreibung	Spannungsarmer selbstverlaufender Zementfließspachtel für Schichtdicken von 2 – 40 mm

Anforderungen	Erfüllt	Bemerkung
SVHC	Ja	s. SDB* (Abschnitt 3.2)
VOC-Gehalt	Ja	s. SDB* (Abschnitt 15.1)
CMR-Stoffe der Kategorie 1A/1B < 0,10%	Ja	
GISCODE Einstufung	ZP1	

Vorhandene Dokumente

Sicherheitsdatenblatt (SDB*)	s. Onlineshop
Prüfzeugnisse Sonstiges	EC1+

01/26

Dieses Dokument ist ohne Unterschrift gültig.

Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e.V.
Association for the Control of Emissions from Products for Flooring Installation, Adhesives and Building Materials

GEV EMICODE®

Awarding of licence for the use of EMICODE

Licence Number:	4631/01.01.05
For the product	Würth CERAfix 201-2
Due to application date	17.07.2013

With reference to the classification in accordance with the directives as stipulated in § 10 of the GEV trademark constitution

on behalf of the GEV for the above mentioned product as per § 5, section 4 of the GEV trademark constitution is awarded the licence for the use of the GEV trademark



This product meets with the guidelines for the criteria of use listed reverse.
The company is ordinary member of the GEV.

OM034 05.10.2021
valid until 05.10.2026

The Secretary General
Association for the Control of Emissions in Products for Flooring Installation, Adhesives and Building Materials (GEV)
Völklinger Straße 4 · D-40219 Düsseldorf

Requirement guidelines for the awarding of the EMICODE licence

The product mentioned on the front side of the licence has to fulfil among others the following criteria in accordance with the Constitution and the guidelines of the Technical Advisory Board of the GEV:

- The product meets all the legal requirements, especially the chemical laws and their specifications.
- The product is solvent free as specified in clause 2.4 of the “GEV Classification Criteria”, except if it is a surface treatment product. If the product is assigned to a GISCODE product group then this can be labelled.
- A safety data sheet (SDS) according to local law in its respectively valid version is issued for the product.
- Carcinogenic, mutagenic, reprotoxic substances of the categories 1A or 1B are not added during the manufacture of the product.
- The testing of the product is performed in accordance with the GEV Testing Method. VOC determination is performed in a test chamber followed by the Tenax / thermal desorption procedures with subsequent GC/MS analysis.
- The assignment of an EMICODE class is performed according to the following criteria and TVOC/TSVOC concentration levels. The corresponding EMICODE class shall be used to label the product:

1) Installation products, adhesives and construction products

Parameter	EC 1 PLUS	EC 1	EC 2
	max. allowed concentration [µg/m³]		
TVOC after 3 days	≤ 750	≤ 1000	≤ 3000
TVOC after 28 days	≤ 60	≤ 100	≤ 300
TSVOC after 28 days	≤ 40	≤ 50	≤ 100
R value based on German AgBB LCI (NIK) after 28 days	1	-	-
Sum of non-assessable VOC	≤ 40	-	-
Formaldehyde after 3 days	≤ 50	≤ 50	≤ 50
Acetaldehyde after 3 days	≤ 50	≤ 50	≤ 50
Sum of form- and acetaldehyde	≤ 0.05 ppm	≤ 0.05 ppm	≤ 0.05 ppm
Sum of volatile C1A/C1B after 3 days	≤ 10	≤ 10	≤ 10
Any volatile C1A/C1B after 28 days	≤ 1	≤ 1	≤ 1

2) Products for floor surface treatments for parquet, mineral floors and resilient floorings

Parameter	EC 1 PLUS	EC 1	EC 2
	max. allowed concentration [µg/m³]		
Sum TVOC + TSVOC after 28 days	≤ 100 thereof max. 40 SVOC	≤ 150 thereof max. 50 SVOC	≤ 450 thereof max. 100 SVOC
Formaldehyde after 3 days	≤ 50	≤ 50	≤ 50
Acetaldehyde after 3 days	≤ 50	≤ 50	≤ 50
Any volatile C1A/C1B after 3 days	≤ 10	≤ 10	≤ 10
Any volatile C1A/C1B after 28 days	≤ 1	≤ 1	≤ 1

STATEMENT OF CONFORMITY

Adolf Würth GmbH & Co. KG confirms that the following products are compliant with Model EPD:

Declaration number:	EPD-DBC-20220217-IBF1-EN
Würth Compliant Product Numbers:	5875200402, 5875200403, 5875200404, 5875200412, 5875200201, 5875500500, 5875500501, 5875500502, 5875500530, 5875500540, 5875101506, 5875102506, 5875103506, 5875104506, 5875105506, 5875106506, 5875107506, 5875112506, 5875115506, 5875500560, 5875500210, 5875500550, 5875500200, 5875500400, 5875500420, 5875500410, 5875500430
EPD-Name:	Modified mineral mortar, group 1

In collaboration, the Deutsche Bauchemie e.V. (DBC), the Association of the European Adhesive and Sealant Industry (FEICA), the Industrieverband Klebstoffe e.V. (IVK), and the European Federation for Construction Chemicals (EFFCC) have developed model Environmental Product Declarations for a variety of construction chemical products. These declarations have been verified and published by the IBU (Institut Bauen und Umwelt).

This declaration confirms the compliance of above mentioned product with the specific model EPD.

28.02.2025

ENVIRONMENTAL PRODUCT DECLARATION

as per *ISO 14025* and *EN 15804+A2*

Owner of the Declaration	FEICA, EFCC, IVK, DBC
Programme holder	Institut Bauen und Umwelt e.V. (IBU)
Publisher	Institut Bauen und Umwelt e.V. (IBU)
Declaration number	EPD-DBC-20220217-IBF1-EN
Issue date	26.09.2022
Valid to	25.09.2027

Modified mineral mortars, group 1

FEICA - Association of the European Adhesive and Sealant Industry

EFCC - European Federation for Construction Chemicals

IVK - Industrieverband Klebstoffe e.V.

DBC - Deutsche Bauchemie e.V.

Institut Bauen und Umwelt e.V.

www.ibu-epd.com | https://epd-online.com

ECO PLATFORM EPD VERIFIED



1. General Information

DBC - Deutsche Bauchemie e.V.
EFCC - European Federation for Construction Chemicals
FEICA - Association of the European Adhesive and Sealant Industry
IVK - Industrieverband Klebstoffe e.V.

Modified mineral mortars, group 1

Programme holder
IBU – Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

Owner of the declaration
DBC, Mainzer Landstr. 55, D-60329 Frankfurt a.M.
EFCC, 172 Boulevard du Triomphe, B-1160 Brussels
FEICA, Rue Belliard 40, B-1040 Brussels
IVK, Völklingerstr. 4, D-40219 Düsseldorf

Declaration number
EPD-DBC-20220217-IBF1-EN

Declared product / declared unit
1 kg of modified mineral mortar with a density 800 - 1,700 kg/m³

This declaration is based on the product category rules:
Mineral factory-made mortar, 11.2017
(PCR checked and approved by the SVR)

Scope:
This verified EPD entitles the holder to bear the symbol of the Institut Bauen und Umwelt e.V. It exclusively applies to products produced in Europe and for a period of five years from the date of issue. This EPD may be used by members of FEICA, EFCC, DBC and IVK and their members provided it has been proven that the respective product can be represented by this EPD. For this purpose, a guideline is available at the secretariats of the four associations. The members of the associations are listed on their respective websites.

Issue date
26.09.2022

Valid to
25.09.2027

The owner of the declaration shall be liable for the underlying information and evidence; the IBU shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

The EPD was created according to the specifications of *EN 15804+A2*. In the following, the standard will be simplified as *EN 15804*.

Verification

The standard *EN 15804* serves as the core PCR
Independent verification of the declaration and data according to *ISO 14025:2011*
☐ internally ☒ externally

Dipl. Ing. Hans Peters
(chairman of Institut Bauen und Umwelt e.V.)

Dr. Alexander Röder
(Managing Director Institut Bauen und Umwelt e.V.))

Matthias Schulz
(Independent verifier)

2. Product

2.1 Product description/Product definition

Modified mineral mortars are combinations of one or more inorganic binders, fillers, aqueous dispersions or dispersion powders, water and if necessary additives. They comply with manifold, often specific, functions in the construction, furnishing and refurbishment of buildings. The product displaying the highest environmental impacts was used as a representative product for calculating the Life Cycle Assessment results (worst-case approach).

For the placing on the market in the European Union/European Free Trade Association (EU/EFTA) with the exception of Switzerland) products falling under the Regulation (EU) No 305/2011 (*CPR*) need a Declaration of Performance taking into consideration either the relevant harmonised European standard or the European Technical Assessment and the CE marking. For the application and use of the products the respective national provisions apply.

2.2 Application

Modified mineral mortars are used for the following applications:

Module 1: Modified mineral mortars as repair mortar for the protection and repair of concrete structures
1.1 Products used to restore and/or replace defective concrete
1.2 Products to protect reinforcement, necessary to extend the service life of a concrete structure exhibiting deterioration

Module 2: Adhesives based on modified mineral mortars
2.1 Products for bonding ceramic tiles as well as natural stone for internal and external installations on walls, floors and ceilings
2.2 Products for bonding thermal insulation composite panels

Module 3: Modified mineral mortars as joint fillers
Products for joint filling of wall and floor coverings made of ceramic tiles as well as natural stone for indoor and outdoor applications

Module 4: Modified mineral mortars as screed, floor levelling compounds, fillers, flowing screed
Products for screed/synthetic resin screed for use in floor constructions

Module 5: Modified mineral mortars as levelling compounds for walls and ceilings
Products for levelling and repairing rough, uneven walls, for repairing grit spots, closing blowholes and modelling broken corners and edges

Module 6: Modified mineral mortars as grouts
Products for grouting on holes, recesses, concrete precast columns, foundations and for anchoring machine components indoors and outdoors

Module 7: Modified mineral mortars for liquid applied products for waterproofing of buildings
Products for providing cement-based waterproofing surfaces in structural and civil engineering. For use in new and old buildings as well as beneath tiles
7.1 Liquid-applied water impermeable products for use beneath ceramic tiling
7.2 Products for waterproofing with mineral waterproofing slurries or flexible polymer modified thick coatings
7.3 Products for water proofing in conjunction with ceramic tiles
7.4 Products for waterproofing with flexible polymer modified mineral thick coatings

Module 8: Modified mineral mortars for waterproofing floors and/or walls inside buildings
Products for watertight covering in wet rooms inside buildings

2.3 Technical Data

The density of the products is between 0,80 and 1,70 g/cm³, other relevant technical data can be found in the manufacturer's technical documentation.
Construction products with Declaration of Performance in accordance with *CPR* and the manufacturer's technical documentation:

Module 1: Modified mineral mortars as repair mortar for the protection and repair of concrete structures
1.1 Products used to restore and/or replace defective concrete
The requirements on essential characteristics for all intended uses in accordance with *EN 1504-3*, Tables 1 and 3, must be maintained. These are:
- Compressive strength (*EN 12190*)
- Chloride ion content (*EN 1015-17*)
- Adhesive strength by pull-off test (*EN 1542*)

1.2 Products to protect reinforcement
The requirements on essential characteristics for all intended uses in accordance with *EN 1504-7*, Table 1, must be maintained. This is
- Corrosion protection (*EN 15183*)
Further essential characteristics in accordance with the manufacturer's technical documentation/declaration of performance

Module 2: Adhesives based on modified mineral mortars
2.1 Products for bonding ceramic tiles as well as natural stone for internal and external installations on walls, floors and ceilings
The requirements on essential characteristics according to *EN 12004*, Table 1, must be maintained. These are:
- Tensile adhesion strength after dry storage (*EN 12004-2*)
- Tensile adhesion strength after water immersion (*EN 12004-2*)
- Tensile adhesion strength after heat ageing (*EN 12004-2*)
- Tensile adhesion strength after freeze/thaw cycles (*EN 12004-2*)
- Open time: Tensile strength (*EN 12004-2*)
Further essential characteristics in accordance with the manufacturer's technical documentation/declaration of performance
2.2 The minimum requirement of *EAD 040083-00-0404* External Thermal Insulation Composite Systems with Rendering must be maintained. The essential characteristics are to be specified in accordance with the European technical assessment (ETA, specification no.). Further essential characteristics in accordance with the manufacturer's technical documentation/declaration of performance

Module 3: Modified mineral mortars as joint fillers
The minimum requirements of *EN 13888* must be maintained.

Module 4: Modified mineral mortars as screed, floor levelling compounds, fillers, flowing screed
The requirements on essential characteristics according to *EN 13813* 'Screed material and floor screeds – Screed materials – Properties and requirements' must be maintained. For synthetic resin screeds, these are:
- Bond strength (*EN 13892-8*)
- Reaction to fire (*EN 13501-1*)
Further essential characteristics in accordance with the manufacturer's technical documentation/declaration of performance

Module 5: Modified mineral mortars as levelling compounds for walls and ceilings
Module 5.1: The minimum requirements of *EN 998-1* apply. These are: - Reaction to fire (*EN 13501-1*) -

Compressive strength - Dry bulk density - Capillary water absorption - Water vapour permeability
Further essential characteristics in accordance with the manufacturer's technical documentation/declaration of performance
Module 5.2: The minimum requirements of *EN 13279* apply. Further essential characteristics in accordance with the manufacturer's technical documentation/declaration of performance

Module 6: Modified mineral mortars as grouts
The requirements of *DAfStb Guideline* on 'Production and use of cement-bound flow concrete and grouting mortar' (VeBMR) must be maintained.
The requirements according to *MVV TB* No. C 2.1.4.5 for "Ü-mark" must be maintained.

Module 7: Modified mineral mortars for liquid applied products for waterproofing of buildings
7.1
The requirements according to *EN 14891* , table 1, must be maintained. These are:
- initial tensile adhesion strength *EN 14891*
- Tensile adhesion strength after water contact *EN 14891*
- Waterproofing *EN 14891*
- Crack bridging ability *EN 14891*

7.2
The minimum requirements of the 'Testing principles for granting general building authority approved test certificates for waterproofing with mineral waterproofing slurries and flexible polymer modified thick coatings' (*PG MDS/FPD*) must be maintained.
The characteristics for the proof of usability are to be specified in accordance with the test principles for granting general building authority test certificates for waterproofing with mineral waterproofing slurries and flexible polymer thick coatings.
7.3
The minimum requirements of the 'testing principles for granting general building authority approved test certificates for waterproofing in conjunction with ceramic tiles' (*PG AIV*) must be considered.
7.4
The minimum requirement of *EAD 030295-00-0605* must be maintained. The essential characteristics are to be specified in accordance with the European technical assessment (ETA, specification no.).

Module 8: Modified mineral mortars for waterproofing floors and/or walls inside buildings
The minimum requirement of *EAD 030352-00-0503* must be maintained. The essential characteristics are to be specified in accordance with the European technical assessment (ETA, specification no.).

Constructional data

Name	Value	Unit
Compressive strength	-	N/mm²
Adhesive shear strength	-	N/mm²
Water absorption	-	mg
Water vapor diffusion equivalent air layer thickness	-	m
Thermal conductivity	-	W/(mK)
Tensile bond strength	-	N/mm²
Flexural strength	-	N/mm²
Sound absorption coefficient (if relevant)	-	%

2.4 Delivery status
Modified mineral mortars are generally manufactured and supplied as factory-made dry mortars. Factory-made dry mortar is a finished mixture of base materials which merely requires the addition of water and/or a polymer dispersion on the building site. The products can be supplied in 1-5 kg bags, 15-25 kg sacks, big bags (1 t), minitainers (1.2 t) or as silo goods (5-15 t). Paper sacks with polyethylene lining were modelled as packaging (worst-case approach).

2.5 Base materials/Ancillary materials
Typically, the products covered by this EPD contain the following range of base materials and auxiliaries (% by mass):
Inorganic binder: ~ 2 - 98
Filler materials: ~ 0 - 90
Additives: ~ 0 - 10
Aqueous dispersion and/or dispersion powder: ~ 0 - 35

These ranges are average values and the composition of products complying with the EPD can deviate from these concentration levels in individual cases. More detailed information is available in the respective manufacturer's documentation (e.g. product data sheets).
Note: For companies to declare their products within the scope of this EPD it is not sufficient to simply comply with the product composition shown above. The application of this EPD is only possible for member companies of DBC, EFCC, FEICA, and IVK member associations and only for specific formulations with a total score below the declared maximum score for a product group according to the associated guidance document.

1. substances from the "Candidate List of Substances of Very High Concern for Authorisation" (SVHC)
If this product contains substances listed in the *candidate list* (latest version) exceeding 0.1 percentage by mass, the relevant information can be found in the safety data sheet of the relevant product covered by this model EPD.
2. CMR substances in categories 1A and 1B
If this product contains other carcinogenic, mutagenic, reprotoxic (CMR) substances in categories 1A or 1B which are not on the *candidate list*, exceeding 0.1 percentage by mass, the relevant information can be found in the safety data sheet of the relevant product covered by this model EPD.
3. Biocide products added to the construction product
If this construction product contains biocide products, the active substances, information on the concentration and/or concentration range, the product type together with information on their hazardous properties are listed in the safety data sheet of the respective product.

2.6 Manufacture
The raw materials are stored in silos, big bags or sacks in the manufacturing plant and fed gravimetrically in

accordance with the respective formula and mixed intensively. The mix is then packaged.

2.7 Environment and health during manufacturing

The state of the art involves maximum recirculation of dry waste into production. Wherever dust is incurred during production in the plant, it is directed to a filter system considering the limit values applicable for the workplace and using the corresponding extraction plants. Sack discharge stations connected to the extraction plant offer employees additional protection from dust. Most of the dust collected in the filter system and any residue incurred during production is returned to the manufacturing process.
Powder residues: Residual product is returned to the production process wherever possible.
Air: Process air is dedusted autonomously, whereby the values are far below legal requirements.
Water: The production process does not involve water. Very low volumes of water are required for laboratory tests and for sanitary facilities.
Noise: Noise level measurements have indicated that all values established within the production facility fall below the hearing protection limit of 85dB(A).
Waste: The main types of waste are powder waste, paper (paper bags) and foil. Low volumes of metal scrap (metal containers), waste oil (maintenance), wood (pallets) and commercial waste are incurred. All waste is separated, stored and redirected to the recycling circuit or disposed of.

2.8 Product processing/Installation

Modified mineral mortars can be processed both automatically and manually. The mortars are either automatically removed from a silo using a dry conveyor or manually taken from the container, mixed with water and installed. The professional liability association's rules apply as well as the respective safety data sheets pertaining to the construction products. On account of the various hydrate levels of cement, lime and calcium sulphate binding agents in the mineral mortar, the fresh mortar mixed with water is usually strongly alkaline. In the case of more extensive contact, this alkaline state can cause serious damage to eyes and skin. Therefore, any contact with eyes or skin must be avoided by taking personal protective measures, and the information outlined on the safety data sheet must be observed. Uncontrolled dust emissions should be avoided. Modified mineral mortars may not be discharged into the sewage system, surface water or groundwater. Waste incurred on the building site (packaging, pallets, residual mortar) must be collected separately. Suitable waste disposal companies dispose of packaging materials and mortar sacks and return them to the recycling circuit. Dry mortar residue is taken back by the manufacturing plants and used as a raw material. No dry mortar residue in mortar sacks is incurred. Hard mortar residue can be recycled or disposed of as building site rubble.

2.9 Packaging

A detailed description of packaging is provided in section 2.4. Empty, trickle-free paper containers and clean PE foils can be recycled.

2.10 Condition of use

A modified mineral mortar does not rot and is resistant to ageing when used in accordance with the designated purpose of the respective products. It is a durable product which, when used as adhesive, screed, waterproofing material or repair product, makes an essential contribution towards improving building function and value.

2.11 Environment and health during use

Owing to the stable crystalline bond and firm structure achieved after curing, emissions are extremely low and harmless to health when the respective products are used in accordance with the designated purpose. No risks are known for water, air and soil if the products are used as designated. Natural ionising radiation from mineral mortar is extremely low and negligible in terms of health hazards. Options for applications in indoor areas with permanent stays by people: Evidence of the emission performance of construction products in contact with indoor air and depending on the designated use must be submitted for applications in indoor areas with permanent stays by people, e.g. in accordance with the *German AgBB* test scheme or the *GEV* (Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e.V., Düsseldorf) *EMICODE*® marking system typically applied in Germany.

2.12 Reference service life

Modified mineral mortars decisively improve the usability of building structures and significantly extend their original service lives. The anticipated reference service life depends on the specific installation situation and the exposure associated with the product. It can be influenced by weathering as well as mechanical or chemical loads.

2.13 Extraordinary effects

Fire
In accordance with Commission Decision 94/611EC, modified mineral binding agents comprising finely distributed organic components must always be classified in reaction-to-fire class A1 ‘No contribution to fire’ in accordance with *EN 13501-1*.
Where higher percentages of organic components are involved, it can also be assumed that at least the requirements of *EN 13501-1* are maintained for fire class E and Efl.

Fire protection

Name	Value
Building material class	-
Burning droplets	-
Smoke gas development	-

Water
No relevant volumes of water-soluble substances hazardous to water are washed out when hardened modified mineral mortars are exposed to water (e.g. flooding). Modified mineral mortar is stable in terms of structure and is not subject to any changes in form when exposed to water and drying. If non-hardened modified mineral mortars are exposed to water an increase of the pH will take place.

Mechanical destruction
The mechanical destruction of modified mineral mortars does not lead to any decomposition products which are harmful to the environment or health. Dust

incurred during de-construction should be avoided by taking the appropriate measures (e.g. humidification).

2.14 Re-use phase

Components manufactured using modified mineral mortars can usually be easily demolished. When a building is removed, the materials do not need to be treated as special waste; care should, however, be taken to ensure unmixed residual materials wherever possible. Modified mineral mortars can usually be redirected to normal building material recycling circuits. Re-use is generally in the form of recycled aggregate in building construction and civil engineering. No practical experience is currently available for reusing components comprising cementitious-based products after decommissioning.

2.15 Disposal

The portion of a modified mineral mortar applied to another construction product is rather low. These low amounts do not play a role when the construction product is disposed of. They do not interfere with the disposal/recycling of other components/building materials.
The following waste codes according to the European List of Waste (*2000/532/EC*) can apply:
Mineral mortar: *EWC 17 01 01* and *EWC 10 13 14*
Mineral filler and levelling compound: *EWC 17 01 07*
Calcium sulphate-based filler and levelling compound: *EWC 17 08 02*

2.16 Further information

More information is available on the manufacturer's product or safety data sheets and is available on the manufacturer's websites or on request. Valuable technical information is also available on the associations' websites.

3. LCA: Calculation rules

3.1 Declared Unit

This EPD refers to the declared unit of 1 kg of modified mineral mortar, group 1; applied into the building with a density of 800 - 1,700 kg/m³ in accordance with the IBU *PCR part B* for Mineral Factory-Made Mortars.
The results of the Life Cycle Assessment provided in this declaration have been selected from the product with the highest environmental impact (worst-case scenario).
Depending on the application, a corresponding conversion factor such as the density to convert volumetric use to mass must be taken into consideration.

The Declaration type is according to *EN 15804*: Cradle to gate with options, modules C1–C4, and module D (A1–A3, C, D) and additional modules (A4-A5).

Declared unit

Name	Value	Unit
Declared unit	1	kg
Gross density	800 - 1700	kg/m³

3.2 System boundary

Modules A1, A2 and A3 are taken into consideration in the LCA:
- A1 Production of preliminary products
- A2 Transport to the plant
- A3 Production incl. provision of energy, production of packaging as well as auxiliaries and consumables and waste treatment
- A4 Transport to site
- A5 Installation, product applied into the building during A5 phase operations and packaging disposal.

The end of life for the packaging material considered is described below:
-Incineration, for materials like plastic, wood and paper.
-C1-C2-C4-D
The building deconstruction (demolition process) takes place in the C1 module which considers energy generation and consumption of diesel and all the emissions connected with the fuel-burning process to run the machines. After the demolition, the product is transported to the end-of-life processing (C2 module) where all the impacts related to the transport processes are considered. For precautionary principle and as a worst-case scenario, landfilling is the only end-of-life scenario considered. This is modelled by the landfill process (module C4) where the product ends its life cycle.
Module D accounts for potential benefits that are beyond the defined system boundaries. Credits are generated during the incineration of packaging that is occurring in the A5 module.

3.3 Estimates and assumptions

For this EPD formulation and production data defined and collected by FEICA were considered. Production waste was assumed to be disposed of by landfilling as a worst case.
An average of paper sacks with polyethylene lining and wooden pallets was considered in the LCA.

3.4 Cut-off criteria

All raw materials submitted for the formulations and production data were taken into consideration.
The manufacture of machinery, plant and other infrastructure required for the production of the products under review was not taken into consideration in the LCA.
Transport of packaging materials is excluded.

3.5 Background data

Data from the *GaBi 10* database SP40 (2020) was used as background data.

3.6 Data quality

Representative products were applied for this EPD and the product in the group displaying the highest environmental impact was selected for calculating the LCA results. The background datasets used are less than 4 years old.
Production data and packaging are based on details provided by the manufacturer. The formulation used for evaluation refers to a specific product.
The data quality of the background data is considered to be good.

3.7 Period under review
Representative formulations are valid for 2021.

3.8 Allocation
Mass allocation has been applied when primary data have been used and implemented into the LCA model.

3.9 Comparability
Basically, a comparison or an evaluation of EPD data is only possible if all the data sets to be compared were created according to *EN 15804* and the building context, respectively the product-specific characteristics of performance, are taken into account.

The *GaBi 10* database SP40 (2020) was used.

4. LCA: Scenarios and additional technical information

Characteristic product properties
Information on biogenic carbon
The packaging material contains biogenic carbon content which is presented below.

Information on describing the biogenic Carbon Content at factory gate

Name	Value	Unit
Biogenic Carbon Content in product	-	kg C
Biogenic Carbon Content in accompanying packaging	0.0194	kg C

For the preparation of building life cycle assessments, it must be taken into account that in module A5 (installation in the building) the biogenic amount of CO_2 (0.0194 kg C *3.67 = 0.071 kg CO_2-eq.) of the packaging bound in module A1-A3 is mathematically booked out.

Transport to the building site (A4)

Name	Value	Unit
Transport distance	1000	km
Gross weight	34 - 40	t
Payload capacity	27	t

Installation into the building (A5)

Name	Value	Unit
Other resources for packaging material	0.055	kg
Material loss	0.01	kg
Water consumption	0.0003	m^3

Material loss considers the amount of product not used during the application phase into the building. This amount is 1 % of the product and, impacts related to the production of this part are assigned to the A5 module. This percentage is considered as waste to disposal and impacts of its end of life have been considered into the LCA model and declared in A5.

End of life (C1-C4)

Name	Value	Unit
Collected as mixed construction waste	1.121	kg
Landfilling	1.121	kg

The value above 1 kg is due to the use of water during the installation phase where 50 % of water evaporate while 50 % remain in the product.

5. LCA: Results

DESCRIPTION OF THE SYSTEM BOUNDARY (X = INCLUDED IN LCA; ND = MODULE OR INDICATOR NOT DECLARED; MNR = MODULE NOT RELEVANT)

PRODUCT STAGE			CONSTRUCTION PROCESS STAGE		USE STAGE							END OF LIFE STAGE				BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARIES
Raw material supply	Transport	Manufacturing	Transport from the gate to the site	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	X	X	ND	ND	MNR	MNR	MNR	ND	ND	X	X	ND	X	X

RESULTS OF THE LCA - ENVIRONMENTAL IMPACT according to EN 15804+A2: 1 kg of modified mineral mortar, group 1

Core Indicator	Unit	A1-A3	A4	A5	C1	C2	C4	D
GWP-total	[kg CO_2-Eq.]	4.88E-1	5.06E-2	1.05E-1	3.12E-4	1.39E-2	1.71E-2	-3.50E-2
GWP-fossil	[kg CO_2-Eq.]	5.58E-1	5.00E-2	1.36E-2	2.98E-4	1.33E-2	1.70E-2	-3.49E-2
GWP-biogenic	[kg CO_2-Eq.]	-6.95E-2	1.46E-4	9.10E-2	1.38E-5	6.08E-4	5.38E-5	-8.21E-5
GWP-luluc	[kg CO_2-Eq.]	4.13E-4	4.05E-4	5.72E-6	7.17E-9	3.13E-7	4.89E-5	-2.45E-5
ODP	[kg CFC11-Eq.]	2.81E-11	6.01E-18	2.81E-13	3.18E-20	1.39E-18	6.30E-17	-3.66E-16
AP	[mol H^+-Eq.]	1.80E-3	1.50E-4	3.50E-5	4.04E-6	4.19E-5	1.22E-4	-4.90E-5
EP-freshwater	[kg P-Eq.]	9.16E-7	1.52E-7	1.49E-8	6.45E-11	2.81E-9	2.92E-8	-4.52E-8
EP-marine	[kg N-Eq.]	3.45E-4	6.68E-5	8.93E-6	1.83E-6	1.92E-5	3.14E-5	-1.27E-5
EP-terrestrial	[mol N-Eq.]	3.72E-3	7.48E-4	1.14E-4	2.01E-5	2.12E-4	3.45E-4	-1.36E-4
POCP	[kg NMVOC-Eq.]	1.33E-3	1.32E-4	2.83E-5	5.51E-6	3.80E-5	9.51E-5	-3.64E-5
ADPE	[kg Sb-Eq.]	5.74E-8	3.59E-9	7.92E-10	9.03E-12	3.94E-10	1.53E-9	-5.74E-9
ADPF	[MJ]	9.91E+0	6.66E-1	1.24E-1	4.27E-3	1.86E-1	2.23E-1	-5.92E-1
WDP	[m^3 world-Eq deprived]	8.79E-2	4.47E-4	2.42E-2	5.90E-7	2.58E-5	1.78E-3	-3.63E-3

Caption	GWP = Global warming potential; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential of land and water; EP = Eutrophication potential; POCP = Formation potential of tropospheric ozone photochemical oxidants; ADPE = Abiotic depletion potential for non-fossil resources; ADPF = Abiotic depletion potential for fossil resources; WDP = Water (user) deprivation potential

RESULTS OF THE LCA - INDICATORS TO DESCRIBE RESOURCE USE according to EN 15804+A2: 1 kg of modified mineral mortar, group 1

Indicator	Unit	A1-A3	A4	A5	C1	C2	C4	D
PERE	[MJ]	9.81E-1	3.74E-2	7.42E-1	1.35E-5	5.88E-4	2.92E-2	-1.30E-1
PERM	[MJ]	7.21E-1	0.00E+0	-7.21E-1	0.00E+0	0.00E+0	0.00E+0	0.00E+0
PERT	[MJ]	1.70E+0	3.74E-2	2.15E-2	1.35E-5	5.88E-4	2.92E-2	-1.30E-1
PENRE	[MJ]	8.86E+0	6.67E-1	2.01E-1	4.28E-3	1.87E-1	2.23E-1	-5.92E-1
PENRM	[MJ]	1.05E+0	0.00E+0	-8.66E-2	0.00E+0	0.00E+0	0.00E+0	0.00E+0
PENRT	[MJ]	9.91E+0	6.67E-1	1.14E-1	4.28E-3	1.87E-1	2.23E-1	-5.92E-1
SM	[kg]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
RSF	[MJ]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
NRSF	[MJ]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
FW	[m^3]	2.46E-3	4.33E-5	5.71E-4	2.42E-8	1.05E-6	5.63E-5	-1.50E-4

Caption	PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water

RESULTS OF THE LCA – WASTE CATEGORIES AND OUTPUT FLOWS according to EN 15804+A2: 1 kg of modified mineral mortar, group 1

Indicator	Unit	A1-A3	A4	A5	C1	C2	C4	D
HWD	[kg]	2.60E-5	3.10E-8	2.60E-7	4.15E-13	1.81E-11	3.40E-9	-2.36E-10
NHWD	[kg]	3.12E-2	1.02E-4	1.44E-2	4.37E-7	1.91E-5	1.12E+0	-2.74E-4
RWD	[kg]	2.46E-4	8.25E-7	3.74E-6	4.59E-9	2.00E-7	2.54E-6	-4.43E-5
CRU	[kg]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
MFR	[kg]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
MER	[kg]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
EEE	[MJ]	0.00E+0	0.00E+0	1.48E-1	0.00E+0	0.00E+0	0.00E+0	0.00E+0
EET	[MJ]	0.00E+0	0.00E+0	2.66E-1	0.00E+0	0.00E+0	0.00E+0	0.00E+0

Caption	HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported electrical energy; EET = Exported thermal energy

RESULTS OF THE LCA – additional impact categories according to EN 15804+A2-optional: 1 kg of modified mineral mortar, group 1

Indicator	Unit	A1-A3	A4	A5	C1	C2	C4	D
PM	[Disease Incidence]	ND	ND	ND	ND	ND	ND	ND
IRP	[kBq U235-Eq.]	ND	ND	ND	ND	ND	ND	ND
ETP-fw	[CTUe]	ND	ND	ND	ND	ND	ND	ND
HTP-c	[CTUh]	ND	ND	ND	ND	ND	ND	ND
HTP-nc	[CTUh]	ND	ND	ND	ND	ND	ND	ND
SQP	[-]	ND	ND	ND	ND	ND	ND	ND

Caption	PM = Potential incidence of disease due to PM emissions; IR = Potential Human exposure efficiency relative to U235; ETP-fw = Potential comparative Toxic Unit for ecosystems; HTP-c = Potential comparative Toxic Unit for humans (cancerogenic); HTP-nc = Potential comparative Toxic Unit for humans (not cancerogenic); SQP = Potential soil quality index

Potential Human exposure efficiency relative to U235, Disclaimer 1 – This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure or radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, radon and (from) some construction materials is also not measured by this indicator.

ADP minerals & metals, ADP fossil, WDP, ETF-fw, HTP-c, HTP-nc, SQP, Disclaimer 2 – The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experience with the indicator.

Additional environmental impact indicators (suggested by *EN15804*, table 4) are not declared in the EPD. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high and as there is limited experience with the indicator (see ILCD classification in *EN 15804*, table 5). For this reason, results based on these indicators are not considered suitable for a decision-making process and are thus not declared in the EPD.

6. LCA: Interpretation

The majority of impacts are associated with the production phase (A1-A3). The most significant contribution to the production phase impacts is the upstream production of raw materials as the main driver. Besides the cement also the dispersion powder influences the results significantly, although this is only used for up to 8 % of the total composition. Significant contributions to Primary Energy Demand – Non-renewable (PENRT) derive from the energy resources used in the production of raw materials. The largest contributor to Primary Energy Demand – Renewable (PERT) is the consumption of renewable energy resources required for the generation and supply of electricity. During manufacturing (A1-A3) some influence also arises due to the wooden pallets and paper used as packaging that need solar energy for photosynthesis. It should be noted that Primary Energy Demand – Renewable (PERT) generally represents a small percentage of the production phase primary energy demand with the bulk of the demand coming from non-renewable energy resources.

In all EPDs, CO_2 is the most important contributor to Global Warming Potential (GWP). For the Acidification Potential (AP), NOx and SO_2 contribute the largest share.
Transportation to the construction site (A4) and the installation process (A5) make a minor contribution to almost all impacts. The only exception is a relevant influence of carbon dioxide emissions in module A5 to Global Warming Potential (GWP) due to the incineration of the packaging materials plastic, paper and pallets.
In module A4, transport to construction site, values for Eutrophication (freshwater, marine and terrestrial) have an impact due principally to the emission of phosphate. Furthermore, climate change from land use change is influenced by transport processes, due to the diesel production used as fuel, because part of this diesel has been produced from bio-based raw materials.
The end-of-life phases have a negligible influence on all impacts.

7. Requisite evidence

Leaching
Special tests and evidence have not been carried out or provided within the framework of drawing up this Model EPD. Some member states require special documentation on leaching for specific areas of application. This documentation has to be provided separately and is specific to the product in question.

If of relevance for the application (usually if the products are used outside of buildings) the leaching behaviour has to be measured e.g. according to *DIN EN 12457/1--4* or *DIN EN 14405* combined with the Council decision *2003/33/EC*.

8. References

EN 998-1

EN 998-1:2016, Specification for mortar for masonry – Part 1: Rendering and plastering mortar

EN 1015-17
EN 1015-17:2005-01, Methods of test for mortar for masonry – Part 17: Determination of water-soluble chloride content of fresh mortars

EN 1504-3
EN 1504-3:2005-12, Products and systems for the protection and repair of concrete structures – Definitions, requirements, quality control and evaluation of conformity – Part 3: Structural and non-structural repair

EN 1504-7
EN 1504-7:2006-08, Products and systems for the protection and repair of concrete structures – Definitions, requirements, quality control and evaluation of conformity – Part 7: Reinforcement corrosion protection

EN 1542
EN 1542:1999-07, Products and systems for the protection and repair of concrete structures – Test methods – Measurement of bond strength by pull-off

EN 12004
EN 12004:2012, Adhesives for tiles – Requirements, evaluation of conformity, classification and designation

EN 12004-2
EN 12004-2:2017, Adhesives for ceramic tiles - Part 2: Test methods

EN 12190
EN 12190:1998-12, Products and systems for the protection and repair of concrete structures – Test methods – Determination of compressive strength of repair mortar

DIN EN 12457-1
DIN EN 12457-1:2003-01, Characterization of waste - Leaching; Compliance test for leaching of granular and sludges - Part 1: One stage batch test at a liquid to solid ration of 2 l/kg with particle size below 4 mm (without or with size reduction)

DIN EN 12457-2
DIN EN 12457-2:2003-01, Characterization of waste - Leaching; Compliance test for leaching of granular and sludges - Part 2: One stage batch test at a liquid to solid ratio of 10 l/kg with particle size below 4 mm (without or with size reduction)

DIN EN 12457-3
DIN EN 12457-3:2021-03, Characterization of waste - Leaching - Compliance test for leaching of granular waste materials and sludges - Part 3: Two stage batch test at a liquid to solid ratio of 2 l/kg and 8 l/kg for materials with high solid content with particle size below 4 mm (without or with size reduction)

DIN EN 12457-4
DIN EN 12457-4:2003-01, Characterization of waste - Leaching; Compliance test for leaching of granular waste materials and sludges - Part 4: One stage batch test at a liquid to solid ratio of 10 l/kg for materials with particle size below 10 mm (without or with limited size reduction)

EN 13279
EN 13279-1:2008, Gypsum binders and gypsum plasters – Part 1: Definitions and requirements

EN 13501-1
EN 13501-1:2018, Fire classification of construction products and building products – Part 1: Classification using data from reaction to fire tests

EN 13813
EN 13813:2002-10, Screed material and floor screeds – Screed materials – Properties and requirements

EN 13888
EN 13888:2009, Grout for tiles – Requirements, evaluation of conformity, classification and designation

EN 13892-8
EN 13892-8:2003-02, Methods of test for screed materials – Part 8: Determination of bond strength

ISO 14025
DIN EN ISO 14025:2011-10, Environmental labels and declarations — Type III environmental declarations — Principles and procedures

DIN EN 14405
DIN EN 14405:2017-05, Characterization of waste - Leaching behaviour test - Up-flow percolation test (under specified conditions)

EN 14891
EN 14891:2012-04, Liquid-applied water impermeable products for use beneath ceramic tiling bonded with adhesives – Requirements, test methods, evaluation of conformity, classification and designation

EN 15183
EN 15183:2006-11, Products and systems for the protection and repair of concrete structures – Test methods – Corrosion protection test

EN 15804
EN 15804+A2+AC:2021, Sustainability of construction works — Environmental Product Declarations — Core rules for the product category of construction products

EAD 030295-00-0605
EAD 030295-00-0605, Flexible polymer modified mineral thick coating

EAD 030352-00-0503
EAD 030352-00-0503:2019:01, Liquid applied watertight covering kits for wet room floors and/or walls

EAD 040083-00-0404
EAD 040083-00-0404:2013, External Thermal Insulation Composite Systems with Rendering

96/603/EC
Commission decision of 4 October 1996 for specifying a directory of products to be classified as category A "No contribution to fire" in accordance with decision 94/611/EC on construction products for implementing Article 20 of Directive 89/106/EEC

2000/532/EC

Commission decision dated 3 May 2000 replacing decision 94/3/EC on a waste directory in accordance with Article 1 a) of Council Directive 75/442/EEC on waste and Council decision 94/904/EC on a directory of hazardous waste in terms of Article 1, paragraph 4 of Directive 91/689/EEC on hazardous waste

2003/33/EC:
Council Decision of 19 December 2002 establishing criteria and procedures for the acceptance of waste at landfills pursuant to Article 16 of and Annex II to Directive 1999/31/EC

Candidate list
Candidate List of substances of very high concern for Authorisation, published in accordance with Article 59(10) of the REACH Regulation, ECHA, www.echa.europa.eu/candidate-list-table

CPR
CPR Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 laying down harmonised conditions for the marketing of construction products and repealing Council Directive 89/106/EEC

DAfStb Guideline
DAfStb Guideline on 'Production and use of cement-bound flow concrete and grouting mortar' (VeBMR), 2019-07

Decopaint Directive
Directive 2004/42/CE of the European Parliament and the council of 21 April 2004 on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products and amending Directive 1999/13/EC

EWC 101314
2000/532/EC European Waste Catalogue / Ordinance on European List of Wastes: Waste concrete and concrete sludge

EWC 170101
2000/532/EC European Waste Catalogue / Ordinance on European List of Wastes: Concrete

EWC 170107
2000/532/EC European Waste Catalogue / Ordinance on European List of Wastes: Mixtures of concrete, bricks, tiles and ceramics

EWC 170802
2000/532/EC European Waste Catalogue / Ordinance on European List of Wastes: Gypsum based construction metals e.g. for plasterboard

GaBi 10
GaBi 10: Software and database for comprehensive analysis. LBP, University of Stuttgart and Sphera, 2020

GaBi 10 documentation
Gabi 10: documentation of GaBi 10 data sets from the data base for Life Cycle Engineering LBP, University of Stuttgart and Sphera, http://documentation.gabi-software.com/, 2020

IBU 2021
Institut Bauen und Umwelt e.V.: General Instructions for the EPD programme of Institut Bauen und Umwelt e.V. EPD programme. Version 2.0. Berlin: Institut Bauen und Umwelt e.V., 2021
www.ibu-epd.com

MVV TB
Ü-mark in accordance with 'Model Administrative Order laying down Technical Building Regulations' (MVV TB) no. C 2.1.4.5

PCR Part A
Product Category Rules for Building-Related Products and Services, Part A: Calculation Rules for the Life Cycle Assessment and Requirements on the Project report, Version 1.1, Institut Bauen und Umwelt e.V., 2021-01

PCR Part B
Product Category Rules for Construction Products, Part B: Mineral Factory-Made Mortars, 2017-11

PG AIV
Testing principles regarding the issuing of general building authority test certificates for waterproofing with waterproofing in conjunction with ceramic tiles (PG-AIV:2018-03)

PG MDS/FPD
Testing principles regarding the issuing of general building authority test certificates for waterproofing with mineral waterproofing slurries and flexible polymer thick coatings (PG-MDS/FPD:2016-11)

REACH
Directive (EG) No. 1907/2006 of the European Parliament and of the Council dated 18 December 2006 on the registration, evaluation, approval and restriction of chemical substances (REACH), for establishing a European Agency for chemical substances, for amending Directive 1999/45/EC and for annulment of Directive (EEC) No. 793/93 of the Council, Directive (EC) No. 1488/94 of the Commission, Guideline 76/769/EEC of the Council and Guidelines 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC of the Commission.

Publisher
Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

Tel +49 (0)30 3087748- 0
Fax +49 (0)30 3087748- 29
Mail info@ibu-epd.com
Web **www.ibu-epd.com**

Programme holder
Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

Tel +49 (0)30 - 3087748- 0
Fax +49 (0)30 – 3087748 - 29
Mail info@ibu-epd.com
Web **www.ibu-epd.com**

Author of the Life Cycle Assessment
Sphera Solutions GmbH
Hauptstraße 111- 113
70771 Leinfelden-Echterdingen
Germany

Tel +49 711 341817-0
Fax +49 711 341817-25
Mail info@sphera.com
Web **www.sphera.com**

Owner of the Declaration
Industrieverband Klebstoffe e.V
Völklinger Straße 4
40219 Düsseldorf
Germany

Tel +49 (0)211 67931-10
Fax +49 (0)211 67931-33
Mail info@klebstoffe.com
Web **www.klebstoffe.com**

Deutsche Bauchemie e.V.
Mainzer Landstr. 55
60329 Frankfurt
Germany

Tel +49 (0)69 2556-1318
Fax +49 (0)69 2556-1319
Mail info@deutsche-bauchemie.de
Web **www.deutsche-bauchemie.de**

EFCC - European Federation for Construction Chemicals
Boulevard du Triomphe 172
1160 Brussels
Belgium

Tel +32289720-39
Fax +32289720-37
Mail info@efcc.be
Web **www.efcc.eu**

FEICA - Association of the European Adhesive and Sealant Industry
Rue Belliard 40 box 10
1040 Brussels
Belgium

Tel +32 (0)267 673 20
Fax +32 (0)267 673 99
Mail info@feica.eu
Web **www.feica.eu**