SENTINEL HOLDING
INSTITUT

SHI PRODUCT PASSPORT

Find products. Certify buildings.

SHI Product Passport No.:

13373-10-1082

Klebedichtband EURASOL PLUS

Product group: Adhesive tapes / Joint sealing tapes - Sealing tapes

WÜRTH

Adolf Würth GmbH & Co. KG
Reinhold-Würth-Straße 12-17
74653 Künzelsau-Gaisbach

Product qualities:

- SHI Product Assessment 2024
- QNG Qualitätssiegel Nachhaltiges Gebäude
- DGNB NEW CONSTRUCTION 2023.2
- DGNB NEW CONSTRUCTION 2023
- DGNB NEW CONSTRUCTION 2018
- BNB-BN NEUBAU V2015
- BREEAM DE NEUBAU 2018
- LEED v4.1 (outside US)

CERTIFIED SUSTAINABLE PRODUCT
SHI PRODUCT PASSPORT
SENTINEL HOLDING INSTITUT
www.sentinel-holding.eu

Köttner

Helmut Köttner
Scientific Director
Freiburg, 26 August 2026

Product:
Klebedichtband EURASOL PLUS

SHI Product Passport no.:
13373-10-1082

WÜRTH

Contents

SHI Product Assessment 2024	1
QNG - Qualitätssiegel Nachhaltiges Gebäude	2
DGNB New Construction 2023.2	3
DGNB New Construction 2023	4
DGNB New Construction 2018	5
BNB-BN Neubau V2015	6
BREEAM DE Neubau 2018	7
LEED v4.1	8
Product labels	9
Legal notices	10
Technical data sheet/attachments	11

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar

SENTINEL HOLDING
INSTITUT

Product:
Klebedichtband EURASOL PLUS

SHI Product Passport no.:
13373-10-1082

WÜRTH

SHI Product Assessment 2024

Since 2008, Sentinel Holding Institut GmbH (SHI) has been establishing a unique standard for products that support healthy indoor air. Experts carry out independent product assessments based on clear and transparent criteria. In addition, the independent testing company SGS regularly audits the processes and data accuracy.

Criteria	Product category	Harmful substance limit	Assessment
SHI Product Assessment	Other products	TVOC ≤ 300 µg/m^3 Formaldehyd ≤ 24 µg/m^3	Indoor Air Quality Certified
Valid untill: 14 June 2027			

SENTINEL HOLDING
INSTITUT

Product:
Klebedichtband EURASOL PLUS

SHI Product Passport no.:
13373-10-1082

WÜRTH

QNG - Qualitätssiegel Nachhaltiges Gebäude

The Qualitätssiegel Nachhaltiges Gebäude (Quality Seal for Sustainable Buildings), developed by the German Federal Ministry for Housing, Urban Development and Building (BMWSB), defines requirements for the ecological, socio-cultural, and economic quality of buildings. The Sentinel Holding Institut evaluates construction products in accordance with QNG requirements for certification and awards the QNG ready label. Compliance with the QNG standard is a prerequisite for eligibility for the KfW funding programme. For certain product groups, the QNG currently has no specific requirements defined. Although classified as not assessment-relevant, these products remain suitable for QNG-certified projects.

Criteria	Pos. / product group	Considered substances	QNG assessment
3.1.3 Schadstoffvermeidung in Baumaterialien			QNG ready - Not relevant for assessment

SENTINEL HOLDING
INSTITUT

Product:
Klebedichtband EURASOL PLUS

SHI Product Passport no.:
13373-10-1082

WÜRTH

DGNB New Construction 2023.2

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact			Not relevant for assessment

SENTINEL HOLDING
INSTITUT

Product:
Klebedichtband EURASOL PLUS

SHI Product Passport no.:
13373-10-1082

WÜRTH

DGNB New Construction 2023

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings. The 2023 version sets high standards for ecological, economic, socio-cultural, and functional aspects throughout the entire life cycle of a building.

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 03.05.2024 (3rd edition)			Not relevant for assessment

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 29.05.2025 (4th edition)	not applicable		Not relevant for assessment

SENTINEL HOLDING
INSTITUT

Product:
Klebedichtband EURASOL PLUS

SHI Product Passport no.:
13373-10-1082

WÜRTH

DGNB New Construction 2018

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings.

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact	not applicable	not applicable	Not relevant for assessment

SENTINEL HOLDING
INSTITUT

Product:
Klebedichtband EURASOL PLUS

SHI Product Passport no.:
13373-10-1082

WÜRTH

BNB-BN Neubau V2015

The Bewertungssystem Nachhaltiges Bauen (Assessment System for Sustainable Building) is a tool for evaluating public office and administrative buildings, educational facilities, laboratory buildings, and outdoor areas in Germany. The BNB was developed by the former Federal Ministry for the Environment, Nature Conservation, Building and Nuclear Safety (BMUB) and is now overseen by the Federal Ministry for Housing, Urban Development and Building (BMWSB).

Criteria	Pos. / product type	Considered substance group	Quality level
1.1.6 Risiken für die lokale Umwelt			Not relevant for assessment

SENTINEL HOLDING
INSTITUT

Product:
Klebedichtband EURASOL PLUS

SHI Product Passport no.:
13373-10-1082

WÜRTH

BREEAM DE Neubau 2018

BREEAM (Building Research Establishment Environmental Assessment Methodology) is a UK-based building assessment system that evaluates the sustainability of new constructions, refurbishments, and conversions. Developed by the Building Research Establishment (BRE), the system aims to assess and improve the environmental, economic, and social performance of buildings.

Criteria	Product category	Considered substances	Quality level
Hea 02 Indoor Air Quality			Not relevant for assessment

SENTINEL HOLDING
INSTITUT

Product:
Klebedichtband EURASOL PLUS

SHI Product Passport no.:
13373-10-1082

WÜRTH

LEED v4.1

LEED (Leadership in Energy and Environmental Design) is an internationally recognised building certification system developed by the U.S. Green Building Council. It is one of the most widely used sustainability standards for buildings worldwide and is particularly applied in internationally oriented projects. LEED assesses buildings holistically across categories such as energy efficiency, resource conservation, material selection, indoor environmental quality and site sustainability. Depending on the number of points achieved, projects are awarded one of the certification levels: LEED Certified, Silver, Gold or Platinum.

Criteria	Product category	Considered substances	Assessment
EQ Credit: Low-Emitting Materials			Not relevant for assessment

SENTINEL HOLDING
INSTITUT

Product:
Klebedichtband EURASOL PLUS

SHI Product Passport no.:
13373-10-1082

WÜRTH

Product labels

In the construction industry, high-quality materials are crucial for a building's indoor air quality and sustainability. Product labels and certificates offer guidance to meet these requirements. However, the evaluation criteria of these labels vary, and it is important to carefully assess them to ensure products align with the specific needs of a construction project.

The EMICODE® label, awarded by the German manufacturers' association "GEV – Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e. V.", is primarily relevant for flooring installation materials. The EMICODE® EC1^{PLUS} label, as the premium class, sets significantly stricter emission limits than the other label variants.

Products bearing the Sentinel Holding Institute QNG-ready seal are suitable for projects aiming to achieve the "Qualitätssiegel Nachhaltiges Gebäude" (Quality Seal for Sustainable Buildings). QNG-ready products meet the requirements of QNG Appendix Document 3.1.3, "Avoidance of Harmful Substances in Building Materials." The KfW loan program Climate-Friendly New Construction with QNG may allow for additional funding.

Product:
Klebedichtband EURASOL PLUS

SHI Product Passport no.:
13373-10-1082

WÜRTH

Legal notices

(*) These criteria apply to the construction project as a whole. While individual products can positively contribute to the overall building score through proper planning, the evaluation is always conducted at the building level. The information was provided entirely by the manufacturer.

Find our criteria here: https://www.sentinel-holding.eu/de/Themenwelten/Pr%C3%BCfkriterien%20f%C3%BCr%20Produkte

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar

SGS TÜV SAAR

Publisher

Sentinel Holding Institut GmbH
Bötzinger Str. 38
79111 Freiburg im Breisgau
Germany
Tel.: +49 761 590 481-70
info@sentinel-holding.eu
www.sentinel-holding.eu


KLEBEDICHTBAND EURASOL® PLUS





Sicher verpackt im praktischen Tragekarton





Art.-Nr.	0992 710 060
VE	6
Trägermaterial	PE-Folie mit Gittergewebe
Klebstoffbasis	Modifiziertes Acrylat
Farbe	Weiß
Breite	60 mm
Länge	25 m
Verarbeitungstemperatur min./max.	0 bis 50 °C
Temperaturbeständigkeit min./max.	-40 bis 100 °C
UV-Beständigkeit	3 Monate
Lösemittelfrei	Ja

Anwendungsgebiet

Geeignet für den Einsatz im Innen- und Außenbereich (UV-Beständigkeit 3 Monate)

- Dauerhaftes Verkleben von Dachunterspannbahnen, Dampfsperren und Dampfbremsen.
- Bequemes Verkleben dieser Folien im Eck- und Kantenbereich, z.B. auf Holz (≤ 20% Holzfeuchte), Metall, harter Kunststoff

EURASOL Plus ist optimal für die Verklebung von Wütop Dampfbremsen, Wütop Dampfsperren und Wütop Dachunterspannbahnen auf PP-Basis geeignet und wurde auf diesen Folien getestet. Daher empfehlen wir den Einsatz dieser Wütop-Folien, um mit dem Würth Luftdichtsystem ein optimales Ergebnis zu erzielen.

Hinweis

Der Untergrund muss trocken, fett–, span– und staubfrei sein. Im verklebten Bereich darauf achten, dass sich kein Stauwasser bilden kann.
10 Jahre Systemgarantie gilt bei Einsatz auf luftdichter Ebene im Innenbereich.

Die Verarbeitungsangaben sind Empfehlungen, die auf unseren Versuchen und Erfahrungen beruhen; vor jedem Anwendungsfall sind Eigenversuche durchzuführen. Aufgrund der Vielzahl der Anwendungen sowie der Lagerungs- und Verarbeitungsbedingungen übernehmen wir keine Gewährleistung für ein bestimmtes Verarbeitungsergebnis. Soweit unser kostenloser Kundendienst technische Auskünfte gibt bzw. beratend tätig wird, erfolgt dies unter Ausschluss jeglicher Haftung, es sei denn, die Beratung bzw. Auskunft gehört zu unserem geschuldeten, vertraglich vereinbarten Leistungsumfang oder der Berater handelte vorsätzlich. Wir gewährleisten gleich bleibende Qualität unserer Produkte, technische Änderungen und Weiterentwicklungen behalten wir uns vor.

STEP - 2017-03-09 - 18443 - ©

Spezielles Klebeband für Eck– und Kantenverklebungen

Geprüfte Alterungsbeständigkeit

- Maximale Sicherheit bei Blower-Door-Prüfungen
- Schützt vor Feuchtigkeit und Schimmelbildung in der Dämmung

Ausgezeichnete Anfangs- und Endhaftung

Schnelle, einfache und sichere Verarbeitung

Flexibles Trägermaterial

Passt sich sehr gut Durchdringungen an

Geteiltes Trennpapier

Sehr schnelle und bequeme Verklebung von Kanten und Ecken

Lösemittelfrei

Leistungsnachweis

- Zertifiziert über thermische Alterungs- und Feuchtebeständigkeit von Universität Kassel
- Nachweis der Luftdichtheit durch Fraunhofer Institut für Bauphysik in Stuttgart in Anlehnung an DIN 18055 / DIN EN 42 und DIN V 4108-7 / prEN 12114
- ENeV

Anleitung

Eurasol Plus in der Mitte knicken und eine Hälfte des Abdeckpapiers wenige Zentimeter abziehen. Das Band dann auf einer Seite der Ecke fixieren. Durch Abziehen des Abdeck papiers wird die Klebebandhälfte auf der gesamten Länge durch Andrücken verklebt. Anschließend wird die andere Hälfte des Abdeckpapiers abgezogen und das Band angedrückt. Bitte auf ausreichenden Anpressdruck achten.
Am Ende der Verklebung das Klebeband mit einem Messer abtrennen.

HERSTELLERERKLÄRUNG

Projekt EURASOL Plus

Firma Adolf Würth GmbH & Co. KG

Ansprechpartner Carl-Arndt Saul

Telefon 07940 15 2354

E-Mail carl-arndt.saul@wuerth.com

Gewerk

Einbauort

Produktbezeichnung WÜRTH EURASOL Plus Art. 0992 710 060

Anwendung/ Beschreibung

Menge/behandelte Fläche/Stückzahl

VOC Gehalt

Anforderungen	Erfüllt	Bemerkung
TCEP < 0,1%	ja	
Chlorparaffine < 0,1%	ja	
PBB < 0,1 %	ja	
PBDE < 0,1%	ja	
SVHC < 0,1%	ja	

Vorhandene Dokumente

Sicherheitsdatenblatt nicht erforderlich

Prüfzeugnisse

Sonstiges

i. V. C. A. Saul

WÜRTH
Adolf Würth GmbH & Co. KG
Reinhold-Würth-Str. 12-17
74653 Künzelsau/Deutschland
T +49 7940 15-0 · F +49 7940 15-1000
info@wuerth.com · www.wuerth.de

09.05.2025 Datum

Carl-Arndt Saul Unterschrift

Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e.V.

GEV
EMICODE®

Lizenzerteilung zur Führung des EMICODE

Lizenzierungs-Nummer:	8110/01.01.14
Für den Artikel	EURASOL PLUS
wird auf Antrag vom	06.06.2017

unter Bezugnahme auf die Einstufung gemäß den nach § 10 der GEV-Zeichensatzung festgelegten Richtlinien

namens der Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e.V. für den oben genannten Artikel nach § 5 Abs. 4 der GEV-Zeichensatzung die Lizenz zur Führung des GEV-Zeichens

GEV-EMICODE® EC 1 PLUS sehr emissionsarm

erteilt. Damit erfüllt dieser Artikel die rückseitig aufgeführten Kriterien.
Die Firma ist ordentliches Mitglied der GEV.

OM100 14.06.2022
gültig bis 14.06.2027

Der Geschäftsführer
Gemeinschaft Emissionskontrollierte Verlegewerkstoffe,
Klebstoffe und Bauprodukte e.V.
Völklinger Straße 4 · D-40219 Düsseldorf

Hinweise zu den Voraussetzungen über die Vergabe der Lizenz für den EMICODE

Das gemäß vorseitiger Lizenz eingestufte Produkt hat nach der Satzung und den Richtlinien des Technischen Beirats der GEV u.a. den folgenden Kriterien zu genügen:

- Das Produkt entspricht allen gesetzlichen Bestimmungen, insbesondere denen des Chemikalienrechtes und seiner Verordnungen.
- Das Produkt ist nach der Definition der TRGS 610 lösemittelfrei, sofern es sich nicht um ein Oberflächenprodukt handelt. Soweit es einer Produktgruppe nach GISCODE zuzuordnen ist, wird diese angegeben.
- Für das Produkt wird ein Sicherheitsdatenblatt nach lokalem Recht in der jeweils aktuellen Fassung erstellt.
- Krebserregende, erbgutverändernde oder fruchtschädigende Stoffe der Klassen 1A und 1B werden dem Produkt bei der Herstellung nicht zugesetzt.
- Die Prüfung des Produktes erfolgt nach der definierten „GEV-Prüfmethode". Die VOC-Bestimmung wird dabei in einer Prüfkammer nach dem Tenax-Thermodesorptions-Verfahren mit nachgeschalteter GC/MS-Analyse durchgeführt.
- Die Einstufung in EMICODE-Klassen erfolgt entsprechend den nachstehenden Bezeichnungen und TVOC/TSVOC-Konzentrationsbereichen. Zur Produktkennzeichnung ist die zutreffende EMICODE-Klasse zu verwenden:

1) Verlegewerkstoffe, Klebstoffe und Bauprodukte

Parameter	EC 1 PLUS	EC 1	EC 2
	max. zulässige Konzentration [µg/m³]		
TVOC nach 3 Tagen	≤ 750	≤ 1000	≤ 3000
TVOC nach 28 Tagen	≤ 60	≤ 100	≤ 300
TSVOC nach 28 Tagen	≤ 40	≤ 50	≤ 100
R-Wert basierend auf AgBB-NIK-Werten nach 28 Tagen	1	-	-
Summe der nicht bewertbaren VOC	≤ 40	-	-
Formaldehyd nach 3 Tagen	≤ 50	≤ 50	≤ 50
Acetaldehyd nach 3 Tagen	≤ 50	≤ 50	≤ 50
Summe von Form- und Acetaldehyd	≤ 0,05 ppm	≤ 0,05 ppm	≤ 0,05 ppm
Summe von flüchtigen K1A/K1B Stoffen nach 3 Tagen	≤ 10	≤ 10	≤ 10
Jeder flüchtige K1A/K1B Stoff nach 28 Tagen	≤ 1	≤ 1	≤ 1

2) Oberflächenbehandlungsmittel für Parkett, mineralische Böden und elastische Bodenbeläge

Parameter	EC 1 PLUS	EC 1	EC 2
	max. zulässige Konzentration [µg/m³]		
Summe TVOC + TSVOC nach 28 Tagen	≤ 100 davon max. 40 SVOC	≤ 150 davon max. 50 SVOC	≤ 450 davon max. 100 SVOC
Formaldehyd nach 3 Tagen	≤ 50	≤ 50	≤ 50
Acetaldehyd nach 3 Tagen	≤ 50	≤ 50	≤ 50
Jeder flüchtige K1A/K1B Stoff nach 3 Tagen	≤ 10	≤ 10	≤ 10
Jeder flüchtige K1A/K1B Stoff nach 28 Tagen	≤ 1	≤ 1	≤ 1