SENTINEL HOLDING
INSTITUT

SHI PRODUCT PASSPORT

Find products. Certify buildings.

SHI Product Passport No.:

13373-10-1122

Wandmanschette CERAfix 309

Product group: Waterproofing membranes - Sealing / Bitumen membranes

WÜRTH

Adolf Würth GmbH & Co. KG
Reinhold-Würth-Straße 12-17
74653 Künzelsau-Gaisbach

Product qualities:

- SHI Product Assessment 2024 ✓
- QNG Qualitätssiegel Nachhaltiges Gebäude ✓
- DGNB NEW CONSTRUCTION 2023.2 ✓
- DGNB NEW CONSTRUCTION 2023 ✓
- DGNB NEW CONSTRUCTION 2018 ✓
- BNB-BN NEUBAU V2015 ✓
- EU TAXONOMY ✓
- BREEAM DE NEUBAU 2018 ✓
- LEED v4.1 (outside US) ✓

CERTIFIED SUSTAINABLE PRODUCT
SHI PRODUCT PASSPORT
SENTINEL HOLDING INSTITUT
www.sentinel-holding.eu

Köttner

Helmut Köttner
Scientific Director
Freiburg, 26 August 2026

Product:
Wandmanschette CERAfix 309

SHI Product Passport no.:
13373-10-1122

WÜRTH

Contents

SHI Product Assessment 2024	1
QNG - Qualitätssiegel Nachhaltiges Gebäude	2
DGNB New Construction 2023.2	3
DGNB New Construction 2023	4
DGNB New Construction 2018	5
BNB-BN Neubau V2015	6
EU taxonomy	7
BREEAM DE Neubau 2018	8
LEED v4.1	9
Product labels	10
Legal notices	11
Technical data sheet/attachments	12

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar

SENTINEL HOLDING
INSTITUT

Product:
Wandmanschette CERAfix 309

SHI Product Passport no.:
13373-10-1122

WÜRTH

SHI Product Assessment 2024

Since 2008, Sentinel Holding Institut GmbH (SHI) has been establishing a unique standard for products that support healthy indoor air. Experts carry out independent product assessments based on clear and transparent criteria. In addition, the independent testing company SGS regularly audits the processes and data accuracy.

Criteria	Product category	Harmful substance limit	Assessment
SHI Product Assessment	Other products	TVOC ≤ 300 µg/m^3 Formaldehyd ≤ 24 µg/m^3	Indoor Air Quality Certified
Valid untill: 26 February 2030			

SENTINEL HOLDING
INSTITUT

Product:
Wandmanschette CERAfix 309

SHI Product Passport no.:
13373-10-1122

WÜRTH

QNG - Qualitätssiegel Nachhaltiges Gebäude

The Qualitätssiegel Nachhaltiges Gebäude (Quality Seal for Sustainable Buildings), developed by the German Federal Ministry for Housing, Urban Development and Building (BMWSB), defines requirements for the ecological, socio-cultural, and economic quality of buildings. The Sentinel Holding Institut evaluates construction products in accordance with QNG requirements for certification and awards the QNG ready label. Compliance with the QNG standard is a prerequisite for eligibility for the KfW funding programme. For certain product groups, the QNG currently has no specific requirements defined. Although classified as not assessment-relevant, these products remain suitable for QNG-certified projects.

Criteria	Pos. / product group	Considered substances	QNG assessment
3.1.3 Schadstoffvermeidung in Baumaterialien			QNG ready - Not relevant for assessment

SENTINEL HOLDING
INSTITUT

Product:
Wandmanschette CERAfix 309

SHI Product Passport no.:
13373-10-1122

WÜRTH

DGNB New Construction 2023.2

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact			Not relevant for assessment

SENTINEL HOLDING
INSTITUT

Product:
Wandmanschette CERAfix 309

SHI Product Passport no.:
13373-10-1122

WÜRTH

DGNB New Construction 2023

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings. The 2023 version sets high standards for ecological, economic, socio-cultural, and functional aspects throughout the entire life cycle of a building.

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 03.05.2024 (3rd edition)			Not relevant for assessment

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 29.05.2025 (4th edition)			Not relevant for assessment

SENTINEL HOLDING
INSTITUT

Product:
Wandmanschette CERAfix 309

SHI Product Passport no.:
13373-10-1122

WÜRTH

DGNB New Construction 2018

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings.

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact			Not relevant for assessment

SENTINEL HOLDING
INSTITUT

Product:
Wandmanschette CERAfix 309

SHI Product Passport no.:
13373-10-1122

WÜRTH

BNB-BN Neubau V2015

The Bewertungssystem Nachhaltiges Bauen (Assessment System for Sustainable Building) is a tool for evaluating public office and administrative buildings, educational facilities, laboratory buildings, and outdoor areas in Germany. The BNB was developed by the former Federal Ministry for the Environment, Nature Conservation, Building and Nuclear Safety (BMUB) and is now overseen by the Federal Ministry for Housing, Urban Development and Building (BMWSB).

Criteria	Pos. / product type	Considered substance group	Quality level
1.1.6 Risiken für die lokale Umwelt			Not relevant for assessment

SENTINEL HOLDING
INSTITUT

Product:
Wandmanschette CERAfix 309

SHI Product Passport no.:
13373-10-1122

WÜRTH

EU taxonomy

The EU Taxonomy classifies economic activities and products according to their environmental impact. At the product level, the EU regulation defines clear requirements for harmful substances, formaldehyde and volatile organic compounds (VOCs). The Sentinel Holding Institut GmbH labels qualified products that meet this standard.

Criteria	Product type	Considered substances	Assessment
DNSH - Pollution prevention and control	Sonstige	Stoffe nach Anlage C	compliant
Verification: EC1+ Zertifizierung			

SENTINEL HOLDING
INSTITUT

Product:
Wandmanschette CERAfix 309

SHI Product Passport no.:
13373-10-1122

WÜRTH

BREEAM DE Neubau 2018

BREEAM (Building Research Establishment Environmental Assessment Methodology) is a UK-based building assessment system that evaluates the sustainability of new constructions, refurbishments, and conversions. Developed by the Building Research Establishment (BRE), the system aims to assess and improve the environmental, economic, and social performance of buildings.

Criteria	Product category	Considered substances	Quality level
Hea 02 Indoor Air Quality			Not relevant for assessment

SENTINEL HOLDING
INSTITUT

Product:
Wandmanschette CERAfix 309

SHI Product Passport no.:
13373-10-1122

WÜRTH

LEED v4.1

LEED (Leadership in Energy and Environmental Design) is an internationally recognised building certification system developed by the U.S. Green Building Council. It is one of the most widely used sustainability standards for buildings worldwide and is particularly applied in internationally oriented projects. LEED assesses buildings holistically across categories such as energy efficiency, resource conservation, material selection, indoor environmental quality and site sustainability. Depending on the number of points achieved, projects are awarded one of the certification levels: LEED Certified, Silver, Gold or Platinum.

Criteria	Product category	Considered substances	Assessment
EQ Credit: Low-Emitting Materials			Not relevant for assessment

SENTINEL HOLDING
INSTITUT

Product:
Wandmanschette CERAfix 309

SHI Product Passport no.:
13373-10-1122

WÜRTH

Product labels

In the construction industry, high-quality materials are crucial for a building's indoor air quality and sustainability. Product labels and certificates offer guidance to meet these requirements. However, the evaluation criteria of these labels vary, and it is important to carefully assess them to ensure products align with the specific needs of a construction project.

The EMICODE® label, awarded by the German manufacturers' association "GEV – Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e. V.", is primarily relevant for flooring installation materials. The EMICODE® EC1^{PLUS} label, as the premium class, sets significantly stricter emission limits than the other label variants.

This product is SHI Indoor Air Quality certified and recommended by Sentinel Holding Institut. Indoor-air-focused construction, renovation, and operation of buildings is made possible by transparent and verifiable criteria thanks to the Sentinel Holding concept.

Products bearing the Sentinel Holding Institute QNG-ready seal are suitable for projects aiming to achieve the "Qualitätssiegel Nachhaltiges Gebäude" (Quality Seal for Sustainable Buildings). QNG-ready products meet the requirements of QNG Appendix Document 3.1.3, "Avoidance of Harmful Substances in Building Materials." The KfW loan program Climate-Friendly New Construction with QNG may allow for additional funding.

Product:
Wandmanschette CERAfix 309

SHI Product Passport no.:
13373-10-1122

WÜRTH

Legal notices

(*) These criteria apply to the construction project as a whole. While individual products can positively contribute to the overall building score through proper planning, the evaluation is always conducted at the building level. The information was provided entirely by the manufacturer.

Find our criteria here: https://www.sentinel-holding.eu/de/Themenwelten/Pr%C3%BCfkriterien%20f%C3%BCr%20Produkte

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar

SGS

SGS TÜV SAAR


Publisher

Sentinel Holding Institut GmbH
Bötzinger Str. 38
79111 Freiburg im Breisgau
Germany
Tel.: +49 761 590 481-70
info@sentinel-holding.eu
www.sentinel-holding.eu

TECHNISCHES DATENBLATT

Wandmanschette CERAfix® 309

Art.-Nr. 5875 100 309
VE: 25



Wandmanschette zum schnellen und sicheren Abdichten von Wanddurchgängen

- Sichere Abdichtung mit konstanter Schichtdicke
- Hoher Haftverbund
- Hohe Wasserdruckbeständigkeit
- Hohe Dehnfähigkeit
- Gleichbleibende Dichtschicht
- Einfache und schnelle Verarbeitung
- Direkt mit Fliesen belegbar
- Hohe Beständigkeit gegen aggressive Medien

Werkstoff	Polypropylen-Vlies (ober-/unterseitig)/Polyethylen-Folie (mittig)
Schenkelbreite	120 mm
Durchmesser Rohrdurchführung min./max.	19-50 mm
Farbe	Rot HKS 14
Schenkellänge	120 mm
Dicke	0,51 mm
Beständigkeit gegen	Alterung
Wasserdampfdurchlässigkeit min. (Druck)	1,5 bar
Wasserdampfdurchlässigkeit Bedingung	nach DIN EN 1928
Dehnung längs max.	80 %
Dehnung quer max.	120 %
Zugkraft quer bei 50 mm	150 N
Zugkraft längs bei 50 mm	296,66 N
Baustoffklasse	B2 - Normal entflammbar
Baustoffklasse Bedingung	nach DIN 4102-1
Lagerfähigkeit ab Herstellung	24 Monate

KERAMIK BALKON 3. ABDICHTEN NATURSTEIN

SENTINEL HAUS INSTITUT

Anwendungsgebiet

Verwendbar für die Wassereinwirkungsklassen W0-I bis W3-I, W1-B u. W2-B gemäß DIN 18531, 18534 und 18535. Als Systemkomponente in allen CERAfix Abdichtungssystemen verwendbar.

PR01_5875100309, TDB, Rev: 0.35, Stand: 17. 10. 2024

TECHNISCHES DATENBLATT

Anwendungsinformationen

Untergrund:
Trocken, tragfähig, frei von haftmindernden Substanzen (Öl, Fett, Staub, sonstige Verunreinigungen).

Anwendung:
Die Wandmanschette CERAfix 309 wird in allen CERAfix Abdichtungssystemen vom CERAfix 302, CERAfix 305, CERAfix 301und CERAfix 300 eingesetzt zum Abdichten an Rohrdurchführungen. Abdichtung von Rohrdurchführen im Wandbereich für die Wassereinwirkungsklasse W0 -I bis W3-I , W1-B u. W2-B gemäß DIN 18531, 18534 und 18535. Für das Andichten im Wandbereich von Rohrdurchführen wird je nach entsprechendem Durchmesser CERAfix 308 oder CERAfix 309 verwendet.

Ablauf:
Die Rohrdurchführungen anrauen und säubern, auf den entsprechenden Untergrund und auf die Rohrdurchführungen die entsprechende Abdichtung auftragen. Zum Abschluss den Loch Durchmesser von CERAfix 309 über das Rohr stülpen und gut mit der entsprechenden Abdichtung überarbeiten, um eine dichte Verbindung zur Flächenabdichtung herzustellen.

Leistungsnachweis

EMICODE EC1plus: Sehr emissionsarm - Das Klassifizierungssystem EMICODE zeichnet die Umwelt- und Gesundheitsverträglichkeit von Bauprodukten aus. Die emissionsärmsten Produkte tragen das Zeichen EC1plus.

Hinweis

Materialidentisch mit Abdichtbahn CERAfix 305

Entsorgungshinweise

Materialreste können über den Hausmüll entsorgt werden.

Die Verarbeitungsangaben sind Empfehlungen, die auf unseren Versuchen und Erfahrungen beruhen; vor jedem Anwendungsfall sind Eigenversuche durchzuführen. Aufgrund der Vielzahl der Anwendungen sowie der Lagerungs- und Verarbeitungsbedingungen übernehmen wir keine Gewährleistung für ein bestimmtes Verarbeitungsergebnis. Soweit unserer kostenloser Kundendienst technische Auskünfte gibt bzw. beratend tätig wird, erfolgt dies unter Ausschluss jeglicher Haftung, es sei denn, die Beratung bzw. Auskunft gehört zu unserem geschuldeten, vertraglich vereinbarten Leistungsumfang oder der Berater handelte vorsätzlich. Wir gewährleisten gleich bleibende Qualität unserer Produkte, technische Änderungen und Weiterentwicklungen behalten wir uns vor.

PR01_5875100309, TDB, Rev: 0.35, Stand: 17. 10. 2024

HERSTELLERERKLÄRUNG

Firma	Adolf Würth GmbH & Co. KG
Artikelnummer	5875100309
Produktbezeichnung	Wandmanschette CERAfix 309
Anwendung/ Beschreibung	Wandmanschette zum schnellen und sicheren Abdichten von Wanddurchgängen

Anforderungen	Erfüllt	Bemerkung
SVHC < 0,10 %	Ja	
CMR-Stoffe der Kategorie 1A/1B < 0,10%	Ja	

Vorhandene Dokumente

Sicherheitsdatenblatt (SDB*)	nicht vorhanden, da Erzeugnis
Prüfzeugnisse Sonstiges	EC1+

01/26

Dieses Dokument ist ohne Unterschrift gültig.

Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e.V.

GEV EMICODE®

Lizenzerteilung zur Führung des EMICODE

Lizenzierungs-Nummer:	11629/09.03.00
Für den Artikel	Wandmanschette CERAfix 309
wird auf Antrag vom	31.03.2020

unter Bezugnahme auf die Einstufung gemäß den nach § 10 der GEV-Zeichensatzung festgelegten Richtlinien

namens der Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e.V. für den oben genannten Artikel nach § 5 Abs. 4 der GEV-Zeichensatzung die Lizenz zur Führung des GEV-Zeichens

GEV-EMICODE® EC 1 PLUS sehr emissionsarm

erteilt. Damit erfüllt dieser Artikel die rückseitig aufgeführten Kriterien.
Die Firma ist ordentliches Mitglied der GEV.

OM023 26.02.2025
gültig bis 26.02.2030

Der Geschäftsführer
Gemeinschaft Emissionskontrollierte Verlegewerkstoffe,
Klebstoffe und Bauprodukte e.V.
Völklinger Straße 4 · D-40219 Düsseldorf

Hinweise zu den Voraussetzungen über die Vergabe der Lizenz für den EMICODE

Das gemäß vorseitiger Lizenz eingestufte Produkt hat nach der Satzung und den Richtlinien des Technischen Beirats der GEV u.a. den folgenden Kriterien zu genügen:

- Das Produkt entspricht allen gesetzlichen Bestimmungen, insbesondere denen des Chemikalienrechtes und seiner Verordnungen.
- Das Produkt ist nach der Definition der TRGS 610 lösemittelfrei, sofern es sich nicht um ein Oberflächenprodukt handelt. Soweit es einer Produktgruppe nach GISCODE zuzuordnen ist, wird diese angegeben.
- Für das Produkt wird ein Sicherheitsdatenblatt nach lokalem Recht in der jeweils aktuellen Fassung erstellt.
- Krebserregende, erbgutverändernde oder fruchtschädigende Stoffe der Klassen 1A und 1B werden dem Produkt bei der Herstellung nicht zugesetzt.
- Die Prüfung des Produktes erfolgt nach der definierten „GEV-Prüfmethode“. Die VOC-Bestimmung wird dabei in einer Prüfkammer nach dem Tenax-Thermodesorptions-Verfahren mit nachgeschalteter GC/MS-Analyse durchgeführt.
- Die Einstufung in EMICODE-Klassen erfolgt entsprechend den nachstehenden Bezeichnungen und TVOC/TSVOC-Konzentrationsbereichen. Zur Produktkennzeichnung ist die zutreffende EMICODE-Klasse zu verwenden:

1) Verlegewerkstoffe, Klebstoffe und Bauprodukte

Parameter	EC 1 PLUS	EC 1	EC 2
	max. zulässige Konzentration [µg/m³]		
TVOC nach 3 Tagen	≤ 750	≤ 1000	≤ 3000
TVOC nach 28 Tagen	≤ 60	≤ 100	≤ 300
TSVOC nach 28 Tagen	≤ 40	≤ 50	≤ 100
R-Wert basierend auf AgBB-NIK-Werten nach 28 Tagen	≤ 1	-	-
Summe der nicht bewertbaren VOC	≤ 40	-	-
Formaldehyd nach 3 Tagen	≤ 50	≤ 50	≤ 50
Acetaldehyd nach 3 Tagen	≤ 50	≤ 50	≤ 50
Summe von Form- und Acetaldehyd	≤ 0,05 ppm	≤ 0,05 ppm	≤ 0,05 ppm
Summe von flüchtigen K1A/K1B Stoffen nach 3 Tagen	< 10	< 10	< 10
Jeder flüchtige K1A/K1B Stoff nach 28 Tagen	< 1	< 1	< 1

2) Oberflächenbehandlungsmittel für Parkett, mineralische Böden und elastische Bodenbeläge

Parameter	EC 1 PLUS	EC 1	EC 2
	max. zulässige Konzentration [µg/m³]		
Summe TVOC + TSVOC nach 28 Tagen	≤ 100 davon max. 40 SVOC	≤ 150 davon max. 50 SVOC	≤ 400 davon max. 100 SVOC
Formaldehyd nach 3 Tagen	≤ 50	≤ 50	≤ 50
Acetaldehyd nach 3 Tagen	≤ 50	≤ 50	≤ 50
Jeder flüchtige K1A/K1B Stoff nach 3 Tagen	< 10	< 10	< 10
Jeder flüchtige K1A/K1B Stoff nach 28 Tagen	< 1	< 1	< 1