SENTINEL HOLDING
INSTITUT

SHI PRODUCT PASSPORT

Find products. Certify buildings.

SHI Product Passport No.:

15160-10-1000

Black Line

Product group: Design floors - Floor coverings / Wall coverings

Einkaufsgesellschaft Christiansen-Knutzen oHG
Parkallee 16
24782 Büdelsdorf

Product qualities:

- SHI Product Assessment 2024
- QNG Qualitätssiegel Nachhaltiges Gebäude
- DGNB NEW CONSTRUCTION 2023.2
- DGNB NEW CONSTRUCTION 2023
- DGNB NEW CONSTRUCTION 2018
- BNB-BN NEUBAU V2015
- EU TAXONOMY
- BREEAM DE NEUBAU 2018
- LEED v4.1 (outside US)

CERTIFIED SUSTAINABLE PRODUCT
SHI PRODUCT PASSPORT
SENTINEL HOLDING INSTITUT
www.sentinel-holding.eu

Köttner

Helmut Köttner
Scientific Director
Freiburg, 17 August 2026

SENTINEL HOLDING
INSTITUT

Product:
Black Line

SHI Product Passport no.:
15160-10-1000

Contents

SHI Product Assessment 2024	1
QNG - Qualitätssiegel Nachhaltiges Gebäude	2
DGNB New Construction 2023.2	3
DGNB New Construction 2023	4
DGNB New Construction 2018	5
BNB-BN Neubau V2015	6
EU taxonomy	7
BREEAM DE Neubau 2018	8
LEED v4.1	9
Product labels	10
Legal notices	11
Technical data sheet/attachments	12

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar

SENTINEL HOLDING
INSTITUT

Product:
Black Line

SHI Product Passport no.:
15160-10-1000

SHI Product Assessment 2024

Since 2008, Sentinel Holding Institut GmbH (SHI) has been establishing a unique standard for products that support healthy indoor air. Experts carry out independent product assessments based on clear and transparent criteria. In addition, the independent testing company SGS regularly audits the processes and data accuracy.

Criteria	Product category	Harmful substance limit	Assessment
SHI Product Assessment	Other floor coverings	TVOC ≤ 160 µg/m^3 Formaldehyd ≤ 10 µg/m^3	Indoor Air Quality Certified
Valid untill: 13 October 2028			

SENTINEL HOLDING
INSTITUT

Product:
Black Line

SHI Product Passport no.:
15160-10-1000

QNG - Qualitätssiegel Nachhaltiges Gebäude

The Qualitätssiegel Nachhaltiges Gebäude (Quality Seal for Sustainable Buildings), developed by the German Federal Ministry for Housing, Urban Development and Building (BMWSB), defines requirements for the ecological, socio-cultural, and economic quality of buildings. The Sentinel Holding Institut evaluates construction products in accordance with QNG requirements for certification and awards the QNG ready label. Compliance with the QNG standard is a prerequisite for eligibility for the KfW funding programme. For certain product groups, the QNG currently has no specific requirements defined. Although classified as not assessment-relevant, these products remain suitable for QNG-certified projects.

Criteria	Pos. / product group	Considered substances	QNG assessment
3.1.3 Schadstoffvermeidung in Baumaterialien	2.2 Resilient floor coverings – including multilayer systems	VOC / Emissions / hazardous substances / polycyclic aromatic hydrocarbons (PAH) / SVHC / heavy metals	QNG ready
Verification: Eurofins Indoor Air Comfort Gold Zertifikat vom 13.10.2023 (Zertifikats Nr. IACG-396-01-01-2023). Herstellererklärung vom 29.01.2025			

SENTINEL HOLDING
INSTITUT

Product:
Black Line

SHI Product Passport no.:
15160-10-1000

DGNB New Construction 2023.2

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact			Not relevant for assessment

SENTINEL HOLDING
INSTITUT

Product:
Black Line

SHI Product Passport no.:
15160-10-1000

DGNB New Construction 2023

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings. The 2023 version sets high standards for ecological, economic, socio-cultural, and functional aspects throughout the entire life cycle of a building.

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 03.05.2024 (3rd edition)	7 Floor coverings (Resilient floor coverings)	VVOCs, VOC, SVOC emissions and content of hazardous substances	Quality level 3
Verification: Eurofins Indoor Air Comfort Gold Zertifikat vom 13.10.2023 (Zertifikats Nr. IACG-396-01-01-2023). Herstellererklärung vom 29.01.2025.			

Criteria	Assessment
SOC1.2 Indoor air quality (*)	May positively contribute to the overall building score
Verification: SHI Schadstoffgeprüft	

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 29.05.2025 (4th edition)	7 Floor coverings for indoor use (elastic floor coverings)	VVOCs, VOC, SVOC emissions and content of hazardous substances	Quality level 3
Verification: Eurofins Indoor Air Comfort Gold Zertifikat vom 13.10.2023 (Zertifikats Nr. IACG-396-01-01-2023). Herstellererklärung vom 29.01.2025.			

SENTINEL HOLDING
INSTITUT

Product:
Black Line

SHI Product Passport no.:
15160-10-1000

DGNB New Construction 2018

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings.

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact	7 Floor coverings (Resilient floor coverings)	VOC / SVOC / hazardous substances	Quality level 4
Verification: Eurofins Indoor Air Comfort Gold Zertifikat vom 13.10.2023 (Zertifikats Nr. IACG-396-01-01-2023). Herstellererklärung vom 29.01.2025.			

SENTINEL HOLDING
INSTITUT

Product:
Black Line

SHI Product Passport no.:
15160-10-1000

BNB-BN Neubau V2015

The Bewertungssystem Nachhaltiges Bauen (Assessment System for Sustainable Building) is a tool for evaluating public office and administrative buildings, educational facilities, laboratory buildings, and outdoor areas in Germany. The BNB was developed by the former Federal Ministry for the Environment, Nature Conservation, Building and Nuclear Safety (BMUB) and is now overseen by the Federal Ministry for Housing, Urban Development and Building (BMWSB).

Criteria	Pos. / product type	Considered substance group	Quality level
1.1.6 Risiken für die lokale Umwelt	2a Elastic floor coverings – with and without bonded underlay or insulation layer	VOC / hazardous substances / heavy metals	Quality level 3
Verification: Eurofins Indoor Air Comfort Gold Zertifikat vom 13.10.2023 (Zertifikats Nr. IACG-396-01-01-2023). Herstellererklärung vom 29.01.2025			

SENTINEL HOLDING
INSTITUT

Product:
Black Line

SHI Product Passport no.:
15160-10-1000

EU taxonomy

The EU Taxonomy classifies economic activities and products according to their environmental impact. At the product level, the EU regulation defines clear requirements for harmful substances, formaldehyde and volatile organic compounds (VOCs). The Sentinel Holding Institut GmbH labels qualified products that meet this standard.

Criteria	Product type	Considered substances	Assessment
DNSH - Pollution prevention and control	Floor coverings (including associated adhesives and sealants)	Stoffe nach Anlage C, Formaldehyd, Karzinogene VOC Kategorie 1A/1B	compliant
Verification: Eurofins Indoor Air Comfort Gold Zertifikat vom 13.10.2023 (Zertifikats Nr. IACG-396-01-01-2023). Herstellererklärung vom 29.01.2025			

SENTINEL HOLDING
INSTITUT

Product:
Black Line

SHI Product Passport no.:
15160-10-1000

BREEAM DE Neubau 2018

BREEAM (Building Research Establishment Environmental Assessment Methodology) is a UK-based building assessment system that evaluates the sustainability of new constructions, refurbishments, and conversions. Developed by the Building Research Establishment (BRE), the system aims to assess and improve the environmental, economic, and social performance of buildings.

Criteria	Product category	Considered substances	Quality level
Hea 02 Indoor Air Quality	Flooring materials (including floor levelling compounds and resin flooring)	Emissions: Formaldehyde, TVOC, TSVOC, carcinogens	Exemplary quality
Verification: Eurofins Indoor Air Comfort Gold Zertifikat vom 13.10.2023 (Zertifikats Nr. IACG-396-01-01-2023). Herstellererklärung vom 29.01.2025			

SENTINEL HOLDING
INSTITUT

Product:
Black Line

SHI Product Passport no.:
15160-10-1000

LEED v4.1

LEED (Leadership in Energy and Environmental Design) is an internationally recognised building certification system developed by the U.S. Green Building Council. It is one of the most widely used sustainability standards for buildings worldwide and is particularly applied in internationally oriented projects. LEED assesses buildings holistically across categories such as energy efficiency, resource conservation, material selection, indoor environmental quality and site sustainability. Depending on the number of points achieved, projects are awarded one of the certification levels: LEED Certified, Silver, Gold or Platinum.

Criteria	Product category	Considered substances	Assessment
EQ Credit: Low-Emitting Materials	Bodenbeläge	Emissionen: Formaldehyd, VOC, Krebserregende Stoffe	compliant
Verification: Eurofins Indoor Air Comfort Gold Zertifikat vom 13.10.2023 (Zertifikats Nr. IACG-396-01-01-2023). Herstellererklärung vom 29.01.2025			

SENTINEL HOLDING
INSTITUT

Product:
Black Line

SHI Product Passport no.:
15160-10-1000

Product labels

In the construction industry, high-quality materials are crucial for a building's indoor air quality and sustainability. Product labels and certificates offer guidance to meet these requirements. However, the evaluation criteria of these labels vary, and it is important to carefully assess them to ensure products align with the specific needs of a construction project.

This product is SHI Indoor Air Quality certified and recommended by Sentinel Holding Institut. Indoor-air-focused construction, renovation, and operation of buildings is made possible by transparent and verifiable criteria thanks to the Sentinel Holding concept.

Products bearing the Sentinel Holding Institute QNG-ready seal are suitable for projects aiming to achieve the "Qualitätssiegel Nachhaltiges Gebäude" (Quality Seal for Sustainable Buildings). QNG-ready products meet the requirements of QNG Appendix Document 3.1.3, “Avoidance of Harmful Substances in Building Materials.” The KfW loan program Climate-Friendly New Construction with QNG may allow for additional funding.

SENTINEL HOLDING
INSTITUT

Product:
Black Line

SHI Product Passport no.:
15160-10-1000

Legal notices

(*) These criteria apply to the construction project as a whole. While individual products can positively contribute to the overall building score through proper planning, the evaluation is always conducted at the building level. The information was provided entirely by the manufacturer.

Find our criteria here: https://www.sentinel-holding.eu/de/Themenwelten/Pr%C3%BCfkriterien%20of%C3%BCr%20Produkte

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar

Publisher

Sentinel Holding Institut GmbH
Bötzinger Str. 38
79111 Freiburg im Breisgau
Germany
Tel.: +49 761 590 481-70
info@sentinel-holding.eu
www.sentinel-holding.eu

Technische Daten

Black Line 30

Produktspezifikation

Belagsart nach ISO 10582	Heterogenes PVC
ISO 14001	√
ISO 9001	√
ISO 24340 Nutzschicht	0,3 mm + Polyurethan
ISO 24346 Gesamtstärke	2,0 mm
ISO 23997 Flächengewicht	+/- 3,620 kg/m²
ISO23999 Dimensionsstabilität	In Längsrichtung: -0.05%
	In Querrichtung: -0.05%
EN 1081 Durchgangswiderstand	Horizontal: 5.2 x 10^7 Ω
	Vertikal: 2.2 x 10^{12} Ω
EN 1815 Elektrostatisches Verhalten	Gummi-Testschuh: +0,3 kV
ISO 10140-1 Maximale Schalldämmung	ΔL_w 4 dB
ISO 354 Maximale Schallabsorption	δs 0.05
EN 12667 / ISO 8302 Wärmedurchlasswiderstand	0,014 m²K/W
EN 13501-1 - 1:2007 Brandverhalten	Bfl-s1
ISO 24343-1 Resteindruck	-0.02 mm
ISO 4918 Stuhlrollenbeanspruchung	√
EN 13893 Rutschhemmung	0.4 mμ (R9)
ISO 10582 Beanspruchungsklasse	23 - intensive private Nutzung
	31 - leicht gewerbliche Nutzung
ISO 24344A Biegsamkeit	-
ISO 26987 Cheimikalienbeständigkeit	Klasse O - Gut
EN 71 Toxität	Nicht toxisch
EN ISO 105 B02 Lichtechtheit	6-8 abhängig vom Design
Fußbodenheizung	28 °C √
Format Diele	121,92 x 22,86 cm oder 121,92 x 18,42 cm
Verpackungseinheit	12 Dielen / 3,34 m² oder 15 Dielen / 3,37 m²

Technische Daten

Black Line 55

Produktspezifikation

Belagsart nach ISO 10582	Heterogenes PVC
ISO 14001	√
ISO 9001	√
ISO 24340 Nutzschicht	0,55 mm + Polyurethan
ISO 24346 Gesamtstärke	2,5 mm
ISO 23997 Flächengewicht	+/- 4,350 kg/m²
ISO23999 Dimensionsstabilität	In Längsrichtung: -0.08
	In Querrichtung: -0.04
EN 1081 Durchgangswiderstand	Horizontal: 1.0 x 10^{16} Ω
	Vertikal: 1.0 x 10^{13} Ω
EN 1815 Elektrostatisches Verhalten	Gummi-Testschuh: -0,3 kV
ISO 10140-1 Maximale Schalldämmung	ΔL_w 5 dB
ISO 354 Maximale Schallabsorption	δs 0.05
EN 12667 / ISO 8302 Wärmedurchlasswiderstand	0,014 m²K/W
EN 13501-1 - 1:2007 Brandverhalten	Bfl-s1
ISO 24343-1 Resteindruck	0.11 mm
ISO 4918 Stuhlrollenbeanspruchung	√
EN 13893 Rutschhemmung	0.6 mμ (R9)
ISO 10582 Beanspruchungsklasse	33 - intensive gewerbliche Nutzung
	42 - normale industrielle Nutzung
ISO 24344A Biegsamkeit	-
ISO 26987 Cheimikalienbeständigkeit	Klasse O - Gut
EN 71 Toxität	Nicht toxisch
Phthalatfrei	√
EN ISO 105 B02 Lichtechtheit	6-8 abhängig vom Design
Fußbodenheizung	28 °C √
Format Diele	121,92 x 22,86 cm
Verpackungseinheit	12 Dielen / 3,34 m²

Technische Daten

Black Line Herringbone 55

Produktspezifikation

Belagsart nach ISO 10582	Heterogenes PVC
ISO 14001	√
ISO 9001	√
ISO 24340 Nutzschicht	0,55 mm + Polyurethan
ISO 24346 Gesamtstärke	2,5 mm
ISO 23997 Flächengewicht	+/- 4,350 kg/m²
ISO23999 Dimensionsstabilität	In Längsrichtung: -0.08%
	In Querrichtung: -0.04%
EN 1081 Durchgangswiderstand	Horizontal: 1.0 x 10^{16} Ω
	Vertikal: 1.0 x 10^{13} Ω
EN 1815 Elektrostatisches Verhalten	Gummi-Testschuh: -0,3 kV
ISO 10140-1 Maximale Schalldämmung	ΔL_w 5 dB
ISO 354 Maximale Schallabsorption	δs 0.05
EN 12667 / ISO 8302 Wärmedurchlasswiderstand	0,014 m²K/W
EN 13501-1 - 1:2007 Brandverhalten	Bfl-s1
ISO 24343-1 Resteindruck	0.11 mm
ISO 4918 Stuhlrollenbeanspruchung	√
EN 13893 Rutschhemmung	0.6 mμ (R9)
ISO 10582 Beanspruchungsklasse	33 - intensive gewerbliche Nutzung
	42 - normale industrielle Nutzung
ISO 24344A Biegsamkeit	-
ISO 26987 Chemikalienbeständigkeit	Klasse O - Gut
EN 71 Toxität	Nicht toxisch
Phthalatfrei	√
EN ISO 105 B02 Lichtechtheit	6-8 abhängig vom Design
Fußbodenheizung	28 °C √
Format Diele	60,96 x 11,43 cm
Verpackungseinheit	48 Dielen / 3,34 m²

Technische Daten

Black Line Tiles 30

Produktspezifikation

Belagsart nach ISO 10582	Heterogenes PVC
ISO 14001	√
ISO 9001	√
ISO 24340 Nutzschicht	0,3 mm + Polyurethan
ISO 24346 Gesamtstärke	2,0 mm
ISO 23997 Flächengewicht	+/- 3,620 kg/m²
ISO23999 Dimensionsstabilität	In Längsrichtung: -0.05%
	In Querrichtung: -0.05%
EN 1081 Durchgangswiderstand	Horizontal: 5.2 x 10^7 Ω
	Vertikal: 2.2 x 10^{12} Ω
EN 1815 Elektrostatisches Verhalten	Gummi-Testschuh: +0,3 kV
ISO 10140-1 Maximale Schalldämmung	ΔL_w 4 dB
ISO 354 Maximale Schallabsorption	δs 0.05
EN 12667 / ISO 8302 Wärmedurchlasswiderstand	0,014 m²K/W
EN 13501-1 - 1:2007 Brandverhalten	Bfl-s1
ISO 24343-1 Resteindruck	-0.02 mm
ISO 4918 Stuhlrollenbeanspruchung	√
EN 13893 Rutschhemmung	0.4 mμ (R9)
ISO 10582 Beanspruchungsklasse	23 - intensive private Nutzung
	31 - leicht gewerbliche Nutzung
ISO 24344A Biegsamkeit	-
ISO 26987 Cheimikalienbeständigkeit	Klasse O - Gut
EN 71 Toxität	Nicht toxisch
EN ISO 105 B02 Lichtechtheit	6-8 abhängig vom Design
Fußbodenheizung	28 °C √
Format Diele	91,44 x 45,72 cm
Verpackungseinheit	10 Fliesen / 4,18 m²

Herstellererklärung

29.01.2025

Sehr geehrte Damen und Herren,

hiermit bestätigen wir, dass bei der Produktion unserer aktuellen Designbodenkollektionen unter Einhaltung des AgBB-Schemas von folgenden Inhaltsstoffen abgesehen wird:

1) SVHC und CMR-Stoffe der Kategorie 1A und 1B < 0,1%

2) Reproduktionstoxische Phthalate < 0,1% und Cadmium-, Zinn- und Bleistabilisatoren

3) Chlorparaffine (SCCPs + MCCPs + LCCPs) < 0,1%

Mit freundlichen Grüßen

Produktmanagement Boden

Repac Montagetechnik GmbH & Co. KG
Ronnenberger Str. 15
30989 Gehrden

Tel. 0 51 08 / 92 91 0
E-Mail info@repac.de
Internet www.repac.de

Sitz der Gesellschaft: Gehrden
Registergericht: Amtsgericht Hannover, HRA 100599
Persönlich haftende Gesellschafterin:
Repac Montagetechnik Verwaltungs-GmbH
Sitz der Gesellschaft: Gehrden
Registergericht: Amtsgericht Hannover, HRB 101008
Geschäftsführer: Andree Kube, Rüdiger Timm