SENTINEL HOLDING
INSTITUT

SHI PRODUCT PASSPORT

Find products. Certify buildings.

SHI Product Passport No.:

2318-10-1046

REVOPUR® TC 415

Product group: Coatings - Construction chemicals - Sealants

FRANKEN SYSTEMS

FRANKEN SYSTEMS GmbH
Südstraße 3
97258 Gollhofen

Product qualities:

- QNG – Qualitätssiegel Nachhaltiges Gebäude ✓
- DGNB NEW CONSTRUCTION 2023 ✓
- DGNB NEW CONSTRUCTION 2018 ✓
- BNB-BN NEUBAU V2015 ✓
- BREEAM DE NEUBAU 2018 ✓
- LEED v4.1 (outside US) ✓

CERTIFIED SUSTAINABLE PRODUCT – SHI PRODUCT PASSPORT – SENTINEL HOLDING INSTITUT – www.sentinel-holding.eu

Köttner

Helmut Köttner
Scientific Director
Freiburg, 18 May 2026

SENTINEL HOLDING
INSTITUT

Product:
REVOPUR® TC 415

SHI Product Passport no.:
2318-10-1046

FRANKEN SYSTEMS

Contents

QNG - Qualitätssiegel Nachhaltiges Gebäude	1
DGNB New Construction 2023	2
DGNB New Construction 2018	3
BNB-BN Neubau V2015	4
BREEAM DE Neubau 2018	5
LEED v4.1	6
Product labels	7
Legal notices	8
Technical data sheet/attachments	9

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar

SGS TÜV SAAR

SENTINEL HOLDING
INSTITUT

Product:
REVOPUR® TC 415

SHI Product Passport no.:
2318-10-1046

FRANKEN SYSTEMS

QNG - Qualitätssiegel Nachhaltiges Gebäude

The Qualitätssiegel Nachhaltiges Gebäude (Quality Seal for Sustainable Buildings), developed by the German Federal Ministry for Housing, Urban Development and Building (BMWSB), defines requirements for the ecological, socio-cultural, and economic quality of buildings. The Sentinel Holding Institut evaluates construction products in accordance with QNG requirements for certification and awards the QNG ready label. Compliance with the QNG standard is a prerequisite for eligibility for the KfW funding programme. For certain product groups, the QNG currently has no specific requirements defined. Although classified as not assessment-relevant, these products remain suitable for QNG-certified projects.

Criteria	Pos. / product group	Considered substances	QNG assessment
3.1.3 Schadstoffvermeidung in Baumaterialien	5.7 Synthetic resin screeds and reactive polyurethane coatings	VOC / Emissions / hazardous substances	QNG ready
Verification: Technisches Datenblatt aus KW 42/2023 (Abschnitt "Sicherheitshinweise")			

SENTINEL HOLDING
INSTITUT

Product:
REVOPUR® TC 415

SHI Product Passport no.:
2318-10-1046

FRANKEN SYSTEMS

DGNB New Construction 2023

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings. The 2023 version sets high standards for ecological, economic, socio-cultural, and functional aspects throughout the entire life cycle of a building.

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 03.05.2024 (3rd edition)	20 Reactive PU products	VOCs, hazardous substances	Quality level 4
Verification: Technisches Datenblatt aus KW 42/2023. Emicode EC1+ Zertifikat vom 05.08.2025.			

Criteria	Assessment
ECO1.1 Life cycle cost (*)	May positively contribute to the overall building score
Verification: Wartungsarm und durch längere Nutzungsdauer geringere Lebenszykluskosten	

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 29.05.2025 (4th edition)	20 Reactive PU products	VOCs, hazardous substances	Quality level 4
Verification: Technisches Datenblatt aus KW 42/2023. Emicode EC1+ Zertifikat vom 05.08.2025.			

SENTINEL HOLDING
INSTITUT

Product:
REVOPUR® TC 415

SHI Product Passport no.:
2318-10-1046

FRANKEN SYSTEMS

DGNB New Construction 2018

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings.

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact	20 Reactive PU products for coating mineral floor	VOC / hazardous substances	Quality level 4
Verification: Technisches Datenblatt aus KW 42/2023. Emicode EC1+ Zertifikat vom 05.08.2025.			

SENTINEL HOLDING
INSTITUT

Product:
REVOPUR® TC 415

SHI Product Passport no.:
2318-10-1046

FRANKEN SYSTEMS

BNB-BN Neubau V2015

The Bewertungssystem Nachhaltiges Bauen (Assessment System for Sustainable Building) is a tool for evaluating public office and administrative buildings, educational facilities, laboratory buildings, and outdoor areas in Germany. The BNB was developed by the former Federal Ministry for the Environment, Nature Conservation, Building and Nuclear Safety (BMUB) and is now overseen by the Federal Ministry for Housing, Urban Development and Building (BMWSB).

Criteria	Pos. / product type	Considered substance group	Quality level
1.1.6 Risiken für die lokale Umwelt	17 Reactive PU products – also in system constructions 1K and 2K systems	VOC / hazardous substances	Quality level 5
Verification: Technisches Datenblatt aus KW 42/2023. EMICODE EC1+ Zertifikat von 05.08.2025.			

SENTINEL HOLDING
INSTITUT

Product:
REVOPUR® TC 415

SHI Product Passport no.:
2318-10-1046

FRANKEN SYSTEMS

BREEAM DE Neubau 2018

BREEAM (Building Research Establishment Environmental Assessment Methodology) is a UK-based building assessment system that evaluates the sustainability of new constructions, refurbishments, and conversions. Developed by the Building Research Establishment (BRE), the system aims to assess and improve the environmental, economic, and social performance of buildings.

Criteria	Product category	Considered substances	Quality level
Hea 02 Indoor Air Quality			Not relevant for assessment

SENTINEL HOLDING
INSTITUT

Product:
REVOPUR® TC 415

SHI Product Passport no.:
2318-10-1046

FRANKEN SYSTEMS

LEED v4.1

LEED (Leadership in Energy and Environmental Design) is an internationally recognised building certification system developed by the U.S. Green Building Council. It is one of the most widely used sustainability standards for buildings worldwide and is particularly applied in internationally oriented projects. LEED assesses buildings holistically across categories such as energy efficiency, resource conservation, material selection, indoor environmental quality and site sustainability. Depending on the number of points achieved, projects are awarded one of the certification levels: LEED Certified, Silver, Gold or Platinum.

Criteria	Product category	Considered substances	Assessment
EQ Credit: Low-Emitting Materials			Not relevant for assessment

SENTINEL HOLDING
INSTITUT

Product:
REVOPUR® TC 415

SHI Product Passport no.:
2318-10-1046

FRANKEN SYSTEMS

Product labels

In the construction industry, high-quality materials are crucial for a building's indoor air quality and sustainability. Product labels and certificates offer guidance to meet these requirements. However, the evaluation criteria of these labels vary, and it is important to carefully assess them to ensure products align with the specific needs of a construction project.

The EMICODE® label, awarded by the German manufacturers' association "GEV – Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e. V.", is primarily relevant for flooring installation materials. The EMICODE® EC1^{PLUS} label, as the premium class, sets significantly stricter emission limits than the other label variants.

The IBU ("Institut Bauen und Umwelt e.V.") is an initiative of building product manufacturers committed to sustainability in construction. It serves as the programme operator for Environmental Product Declarations (EPDs) in accordance with the EN 15804 standard. The IBU EPD programme provides comprehensive life cycle assessments and environmental impact data for construction products, supported by independent third-party verification.

Products bearing the Sentinel Holding Institute QNG-ready seal are suitable for projects aiming to achieve the "Qualitätssiegel Nachhaltiges Gebäude" (Quality Seal for Sustainable Buildings). QNG-ready products meet the requirements of QNG Appendix Document 3.1.3, "Avoidance of Harmful Substances in Building Materials." The KfW loan program Climate-Friendly New Construction with QNG may allow for additional funding.

SENTINEL HOLDING
INSTITUT

Product:
REVOPUR® TC 415

SHI Product Passport no.:
2318-10-1046

FRANKEN SYSTEMS

Legal notices

(*) These criteria apply to the construction project as a whole. While individual products can positively contribute to the overall building score through proper planning, the evaluation is always conducted at the building level. The information was provided entirely by the manufacturer.

Find our criteria here: https://www.sentinel-holding.eu/de/Themenwelten/Pr%C3%BCfkriterien%20f%C3%BCr%20Produkte

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar

SGS

SGS TÜV SAAR

Publisher

Sentinel Holding Institut GmbH
Bötzinger Str. 38
79111 Freiburg im Breisgau
Germany
Tel.: +49 761 590 481-70
info@sentinel-holding.eu
www.sentinel-holding.eu

Technisches Merkblatt

REVOPUR® TC415

1-komponentiges, lösemittelfreies Bindemittel für Marmorkiesel

Einsatzgebiete

REVOPUR® TC415 wird als Bindemittel zur Herstellung von Quarzkiesel, Marmorkiesel oder Granitgranulatbelägen eingesetzt.

Merkmale

- 1-komponentig
- Polyurethan
- UV-beständig
- feuchtigkeitsreagierend
- lösemittelfrei
- weichmacherfrei
- ökologisch / EMICODE EC1 PLUS
- glänzend

Eigenschaften*

- Verarbeitungszeit: ca. 3 Stunden
- regenfest nach: ca. 6 Stunden
- überarbeitbar / begehbar nach: ca. 12 Stunden
- belastbar nach: ca. 24 Stunden
- mögliche Verarbeitungstemperatur: von +5°C bis +50°C
- empfohlene Verarbeitungstemperatur: von +5°C bis +40°C
- Farbton: farblos

*Alle Messungen bei +21 °C und einer relativen Luftfeuchte von 50 %. Durch Witterungseinflüsse wie Wind, Luftfeuchte und Temperatur werden die angegebenen Werte verändert.

Verbrauch

- ca. 1,30 kg (1 Beutel) REVOPUR® TC415
  für 25 kg Marmorkiesel
- Mischung ca. 16,00 – 18,00 kg/m² bei 8mm Schichtdicke

Lieferform

- 4 x 1,3 kg Aluminiumbeutel im Kunststoffgebinde

Lagerung

Originalgebinde bei +5 °C bis +30 °C trocken lagern.
Direkte Sonnenbestrahlung der Gebinde sollte, auch auf der Baustelle, vermieden werden.
Ab Produktion 12 Monate haltbar.

Verarbeitung

Untergrund
Der Untergrund muss sauber, trocken, griffig und tragfähig sein, genügend Dichtigkeit und Festigkeit aufweisen, frei von trennenden Substanzen wie Schmutz, Öl, Fett usw. sein.
Ablüftzeiten bzw. die Überarbeitbarkeit der einzelnen Lagen sind einzuhalten.



Anwendung
Das gemischte Bindemittel, gemischt mit Marmorkiesel, wird auf den Untergrund aufgebracht und gleichmäßig verteilt. Um Ansätze / Absätze zu vermeiden, muss die gesamte Fläche in einem Schritt, ohne Arbeitsunterbrechung, fertiggestellt werden.
Um Farbunterschiede zu vermeiden, muss darauf geachtet werden, dass Produkte mit gleicher Chargennummer verwendet werden.

Mischen
Unmittelbar vor Verarbeitung gut durchkneten/durchrühren.

Werkzeuge und Hilfsmittel



Sicherheitshinweise

Angaben zur persönlichen Schutzausrüstung entnehmen Sie bitte dem Produkt-Sicherheitsdatenblatt.
GISCODE: PU10

Allgemeine Hinweise

Zeitangaben verkürzen sich bei höheren und verlängern sich bei niedrigen Umgebungs- und Untergrundtemperaturen. Die verwendeten Verarbeitungswerkzeuge und Geräte sowie unterschiedlichen Baustellenbedingungen haben einen Einfluss auf die angegebenen Verbrauchswerte. Diese können sich somit verändern. Aus dem Untergrund resultierende Unebenheiten können mit dem Produkt nicht ausgeglichen werden.
Das Produkt darf nicht mit systemfremden Stoffen gemischt und verarbeitet werden. Es dürfen keine anderen Materialien, als die von FRANKEN SYSTEMS GmbH angegeben, verwendet werden.
Die aktuelle Ausgabe der DAfStb Richtlinie „Schutz und Instandsetzung von Betonbauteilen“ ist zu beachten.

FRANKEN SYSTEMS GmbH | Südstraße 3 | 97258 Gollhofen | T +49 9339 988 69 – 0
F +49 9339 988 69 – 99 | E info@franken-systems.de | www.franken-systems.de

Verdünnung

Das Produkt darf nicht verdünnt werden.

Das Reinigen von Werkzeugen ist mit Systemreiniger möglich, s. Grundierungsempfehlung REVOPUR® (TL35).

Sonstiges

Die vorstehenden Informationen und unsere anwendungstechnische Beratung in Wort, Schrift sowie durch Versuche erfolgen nach bestem Wissen. Sie gelten jedoch nur als unverbindliche Hinweise, auch in Bezug auf etwaige Schutzrechte Dritter. Die Beratung befreit Sie nicht von einer eigenen Prüfung unserer aktuellen Beratungshinweise - insbesondere unserer Sicherheitsdatenblätter und technischen Informationen - und unserer Produkte im Hinblick auf ihre Eignung für die beabsichtigten Verfahren und Zwecke. Anwendung, Verwendung und Verarbeitung unserer Produkte und der aufgrund unserer anwendungstechnischen Beratung von Ihnen gewählte Einsatzzweck liegen außerhalb unserer Kontrollmöglichkeiten und sind daher ausschließlich in Ihrem Verantwortungsbereich. Der Verkauf unserer Produkte erfolgt nach Maßgabe unserer jeweils aktuellen Allgemeinen Verkaufs- und Lieferbedingungen. Auf den Produktetiketten befindliche Warnhinweise sind zu berücksichtigen. Es sind die jeweils gültigen Unterlagen in ihrer neuesten Ausgabe zu verwenden.
Bitte prüfen Sie die Aktualität der verwendeten Unterlagen und / oder fordern Sie vor jeder Anwendung ein aktuelles Dokument an.

ABSCHNITT 1: Bezeichnung des Stoffs beziehungsweise des Gemischs und des Unternehmens

1.1 Produktidentifikator

Handelsname: REVOPUR® TC415

UFI: 5910-S049-200X-RMRT

1.2 Relevante identifizierte Verwendungen des Stoffs oder Gemischs und Verwendungen, von denen abgeraten wird

Allgemeine Verwendung: Beschichtungsmittel
Nur für gewerbliche Anwender

1.3 Einzelheiten zum Lieferanten, der das Sicherheitsdatenblatt bereitstellt

Firmenbezeichnung: FRANKEN SYSTEMS GmbH
Straße/Postfach: Südstraße 3
PLZ, Ort: 97258 Gollhofen
Deutschland
WWW: www.franken-systems.de
E-Mail: info@franken-systems.de
Telefon: +49 9339 98869-0
Telefax: +49 9339 98869-99
Auskunft gebender Bereich:
Telefon: +49 9339 98869-0, Email: info@franken-systems.de

1.4 Notrufnummer

GIZ-Nord, Göttingen, Deutschland,
Telefon: +49 551-19240

ABSCHNITT 2: Mögliche Gefahren

2.1 Einstufung des Stoffs oder Gemischs

Einstufung gemäß EG-Verordnung 1272/2008 (CLP)

Acute Tox. 4; H332 Gesundheitsschädlich bei Einatmen.
Skin Sens. 1; H317 Kann allergische Hautreaktionen verursachen.
STOT SE 3; H335 Kann die Atemwege reizen.

2.2 Kennzeichnungselemente

Kennzeichnung (CLP)



Signalwort: **Achtung**

Gefahrenhinweise:	H317	Kann allergische Hautreaktionen verursachen.
	H332	Gesundheitsschädlich bei Einatmen.
	H335	Kann die Atemwege reizen.
Sicherheitshinweise:	P261	Einatmen von Nebel/Dampf/Aerosol vermeiden.
	P280	Schutzhandschuhe/Schutzkleidung/Augenschutz tragen.
	P302+P352	BEI BERÜHRUNG MIT DER HAUT: Mit viel Wasser/Seife waschen.
	P304+P340	BEI EINATMEN: Die Person an die frische Luft bringen und für ungehinderte Atmung sorgen.
	P312	Bei Unwohlsein GIFTINFORMATIONSZENTRUM/Arzt anrufen.
	P362+P364	Kontaminierte Kleidung ausziehen und vor erneutem Tragen waschen.
	P403+P233	An einem gut belüfteten Ort aufbewahren. Behälter dicht verschlossen halten.

Besondere Kennzeichnung

	EUH204	Enthält Isocyanate. Kann allergische Reaktionen hervorrufen.
	EUH210	Sicherheitsdatenblatt auf Anfrage erhältlich.

Hinweistext für Etiketten: Enthält Hexamethylen-1,6-diisocyanat Homopolymer; Reaktionsmasse aus Methyl-1,2,2,6,6-pentamethyl-4-piperidylsebacat und bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacat

2.3 Sonstige Gefahren

Personen mit Überempfindlichkeit der Atemwege (z.B. Asthma, chronische Bronchitis) dürfen aus Schutzgründen mit dem Produkt nicht umgehen.
Symptome an den Atemwegen können auch noch einige Stunden nach einer Überexposition auftreten.
Dämpfe und Aerosole sind die Hauptgefahr für die Atemwege.
Besondere Rutschgefahr durch auslaufendes/verschüttetes Produkt.

Endokrinschädliche Eigenschaften, Ergebnisse der PBT- und vPvB-Beurteilung:

Keine Daten verfügbar

ABSCHNITT 3: Zusammensetzung/Angaben zu Bestandteilen

3.1 Stoffe: nicht anwendbar

3.2 Gemische

Gefährliche Inhaltsstoffe:

Identifikatoren	Bezeichnung Einstufung	Gehalt
REACH 01-2119485796-17-xxxx EG-Nr. 500-060-2 CAS 28182-81-2	Hexamethylen-1,6-diisocyanat Homopolymer Acute Tox. 4; H332. Skin Sens. 1; H317. STOT SE 3; H335.	>= 50 %
REACH 01-2119969278-20-xxxx EG-Nr. 229-194-7 CAS 6425-39-4	2,2'-Dimorpholinyldiethylether Eye Irrit. 2; H319.	1 - 5 %
REACH 01-2119491304-40-xxxx Listennr. 915-687-0 CAS 1065336-91-5	Reaktionsmasse aus Methyl-1,2,2,6,6-pentamethyl-4-piperidylsebacat und bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacat Skin Sens. 1A; H317. Aquatic Acute 1; H400. Aquatic Chronic 1; H410.	< 0,25 %

Wortlaut der H- und EUH-Gefahrenhinweise: siehe unter Abschnitt 16.

ABSCHNITT 4: Erste-Hilfe-Maßnahmen

4.1 Beschreibung der Erste-Hilfe-Maßnahmen

Allgemeine Hinweise: Ist ärztlicher Rat erforderlich, Verpackung oder Kennzeichnungsetikett bereithalten. Kontaminierte Kleidung ausziehen und vor erneutem Tragen waschen. Symptome können zeitlich verzögert auftreten.

Bei Einatmen: Bei Atembeschwerden die betroffene Person an die frische Luft bringen und in einer Position ruhigstellen, die das Atmen erleichtert. Bei Atembeschwerden ist ärztliche Hilfe erforderlich.

Nach Hautkontakt: Sofort mit Wasser und Seife abwaschen und gründlich nachspülen. Bei Hautreaktionen Arzt aufsuchen.

Nach Augenkontakt: Sofort bei geöffnetem Lidspalt 10 bis 15 Minuten mit fließendem Wasser spülen. Eventuell vorhandene Kontaktlinsen nach Möglichkeit entfernen. Weiter ausspülen. Bei auftretenden oder anhaltenden Beschwerden Augenarzt aufsuchen.

Nach Verschlucken: Sofort Mund ausspülen und reichlich Wasser nachtrinken. Niemals darf einem Bewusstlosen etwas über den Mund verabreicht werden. Kein Erbrechen herbeiführen. Arzt hinzuziehen.

4.2 Wichtigste akute und verzögert auftretende Symptome und Wirkungen

Kann allergische Hautreaktionen verursachen. Gesundheitsschädlich bei Einatmen. Kann die Atemwege reizen.

4.3 Hinweise auf ärztliche Soforthilfe oder Spezialbehandlung

Symptomatisch behandeln (Dekontamination, Vitalfunktionen). Kein spezifisches Antidot bekannt.
Bei Inhalation zur Lungenödemprophylaxe möglichst frühzeitig eine inhalative Cortisontherapie einleiten (z.B. alle 10 Minuten 5 Hübe eines cortisonhaltigen Dosier-Aerosols), Codein gegen Reizhusten.

ABSCHNITT 5: Maßnahmen zur Brandbekämpfung

5.1 Löschmittel

Geeignete Löschmittel: Kohlendioxid (CO_2), alkoholbeständiger Schaum, Trockenlöschpulver, Wassersprühstrahl.

Aus Sicherheitsgründen ungeeignete Löschmittel:

Wasservollstrahl

5.2 Besondere vom Stoff oder Gemisch ausgehende Gefahren

Brennbar. Bei Brand entsteht dichter schwarzer Rauch. Im Brandfall können entstehen: giftige Gase/Dämpfe, Cyanide, Stickoxide (NOx), Kohlenmonoxid und Kohlendioxid. Dämpfe bilden mit Luft explosionsfähige Gemische, die schwerer als Luft sind.

5.3 Hinweise für die Brandbekämpfung

Besondere Schutzausrüstung bei der Brandbekämpfung:

Umgebungsluftunabhängiges Atemschutzgerät und Chemikalienschutzanzug tragen.

Zusätzliche Hinweise: Gefährdete Behälter mit Sprühwasser kühlen, aber direkten Kontakt des Wassers mit dem Produkt unbedingt vermeiden.
Bildung von Kohlendioxid: Gefahr des Berstens des Behälters.
Eindringen von Löschwasser in Oberflächengewässer oder Grundwasser vermeiden.

ABSCHNITT 6: Maßnahmen bei unbeabsichtigter Freisetzung

6.1 Personenbezogene Vorsichtsmaßnahmen, Schutzausrüstungen und in Notfällen anzuwendende Verfahren

Einatmen von Nebel/Dampf/Aerosol vermeiden. Substanzkontakt vermeiden.
Wenn möglich, Undichtigkeit beseitigen. Für ausreichende Lüftung sorgen.
Geeignete Schutzausrüstung tragen. Bei Einwirkung von Dämpfen/Aerosol Atemschutz verwenden. Ungeschützte Personen fernhalten.
Kontaminierte Kleidung ausziehen und vor erneutem Tragen waschen.

6.2 Umweltschutzmaßnahmen

Eindringen in Erdreich, Gewässer oder Kanalisation verhindern.
Bei Freisetzung zuständige Behörden benachrichtigen.

6.3 Methoden und Material für Rückhaltung und Reinigung

Mit feuchtem flüssigkeitsbindendem Material (z.B. Sand, Chemiekalienbinder auf der Basis Calciumsilikathydrat) abdecken. Nach ca. 1 Stunde in Abfallgebinde mechanisch aufnehmen, nicht verschließen (CO_2-Entwicklung).
feucht halten und an gesichertem Ort im Freien 7 bis 14 Tage stehen lassen.
Rückstände mit Dekontaminationsmittel versetzen und mehrere Tage in einem offenen Behälter stehen lassen, bis keine Reaktion mehr zu beobachten ist. Anschließend Behälter verschließen und entsorgen.
Verschüttetes Produkt zur Wiederverwendung nie in den Originalbehälter geben.

Zusätzliche Hinweise: Besondere Rutschgefahr durch auslaufendes/verschüttetes Produkt.

6.4 Verweis auf andere Abschnitte

Siehe ergänzend Abschnitt 8 und 13.

ABSCHNITT 7: Handhabung und Lagerung

7.1 Schutzmaßnahmen zur sicheren Handhabung

Hinweise zum sicheren Umgang:

Einatmen von Nebel/Dampf/Aerosol vermeiden.
Für gute Be- und Entlüftung von Lager und Arbeitsplatz sorgen.
Geeignete Schutzausrüstung tragen.
Bei Gebrauch nicht essen, trinken oder rauchen. Nach Gebrauch Hände gründlich waschen. Die Luftbewegung muss von den Personen weg erfolgen.
Kontaminierte Kleidung ausziehen und vor erneutem Tragen waschen. Berührung mit den Augen und der Haut vermeiden.
Augenspülflasche oder Augendusche im Arbeitsraum bereitstellen.

Hinweise zum Brand- und Explosionsschutz:

Vor Hitze schützen.
Bei Handhabung größerer Mengen Maßnahmen gegen elektrostatische Aufladung treffen.

7.2 Bedingungen zur sicheren Lagerung unter Berücksichtigung von Unverträglichkeiten

Anforderungen an Lagerräume und Behälter:

Behälter dicht geschlossen halten und an einem kühlen, gut gelüfteten Ort aufbewahren.
Behälter trocken halten. Nur im Originalbehälter aufbewahren.
Vor Hitze und direkter Sonneneinstrahlung schützen.
Behälter aufrecht lagern.

Zusammenlagerungshinweise:

Von Nahrungsmitteln, Getränken und Futtermitteln fernhalten.
Fernhalten von Säuren und Laugen.

Sonstige Hinweise: Kohlendioxidentwicklung bei Einwirkung von Wasser oder Luftfeuchtigkeit.

Lagerklasse: 10 = Brennbare Flüssigkeiten, die keiner der vorgenannten LGK zuzuordnen sind

7.3 Spezifische Endanwendungen

Es liegen keine Informationen vor.

ABSCHNITT 8: Begrenzung und Überwachung der Exposition/Persönliche Schutzausrüstungen

8.1 Zu überwachende Parameter

Arbeitsplatzgrenzwerte:

CAS-Nr.	Bezeichnung	Typ	Grenzwert
822-06-0	Hexamethylen-1,6-diisocyanat	Deutschland: TRGS 900 Kurzzeit	0,02 mg/m³
		Deutschland: TRGS 900 Langzeit	0,01 mg/m³
		Europa: BOELV: STEL	20 µg/m³ (kann über die Haut aufgenommen werden)
		Europa: BOELV: TWA	10 µg/m³ (kann über die Haut aufgenommen werden)

Biologische Grenzwerte:

CAS-Nr.	Bezeichnung	Typ	Grenzwert	Parameter	Probenahme
822-06-0	Hexamethylen-1,6-diisocyanat	Deutschland: TRGS 903, Urin	15 µg/g Creatinin	Hexamethylendiamin nach Hydrolyse	Expositionsende bzw. Schichtende

DNEL/DMEL:

Angabe zu Hexamethylen-1,6-diisocyanat
DNEL Arbeiter lokal, kurzzeitig, inhalativ: 1 mg/m³
DNEL Arbeiter lokal, langzeitig, inhalativ: 0,5 mg/m³

PNEC:

Angabe zu Hexamethylen-1,6-diisocyanat
PNEC Wasser (Süßwasser): 0,127 mg/L
PNEC Wasser (Meerwasser): 0,0127 mg/L
PNEC Wasser (periodische Freisetzung): 1,27 mg/L
PNEC Kläranlage: 38,28 mg/L
PNEC Sediment (Süßwasser): 266.701 mg/kg dw
PNEC Sediment (Meerwasser): 266.700 mg/kg dw
PNEC Boden: 531.830 mg/kg dw

8.2 Begrenzung und Überwachung der Exposition

Innenanwendung: Für gute Belüftung bzw. Abzug sorgen oder mit völlig geschlossenen Apparaturen arbeiten.
Außenanwendung: Für gute Belüftung sorgen.

Persönliche Schutzausrüstung

Begrenzung und Überwachung der Exposition am Arbeitsplatz

Atemschutz:

Bei unzureichender Belüftung Atemschutz.
Bei Überschreitung der Arbeitsplatzgrenzwerte (AGW) ist ein Atemschutzgerät zu tragen.
Kombinationsfilter ABEK gemäß EN 14387 benutzen.

Handschutz:

Schutzhandschuhe gemäß DIN EN ISO 374-1.
Handschuhmaterial: Butylkautschuk
Durchbruchzeit (maximale Tragedauer): >= 480 min
Schichtstärke: >= 0,7 mm
Handschuhmaterial: Nitrilkautschuk
Durchbruchzeit (maximale Tragedauer): >= 480 min
Schichtstärke: >= 0,4 mm
Handschuhmaterial: Chloroprenkautschuk
Durchbruchzeit (maximale Tragedauer): >= 480 min
Schichtstärke: >= 0,5 mm

Die Angaben des Herstellers der Schutzhandschuhe zu Durchlässigkeiten und Durchbruchzeiten sind zu beachten.

Augenschutz:

Dicht schließende Schutzbrille gemäß DIN EN ISO 16321-1.

Körperschutz:

Bei der Arbeit geeignete Schutzkleidung tragen.

Schutz- und Hygienemaßnahmen:

Einatmen von Nebel/Dampf/Aerosol vermeiden.
Die Luftbewegung muss von den Personen weg erfolgen.
Kontaminierte Kleidung ausziehen und vor erneutem Tragen waschen. Berührung mit den Augen und der Haut vermeiden.
Personen mit Überempfindlichkeit der Atemwege (z.B. Asthma, chronische Bronchitis) dürfen aus Schutzgründen mit dem Produkt nicht umgehen. Bei Gebrauch nicht essen, trinken oder rauchen. Nach Gebrauch Hände gründlich waschen.
Augenspülflasche oder Augendusche im Arbeitsraum bereitstellen.

Begrenzung und Überwachung der Umweltexposition

Siehe "6.2 Umweltschutzmaßnahmen".

ABSCHNITT 9: Physikalische und chemische Eigenschaften

9.1 Angaben zu den grundlegenden physikalischen und chemischen Eigenschaften

Aggregatzustand bei 20 °C und 101,3 kPa	flüssig
Farbe:	gelb
Geruch:	charakteristisch
Schmelzpunkt/Gefrierpunkt:	<= 0 °C
Siedepunkt oder Siedebeginn und Siedebereich:	> 200 °C
Entzündbarkeit:	Brennbar
Untere und obere Explosionsgrenze:	Keine Daten verfügbar
Flammpunkt:	> 100 °C (DIN EN 22719)
Zündtemperatur:	> 200 °C (DIN 51794)
Zersetzungstemperatur:	> 230 °C
pH-Wert:	Keine Daten verfügbar
Kinematische Viskosität:	Keine Daten verfügbar
Wasserlöslichkeit:	Reagiert mit Wasser
Verteilungskoeffizient n-Oktanol/Wasser (log-Wert):	Keine Daten verfügbar
Dampfdruck:	bei 20 °C: <= 0,1 hPa
Dichte:	bei 20 °C: 1,12 g/mL
Relative Dampfdichte:	Keine Daten verfügbar
Partikeleigenschaften:	Nicht anwendbar

9.2 Sonstige Angaben

Explosive Eigenschaften:	Das Produkt ist nicht explosionsgefährlich.
Oxidierende Eigenschaften:	nicht brandfördernd
Selbstentzündungstemperatur:	Keine Daten verfügbar

ABSCHNITT 10: Stabilität und Reaktivität

10.1 Reaktivität

Siehe Unterabschnitt "Möglichkeit gefährlicher Reaktionen".

10.2 Chemische Stabilität

Stabil unter angegebenen Lagerungsbedingungen.

10.3 Möglichkeit gefährlicher Reaktionen

Reagiert mit Wasser, Alkohole, Aminen und Basen.
Bildung von Kohlendioxid. Berstgefahr geschlossener Gebinde. Erhitzen führt zu Drucksteigerung: Berst- und Explosionsgefahr.

10.4 Zu vermeidende Bedingungen

Von Hitzequellen, Funken und offenen Flammen fernhalten.
Gegen direkte Sonneneinstrahlung schützen.
Vor Feuchtigkeit schützen.

10.5 Unverträgliche Materialien

Säuren, Laugen, Wasser, Amine, Alkohol.

10.6 Gefährliche Zersetzungsprodukte

Keine gefährlichen Zersetzungsprodukte, wenn die Vorschriften für die Lagerung und Umgang beachtet werden.

Thermische Zersetzung: > 230 °C

ABSCHNITT 11: Toxikologische Angaben

11.1 Angaben zu den Gefahrenklassen im Sinne der Verordnung (EG) Nr. 1272/2008

Toxikologische Wirkungen: Die Aussagen sind von den Eigenschaften der Einzelkomponenten abgeleitet. Für das Produkt als solches liegen keine toxikologischen Daten vor.

Akute Toxizität (oral): Aufgrund der verfügbaren Daten sind die Einstufungskriterien nicht erfüllt.
ATEmix (berechnet): ATE > 2000 mg/kg.

Akute Toxizität (dermal): Fehlende Daten.

Akute Toxizität (inhalativ): Acute Tox. 4; H332 = Gesundheitsschädlich bei Einatmen.

Ätz-/Reizwirkung auf die Haut: Fehlende Daten.

Schwere Augenschädigung/-reizung: Fehlende Daten.

Sensibilisierung der Atemwege: Fehlende Daten.

Sensibilisierung der Haut: Skin Sens. 1; H317 = Kann allergische Hautreaktionen verursachen.

Keimzellmutagenität/Genotoxizität: Fehlende Daten.

Karzinogenität: Fehlende Daten.

Reproduktionstoxizität: Fehlende Daten.

Wirkungen auf und über die Muttermilch: Fehlende Daten.

Spezifische Zielorgan-Toxizität (einmalige Exposition): STOT SE 3; H335 = Kann die Atemwege reizen.

Spezifische Zielorgan-Toxizität (wiederholte Exposition): Fehlende Daten.

Aspirationsgefahr: Fehlende Daten.

11.2 Angaben über sonstige Gefahren

Endokrinschädliche Eigenschaften:

Keine Daten verfügbar

Sonstige Angaben: Angabe zu Hexamethylen-1,6-diisocyanat Homopolymer
LC50 Ratte, inhalativ, weiblich, Nebel/Staub: > 0,39 mg/L/4h (OECD 403).

Symptome

Bei längerer Berührung sind Gerb- und Reizeffekte möglich.

Personen mit Überempfindlichkeit der Atemwege (z.B. Asthma, chronische Bronchitis) dürfen aus Schutzgründen mit dem Produkt nicht umgehen.
Symptome an den Atemwegen können auch noch einige Stunden nach einer Überexposition auftreten.
Dämpfe und Aerosole sind die Hauptgefahr für die Atemwege.

ABSCHNITT 12: Umweltbezogene Angaben

12.1 Toxizität

Aquatische Toxizität:

Angabe zu Hexamethylen-1,6-diisocyanat
Akute Fischtoxizität
LC50 Danio rerio (Zebrabärbling): >100 mg/L/96h (OECD 203)
Akute Daphnientoxizität
EC50 Daphnia magna (Großer Wasserfloh): >127 mg/L/48h (OECD 202)
Algentoxizität
EC50 Scenedesmus subspicatus: >1000 mg/L/72h (OECD 201)
Bakterientoxizität
Belebtschlamm EC20 >880 mg/L/3h (OECD 209)

Wassergefährdungsklasse:

1 = schwach wassergefährdend

12.2 Persistenz und Abbaubarkeit

Sonstige Hinweise:

Biologische Abbaubarkeit: 1 %/28 d. (OECD 302C).
Nicht leicht abbaubar.

Setzt sich mit Wasser an der Grenzfläche unter Bildung von Kohlendioxid zu einem festen, hochschmelzenden und unlöslichen Reaktionsprodukt (Polyharnstoff) um.
Polyharnstoff ist nach bisher vorliegenden Erfahrungen inert und nicht abbaubar.

12.3 Bioakkumulationspotenzial

Verteilungskoeffizient n-Octanol/Wasser:

Keine Daten verfügbar

12.4 Mobilität im Boden

Keine Daten verfügbar

12.5 Ergebnisse der PBT- und vPvB-Beurteilung

Keine Daten verfügbar

12.6 Endokrinschädliche Eigenschaften

Keine Daten verfügbar

12.7 Andere schädliche Wirkungen

Allgemeine Hinweise:

Nicht in das Grundwasser, in Gewässer oder in die Kanalisation gelangen lassen.

ABSCHNITT 13: Hinweise zur Entsorgung

13.1 Verfahren der Abfallbehandlung

Produkt

Abfallschlüsselnummer:

08 05 01* = Isocyanatabfälle
* = Die Entsorgung ist nachweispflichtig.

Empfehlung:

Entsorgung gemäß den behördlichen Vorschriften.
Darf nicht zusammen mit Hausmüll entsorgt werden.

Verpackung

Empfehlung: Entsorgung gemäß den behördlichen Vorschriften.
Kontaminierte Verpackungen sind wie der Stoff zu behandeln.

Weitere Angaben

Nicht über die Kanalisation entsorgen.

Abschnitt 14. Angaben zum Transport

14.1 UN-Nummer oder ID-Nummer

ADR/RID, IMDG, IATA-DGR:
entfällt

14.2 Ordnungsgemäße UN-Versandbezeichnung

ADR/RID, IMDG, IATA-DGR:
Nicht eingeschränkt

14.3 Transportgefahrenklassen

ADR/RID, IMDG, IATA-DGR:
entfällt

14.4 Verpackungsgruppe

ADR/RID, IMDG, IATA-DGR:
entfällt

14.5 Umweltgefahren

Umweltgefährlich: Stoff/Gemisch ist nach den Kriterien der UN-Modellvorschriften nicht für die Umwelt gefährlich.
Meeresschadstoff: nein

14.6 Besondere Vorsichtsmaßnahmen für den Verwender

Kein Gefahrgut im Sinne dieser Transportvorschriften.

14.7 Massengutbeförderung auf dem Seeweg gemäß IMO-Instrumenten

Keine Daten verfügbar

ABSCHNITT 15: Rechtsvorschriften

15.1 Vorschriften zu Sicherheit, Gesundheits- und Umweltschutz/spezifische Rechtsvorschriften für den Stoff oder das Gemisch

Nationale Vorschriften - Deutschland

Lagerklasse: 10 = Brennbare Flüssigkeiten, die keiner der vorgenannten LGK zuzuordnen sind

Wassergefährdungsklasse:
1 = schwach wassergefährdend

Technische Anleitung Luft: 5.2.5 Klasse I

Hinweise zur Beschäftigungsbeschränkung:

Beschäftigungsbeschränkungen für Jugendliche beachten.
Beschäftigungsbeschränkungen für werdende und stillende Mütter beachten.

Sonstige Vorschriften, Beschränkungen und Verordnungen:

Das Produkt unterliegt nicht der Chemikalienverbotsverordnung (ChemVerbotsV).

Nationale Vorschriften - EG-Mitgliedstaaten

Gehalt an flüchtigen organischen Verbindungen (VOC):

0 g/L

Kennzeichnung der Verpackung bei einem Inhalt <= 125mL



Signalwort: **Achtung**

Gefahrenhinweise:	H317	Kann allergische Hautreaktionen verursachen.
	EUH204	Enthält Isocyanate. Kann allergische Reaktionen hervorrufen.
	EUH210	Sicherheitsdatenblatt auf Anfrage erhältlich.
Sicherheitshinweise:	P261	Einatmen von Nebel/Dampf/Aerosol vermeiden.
	P280	Schutzhandschuhe/Schutzkleidung/Augenschutz tragen.
	P302+P352	BEI BERÜHRUNG MIT DER HAUT: Mit viel Wasser/Seife waschen.
	P362+P364	Kontaminierte Kleidung ausziehen und vor erneutem Tragen waschen.

Sonstige Vorschriften, Beschränkungen und Verordnungen:

Verwendungsbeschränkung gemäß REACH Anhang XVII Nr.: 3, 75

15.2 Stoffsicherheitsbeurteilung

Für dieses Gemisch ist keine Stoffsicherheitsbeurteilung erforderlich.

ABSCHNITT 16: Sonstige Angaben

Wortlaut der H-Sätze unter Abschnitt 2 und 3:

H317 = Kann allergische Hautreaktionen verursachen.
H319 = Verursacht schwere Augenreizung.
H332 = Gesundheitsschädlich bei Einatmen.
H335 = Kann die Atemwege reizen.
H400 = Sehr giftig für Wasserorganismen.
H410 = Sehr giftig für Wasserorganismen mit langfristiger Wirkung.
EUH204 = Enthält Isocyanate. Kann allergische Reaktionen hervorrufen.
EUH210 = Sicherheitsdatenblatt auf Anfrage erhältlich.

Literatur: BG RCI:
- Merkblatt M017 'Lösemittel'
- Merkblatt M 044: 'Isocyanate und Polyurethane'
- Merkblatt M050 'Umgang mit Gefahrstoffen'
- Merkblatt M053 'Arbeitsschutzmaßnahmen bei Tätigkeiten mit Gefahrstoffen'

Grund der letzten Änderungen:

Änderung in Abschnitt 8: Arbeitsplatzgrenzwerte
Änderung in Abschnitt 8: Arbeitsplatzgrenzwerte

Erstausgabedatum: 23.12.2020

Datenblatt ausstellender Bereich:

siehe Abschnitt 1: Auskunft gebender Bereich

Abkürzungen und Akronyme:

Acute Tox.: Akute Toxizität
ADN: Europäisches Übereinkommen über die internationale Beförderung gefährlicher Güter auf Binnenwasserstraßen
ADR: Europäisches Übereinkommen über die internationale Beförderung gefährlicher Güter auf der Straße
AGW: Arbeitsplatzgrenzwert
Aquatic Acute: Gewässergefährdend - akut
Aquatic Chronic: Gewässergefährdend - chronisch
AS/NZS: Australische/neuseeländische Norm
BG RCI: Berufsgenossenschaft Rohstoffe und Chemische Industrie
CAS: Chemical Abstracts Service
CFR: Code of Federal Regulations
CLP: Einstufung, Kennzeichnung und Verpackung
DMEL: Abgeleitete Expositionshöhe mit minimaler Beeinträchtigung
DNEL: Abgeleitete Nicht-Effekt-Konzentration
EC50: Effektive Konzentration 50%
EG: Europäische Gemeinschaft
EmS: Unfallbekämpfungsmaßnahmen auf Schiffen, die gefährliche Güter befördern
EN: Europäische Norm
EQ: Freigestellte Mengen
EU: Europäische Union
Eye Irrit.: Reizwirkung auf die Augen
IATA: Verband für den internationalen Lufttransport
IATA-DGR: Verband für den internationalen Lufttransport – Gefahrgutvorschriften
IBC-Code: Internationaler Code für den Bau und die Ausrüstung von Schiffen zur Beförderung gefährlicher Chemikalien als Massengut
IMDG-Code: Gefahrgutvorschriften für den internationalen Seetransport
IMO: Internationale Seeschifffahrts-Organisation
LC50: Median-Letalkonzentration
MAK: Maximale Arbeitsplatz-Konzentration
MARPOL: Internationales Übereinkommen zur Verhütung der Meeresverschmutzung durch Schiffe
OSHA: Arbeitsschutzadministration, Amerika
PBT: Persistent, bioakkumulierbar und toxisch
PNEC: Abgeschätzte Nicht-Effekt-Konzentration
REACH: Registrierung, Bewertung, Zulassung und Beschränkung chemischer Stoffe
RID: Ordnung für die internationale Eisenbahnbeförderung gefährlicher Güter
Skin Sens.: Sensibilisierung der Haut
STOT SE: Spezifische Zielorgan-Toxizität - einmalige Exposition
TRGS: Technische Regeln für Gefahrstoffe
vPvB: Sehr persistent und sehr bioakkumulierbar

Die Angaben in diesem Datenblatt sind nach bestem Wissen zusammengestellt und entsprechen dem Stand der Kenntnis zum Überarbeitungsdatum. Sie sichern jedoch nicht die Einhaltung bestimmter Eigenschaften im Sinne der Rechtsverbindlichkeit zu.

ENVIRONMENTAL PRODUCT DECLARATION

as per *ISO 14025* and *EN 15804+A2*

Owner of the Declaration	DBC, EFCC, FEICA, IVK
Programme holder	Institut Bauen und Umwelt e.V. (IBU)
Publisher	Institut Bauen und Umwelt e.V. (IBU)
Declaration number	EPD-FEI-20220021-IBG1-EN
Issue date	01.06.2022
Valid to	31.05.2027

Products based on polyurethane or silane-modified polymer, group 1

DBC - Deutsche Bauchemie e.V.

EFCC - European Federation for Construction Chemicals

FEICA - Association of the European Adhesive and Sealant Industry

IVK - Industrieverband Klebstoffe e.V.

Institut Bauen und Umwelt e.V.

www.ibu-epd.com | https://epd-online.com

ECO PLATFORM EPD VERIFIED



1. General Information

DBC - Deutsche Bauchemie e.V.
EFCC - European Federation for Construction Chemicals
FEICA - Association of the European Adhesive and Sealant Industry
IVK - Industrieverband Klebstoffe e.V.

Products based on polyurethane or silane-modified polymer, group 1

Programme holder
IBU – Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

Owner of the declaration
DBC, Mainzer Landstr. 55, D-60329 Frankfurt a.M.
EFCC, 172 Boulevard du Triomphe, B-1160 Brussels
FEICA, Rue Belliard 40, B-1040 Brussels
IVK, Völklingerstr. 4, D-40219 Düsseldorf

Declaration number
EPD-FEI-20220021-IBG1-EN

Declared product / declared unit
1 kg product based on polyurethane or silane-modified polymer; density 1.25 - 1.8 g/cm³

This declaration is based on the product category rules:
Reaction resin products, 07.2014
(PCR checked and approved by the SVR)

Scope:
This verified EPD entitles the holder to bear the symbol of the Institut Bauen und Umwelt e.V. It exclusively applies for products produced in Europe and for a period of five years from the date of issue. This EPD may be used by members of DBC, EFCC, FEICA and IVK and their members provided it has been proven that the respective product can be represented by this EPD. For this purpose a guideline is available at the secretariats of the four associations. The members of the associations are listed on the respective websites.

Issue date
01.06.2022

Valid to
31.05.2027

The owner of the declaration shall be liable for the underlying information and evidence; the IBU shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

The EPD was created according to the specifications of *EN 15804+A2*. In the following, the standard will be simplified as *EN 15804*.

Verification

The standard *EN 15804* serves as the core PCR
Independent verification of the declaration and data according to *ISO 14025:2011*
☐ internally ☒ externally

Dipl. Ing. Hans Peters
(chairman of Institut Bauen und Umwelt e.V.)

Dr. Alexander Röder
(Managing Director Institut Bauen und Umwelt e.V.))

Matthias Schulz
(Independent verifier)

2. Product

2.1 Product description/Product definition

This EPD comprises reactive products based on polyurethane (PU) or silane-modified polymer (SMP) with a volatile organic copound (VOC) content ≤1 % (VOC definition according to *Decopaint Directive*) and a castor oil/-derivatives content ≤ 10%. The one- or two-component reactive PU products are manufactured using polyols and isocyanates. Reactive products based on SMP polymers are usually manufactured as a one-component system from polyols and alkoxysilane in a preliminary stage. The aqueous systems consist of (a) dispersion and are crosslinked by a dispersible isocyanate. The products fulfil manifold, often specific, functions in the construction, furnishing and repair of buildings. The product displaying the highest environmental impacts was used as a representative product for calculating the Life Cycle Assessment results (worst-case approach).

For the placing on the market in the European Union/European Free Trade Association (EU/EFTA) with the exception of Switzerland) products falling under Regulation (EU) No 305/2011 (*CPR*) need a Declaration of Performance taking into consideration either the relevant harmonised European standard or

the European Technical Assessment and the CE marking. For the application and use of the products the respective national provisions apply.

2.2 Application

Products based on polyurethane or silane-modified polymer, group 1, are used for the following applications:

Module 1: Adhesives for parquet and floor coverings
Parquet adhesives in accordance with *EN ISO 17178* for wooden and parquet floors and flooring adhesives in accordance with *EN ISO 22636* for floor coverings

Module 2: Reactive products for protecting and repairing concrete structures
Products for increasing the durability of concrete and reinforced concrete structures as well as for new concrete and for maintenance and repair work (requirements 2.1), products for structural bonding of strengthening materials to an existing concrete structure (requirements 2.2) and products for concrete injection for filling cracks, voids and interstices in concrete (requirements 2.3)

Module 3: Liquid-applied roof waterproofing kits
Reactive products for waterproofing roof constructions which are applied on site

Module 4: Reactive products for liquid-applied bridge deck waterproofing kits
Products for liquid-applied waterproofing for use on concrete bridge decks

Module 5: Screed material, floor screeds and decorative floors
Products for screed/synthetic resin screed for use in floor constructions

Module 6: Reactive products as an adhesive for tiles
Tile adhesives for internal and external tile installations on walls, floors and ceilings

Module 7: Adhesives and sealants
Reactive products for use as:
· Structural and repair adhesives
· Surface and joint sealants
Applications in accordance with the manufacturer's technical documentation/declaration of performance

Module 8: Reactive products for watertight covering kits
Products for waterproofing floors and/or walls in wet rooms inside buildings

Module 9: Reactive products for liquid-applied waterproofing
Liquid applied products for waterproofing of buildings

Module 10: Reactive products for waterproofing and/or for pre-treating mineral substrates
Applications in accordance with the manufacturer's technical documentation

Module 11*:* Liquid-applied waterproofing membranes for use beneath ceramic tiling

Module 12: One-component foam (OCF)
One component foam in a can is a one-component, self-expanding, ready to use polyurethane foam used for various construction applications. It consists of a low viscous semi-fluid in a can that leaves the can as a froth and immediately forms a polyurethane foam.
12.1 Window & External Door Sealing & Insulation:
Installing mechanically fixed external windows and doors with an OCF, as part of a system including sealants and tapes
12.2 Door Installation & Fixation:
Fixing interior doors with an OCF
12.3 General Gap Filling:
Filling of regularly and irregularly shaped spaces between at least two surfaces made of typical building materials with a one-component foam (OCF)

Module 13: Sealants for glazing
Two-component reactive sealants are to be used as the second barrier of the structural hermetic seal in insulating glass units.

Module 14: Bonded glazing sealants
One- and two-component reactive sealants are used for the bonding of insulating glass units in the window frame.

2.3 Technical Data

The density of the products is between 1,25 and 1,8 g/cm³, other relevant technical data can be found in the manufacturer's technical documentation.

Module 1: Reactive products as adhesive for parquet and floor coverings
The minimum requirements of *EN ISO 17178* and *EN ISO 22636* must be maintained.

Module 2: Reactive products for protecting and repairing concrete structures
2.1 The requirements on essential characteristics for all intended uses in accordance with *EN 1504-2*, Tables 1 and 5 must be maintained. These are:
- Permeability to CO_2 (*EN 1062-6*)
- Water vapour permeability (*EN ISO 7783-1/-2*)
- Capillary absorption and permeability to water (*EN 1062-3*)
- Adhesive strength by pull-off test (*EN 1542*)

2.2 Essential characteristics for all intended uses in accordance with *EN 1504-4*, Tables 3.1 and 3.2 (manufacturer's declaration of performance)
2.3 Requirements on essential characteristics for all intended uses in accordance with *EN 1504-5*, Table 3:
- Injectability (*EN 1771*)
- Viscosity (*EN ISO 3219*)

Further essential characteristics in accordance with the manufacturer's technical documentation/declaration of performance

Module 3: Liquid-applied roof waterproofing kits
The minimum requirements of *EAD 030350-00-0402* Liquid-applied roof waterproofing kits must be maintained. The essential characteristics are to be specified in accordance with the European Technical Assessment (ETA, specification no.).

Module 4: Reactive products for liquid-applied bridge deck waterproofing kits
The minimum requirements of *ETAG 033* Liquid-applied bridge deck waterproofing kits must be maintained. The essential characteristics are to be specified in accordance with the European Technical Assessment (ETA, specification no.).

Module 5: Screed material, floor screeds and decorative floors
The requirements on essential characteristics according to E*N 13813* 'Screed material and floor screeds – Screed materials – Properties and requirements'/ must be maintained. For synthetic resin screeds, these are:
- Bond strength (*EN 13892-8*)
- Reaction to fire (*EN 13501-1*)
Further essential characteristics in accordance with the manufacturer's technical documentation/declaration of performance

Module 6: Reactive products as an adhesive for tiles
The requirements on essential characteristics according to *EN12004*, must be maintained. These are:
-Tensile adhesion strength after dry storage (*EN 12004-2*)
-Tensile adhesion strength after water immersion (*EN 12004-2*)
-Tensile adhesion strength after heat ageing *(EN 12004-2*)
-Tensile adhesion strength after freeze/thaw cycles (*EN 12004-2*)
-Open time: Tensile strength (*EN 12004-2*)
Further essential characteristics in accordance with the manufacturer's technical documentation

Module 7: Adhesives and sealants
Performance characteristics in accordance with the manufacturer's technical documentation / declaration of performance

Module 8: Reactive products for watertight covering kits
The minimum requirements of *EAD 030352-00-0503* Liquid applied watertight covering kits for wet room floors and/or walls must be maintained. The essential characteristics are to be specified in accordance with the European Technical Assessment (ETA, specification no.).

Module 9*:* Reactive products for liquid-applied waterproofings
The minimum requirements of the test principles regarding the issuing of general building authority test certificates for liquid-applied products for waterproofing of buildings (*PG-FLK*) must be maintained. The characteristics for the proof of usability are to be specified in accordance with the test principles for granting general building authority test certificates for liquid applied polymer products for waterproofing buildings

Module 10: Reactive products for waterproofing and/or for pre-treating mineral substrates

Name	Value	Unit
Density acc. to EN ISO 2811-1	700 - 1800	kg/m³
Shore hardness A acc. to ISO 48-4	>15	
Shore hardness D acc. to ISO 48-4	>5	
Viscosity acc. to ISO 3219-2	<100	Pas

Other performance characteristics in accordance with the manufacturer's technical documentation/declaration of performance

Module 11: Liquid-applied waterproofing membranes for use beneath ceramic tiling The minimum requirements on essential characteristics according to *EN 14891* - Liquid applied water-impermeable products for use beneath ceramic tiling - Definitions, specifications and test methods- must be maintained. These are:
- Initial tensile adhesion strength
- Tensile adhesion strength after water contact
- Tensile adhesion strength after heat ageing
- Tensile adhesion strength after freeze-thaw cycles
- Waterproofing
- Crack bridging ability

Module 12: One-Component Foams
Physical data of the one-component foam must be indicated in accordance with the respective product standards; these can include, for example:

12.1 Window & External Door Sealing & Insulation
Tensile Strength E*N 17333-4*, Movement Capability *EN 17333-4*, Curing Pressure *EN 17333-2*, Thermal conductivity *EN 17333-5*, Sound Insulation *EN ISO 717-1*, Post expansion *EN 17333-2*

12.2 Door Installation & Fixation
Shear Strength *EN 17333-4*, Tensile Strength *EN 17333-4*, Compression Strength *EN 17333-4*, Curing pressure *EN 17333-2*

12.3 General Gap Filling
Sagging *EN 17333-3* Other performance characteristics in accordance with the manufacturer's technical documents/declaration of performance.

Module 13: Sealants for glazing
Reactive sealants must comply with *EN 1279-4*
Performance characteristics in accordance with the manufacturer's technical documentation/declaration of performance

Module 14: Bonded glazing sealants
Reactive sealants must comply with *RAL-GZ 716* part 2 and *ift-Guideline VE-08/4*.
Performance characteristics in accordance with the manufacturer's technical documentation/declaration of performance

2.4 Delivery status
Liquid or pasty in containers made of tinplate or plastic packed in separate or combi-containers for the required mixing ratio. Packages containing one kg of product in different types of containers. Sealants in plastic cartridges and foil packs. Typical container sizes contain 10 to 25 kg of material. For major works, vats containing approx. 200 kg or IBCs (intermediate bulk containers) containing 1 tonne or more are also used. The LCA is based on tinplate, plastic and wood packaging.

2.5 Base materials/Ancillary materials
Products based on polyurethane or silane-modified polymer with a VOC content ≤1 % and a castor oil/-

derivatives content ≤10 % usually comprise a reactive polymer and a crosslinking system. The polymer component contains polyether and/or polyester polyols. Crosslinking takes place after installation on site. In the case of two-component systems, this involves the use of pre-polymers and polymers based on typically Methylene diphenyl diisocyanate (MDI), Toluene diisocyanate (TDI), Hexamethylene diisocyanate (HDI) or Isophorone diisocyanate (IPDI). The resin mixing ratio is adjusted according to the stoichiometric requirements. Crosslinking starts directly after the components have been mixed. There are also one-component reactive polymer formulations based on PU or SMP which crosslink in the presence of moisture. They comprise prepolymers based on e.g. MDI, TDI, HDI, IPDI or those with alkoxy-silane groups in the case of SMP formulations. In formulations with aqueous dispersions, dispersible isocyanates are used for crosslinking. The formulations can contain auxiliary materials such as accelerators, catalysts, wetting agents, foam regulators and viscosity regulators for fine-tuning the product features. Typically, the products covered by this EPD contain the following ranges of base materials and auxiliaries:
Polyol component: up to approx. 50 %
Crosslinking component: up to approx. 95 %
SMP component: up to approx. 80 %
Plasticiser: ~ 0-25 %
Additives / Pigments: ~ 0-30 %
Water: ~ 0-60 %
VOC: ≤1 % according to the *Decopaint Directive* (**mandatory**)
Castor oil and derivatives: ≤10 % **(mandatory)**

These ranges are average values and the composition of products complying with the EPD can deviate from these concentration levels in individual cases. More detailed information is available in the respective manufacturer's documentation (e.g. product data sheets).
Note: For companies to declare their products within the scope of this EPD it is not sufficient to simply comply with the product composition shown above. The application of this EPD is only possible for member companies of DBC, EFCC, FEICA, and IVK member associations and only for specific formulations with a total score below the declared maximum score for a product group according to the associated guidance document.

1. substances from the "Candidate List of Substances of Very High Concern for Authorisation" (SVHC)
If this product contains substances listed in the candidate list (latest version) exceeding 0.1 percentage by mass, the relevant information can be found in the safety data sheet of the relevant product covered by this model EPD.
2. CMR substances in categories 1A and 1B
If this product contains other carcinogenic, mutagenic, reprotoxic (CMR) substances in categories 1A or 1B which are not on the candidate list, exceeding 0.1 percentage by mass, the relevant information can be found in the safety data sheet of the relevant product covered by this model EPD.
3. Biocide products added to the construction product
If this construction product contains biocide products, the active substances, information on the concentration and/or concentration range, the product type together with information on their hazardous properties are listed in the safety data sheet of the respective product.

2.6 Manufacture
The components of the formulation are usually mixed batch-wise and packaged for delivery.

2.7 Environment and health during manufacturing
As a general rule, no other environmental protection measures other than those specified by law are necessary.

2.8 Product processing/Installation
Products based on polyurethane or silane-modified polymer, are processed by trowelling/knife-coating or rolling, pouring, spraying or injection.
Precautions for safe handling and storage (e.g. air exchange, exhaust ventilation, personal protective measures, precautions required in the handling of isocyanates, conditions for safe storage) must be observed in accordance with the information on the safety data sheet.

2.9 Packaging
A detailed description of packaging is provided in section 2.4. Empty containers and clean foils can be recycled.

2.10 Condition of use
During the use phase, products based on polyurethane or silane-modified polymer are crosslinked and essentially comprise an inert three-dimensional network. They are long-lasting products which protect our buildings in the form of adhesives, coatings or sealants as well as make an essential contribution in retaining their function and long-term value.

2.11 Environment and health during use
Option 1: Products for applications outside indoor areas with permanent stays by people
During use, the reactive products lose their reactive properties and become inert. No risks are known for water, air and soil if the products are used as designated.
Option 2: Products for applications inside indoor areas with permanent stays by people
When used in indoor areas with permanent stays by people, evidence of the emission performance of construction products in contact with indoor air must be submitted according to national requirements (see chapter 7). No further influences by emissions on the environment and health are known.

2.12 Reference service life
Cured products based on polyurethane or silane-modified polymer fulfil manifold, often specific functions in the construction or refurbishment of building structures. They decisively improve the usability of building structures and significantly extend their original service lives. The anticipated reference service life depends on the specific installation situation and the exposure associated with the product. It can be influenced by weathering as well as mechanical or chemical loads.

2.13 Extraordinary effects

Fire
Even without any special fire safety features, cured products based on polyurethane or silane-modified polymer comply with at least the requirements of *EN 13501-1* standard for fire classes E and Efl. In terms of the volumes applied, they have only a marginal influence on the fire performance characteristics (e.g. smoke gas development) of the building structure in which they have been installed. As crosslinked polyurethane systems do not melt or drip, they do not contribute towards spreading fire.

Water
Cured reactive products based on polyurethane or silane-modified polymer are chemically inert and insoluble in water. They are often used to protect building structures from harmful water ingress or the effects of flooding.

Mechanical destruction
Mechanical destruction of cured reactive products based on polyurethane or silane-modified polymer does not lead to any decomposition products which are harmful to the environment or health.

2.14 Re-use phase
According to present knowledge, no environmentally harmful effects are generally anticipated in landfilling, for example, as a result of de-construction and recycling of building materials with adherent crosslinked products. If the crosslinked products can be removed from construction products without large effort, thermal recovery is a practical recycling variant on account of their energy content. Minor adhesion is not taken into consideration during disposal. It does not interfere with the disposal/recycling of the remaining components/building materials.

2.15 Disposal
Residual material which cannot be used or recycled must be combined at a specified ratio and hardened. Hardened product residue is not special waste. Non-hardened product residue is hazardous waste. Empty, dried containers (free of drops and scraped clean) are directed to the recycling process. Residue must be directed to proper waste disposal taking into consideration the local guidelines. The following waste codes according to the European List of Waste (*2000/532/EC*) can apply:
Hardened product residue:
European Waste Calalogue (EWC) code 080112 (waste paint and varnish with the exception of that mentioned in 08 01 11)
EWC code 080410 (waste adhesives and sealants other than mentioned in 08 04 09)

2.16 Further information
More information is available on the manufacturer's product or safety data sheets and on the manufacturer's websites or on request. Valuable technical information is also available on the associations' websites.

3. LCA: Calculation rules

3.1 Declared Unit
This EPD refers to the declared unit of 1 kg of product based on polyurethane or silane-modified polymer, group 1; applied into the building with a density of 1.25 - 1.8 g/cm³ in accordance with the *IBU PCR* part B for reaction resin products.
The results of the Life Cycle Assessment provided in this declaration have been selected from the product with the highest environmental impact (worst-case scenario).
Depending on the application, a corresponding conversion factor such as the density to convert volumetric use to mass must be taken into consideration.

The Declaration type is according to *EN 15804*: Cradle to gate with options, modules C1–C3, and module D (A1–A3, C, D) and additional modules.

Declared unit

Name	Value	Unit
Declared unit	1	kg
Gross density	1.25 - 1.8	g/cm³
Conversion factor to 1 kg	-	-

3.2 System boundary
Modules A1, A2 and A3 are taken into consideration in the LCA:
- A1 Production of preliminary products
- A2 Transport to the plant
- A3 Production incl. provision of energy, production of packaging as well as auxiliaries and consumables and waste treatment
- A4 Transport to site
- A5 Installation, product applied into the building during A5 phase operations and packaging disposal. This stage considers VOC emissions during the installation phase. The declared product does not contain substances in the formulation that directly emit (as) VOC, but VOCs are generated by a chemical reaction that are occurring during this phase. The end of life for the packaging material considered is described below:
  -Incineration, for materials like plastic and wood.
  -Landfill, for inert material like metals (where used).

-C1-C2-C3-D
The building deconstruction (demolition process) takes place in the C1 module which considers energy production and consumption in terms of diesel and all the emissions connected with the fuel-burning process to run the machines. After the demolition, the product is transported to the end-of-life processing (C2 module) where all the impacts related to the transport processes are considered. For precautionary principle and as a worst-case scenario, thermal treatment is the only end-of-life scenario considered. This is modelled by the incineration process (module C3) where the product ends its life cycle.
Module D accounts for potential benefits that are beyond the defined system boundaries. Credits are generated during the incineration of wastes and related electricity produced that are occurring in the A5 module.

3.3 Estimates and assumptions
For this EPD formulation and production data defined and collected by FEICA were considered. Production

waste was assumed to be disposed of by incineration without credits as a worst-case.
An average of steel and plastic containers, and wooden pallets was considered in the LCA.

3.4 Cut-off criteria
All raw materials submitted for the formulations and production data were taken into consideration.
The manufacture of machinery, plant and other infrastructure required for the production of the products under review was not taken into consideration in the LCA.
Transport of packaging materials is excluded.

3.5 Background data
Data from the *GaBi* database SP40 (2020) was used as background data.

3.6 Data quality
Representative products were applied for this EPD and the product in the group displaying the highest environmental impact was selected for calculating the LCA results. The background data sets used are less than 4 years old.
Production data and packaging are based on details provided by the manufacturer. The formulation used for evaluation refers to a specific product.
The data quality of the background data is considered to be good.

3.7 Period under review
Representative formulations are valid for 2021.

3.8 Allocation
Mass allocation has been applied when primary data have been used and implemented into the LCA model.

3.9 Comparability
Basically, a comparison or an evaluation of EPD data is only possible if all the data sets to be compared were created according to *EN 15804* and the building context, respectively the product-specific characteristics of performance, are taken into account.

The *GaBi* database SP40 (2020) was used.

4. LCA: Scenarios and additional technical information

Characteristic product properties
Information on biogenic Carbon
The packaging material contains biogenic carbon content which is presented below.

Information on describing the biogenic Carbon Content at factory gate

Name	Value	Unit
Biogenic Carbon Content in product	0	kg C
Biogenic Carbon Content in accompanying packaging	0.016	kg C

Transport to the building site (A4)

Name	Value	Unit
Transport distance	1000	km
Gross weight	34 - 40	t
Payload capacity	27	t

Assembly (A5)

Name	Value	Unit
Other resources for packaging material	0.1	kg
Material loss	0.01	kg

Material loss regards the amount of product not used during the application phase into the building. This amount is 1% of the product, impacts related to the production of this part are charged to the A5 module. This percentage is considered as waste to disposal and impacts of its end of life have been considered in the LCA model and declared in A5.

End of life (C1-C3)

Name	Value	Unit
Collected as mixed construction waste	1	kg
Incineration	1	kg

5. LCA: Results

DESCRIPTION OF THE SYSTEM BOUNDARY (X = INCLUDED IN LCA; ND = MODULE OR INDICATOR NOT DECLARED; MNR = MODULE NOT RELEVANT)

PRODUCT STAGE			CONSTRUCTION PROCESS STAGE		USE STAGE							END OF LIFE STAGE				BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARIES
Raw material supply	Transport	Manufacturing	Transport from the gate to the site	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	X	X	ND	ND	MNR	MNR	MNR	ND	ND	X	X	X	ND	X

RESULTS OF THE LCA - ENVIRONMENTAL IMPACT according to EN 15804+A2: 1 kg of product based on polyurethane or silane modified polymer, group 1

Core Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	D
GWP-total	[kg CO_2-Eq.]	4.79E+0	5.27E-2	1.80E-1	2.79E-4	1.24E-2	2.21E+0	-9.50E-1
GWP-fossil	[kg CO_2-Eq.]	4.81E+0	5.22E-2	9.38E-2	2.66E-4	1.18E-2	2.21E+0	-9.47E-1
GWP-biogenic	[kg CO_2-Eq.]	-3.57E-2	1.52E-4	8.62E-2	1.24E-5	5.42E-4	8.82E-5	-2.23E-3
GWP-luluc	[kg CO_2-Eq.]	4.50E-3	4.22E-4	4.84E-5	6.39E-9	2.79E-7	2.08E-5	-6.66E-4
ODP	[kg CFC11-Eq.]	6.76E-9	6.27E-18	6.76E-11	2.84E-20	1.24E-18	2.62E-16	-9.93E-15
AP	[mol H^+-Eq.]	1.02E-2	1.56E-4	1.29E-4	3.60E-6	3.73E-5	1.31E-3	-1.33E-3
EP-freshwater	[kg P-Eq.]	1.93E-5	1.59E-7	1.98E-7	5.75E-11	2.51E-9	4.40E-8	-1.23E-6
EP-marine	[kg N-Eq.]	2.67E-3	6.96E-5	3.50E-5	1.63E-6	1.72E-5	6.31E-4	-3.43E-4
EP-terrestrial	[mol N-Eq.]	2.93E-2	7.80E-4	4.11E-4	1.79E-5	1.89E-4	7.26E-3	-3.68E-3
POCP	[kg NMVOC-Eq.]	9.47E-3	1.38E-4	7.20E-3	4.91E-6	3.39E-5	1.62E-3	-9.87E-4
ADPE	[kg Sb-Eq.]	8.18E-6	3.74E-9	8.22E-8	8.06E-12	3.52E-10	4.65E-9	-1.56E-7
ADPF	[MJ]	1.05E+2	6.94E-1	1.11E+0	3.81E-3	1.66E-1	5.87E-1	-1.61E+1
WDP	[m^3 world-Eq deprived]	1.34E+0	4.66E-4	2.69E-2	5.27E-7	2.30E-5	2.17E-1	-9.86E-2

Caption	GWP = Global warming potential; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential of land and water; EP = Eutrophication potential; POCP = Formation potential of tropospheric ozone photochemical oxidants; ADPE = Abiotic depletion potential for non-fossil resources; ADPF = Abiotic depletion potential for fossil resources; WDP = Water (user) deprivation potential

RESULTS OF THE LCA - INDICATORS TO DESCRIBE RESOURCE USE according to EN 15804+A2: 1 kg of product based on polyurethane or silane modified polymer, group 1

Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	D
PERE	[MJ]	6.67E+0	3.90E-2	6.65E-1	1.20E-5	5.25E-4	8.23E-2	-3.52E+0
PERM	[MJ]	5.85E-1	0.00E+0	-5.85E-1	0.00E+0	0.00E+0	0.00E+0	0.00E+0
PERT	[MJ]	7.26E+0	3.90E-2	7.99E-2	1.20E-5	5.25E-4	8.23E-2	-3.52E+0
PENRE	[MJ]	8.33E+1	6.95E-1	1.63E+0	3.81E-3	1.67E-1	2.21E+1	-1.61E+1
PENRM	[MJ]	2.20E+1	0.00E+0	-5.20E-1	0.00E+0	0.00E+0	-2.15E+1	0.00E+0
PENRT	[MJ]	1.05E+2	6.95E-1	1.11E+0	3.81E-3	1.67E-1	5.87E-1	-1.61E+1
SM	[kg]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
RSF	[MJ]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
NRSF	[MJ]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
FW	[m^3]	4.03E-2	4.52E-5	7.22E-4	2.16E-8	9.41E-7	5.11E-3	-4.08E-3

Caption	PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water

RESULTS OF THE LCA – WASTE CATEGORIES AND OUTPUT FLOWS according to EN 15804+A2: 1 kg of product based on polyurethane or silane modified polymer, group 1

Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	D
HWD	[kg]	1.12E-5	3.23E-8	1.12E-7	3.70E-13	1.62E-11	3.34E-10	-6.41E-9
NHWD	[kg]	1.66E-1	1.06E-4	4.75E-2	3.90E-7	1.70E-5	1.11E-2	-7.44E-3
RWD	[kg]	2.34E-3	8.60E-7	2.54E-5	4.09E-9	1.79E-7	2.37E-5	-1.20E-3
CRU	[kg]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
MFR	[kg]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
MER	[kg]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
EEE	[MJ]	0.00E+0	0.00E+0	2.12E-1	0.00E+0	0.00E+0	0.00E+0	0.00E+0
EET	[MJ]	0.00E+0	0.00E+0	3.86E-1	0.00E+0	0.00E+0	0.00E+0	0.00E+0

Caption	HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported electrical energy; EEE = Exported thermal energy

RESULTS OF THE LCA – additional impact categories according to EN 15804+A2-optional: 1 kg of product based on polyurethane or silane modified polymer, group 1

Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	D
PM	[Disease Incidence]	ND	ND	ND	ND	ND	ND	ND
IRP	[kBq U235-Eq.]	ND	ND	ND	ND	ND	ND	ND
ETP-fw	[CTUe]	ND	ND	ND	ND	ND	ND	ND
HTP-c	[CTUh]	ND	ND	ND	ND	ND	ND	ND
HTP-nc	[CTUh]	ND	ND	ND	ND	ND	ND	ND
SQP	[-]	ND	ND	ND	ND	ND	ND	ND

Caption	PM = Potential incidence of disease due to PM emissions; IR = Potential Human exposure efficiency relative to U235; ETP-fw = Potential comparative Toxic Unit for ecosystems; HTP-c = Potential comparative Toxic Unit for humans (cancerogenic); HTP-nc = Potential comparative Toxic Unit for humans (not cancerogenic); SQP = Potential soil quality index

Potential Human exposure efficiency relative to U235, Disclaimer 1 – This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure or radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, radon and (from) some construction materials is also not measured by this indicator.

ADP minerals & metals, ADP fossil, WDP, ETF-fw, HTP-c, HTP-nc, SQP, Disclaimer 2 – The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experience with the indicator.

Additional environmental impact indicators (suggested by *EN15804*, table 4) are not declared in the EPD. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high and as there is limited experience with the indicator (see ILCD classification in EN 15804, table 5). For this reason, results based on these indicators are not considered suitable for a decision-making process and are thus not declared in the EPD.

6. LCA: Interpretation

The majority of impacts are associated with the production phase (A1-A3). The most significant contribution to the production phase impacts is the upstream production of raw materials as the main driver. Another substantial contributor in the production phase, in the category of Abiotic depletion potential for nonfossil resources (ADPminerals& metals), is the steel sheet used as a packaging material. Emissions associated with the manufacturing of products also have some influence on the Formation potential of tropospheric ozone (POCP) in the production phase. In all EPDs, CO_2 is the most important contributor to Global Warming Potential (GWP). For the Acidification Potential (AP), NOx and SO_2 contribute the largest share. In some cases, HCl in water also impacts AP due to the use of TiO_2 as a pigment.
The majority of life cycle energy consumption takes place during the production phase (A1-A3). Significant contributions to Primary Energy Demand – Non-renewable (PENRT) come from the energy resources used in the production of raw materials. The largest contributor to Primary Energy Demand – Renewable (PERT) impacts comes from the consumption of renewable energy resources required for the generation and supply of electricity. It should be noted that Primary Energy Demand – Renewable (PERT) generally represents a small percentage of the production phase primary energy demand with the bulk of the demand coming from non-renewable energy resources.
Transportation to the construction site (A4) and the installation process (A5) make a low contribution to all impacts.
The installation phase influences mainly the Photochemical ozone formation indicator, due to the emission of VOC during the operations. These emissions are not directly related to the pre-products in the resins, but they are related to the reaction products between pre-products and air components (water and oxygen).
The end-of-life phases influence climate change indicators, due to the incineration processes occurring in the C3 module, the process used for modelling the thermal treatment process of the resin.

7. Requisite evidence

VOC
Special tests and evidence have not been carried out or provided within the framework of drawing up this Model EPD. Some member states require special documentation on VOC emissions into indoor air for specific areas of application. This documentation, as well as documentation for voluntary VOC labelling, has to be provided separately and is specific for product in question.

Evidence pertaining to VOC emissions shall show
- either an attestation of compliance with,
- or documentation of test data that are required in any of the existing regulations or in any of the existing voluntary labelling programs for low-emitting products, as far as these

(1) include limits for the parameters TVOC, TSVOC, carcinogens, formaldehyde, acetaldehyde, LCI limits for individual substances (including but not limited to the European list of harmonized LCIs), and the R value;
(2) base their test methods on *EN 16516*;
(3) perform testing and apply the limits after 28 days of storage in a ventilated test chamber, under the conditions specified in *EN 16516*; some regulations

and programs also have limits after 3 days, on top of the 28 days limits;
(4) express the test results as air concentrations in the European Reference Room, as specified in *EN 16516*.

Examples of such regulations are the *Belgian Royal Decree C-2014/24239*, or the *German AgBB/* ABG. Examples of such voluntary labelling programs are *EMICODE*, *Blue Angel* or *Indoor Air Comfort*.

Relevant test results shall be produced either by an *ISO 17025* accredited commercial test lab or by a qualified internal test lab of the manufacturer.
Examples for the applied limits after 28 days of storage in a ventilated test chamber are:
- TVOC: 1000 µg/m³
- TSVOC: 100 µg/m³
- Each carcinogen: 1 µg/m³
- Formaldehyde: 100 µg/m³
- LCI: different per substance involved
- R value: 1 (meaning that, in total, 100 % of the combined LCI values must not be exceeded).

Informative Annexes (2 tables):
Table 1 shown below is an overview of the most relevant regulations and specifications as of October 2021, as regards requirements after 3 days of storage in a ventilated test chamber.
Table 2 provides an overview of the most relevant regulations and specifications as of October 2021, as regards requirements after 28 days of storage in a ventilated test chamber. Some details may be missing in the table due to lack of space. Values given represent maximum values/limits.

	TVOC µg/m³	Sum of carcinogens. C1A,CA2 µg/m³	Formaldehyde µg/m³	Acetaldehyde µg/m³	Sum of Form- and Acetaldehyde
German AgBB/ABG regulation	10 000	10	-/-	-/-	-/-
Belgian regulation	10 000	10	-/-	-/-	-/-
EMICODE EC1	1 000	10	50	50	50 ppb
EMICODE EC1 PLUS	750	10	50	50	50 ppb

	TVOC µg/m³	TSVOC µg/m³	Each carcinogen C1A,CA2 µg/m³	Formalde-hyde µg/m³	Acetalde-hyde µg/m³	LCI	R value	Specials	Sum of non-LCI & non-identified µg/m³
Belgian regulation	1000	100	1	100	200	Belgian list	1	Toluene 300 µg/m³	-/-
French regulations class A+	1000	-/-	-/-	10	200	-/-	-/-	List of 8 VOCs, 4 CMR	-/-
French regulations class A	1500	-/-	-/-	60	300	-/-	-/-	List of 8 VOCs, 4 CMR	-/-
French regulations class B	2000	-/-	-/-	120	400	-/-	-/-	List of 8 VOCs, 4 CMR	-/-
French regulations class C	>2000	-/-	-/-	>120	>400	-/-	-/-	List of 8 VOCs, 4 CMR	-/-
German DIBt/AgBB regulation	1000	100	1	100	300	German AgBB list	1	-/-	100
EMICODE EC1	100	50	1	(after 3 days)	(after 3 days)	-/-	-/-	-/-	-/-
EMICODE EC1 PLUS	60	40	1	(after 3 days)	(after 3 days)	German AgBB list	1	-/-	40
Finnish M1, sealants	20	-/-	1	10	300	EU LCI list	-/-	Ammonia, odour	-/-
Finnish M1, adhesives	200 µg/m²h	-/-	5 µg/m²h	50 µg/m²h	300	EU LCI list	-/-	Ammonia, odour	-/-

8. References

ETAG 033
Liquid applied bridge deck waterproofing kits **ISO 48-4**

ISO 48-4:2018, Rubber, vulcanized or thermoplastic - Determination of hardness- Part 4: Indentation hardness by durometer method (Shore hardness)

EN ISO 717-1
EN ISO 717-1:2020 Acoustics - Rating of sound insulation in buildings and of building elements - Part 1: Airborne sound insulation

EN 1062-3
EN 1062-3:2008-04, Paints and varnishes - Coating materials and coating systems for exterior masonry and concrete - Part 3: Determination of liquid water permeability

EN 1062-6
EN 1062-6:2002-10, Paints and varnishes - Coating materials and coating systems for exterior masonry and concrete - Part 6: Determination of carbon dioxide permeability

EN 1279-4
EN 1279-4:2002 Glass in building - Insulating glass units - Part 4: Methods of test for the physical attributes of edge seals

EN 1504-2
EN 1504-2:2004-12, Products and systems for the protection and repair of concrete structures - Definitions, requirements, quality control and evaluation of conformity - Part 2: Surface protection systems for concrete

EN 1504-4
EN 1504-4:2004-11, Products and systems for the protection and repair of concrete structures - Definitions, requirements, quality control and evaluation of conformity- Part 4: Structural bonding

EN 1504-5
EN 1504-5:2004-12, Products and systems for the protection and repair of concrete structures - Definitions, requirements, quality control and evaluation of conformity - Part 5: Concrete injection

EN 1542
EN 1542:1999-07, Products and systems for the protection and repair of concrete structures - Test methods - Measurement of bond strength by pull-off

EN 1771
EN 1771:2004-11, Products and systems for the protection and repair of concrete structures - Test methods - Determination of injectability and splitting test

ISO 2811-1
ISO 2811-1:2016, Paints and varnishes - Determination of density - Part 1: Pycnometer method

EN ISO 3219
EN ISO 3219:1994-10, Plastics - Polymers/resins in the liquid state or as emulsions or dispersions - Determination of viscosity using a rotational viscometer with defined shear rate

ISO 3219-2
ISO 3219-2:2021, Rheology - Part 2: General principles of rotational and oscillatory rheometry

EN ISO 7783
EN ISO 7783:2019-02, Paints and varnishes - Determination of water-vapour transmission properties - Cup method

EN 12004
EN12004:2012, Adhesives for ceramic tiles

EN 12004-1
EN 12004-1:2017, Adhesives for ceramic tiles – Part 1: Requirements, assessment and verification of constancy of performance, classification and marking

EN 12004-2
EN 12004-2:2017, Adhesives for ceramic tiles - Part 2: Test methods

EN 13501-1
EN 13501-1:2018, Fire classification of construction products and building elements - Part 1: Classification using data from reaction to fire tests

EN 13813
EN 13813:2002-10, Screed material and floor screeds - Screed materials - Properties and requirements

EN 13892-8
EN 13892:2003-02, Methods of test for screed materials - Part 8: Determination of bond strength

ISO 14025
DIN EN ISO 14025:2011-10, Environmental labels and declarations — Type III environmental declarations — Principles and procedures

EN 14891
EN 14891:2012-04, Liquid applied water impermeable products for use beneath ceramic tiling - Definitions, specifications and test methods

EN 15804
EN 15804:2019+A2, Sustainability of construction works — Environmental Product Declarations — Core rules for the product category of construction products

EN 16516
EN 16516:2017
Construction products - Assessment of release of dangerous substances - Determination of emissions into indoor air

EN ISO 17025
EN ISO 17025:2018-03
General requirements for the competence of testing and calibration laboratories

EN ISO 17178
EN ISO 17178:2020-06, Adhesives - Adhesives for bonding parquet to subfloor - Test methods and minimum requirements

EN 17333-2
EN 17333-2:2020+AC:2020, Characterisation of one component foam - Part 2: Expansion characteristics

EN 17333-3
EN 17333-3:2020, Characterisation of one component foam - Part 3: Application

EN 17333-4
EN 17333-4:2020, Characterisation of one component foam - Part 4: Mechanical strength

EN 17333-5
EN 17333-5:2020, Characterisation of one component foam - Part 5: Insulation

EN ISO 22636
EN ISO 22636:2020, Adhesives - Adhesives for floor coverings - Requirements for mechanical and electrical performance

EAD 030350-00-0402
EAD 030350-00-0402:2018-08**,** Liquid Applied Roof Waterproofing Kits

EAD 030352-00-0503
EAD 030352-00-0503:2019-01, Liquid applied watertight covering kits for wet room floors and/or walls

2000/532/EC
Commission decision dated 3 May 2000 replacing decision 94/3/EC on a waste directory in accordance with Article 1 a) of Council Directive 75/442/EEC on waste and Council decision 94/904/EC on a directory of hazardous waste in terms of Article 1, paragraph 4 of Directive 91/689/EEC on hazardous waste

Belgian Royal Decree C-2014/24239
Belgisch Staatsblad 8 MEI 2014, p. 60603. — Koninklijk besluit tot vaststelling van de drempelniveaus voor de emissies naar het binnenmilieu van bouwproducten voor bepaalde geoogde gebruiken

Blue Angel
Environmental label organised by the federal government of Germany www.blauer-engel.de

CPR
CPR Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 laying down harmonised conditions for the marketing of construction products and repealing Council Directive 89/106/EEC

Decopaint Directive
Directive 2004/42/CE of the European Parliament and the council of 21 April 2004 on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products and amending Directive 1999/13/EC

EMICODE
EMICODE, GEV – Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e. V. (pub.).www.emicode.de

GaBi 10 software & documentation
Data base for Life Cycle Engineering LBP, University of Stuttgart and Sphera, documentation of GaBi 10 data sets http://documentation.gabi-software.com/, 2020

German AgBB
Committee for Health-related Evaluation of Building Products: health-related evaluation of emissions of volatile organic compounds (VOC and SVOC) from building products; status: June 2012 www.umweltbundesamt.de/produkte/bauprodukte/agbb.htm

IBU 2021
Institut Bauen und Umwelt e.V.: General Instructions for the EPD programme of Institut Bauen und Umwelt e.V. EPD programme. Version 2.0. Berlin: Institut Bauen und Umwelt e.V., 2021 www.ibu-epd.com

ift-Guideline VE-08/4
ift-Guideline VE-08/4:2017, Beurteilungsgrundlage für geklebte Verglasungssysteme

Indoor Air Comfort
Product certification by Eurofins, Hamburg, Germany www.eurofins.com

PCR Part A
Product Category Rules for Building-Related Products and Services, Part A: Calculation Rules for the Life Cycle Assessment and Requirements on the Project report, Version 1.1, Institut Bauen und Umwelt e.V., 2021-01

PCR Part B
Product Category Rules for Construction Products, Part B: Reaction resin products, Institut Bauen und Umwelt e.V., 2019-01

RAL-GZ 716
RAL-GZ 716:2019-04 part 2, Kunststoff-Fensterprofilsysteme - Gütesicherung

REACH
Directive (EG) No. 1907/2006 of the European Parliament and of the Council dated 18 December 2006 on the registration, evaluation, approval and restriction of chemical substances (REACH), for establishing a European Agency for chemical substances, for amending Directive 1999/45/EC and for annulment of Directive (EEC) No. 793/93 of the Council, Directive (EC) No. 1488/94 of the Commission, Guideline 76/769/EEC of the Council and Guidelines 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC of the Commission.

Publisher
Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

Tel +49 (0)30 3087748- 0
Fax +49 (0)30 3087748- 29
Mail info@ibu-epd.com
Web **www.ibu-epd.com**

Programme holder
Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

Tel +49 (0)30 - 3087748- 0
Fax +49 (0)30 – 3087748 - 29
Mail info@ibu-epd.com
Web **www.ibu-epd.com**

Author of the Life Cycle Assessment
Sphera Solutions GmbH
Hauptstraße 111- 113
70771 Leinfelden-Echterdingen
Germany

Tel +49 711 341817-0
Fax +49 711 341817-25
Mail info@sphera.com
Web **www.sphera.com**

Owner of the Declaration
Industrieverband Klebstoffe e.V
Völklinger Straße 4
40219 Düsseldorf
Germany

Tel +49 (0)211 67931-10
Fax +49 (0)211 67931-33
Mail info@klebstoffe.com
Web **www.klebstoffe.com**

FEICA - Association of the European Adhesive and Sealant Industry
Avenue E. van Nieuwenhuyse 2
B-1160 Brussels
Belgium

Tel +32 (0)267 673 20
Fax +32 (0)267 673 99
Mail info@feica.eu
Web **www.feica.eu**

EFCC - European Federation for Construction Chemicals
Boulevard du Triomphe 172
1160 Brussels
Belgium

Tel +32289720-39
Fax +32289720-37
Mail info@efcc.be
Web **www.efcc.eu**

Deutsche Bauchemie e.V.
Mainzer Landstr. 55
60329 Frankfurt
Germany

Tel +49 (0)69 2556-1318
Fax +49 (0)69 2556-1319
Mail info@deutsche-bauchemie.de
Web **www.deutsche-bauchemie.de**

Nachhaltigkeitsdatenblatt

REVOPUR® TC415

1-komponentiges, lösemittelfreies Bindemittel für Marmorkiesel

Nachhaltige Merkmale:

- Weichmacherfrei
- Lösemittelfrei



Das EMICODE Siegel EC1 Plus ist die Premiumklasse, die die Grenze des technisch Machbaren beschreibt. Ausschließlich Produkte, die die strengen Emissionsansprüche erfüllen, dürfen mit dem EMICODE-Siegel gekennzeichnet werden.

Prüfparameter	Ergebnis	Anforderung	Anforderung erfüllt
Gesamtkonzentration flüchtiger organischer Stoffe ohne Berücksichtigung der Essigsäure (TVOC DIN EN 16516)	< 5 µg/m³	≤ 60 µg/m³	Ja, EC 1 Plus
Gesamtkonzentration schwerflüchtiger organischer Stoffe (TSVOC DIN EN 16516)	< 5 µg/m³	≤ 40 µg/m³	Ja, EC 1 Plus

Wir sorgen für maximale Transparenz unserer Produkte im DGNB Navigator. Zusätzlich erfüllt REVOPUR® TC415 folgende Kriterien:

Kriterium: ENV1.2 Risiken für die lokale Umwelt
Kriterienmatrix: DGNB Neubau 2023
Einstufung: Qualitätsstufe 4/4

FRANKEN SYSTEMS GmbH | Südstraße 3 | 97258 Gollhofen | T +49 9339 988 69 – 0
F +49 9339 988 69 – 99 | E info@franken-systems.de | www.franken-systems.de

Um eine EPD zu erhalten wird der komplette Lebenszyklus von REVOPUR® TC415 betrachtet. Aus diesem Grund bildet die EPD eine wichtige Grundlage für die Bewertung der Nachhaltigkeit von Bauwerken.

Mit der Deklaration unserer Produkte auf dem österreichischen Web-Portal „baubook“ für Bauprodukte, Bauteile und Tools, soll das ökologische und gesunde Bauen zukünftig noch einfacher funktionieren.

Das QNG ready Siegel des Sentinel Haus Instituts kennzeichnet Produkte, welche für die KfW-Förderung „Klimafreundliches Wohngebäude/Nichtwohngebäude" qualifiziert sind.
Dieses Produkt ist im Portal für das gesunde und nachhaltige Betreiben, Bauen, Sanieren und Renovieren von Gebäuden gelistet.

Die EU-Taxonomie klassifiziert wirtschaftliche Aktivitäten und Produkte nach ihren Umweltauswirkungen. Auf der Produktebene gibt es gemäß der EU-Verordnung klare Anforderungen zu Formaldehyd und flüchtigen organischen Verbindungen (VOC).

Kriterium:	DNSH – Vermeidung und Verminderung der Umweltverschmutzung
Betrachtete Stoffe:	Stoffe nach Anlage C
Bewertung:	EU-Taxonomie konform

Alle Dateien und Informationen aus einer Hand!
Mit Scannen dieses QR-Codes öffnet sich das Portal:

ausschreiben.de/catalog/frankensystems

Hier sind die Produkte sowie gesamte Abdichtungs- und Beschichtungssysteme der Franken Systems GmbH transparent und übersichtlich aufgelistet.

Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e.V.

GEV EMICODE®

Lizenzerteilung zur Führung des EMICODE

Lizenzierungs-Nummer:	12630/01.09.20
Für den Artikel	REVOPUR TC 415
der Firma	FRANKEN SYSTEMS GmbH
wird auf Antrag vom	09.11.2020

unter Bezugnahme auf die Einstufung gemäß den nach § 10 der GEV-Zeichensatzung festgelegten Richtlinien

namens der Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e.V. für den oben genannten Artikel nach § 5 Abs. 4 der GEV-Zeichensatzung die Lizenz zur Führung des GEV-Zeichens

GEV-EMICODE® EC 1 PLUS sehr emissionsarm

erteilt. Damit erfüllt dieser Artikel die rückseitig aufgeführten Kriterien.
Die Firma ist ordentliches Mitglied der GEV.

OM193 05.08.2025
gültig bis 05.08.2030

Der Geschäftsführer
Gemeinschaft Emissionskontrollierte Verlegewerkstoffe,
Klebstoffe und Bauprodukte e.V.
Völklinger Straße 4 · D-40219 Düsseldorf

Hinweise zu den Voraussetzungen über die Vergabe der Lizenz für den EMICODE

Das gemäß vorseitiger Lizenz eingestufte Produkt hat nach der Satzung und den Richtlinien des Technischen Beirats der GEV u.a. den folgenden Kriterien zu genügen:

- Das Produkt entspricht allen gesetzlichen Bestimmungen, insbesondere denen des Chemikalienrechtes und seiner Verordnungen.
- Das Produkt ist nach der Definition der TRGS 610 lösemittelfrei, sofern es sich nicht um ein Oberflächenprodukt handelt. Soweit es einer Produktgruppe nach GISCODE zuzuordnen ist, wird diese angegeben.
- Für das Produkt wird ein Sicherheitsdatenblatt nach lokalem Recht in der jeweils aktuellen Fassung erstellt.
- Krebserregende, erbgutverändernde oder fruchtschädigende Stoffe der Kategorien 1A und 1B werden dem Produkt bei der Herstellung nicht aktiv zugesetzt (Ausnahmeregelungen siehe Kapitel 3.1.2.2 der GEV-Einstufungskriterien).
- Die Prüfung des Produktes erfolgt nach der definierten „GEV-Prüfmethode“. Die VOC-Bestimmung wird dabei in einer Prüfkammer nach dem Tenax-Thermodesorptions-Verfahren mit nachgeschalteter GC/MS-Analyse durchgeführt.
- Die Einstufung in EMICODE-Klassen erfolgt entsprechend den nachstehenden Bezeichnungen und TVOC/TSVOC-Konzentrationsbereichen. Zur Produktkennzeichnung ist die zutreffende EMICODE-Klasse zu verwenden:

1) Verlegewerkstoffe, Klebstoffe und Bauprodukte

Parameter	EC 1 PLUS	EC 1	EC 2
	max. zulässige Konzentration [µg/m³]		
TVOC nach 3 Tagen	≤ 750	≤ 1000	≤ 3000
TVOC nach 28 Tagen	≤ 60	≤ 100	≤ 300
TSVOC nach 28 Tagen	≤ 40	≤ 50	≤ 100
R-Wert basierend auf AgBB-NIK-Werten nach 28 Tagen	≤ 1	≤ 1	-
Summe der nicht bewertbaren VOC	≤ 40	-	-
Formaldehyd nach 3 Tagen	≤ 50	≤ 50	≤ 50
Formaldehyd nach 28 Tagen	≤ 10	≤ 10	≤ 10
Acetaldehyd nach 3 Tagen	≤ 50	≤ 50	≤ 50
Summe von Form- und Acetaldehyd	≤ 0,05 ppm	≤ 0,05 ppm	≤ 0,05 ppm
Summe von flüchtigen K1A/K1B-Stoffen nach 3 Tagen	< 10	< 10	< 10
Jeder flüchtige K1A/K1B-Stoff nach 28 Tagen	< 1	< 1	< 1

2) Oberflächenbehandlungsmittel für Parkett, mineralische Böden und elastische Bodenbeläge

Parameter	EC 1 PLUS	EC 1	EC 2
	max. zulässige Konzentration [µg/m³]		
Summe TVOC + TSVOC nach 28 Tagen	≤ 100 davon max. 40 SVOC	≤ 150 davon max. 50 SVOC	≤ 400 davon max. 100 SVOC
R-Wert basierend auf AgBB-NIK-Werten nach 28 Tagen	≤ 1	≤ 1	-
Summe der nicht bewertbaren VOC	≤ 40	-	-
Formaldehyd nach 3 Tagen	≤ 50	≤ 50	≤ 50
Formaldehyd nach 28 Tagen	≤ 10	≤ 10	≤ 10
Acetaldehyd nach 3 Tagen	≤ 50	≤ 50	≤ 50
Summe von Form- und Acetaldehyd	≤ 0,05 ppm	≤ 0,05 ppm	≤ 0,05 ppm
Summe von flüchtigen K1A/K1B-Stoffen nach 3 Tagen	< 10	< 10	< 10
Jeder flüchtige K1A/K1B-Stoff nach 28 Tagen	< 1	< 1	< 1

FRANKEN SYSTEMS GmbH
Südstraße 3
97258 Gollhofen

Ansprechpartner
Volker Kramer

E-Mail
v.kramer@franken-systems.de

Telefon
+49 9339 98868-80

Gollhofen, den 29.07.2025

Herstellerbestätigung FRANKEN SYSTEMS GmbH – Sentinel-Haus Institut

Sehr geehrte Damen und Herren,

für die Produkte:

- REVOPUR® WP200
- REVOPUR® WP240
- FRANKOSIL® 1K PLUS
- FRANKOSIL® 1K PLUS Graphit
- FUGENLIQUID JF200 R
- REVOPUR® TC415

erklären wir das folgende Kriterien zutreffen:

Die oben genannten Produkte enthalten keine Chlorparaffine, TCEP, PBB und PBDE. Die Produkte überschreiten somit den Grenzwert von ≤ 0,10 % nicht.

Mit freundlichen Grüßen aus dem Frankenland

i. V. Volker Kramer
FRANKEN SYSTEMS GmbH