SENTINEL HOLDING
INSTITUT

SHI PRODUCT PASSPORT

Find products. Certify buildings.

SHI Product Passport No.:

15171-10-1002

JACKODUR EVO

Product group: Insulation - Roof and facade - Shell construction / Basement

JACKON Insulation GmbH
Ritzlebener Str. 1
39619 Arendsee OT Mechau

Product qualities:

- SHI Product Assessment 2024 ✓
- QNG Qualitätssiegel Nachhaltiges Gebäude ✓
- DGNB NEW CONSTRUCTION 2023.2 ✓
- DGNB NEW CONSTRUCTION 2023 ✓
- DGNB NEW CONSTRUCTION 2018 ✓
- BNB-BN NEUBAU V2015 ✓
- EU TAXONOMY ✓
- BREEAM DE NEUBAU 2018 ✓
- LEED v4.1 (outside US) ✓

CERTIFIED SUSTAINABLE PRODUCT
SHI PRODUCT PASSPORT
SENTINEL HOLDING INSTITUT
www.sentinel-holding.eu

Köttner

Helmut Köttner
Scientific Director
Freiburg, 26 August 2026

Product:
JACKODUR EVO

SHI Product Passport no.:
15171-10-1002

JACKON by BEW

Contents

SHI Product Assessment 2024	1
QNG - Qualitätssiegel Nachhaltiges Gebäude	2
DGNB New Construction 2023.2	3
DGNB New Construction 2023	4
DGNB New Construction 2018	7
BNB-BN Neubau V2015	8
EU taxonomy	9
BREEAM DE Neubau 2018	10
LEED v4.1	11
Product labels	12
Legal notices	13
Technical data sheet/attachments	12

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar

SGS TÜV SAAR

SENTINEL HOLDING
INSTITUT

Product:
JACKODUR EVO

SHI Product Passport no.:
15171-10-1002

JACKON by BEWI

SHI Product Assessment 2024

Since 2008, Sentinel Holding Institut GmbH (SHI) has been establishing a unique standard for products that support healthy indoor air. Experts carry out independent product assessments based on clear and transparent criteria. In addition, the independent testing company SGS regularly audits the processes and data accuracy.

Criteria	Product category	Harmful substance limit	Assessment
SHI Product Assessment	Insulation materials	TVOC ≤ 300 µg/m³ Formaldehyd ≤ 24 µg/m³	Indoor Air Quality Certified
Valid untill: 05 June 2028			

SENTINEL HOLDING
INSTITUT

Product:
JACKODUR EVO

SHI Product Passport no.:
15171-10-1002

JACKON by BEWI

QNG - Qualitätssiegel Nachhaltiges Gebäude

The Qualitätssiegel Nachhaltiges Gebäude (Quality Seal for Sustainable Buildings), developed by the German Federal Ministry for Housing, Urban Development and Building (BMWSB), defines requirements for the ecological, socio-cultural, and economic quality of buildings. The Sentinel Holding Institut evaluates construction products in accordance with QNG requirements for certification and awards the QNG ready label. Compliance with the QNG standard is a prerequisite for eligibility for the KfW funding programme. For certain product groups, the QNG currently has no specific requirements defined. Although classified as not assessment-relevant, these products remain suitable for QNG-certified projects.

Criteria	Pos. / product group	Considered substances	QNG assessment
3.1.3 Schadstoffvermeidung in Baumaterialien	12.1 Rigid plastic foam insulation boards and spray foams	Halogenated propellants / SVHC: HBCD, TCEP / emissions	QNG ready
Verification: Herstellererklärung 11.05.26			

SENTINEL HOLDING
INSTITUT

Product:
JACKODUR EVO

SHI Product Passport no.:
15171-10-1002

JACKON by BEWI

DGNB New Construction 2023.2

Außenanwendung

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact	40 Dämmplatten aus Kunststoffschäumen (innen und außen)	Gehalt an gefährlichen Stoffen: TCEP (SVHC), Halogenierte Treibmittel	Quality level 4
Verification: Herstellererklärung 11.05.26			

Innenanwendung

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact			Not relevant for assessment
Verification: Nur XPS-Dämmplatten an der Gebäudehülle außen sind bewertungsrelevant.			

SENTINEL HOLDING
INSTITUT

Product:
JACKODUR EVO

SHI Product Passport no.:
15171-10-1002

JACKON by BEWI

DGNB New Construction 2023

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings. The 2023 version sets high standards for ecological, economic, socio-cultural, and functional aspects throughout the entire life cycle of a building.

Außenanwendung

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 29.05.2025 (4th edition)	40 Synthetic foam insulation for buildings	Halogenated propellants / SVHC: HBCD, TCEP / emissions	Quality level 4
Verification: Herstellererklärung 11.05.26			

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 03.05.2024 (3rd edition)	40 Synthetic foam insulation for buildings and building services	Halogenated propellants	Quality level 4
Verification: Herstellererklärung 11.05.26			

Innenanwendung

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 03.05.2024 (3rd edition)	not applicable		Not relevant for assessment
Verification: Nur XPS-Dämmplatten an der Gebäudehülle außen sind bewertungsrelevant.			

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 29.05.2025 (4th edition)	not applicable		Not relevant for assessment
Verification: Nur XPS-Dämmplatten an der Gebäudehülle außen sind bewertungsrelevant.			

Criteria	Assessment
ENV1.1 Climate action and energy (*)	May positively contribute to the overall building score
Verification: Es liegt eine EPD vor. - Eine effizientere Energienutzung im Gebäude wird durch den Wärmedämmstoff hervorgerufen. - Das Produkt besteht zu einem Teil aus recyceltem (CO2-reduzierten) PS	

Criteria	Assessment
ECO1.1 Life cycle cost (*)	May positively contribute to the overall building score
Verification: Das Produkt trägt durch die Reduktion der Energiekosten zur Senkung der Lebenszykluskosten bei.	

Criteria	Assessment
ECO2.6 Climate resilience (*)	May positively contribute to the overall building score
Verification: Das Produkt ist ein Wärmedämmstoff und trägt damit zum Kühl- oder Hitzeschutz des Gebäude bei.	

Criteria	Assessment
SOC1.1 Thermal comfort (*)	May positively contribute to the overall building score
Verification: Das Produkt ist eine Wärmedämmstoff und kann damit die Innenraumtemperatur mit regulieren.	

Criteria	Assessment
SOC1.2 Indoor air quality (*)	May positively contribute to the overall building score
Verification: Das Produkt entspricht dem AgBB Schema	

Criteria	Assessment
TEC1.3 Quality of the building envelope (*)	May positively contribute to the overall building score
Verification: Das Wärmedämmprodukt minimiert den Wärme-/Kältedurchgang an der Gebäudehülle.	

SENTINEL HOLDING
INSTITUT

Product:
JACKODUR EVO

SHI Product Passport no.:
15171-10-1002

JACKON by BEWI

DGNB New Construction 2018

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings.

Außenanwendung

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact	40 Synthetic insulating materials for buildings and building services	Halogenated propellants	Quality level 4
Verification: Herstellererklärung 11.05.26			

Innenanwendung

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact	not applicable	not applicable	Not relevant for assessment

SENTINEL HOLDING
INSTITUT

Product:
JACKODUR EVO

SHI Product Passport no.:
15171-10-1002

JACKON by BEWI

BNB-BN Neubau V2015

The Bewertungssystem Nachhaltiges Bauen (Assessment System for Sustainable Building) is a tool for evaluating public office and administrative buildings, educational facilities, laboratory buildings, and outdoor areas in Germany. The BNB was developed by the former Federal Ministry for the Environment, Nature Conservation, Building and Nuclear Safety (BMUB) and is now overseen by the Federal Ministry for Housing, Urban Development and Building (BMWSB).

Außenanwendung

Criteria	Pos. / product type	Considered substance group	Quality level
1.1.6 Risiken für die lokale Umwelt	36a Mineral and non-mineral external wall insulations (external wall paints see Position 6, plasters see Position 35)	Biocides / hazardous substances / halogenated blowing agents	Quality level 3
Verification: Herstellererklärung 11.05.26			

Innenanwendung

Criteria	Pos. / product type	Considered substance group	Quality level
1.1.6 Risiken für die lokale Umwelt	36b Mineral and non-mineral interior insulations	VOC / biocides / hazardous substances / individual hazardous substances (formaldehyde) / halogenated blowing agents	Quality level 4
Verification: Herstellererklärung 11.05.26, Prüfbericht-Nr.: DE224QSX 001			

SENTINEL HOLDING
INSTITUT

Product:
JACKODUR EVO

SHI Product Passport no.:
15171-10-1002

JACKON by BEWI

EU taxonomy

The EU Taxonomy classifies economic activities and products according to their environmental impact. At the product level, the EU regulation defines clear requirements for harmful substances, formaldehyde and volatile organic compounds (VOCs). The Sentinel Holding Institut GmbH labels qualified products that meet this standard.

Außenanwendung

Criteria	Product type	Considered substances	Assessment
DNSH - Pollution prevention and control	Sonstige	Stoffe nach Anlage C	compliant
Verification: Herstellererklärung 11.05.26			

Innenanwendung

Criteria	Product type	Considered substances	Assessment
DNSH - Pollution prevention and control	Internal insulation	Stoffe nach Anlage C, Formaldehyd, Karzinogene VOC Kategorie 1A/1B	compliant
Verification: Herstellererklärung 11.05.26, Prüfbericht-Nr.: DE224QSX 001			

SENTINEL HOLDING
INSTITUT

Product:
JACKODUR EVO

SHI Product Passport no.:
15171-10-1002

JACKON by BEWI

BREEAM DE Neubau 2018

BREEAM (Building Research Establishment Environmental Assessment Methodology) is a UK-based building assessment system that evaluates the sustainability of new constructions, refurbishments, and conversions. Developed by the Building Research Establishment (BRE), the system aims to assess and improve the environmental, economic, and social performance of buildings.

Außenanwendung

Criteria	Product category	Considered substances	Quality level
Hea 02 Indoor Air Quality			Not relevant for assessment

Innenanwendung

Criteria	Product category	Considered substances	Quality level
Hea 02 Indoor Air Quality	Ceiling, wall, and acoustic and thermal insulation materials	Emissions: Formaldehyde, TVOC, TSVOC, carcinogens	Exemplary quality
Verification: Prüfbericht-Nr.: DE224QSX 001			

SENTINEL HOLDING
INSTITUT

Product:
JACKODUR EVO

SHI Product Passport no.:
15171-10-1002

JACKON by BEWI

LEED v4.1

LEED (Leadership in Energy and Environmental Design) is an internationally recognised building certification system developed by the U.S. Green Building Council. It is one of the most widely used sustainability standards for buildings worldwide and is particularly applied in internationally oriented projects. LEED assesses buildings holistically across categories such as energy efficiency, resource conservation, material selection, indoor environmental quality and site sustainability. Depending on the number of points achieved, projects are awarded one of the certification levels: LEED Certified, Silver, Gold or Platinum.

Außenanwendung

Criteria	Product category	Considered substances	Assessment
EQ Credit: Low-Emitting Materials			Not relevant for assessment

Innenanwendung

Criteria	Product category	Considered substances	Assessment
EQ Credit: Low-Emitting Materials	Dämmstoffe	Emissionen: Formaldehyd, VOC, Krebserregende Stoffe	compliant
Verification: Prüfbericht-Nr.: DE224QSX 001			

SENTINEL HOLDING
INSTITUT

Product:
JACKODUR EVO

SHI Product Passport no.:
15171-10-1002

JACKON by BEWI

Product labels

In the construction industry, high-quality materials are crucial for a building's indoor air quality and sustainability. Product labels and certificates offer guidance to meet these requirements. However, the evaluation criteria of these labels vary, and it is important to carefully assess them to ensure products align with the specific needs of a construction project.

This product is SHI Indoor Air Quality certified and recommended by Sentinel Holding Institut. Indoor-air-focused construction, renovation, and operation of buildings is made possible by transparent and verifiable criteria thanks to the Sentinel Holding concept.

Products bearing the Sentinel Holding Institute QNG-ready seal are suitable for projects aiming to achieve the "Qualitätssiegel Nachhaltiges Gebäude" (Quality Seal for Sustainable Buildings). QNG-ready products meet the requirements of QNG Appendix Document 3.1.3, "Avoidance of Harmful Substances in Building Materials." The KfW loan program Climate-Friendly New Construction with QNG may allow for additional funding.

EPD-Global (formerly EPD-Norge) is the Norwegian program operator for Environmental Product Declarations (EPDs). The program follows ISO 14025 and EN 15804 and ensures that EPDs for construction and industrial products are published in a consistent, verified and comparable manner. Before publication, each EPD undergoes independent third-party verification; EPD-Norge provides clear procedures, Product Category Rules (PCR/NPCR) and a public register for this purpose.

Product:
JACKODUR EVO

SHI Product Passport no.:
15171-10-1002

Legal notices

(*) These criteria apply to the construction project as a whole. While individual products can positively contribute to the overall building score through proper planning, the evaluation is always conducted at the building level. The information was provided entirely by the manufacturer.

Find our criteria here: https://www.sentinel-holding.eu/de/Themenwelten/Pr%C3%BCfkriterien%20f%C3%BCr%20Produkte

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar

Publisher

Sentinel Holding Institut GmbH
Bötzinger Str. 38
79111 Freiburg im Breisgau
Germany
Tel.: +49 761 590 481-70
info@sentinel-holding.eu
www.sentinel-holding.eu

JACKODUR® EVO 300 Standard

λ_D = 0,032 W/(m·K) für alle Dämmstoffdicken
erfüllt alle Anforderungen nach DGNB, QNG und BNB



Die Evolution der Multilayerplatten.

JACKODUR® EVO ist die neue Generation an Wärmedämmung aus extrudiertem Polystyrolschaum (XPS). Die druckfesten Dämmplatten werden umweltfreundlich produziert und enthalten als Zellinhalt Luft. Die unerreichte Langlebigkeit und die extrem einfache Verarbeitung zeichnen die Wärmedämmung aus. Die Dämmplatten werden mit der Multilayertechnik produziert, so dass bei der Verarbeitung eine sichere und schnelle einlagige Verlegung bis 400 mm Dicke gewährleistet wird.

Vorteile:

- Nennwert 0,032 W/(m·K) in allen Dicken
- umweltfreundlich und ohne halogenierte Treibmittel produziert
- Dicken 40 bis 400 mm
- sichere und schnelle einlagige Verlegung



Besonders geeignet für:

- Perimeterdämmung unter Bodenplatte (DIN 4108-10 PB-dh)
- Kelleraußenwanddämmung
- Umkehrdach (bekiest, begrünt und mit Plattenbelägen)
- Kerndämmung
- Dämmung unter Estrich

www.jackon-insulation.com

JACKON by BEWI


Technische Daten JACKODUR® EVO

Eigenschaften	Angabe / Einheit	Norm	JACKODUR® EVO 300 Standard																			
Dicke	mm		40	50	60	80	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400
Zellinhalt			Luft																			
Bemessungswert der Wärmeleitfähigkeit λ	W/(m·K)	DIN 4108-10	0,033																			
Nennwert der Wärmeleitfähigkeit λ_D	W/(m·K)	EN 13164	0,032																			
Wärmedurchlass-widerstand R_D	m²·K/W	EN 13164	1,25	1,55	1,95	2,50	3,10	3,75	4,35	5,00	5,60	6,25	6,85	7,50	8,10	8,75	9,35	10,00	10,60	11,25	11,85	12,50
Wasserdampfdiffusions-widerstandszahl μ		EN 12086	160	140	130	120	140	140	140	140	140	140	140	140	140	140	140	140	140	140	140	140
Wasseraufnahme durch Diffusion, WD(V)	Vol.-%	EN 12088	≤ 3																			
Druckspannung bei 10% Verformung oder Druckfestigkeit	kPa	EN 826	300																			
Dauerdruckfestigkeit, Kriechverhalten (50 Jahre, Stauchung < 2%)	kPa	EN 1606	-																			
Brandverhalten	Euro-klasse	EN 13501-1	E																			
Wasseraufnahme bei langzeitigem Eintauchen, WL(T)	Vol.-%	EN 12087	≤ 0,7																			
Widerstandsfähigkeit gegen Frost-Tau-Wechsel-beanspruchung, FTCD	Vol.-%	EN 12091	≤ 1																			
Dimensionsänderung bei 70°C. und 90% rel. Feuchte, DS(70/90)	%	EN 1604	≤ 5																			
Verformung bei 40 kPa Druck- und 70°C. Temperatur-beanspruchung, DLT(2)5	%	EN 1605	≤ 5																			
Anwendungsgrenz-temperatur	°C		-50 bis +75																			
Kapillarität			keine																			
Oberflächen beschaffenheit			glatt																			
Kantenausprägung			Stufenfalz																			

Wichtige Informationen für Ihre Planung finden Sie unter www.jackon-insulation.com

- Zulassungen, Prüfzeugnisse und Umweltproduktdeklaration (EPD)
- Verarbeitungshinweise
- Sicherheitsdatenblatt

JACKODUR® EVO bietet alle bewährten Eigenschaften einer XPS-Wärmedämmung: Das Material ist druckfest, maßstabil, feuchtigkeitsunempfindlich und verrottungsfest.



JACKODUR FREI HBCD FCKW HFCKW

Frei von HBCD Flammschutzmitteln sowie Flurchlorkohlen-wasserstoffe (FCKW), HFCKW- und HFKW-haltigen Treibmitteln.

JACKON Insulation GmbH
Carl-Benz-Straße 8
D-33803 Steinhagen

T +49 (0) 5204 9955 - 0
F +49 (0) 5204 9955 - 400

E info@jackodur.com
W www.jackon-insulation.com

JACKODUR® und JACKOBOARD® sind eingetragene Warenzeichen der JACKON Insulation GmbH. Irrtümer und Änderungen vorbehalten. Art.-Nr. 0000000 DE/AT/CH 03/2026

epd-global
Powered by EPD-Norway

Environmental product declaration

in accordance with ISO 14025 and EN 15804+A2

JACKODUR EVO



EPD-Global

Owner of the declaration:
BEWI ASA, Insulation and Construction

Product:
JACKODUR EVO

Declared unit:
1 m^3

This declaration is based on Product Category Rules:
CEN Standard EN 15804:2012+A2:2019 serves as core PCR.
NPCR 012:2022 Part B for Thermal insulation products

Program operator:
EPD-Global

Declaration number:
NEPD-15747-19713

Issue date:
29.05.2026

Valid to:
29.05.2031

EPD software:
LCAno EPD generator ID: 1542333

General information

Product

JACKODUR EVO

Owner of the declaration:

BEWI ASA, Insulation and Construction
Contact person: Marc Storm Andersen
Phone: +45 72157902
e-mail: marc.andersen@bewi.com

Program operator:

EPD-Global
Post Box 5250 Majorstuen, 0303 Oslo, Norway
Phone: +47 977 22 020
web: www.epd-global.com

Manufacturer:

BEWI Insulation Germany and Belgium
Europe

Declaration number:

NEPD-15747-19713

Place of production:

JACKON Insulation GmbH
Ritzlebener Str.1
39619 Arendsee, Germany

This declaration is based on Product Category Rules:

CEN Standard EN 15804:2012+A2:2019 serves as core PCR.
NPCR 012:2022 Part B for Thermal insulation products

Management system:

ISO 14001 og 9001 for all production sites

Statement of liability:

The owner of the declaration shall be liable for the underlying information and evidence. EPD-Global shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

Organisation no:

925437948

Declared unit:

1 m^3 JACKODUR EVO

Issue date:

29.05.2026

Declared unit with option:

A1, A2, A3, A4, A5, C1, C2, C3, C4, D

Valid to:

29.05.2031

Year of study:

2025

Functional unit:

1 m^2 of JACKODUR EVO with a thickness (32 mm) designed to provide a thermal resistance (R-value) = 1 m^2K/W within an expected service life for insulation materials. To convert the environmental indicators to the functional unit, the values in the tables on pages 7 to 10 must be multiplied by 0.032.

Comparability:

EPD of construction products may not be comparable if they not comply with EN 15804:2012+A2:2019 and seen in a building context.

General information on verification of EPD from EPD tools:

Independent verification of data, other environmental information and the declaration according to ISO 14025:2010, § 8.1.3 and § 8.1.4. Verification of each EPD is made according to EPD-Global's guidelines for verification and approval requiring that tools are i) integrated into the company's environmental management system, ii) the procedures for use of the EPD tool are approved by EPD-Global, and iii) the process is reviewed annually by an independent third party verifier. See Appendix G of EPD-Global's General Programme Instructions for further information on EPD tools

Development and verification of EPD:

The declaration is created using EPD tool lca.tools ver EPD2022.03, developed by LCA.no. The EPD tool is integrated in the company's management system, and has been approved by EPD-Global. NEPDT97

Developer of EPD: Mark Plate

Reviewer of company-specific input data and EPD: Martin Bendix

Verification of EPD tool:


Independent third party verification of the EPD tool, background data and test-EPD in accordance with EPD-Global's procedures and guidelines for verification and approval of EPD tools.

Third party verifier:

Elisabet Amat, GREENIZE projects

(no signature required)

Approved:



Håkon Hauan, CEO EPD-Global

Product

Product description:

Product description
JACKODUR EVO is an extruded polystyrene foam (XPS) produced according to EN 13164 and available in board shape with a density range from 28 to 33 kg/m3, 31,3 kg/m3 in average (measured). It has specifically low values of thermal conductivity. The boards can be delivered in compressive strength 300 kPa. To meet the need of various applications the boards are produced with different surfaces: with the extrusion skin, planed, grooved or with thermal embossing. JACKODUR EVO boards are supplied with different edge treatments such as butt edge, ship-lap and tongue and groove. The EPD is related to an unlaminated product only; lamination and additional product treatment are not considered. For the placing on the market of the product in the European Union/European Free Trade Association (EU/EFTA) (with the exception of Switzerland) Regulation (EU) No. 305/2011 (CPR) applies. The product needs a declaration of performance taking into consideration EN 13164 Building insulation and the CE-marking.

Product application
The variety of the performance properties of JACKODUR EVO make it suitable for use in a large number of applications such as: perimeter insulation, inverted roof insulation, insulation of pitched roofs, floor insulation including insulation of highly loaded industrial floors, insulation of thermal bridges for exterior walls, External Thermal Insulation Composite Systems (ETICS), insulation of cavity walls, agricultural building ceiling insulation, prefabricated elements e.g. building sandwich panels, insulation for building equipment and industrial installations (pipe sections, ...)

Product specification

Materials	kg	%
Expansion gas	2.14	6.42
Filler	0.134	0.4016
Flame retardant	0.333	0.9979
Fuels, fossil	0.577	1.73
Plastic - Polystyrene (PS)	21.24	63.65
Plastic - Recycled	8.94	26.80
Total	33.37	100.00

Packaging	kg	%
Packaging - Plastic	0.402	100.00
Total incl. packaging	33.77	100.00

Technical data:

Further technical information can be obtained on www.jackon-insulation.com and in the table below

Name	Value	Unit	Norm
Gross density	28 - 33	kg / m3	EN 1602
Compressive strength	0.3	N/mm2	EN 826
Tensile strength	0,1 - 0,4	N/mm2	EN 1607
Reaction to fire	E	class	EN 13501-1
Dimensional stability at 70°C and 90% relative humidity	< 5	%	EN 1605
Deformation under 40 kPa load and 70°C	< 5	%	EN 1605
Compressive creep (50 years, deformation < 2%)	130	sc kPa 3	EN 1606
Long term water absorption by total immersion	0,7	Level i %	EN 12087
Long term water absorption by diffusion	WD(V) 3	class	EN 12088
Freeze-thaw resistance	FTCD1	class	EN 12091
Water vapour diffusion resistance factor	250-80		EN 12086

Market:

Europe

Reference service life, product

A reference service life (RSL) according to ISO 15686 cannot be declared. The durability of JACKODUR EVO is normally at least as long as the lifetime of the building in which it is used
(more than 80 years).

Reference service life, building or construction works

As in the construction where it is used

LCA: Calculation rules

Declared unit:

1 m^3 JACKODUR EVO

Cut-off criteria:

All major raw materials and all the essential energy is included. The production processes for raw materials and energy flows with very small amounts (less than 1%) are not included. These cut-off criteria do not apply for hazardous materials and substances.

< 0,5%

Allocation:

The allocation is made in accordance with the provisions of EN 15804+A2. Incoming energy and water and waste production in-house is allocated equally among all products through mass allocation. Effects of primary production of recycled materials is allocated to the main product in which the material was used. The recycling process and transportation of the material is allocated to this analysis.

Data quality:


Specific data for the product composition are provided by the manufacturer. The data represent the production of the declared product and were collected for EPD development in the year of study. Background data is based on EPDs according to EN 15804 and different LCA databases. The data quality of the raw materials in A1 is presented in the table below.
The two data sets on expansion gas belong to two different blowing agents.

Materials	Source	Data quality	Year
Expansion gas	ecoinvent 3.6	Database	2019
Expansion gas	ecoinvent 3.6	Database	2020
Filler	ecoinvent 3.6	Database	2019
Flame retardant	Ecoinvent 3.6	Database	2019
Fuels, fossil	ecoinvent 3.6	Database	2019
Packaging - Plastic	ecoinvent 3.6	Database	2019
Plastic - Polystyrene (PS)	Plastics Europe + ecoinvent 3.6	European average.	2020
Plastic - Recycled	Supplier	EPD	0

System boundaries (X=included, MND=module not declared, MNR=module not relevant)

Product stage			Construction installation stage		Use stage							End of life stage				Beyond the system boundaries
Raw materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	X	X	MND	MND	MND	MND	MND	MND	MND	X	X	X	X	X

System boundary:



Additional technical information:

The following information describe the scenarios in the different modules of the EPD.

Product & Construction installation stages (A1-A5)
- The product stage includes the acquisition of all raw materials, products and energy, transport to the production site, packaging, and waste processing up to the 'end-of-waste" state or final disposal.
- No solid waste is generated from the production of XPS products, as the cut off is immediately returned to production line (however, some solid waste is produced from the raw material packaging, e.g., PE-folio).
- The blowing agent content in the XPS products is highest right after production, after which it continues to decrease. The release of blowing agent is reported in module A3 since it relates to the production
- A2-A4 is based on a weighted average for BEWI Insulation Germany and Belgium production sites (JACKON Insulation GmbH in Mechau – Germany and JACKON Insulation nv in Olen - Belgium).
- For A4, a weighted average distance is calculated based on the distance from both production sites.

End of Life stage (C1-C4) includes:
- The XPS product is dismantled manually, thus, no environmental impacts are associated with module C1. The dismantled XPS product is transported 50 km to an incineration plant by a EURO 6 diesel truck.
- Incineration of the dismantled XPS is included in module C3. Energy credits related to energy recovery from the incineration is included in module D.

Re-use, recovery, and recycling potential (D) includes:
- Credits for energy recovery related to the incineration is included in module D.
- The packaging materials, LDPE foil reach the end-of-waste stage in module A5, and the benefits from recycling and incineration of the packaging materials are included in module D

LCA: Scenarios and additional technical information

The following information describe the scenarios in the different modules of the EPD.

Transport from production place to user (A4)	Capacity utilisation (incl. return) %	Distance (km)	Fuel/Energy Consumption	Unit	Value (Liter/tonne)
Truck, 16-32 tonnes, EURO 6 (kgkm)	36.7 %	1040.00	0.043	l/tkm	44.72

Assembly (A5)	Unit	Value			
Waste, packaging, plastic to average treatment - A5 (inkl transport) (kg)	kg	0.402			

De-construction demolition (C1)	Unit	Value			
Waste treatment, PS, Insulation, Germany (kg)	kg	31.30			

Transport to waste processing (C2)	Capacity utilisation (incl. return) %	Distance (km)	Fuel/Energy Consumption	Unit	Value (Liter/tonne)
Truck, over 32 tonnes, EURO 6 (kgkm)	53.3 %	50.00	0.023	l/tkm	1.15

Waste processing (C3)	Unit	Value			
Waste, Polystyrene, incineration	kg	28.17			
Recycling of PS	kg	3.13			

Disposal (C4)	Unit	Value			
Landfilling of ashes from incineration of PS	kg	0.08451			
Waste, inert waste, to landfill (kg)	kg	0.00			

Benefits and loads beyond the system boundaries (D)	Unit	Value			
substitution of electricity (MJ)	MJ	16.34			
Substitution of thermal energy (MJ)	MJ	899.51			
Substitution of expandable polystyrene, EPS, granulate (kg)	kg	3.13			

LCA: Results

The LCA results are presented below for the declared unit defined on page 2 of the EPD document.

Environmental impact												
	Indicator	**Unit**	A1	A2	A3	A4	A5	C1	C2	C3	C4	D
	GWP-total	kg CO_2 -eq	5.69E+01	2.54E+00	7.73E+00	2.22E+00	3.18E-02	0.00E+00	1.36E-01	8.98E+01	4.38E-03	-1.69E+01
	GWP-fossil	kg CO_2 -eq	5.67E+01	2.54E+00	7.67E+00	2.22E+00	3.18E-02	0.00E+00	1.36E-01	8.98E+01	4.38E-03	-1.66E+01
	GWP-biogenic	kg CO_2 -eq	1.87E-01	1.05E-03	4.21E-02	9.18E-04	4.39E-06	0.00E+00	5.84E-05	6.19E-04	2.32E-06	-8.02E-02
	GWP-luluc	kg CO_2 -eq	1.37E-02	9.03E-04	1.50E-02	7.89E-04	2.44E-06	0.00E+00	4.15E-05	9.81E-05	6.71E-07	-1.79E-01
	ODP	kg CFC11 -eq	1.34E-06	5.75E-07	1.31E-06	5.02E-07	1.91E-09	0.00E+00	3.29E-08	6.44E-08	4.70E-10	-3.80E-01
	AP	mol H+ -eq	1.32E-01	7.29E-03	1.65E-02	6.37E-03	3.93E-05	0.00E+00	4.39E-04	1.07E-02	1.54E-05	-8.10E-02
	EP-FreshWater	kg P -eq	7.61E-04	2.03E-05	1.75E-04	1.77E-05	6.55E-08	0.00E+00	1.08E-06	6.36E-06	5.91E-08	-6.48E-04
	EP-Marine	kg N -eq	3.21E-02	1.44E-03	3.38E-03	1.26E-03	3.59E-05	0.00E+00	9.61E-05	5.14E-03	4.81E-06	-1.99E-02
	EP-Terrestial	mol N -eq	3.49E-01	1.61E-02	4.10E-02	1.41E-02	1.41E-04	0.00E+00	1.07E-03	5.50E-02	5.47E-05	-2.14E-01
	POCP	kg NMVOC -eq	1.29E-01	6.18E-03	2.60E-01	5.40E-03	4.63E-05	0.00E+00	4.21E-04	1.32E-02	1.51E-05	-7.61E-02
	ADP-minerals&metals[1]	kg Sb-eq	1.52E-04	7.01E-05	8.92E-05	6.12E-05	1.69E-07	0.00E+00	2.43E-06	2.77E-06	2.45E-08	-3.30E-05
	ADP-fossil[1]	MJ	1.84E+03	3.84E+01	2.49E+02	3.35E+01	1.31E-01	0.00E+00	2.21E+00	5.50E+00	3.98E-02	-3.30E+02
	WDP[1]	m^3	4.95E+02	3.71E+01	7.15E+02	3.24E+01	4.64E-01	0.00E+00	1.70E+00	1.22E+01	4.12E-01	-2.67E+02

GWP-total = Global Warming Potential total; GWP-fossil = Global Warming Potential fossil fuels; GWP-biogenic = Global Warming Potential biogenic; GWP-luluc = Global Warming Potential land use and land use change; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential, Accumulated Exceedance; EP-freshwater = Eutrophication potential, fraction of nutrients reaching freshwater end compartment: EP-marine = Eutrophication potential, fraction of nutrients reaching marine end compartment; EP-terrestrial = Eutrophication potential, Accumulated Exceedance; POCP = Formation potential of tropospheric ozone; ADP-minerals&metals = Abiotic depletion potential for non-fossil resources; ADP-fossil = Abiotic depletion for fossil resources potential; WDP = Water (user) deprivation potential, deprivation-weighted water consumption

"Reading example: 9.0 E-03 = 9.0*10-3 = 0.009"

1. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator

Remarks to environmental impacts

Additional environmental impact indicators

Indicator		Unit	A1	A2	A3	A4	A5	C1	C2	C3	C4	D
	PM	Disease incidence	8.64E-07	1.55E-07	8.65E-08	1.36E-07	7.06E-10	0.00E+00	1.25E-08	4.50E-08	1.91E-10	-2.96E-06
	IRP[2]	kgBq U235 -eq	1.61E+00	1.68E-01	2.81E+00	1.47E-01	5.93E-04	0.00E+00	9.68E-03	9.20E-03	1.89E-04	-4.08E-01
	ETP-fw[1]	CTUe	8.60E+03	2.84E+01	1.15E+02	2.48E+01	1.25E-01	0.00E+00	1.62E+00	1.33E+01	7.32E-02	-4.34E+02
	HTP-c[1]	CTUh	2.11E-08	0.00E+00	3.13E-09	0.00E+00	3.00E-12	0.00E+00	0.00E+00	3.78E-09	4.00E-12	-8.94E-09
	HTP-nc[1]	CTUh	8.86E-07	3.11E-08	8.35E-08	2.71E-08	1.18E-10	0.00E+00	1.57E-09	1.49E-07	1.35E-10	-3.92E-07
	SQP[1]	dimensionless	8.93E+01	2.68E+01	6.84E+01	2.34E+01	2.29E-01	0.00E+00	2.54E+00	6.55E-01	1.10E-01	-4.97E+02

PM = Particulate Matter emissions; IRP = Ionizing radiation – human health; ETP-fw = Eco toxicity – freshwater; HTP-c = Human toxicity – cancer effects; HTP-nc = Human toxicity – non cancer effects; SQP = Potential Soil Quality Index (dimensionless)

"Reading example: 9.0 E-03 = 9.0*10-3 = 0.009"

1. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator
2. This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator.

Resource use												
Indicator		Unit	A1	A2	A3	A4	A5	C1	C2	C3	C4	D
	PERE	MJ	1.48E+01	5.49E-01	4.55E+01	4.80E-01	3.32E-03	0.00E+00	2.79E-02	1.58E-01	2.32E-03	-4.12E+02
	PERM	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	PERT	MJ	1.48E+01	5.49E-01	4.55E+01	4.80E-01	3.32E-03	0.00E+00	2.79E-02	1.58E-01	2.32E-03	-4.12E+02
	PENRE	MJ	1.10E+03	3.84E+01	2.49E+02	3.35E+01	1.31E-01	0.00E+00	2.21E+00	5.50E+00	3.98E-02	-3.30E+02
	PENRM	MJ	8.50E+02	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	PENRT	MJ	1.95E+03	3.84E+01	2.49E+02	3.35E+01	1.31E-01	0.00E+00	2.21E+00	5.50E+00	3.98E-02	-3.30E+02
	SM	kg	8.94E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	RSF	MJ	4.93E-01	1.96E-02	8.44E-01	1.72E-02	8.70E-05	0.00E+00	9.74E-04	4.42E-03	5.77E-05	-4.15E-02
	NRSF	MJ	3.12E-01	7.02E-02	6.05E+00	6.14E-02	2.28E-04	0.00E+00	3.27E-03	0.00E+00	9.18E-03	-2.72E+01
	FW	m^3	1.25E+00	4.10E-03	8.40E-02	3.58E-03	6.94E-05	0.00E+00	2.52E-04	1.56E-02	3.66E-05	-3.85E-01

PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non renewable primary energy resources used as raw materials; PENRT = Total use of non renewable primary energy resources; SM = Use of secondary materials; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Net use of fresh water

"Reading example: 9.0 E-03 = 9.0*10-3 = 0.009"

End of life - Waste

Indicator		Unit	A1	A2	A3	A4	A5	C1	C2	C3	C4	D
	HWD	kg	9.10E-02	1.98E-03	4.45E-02	1.73E-03	0.00E+00	0.00E+00	1.21E-04	0.00E+00	7.26E-02	-5.66E-03
	NHWD	kg	4.31E+00	1.87E+00	6.20E-01	1.63E+00	4.02E-01	0.00E+00	1.92E-01	0.00E+00	3.60E-02	-1.59E+00
	RWD	kg	6.27E-04	2.61E-04	2.39E-03	2.28E-04	0.00E+00	0.00E+00	1.51E-05	0.00E+00	2.40E-07	-3.57E-04

HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed

"Reading example: 9.0 E-03 = 9.0*10-3 = 0.009"

End of life - Output flow

Indicator		Unit	A1	A2	A3	A4	A5	C1	C2	C3	C4	D
	CRU	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	MFR	kg	9.51E-01	0.00E+00	0.00E+00	0.00E+00	2.05E-01	0.00E+00	0.00E+00	3.13E+00	0.00E+00	0.00E+00
	MER	kg	2.11E-01	0.00E+00	1.48E-01	0.00E+00	2.01E-05	0.00E+00	0.00E+00	2.82E+01	0.00E+00	0.00E+00
	EEE	MJ	3.25E-01	0.00E+00	8.80E-02	0.00E+00	3.09E-05	0.00E+00	0.00E+00	4.96E+01	0.00E+00	0.00E+00
	EET	MJ	4.91E+00	0.00E+00	1.33E+00	0.00E+00	4.67E-04	0.00E+00	0.00E+00	7.51E+02	0.00E+00	0.00E+00

CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported energy electrical; EET = Exported energy thermal

"Reading example: 9.0 E-03 = 9.0*10-3 = 0.009"

Biogenic Carbon Content

Indicator	Unit	At the factory gate
Biogenic carbon content in product	kg C	0.00E+00
Biogenic carbon content in accompanying packaging	kg C	0.00E+00

Note: 1 kg biogenic carbon is equivalent to 44/12 kg CO2

Additional requirements

Greenhouse gas emissions from the use of electricity in the manufacturing phase

National production mix from import, low voltage (production of transmission lines, in addition to direct emissions and losses in grid) of applied electricity for the manufacturing process (A3).

Electricity mix	Source	Amount	Unit
Electricity, belgium (kWh)	ecoinvent 3.6	248.03	g CO2-eq/kWh
Electricity, with Guarantee of origin, 01.01.2025 - 31.12.2025 - BEWI Arendsee, Germany (kWh)	ecoinvent 3.6	29.24	g CO2-eq/kWh

Dangerous substances

The product contains no substances given by the REACH Candidate list.

Indoor environment

JACKODUR EVO can be used indoor however they are generally not exposed to the indoor air but covered by a finishing element or system.
The VOC emission testing meets the requirements of the AgBB/DIBt method.
The tested products all comply with the requirements of DIBt and AgBB for the use in the indoor environment.
The tested products also all achieved the A+ rating of the French VOC labelling scheme.

Additional Environmental Information

Additional environmental impact indicators required in NPCR Part A for construction products											
Indicator	**Unit**	A1	A2	A3	A4	A5	C1	C2	C3	C4	D
GWPIOBC	kg CO_2 -eq	5.70E+01	2.54E+00	7.73E+00	2.22E+00	3.18E-02	0.00E+00	1.36E-01	8.98E+01	4.54E-03	-1.68E+01

GWP-IOBC: Global warming potential calculated according to the principle of instantaneous oxidation. In order to increase the transparency of biogenic carbon contribution to climate impact, the indicator GWP-IOBC is required as it declares climate impacts calculated according to the principle of instantaneous oxidation. GWP-IOBC is also referred to as GWP-GHG in context to Swedish public procurement legislation.

Bibliography

ISO 14025:2010 Environmental labels and declarations - Type III environmental declarations - Principles and procedures.
ISO 14044:2006 Environmental management - Life cycle assessment - Requirements and guidelines.
EN 15804:2012+A2:2019 Environmental product declaration - Core rules for the product category of construction products.
ISO 21930:2017 Sustainability in buildings and civil engineering works - Core rules for environmental product declarations of construction products.
ecoinvent v3, Allocation, cut-off by classification, Swiss Centre of Life Cycle Inventories.
Iversen et al., (2021) eEPD v2021.09 Background information for EPD generator tool system verification, LCA.no Report number: 07.21
Vold et. al., (2022) EPD generator for NPCR 012 Thermal insulation, Background information for EPD generator application and LCA data, LCA.no report number: 07.22.
NPCR Part A: Construction products and services. Ver. 2.0. April 2021, EPD-Norge.
NPCR 012 Part B for Part B for Thermal insulation products, Ver. 2.0, 31.03.2022, EPD Norway.

epd-global Powered by EPD-Norway	**Program operator and publisher** EPD-Global Postboks 5250 Majorstuen, 0303 Oslo, Norway	Phone: e-mail: web:	+47 977 22 020 post@epd-norge.no www.epd-global.com
BEWI	**Owner of the declaration:** BEWI ASA, Insulation and Construction Hammarvikringen 64, HAMAR 7263, Norway	Phone: e-mail: web:	+45 72157902 marc.andersen@bewi.com https://bewi.com
LCA.no	**Author of the Life Cycle Assessment** LCA.no AS Dokka 6A, 1671 Kråkerøy, Norway	Phone: e-mail: web:	+47 916 50 916 post@lca.no www.lca.no
LCA.no	**Developer of EPD generator** LCA.no AS Dokka 6A, 1671 Kråkerøy, Norway	Phone: e-mail: web:	+47 916 50 916 post@lca.no www.lca.no
ECO PLATFORM EPD VERIFIED	ECO Platform ECO Portal	web: web:	www.eco-platform.org ECO Portal

JACKON Insulation GmbH | Ritzlebener Straße 1 | D-39619 Arendsee

Herstellererklärung für das Produkt JACKODUR EVO

Hiermit bestätigen wir, dass bei den extrudierten Polystyrolhartschaumprodukten JACKODUR EVO keine Stoffe enthalten sind, die

- SVHC entsprechend Verordnung (EG) 1907/2006 (REACH)
- HBCD
- halogenierte Treibmittel wie (H)F(C)KW
- CMR-Stoffe der Kategorie 1A/1B entsprechend CLP-Verordnung 1272/2008

sind.

Arendsee, 11.05.2026

Daniel Geigenfeind
Geschäftsführer

i.V. Dr. Mark Plate
Sustainability and Product Stewardship

JACKON Insulation GmbH
Ritzlebener Straße 1
D-39619 Arendsee (Mechau)
T +49 (0)39036 960-0
F +49 (0)39036 960-290

Commerzbank AG
IBAN DE25 2584 1403 0701 0010 00
BIC COBADEFFXXX
T info@jackodur.com
W www.jackon-insulation.com

Geschäftsführer: Daniel Geigenfeind
Registergericht Stendal / HRB 3496
Steuer-Nr. 106/107/03629
USt.-ID-Nr. DE126959786

Reg.-Nr. 67674