SENTINEL HOLDING
INSTITUT

SHI PRODUCT PASSPORT

Find products. Certify buildings.

SHI Product Passport No.:

2900-10-1002

MEHABIT

Product group: Insulation - Insulating fill

MEHA Dämmstoffe
Qualität seit 1957

MEHA Dämmstoff und Handels GmbH
Böhler Weg 6-10
67105 Schifferstadt

Product qualities:

- SHI Product Assessment 2024
- QNG Qualitätssiegel Nachhaltiges Gebäude
- DGNB NEW CONSTRUCTION 2023
- DGNB NEW CONSTRUCTION 2018
- BNB-BN NEUBAU V2015
- EU taxonomy
- BREEAM DE NEUBAU 2018
- LEED v4.1 (outside US)

CERTIFIED SUSTAINABLE PRODUCT
SHI PRODUCT PASSPORT
SENTINEL HOLDING INSTITUT
www.sentinel-holding.eu

Köttner

Helmut Köttner
Scientific Director
Freiburg, 07 April 2026

SENTINEL HOLDING
INSTITUT

Product:
MEHABIT

SHI Product Passport no.:
2900-10-1002

MEHA Dämmstoffe
Qualität seit 1957

Contents

SHI Product Assessment 2024	1
QNG - Qualitätssiegel Nachhaltiges Gebäude	2
DGNB New Construction 2023	3
DGNB New Construction 2018	5
BNB-BN Neubau V2015	6
EU taxonomy	7
BREEAM DE Neubau 2018	8
LEED v4.1	9
Product labels	10
Legal notices	11
Technical data sheet/attachments	11

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar

SGS TÜV SAAR

SENTINEL HOLDING
INSTITUT

Product:
MEHABIT

SHI Product Passport no.:
2900-10-1002

MEHA Dämmstoffe
Qualität seit 1957

SHI Product Assessment 2024

Since 2008, Sentinel Holding Institut GmbH (SHI) has been establishing a unique standard for products that support healthy indoor air. Experts carry out independent product assessments based on clear and transparent criteria. In addition, the independent testing company SGS regularly audits the processes and data accuracy.

Criteria	Product category	Harmful substance limit	Assessment
SHI Product Assessment	Insulation materials	TVOC ≤ 300 µg/m^3 Formaldehyd ≤ 24 µg/m^3	Indoor Air Quality Certified
Valid untill: 04 July 2027			

SENTINEL HOLDING
INSTITUT

Product:
MEHABIT

SHI Product Passport no.:
2900-10-1002

MEHA Dämmstoffe
Qualität seit 1957

QNG - Qualitätssiegel Nachhaltiges Gebäude

The Qualitätssiegel Nachhaltiges Gebäude (Quality Seal for Sustainable Buildings), developed by the German Federal Ministry for Housing, Urban Development and Building (BMWSB), defines requirements for the ecological, socio-cultural, and economic quality of buildings. The Sentinel Holding Institut evaluates construction products in accordance with QNG requirements for certification and awards the QNG ready label. Compliance with the QNG standard is a prerequisite for eligibility for the KfW funding programme. For certain product groups, the QNG currently has no specific requirements defined. Although classified as not assessment-relevant, these products remain suitable for QNG-certified projects.

Criteria	Pos. / product group	Considered substances	QNG assessment
3.1.3 Schadstoffvermeidung in Baumaterialien	12.4 Insulation materials made from renewable raw materials	Hazardous substances / SVHC: boron compounds / biocides	QNG ready
Verification: Herstellererklärung vom März 2024. Blauer Engel Zertifikat vom 07.02.2022. Laut den Vergabekriterien für den Blauen Engel DE-UZ 132 vom Januar 2020 ist der Einsatz von Bioziden verboten (Abschnitt 3.1.5.3).			

SENTINEL HOLDING
INSTITUT

Product:
MEHABIT

SHI Product Passport no.:
2900-10-1002

MEHA Dämmstoffe
Qualität seit 1957

DGNB New Construction 2023

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings. The 2023 version sets high standards for ecological, economic, socio-cultural, and functional aspects throughout the entire life cycle of a building.

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 03.05.2024 (3rd edition)	not applicable		Not relevant for assessment

Criteria	Assessment
SOC1.2 Indoor air quality (*)	May positively contribute to the overall building score
Verification: SHI-Schadstoffgeprüft	

Criteria	Assessment
ENV1.1 Climate action and energy (*)	May positively contribute to the overall building score
Verification: Datenblatt (Wärmeleitfähigkeit), Broschüre (Nachwachsender Rohstoff Hanf), Prozess ist reversibel, Produkt kann wiederverwendet werden	

Criteria	Assessment
SOC1.3 Sound insulation and acoustic comfort (*)	May positively contribute to the overall building score
Verification: Datenblatt (Trittschallverbesserungsmaß)	

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 29.05.2025 (4th edition)	not applicable		Not relevant for assessment

SENTINEL HOLDING
INSTITUT

Product:
MEHABIT

SHI Product Passport no.:
2900-10-1002

MEHA Dämmstoffe
Qualität seit 1957

DGNB New Construction 2018

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings.

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact	45 Construction products (products) equipped with biocides and flame retardants	Boron compounds	Quality level 4
Verification: Blauer Engel Zertifikat vom 07.02.2022.			

SENTINEL HOLDING
INSTITUT

Product:
MEHABIT

SHI Product Passport no.:
2900-10-1002

MEHA Dämmstoffe
Qualität seit 1957

BNB-BN Neubau V2015

The Bewertungssystem Nachhaltiges Bauen (Assessment System for Sustainable Building) is a tool for evaluating public office and administrative buildings, educational facilities, laboratory buildings, and outdoor areas in Germany. The BNB was developed by the former Federal Ministry for the Environment, Nature Conservation, Building and Nuclear Safety (BMUB) and is now overseen by the Federal Ministry for Housing, Urban Development and Building (BMWSB).

Criteria	Pos. / product type	Considered substance group	Quality level
1.1.6 Risiken für die lokale Umwelt	36b Mineral and non-mineral interior insulations	VOC / biocides / hazardous substances / individual hazardous substances (formaldehyde) / halogenated blowing agents	Quality level 5
Verification: Blauer Engel Zertifikat vom 07.02.2022 Zusätzlich gilt Pos. 46b: Herstellererklärung vom März 2024			

SENTINEL HOLDING
INSTITUT

Product:
MEHABIT

SHI Product Passport no.:
2900-10-1002

MEHA Dämmstoffe
Qualität seit 1957

EU taxonomy

The EU Taxonomy classifies economic activities and products according to their environmental impact. At the product level, the EU regulation defines clear requirements for harmful substances, formaldehyde and volatile organic compounds (VOCs). The Sentinel Holding Institut GmbH labels qualified products that meet this standard.

Criteria	Product type	Considered substances	Assessment
DNSH - Pollution prevention and control	Internal insulation	Substances according to Annex C, formaldehyde, carcinogenic VOCs category 1A/1B	EU taxonomy compliant
Verification: Prüfbericht des Instituts eco-INSTITUT Germany GmbH vom 13.05.2019 / Prüfbericht Nr. 54173-001. Herstellererklärung vom März 2024.			

SENTINEL HOLDING
INSTITUT

Product:
MEHABIT

SHI Product Passport no.:
2900-10-1002

MEHA Dämmstoffe
Qualität seit 1957

BREEAM DE Neubau 2018

BREEAM (Building Research Establishment Environmental Assessment Methodology) is a UK-based building assessment system that evaluates the sustainability of new constructions, refurbishments, and conversions. Developed by the Building Research Establishment (BRE), the system aims to assess and improve the environmental, economic, and social performance of buildings.

Criteria	Product category	Considered substances	Quality level
Hea 02 Indoor Air Quality	Ceiling, wall, and acoustic and thermal insulation materials	Emissions: Formaldehyde, TVOC, TSVOC, carcinogens	Exemplary quality
Verification: Prüfbericht des Instituts eco-INSTITUT Germany GmbH vom 13.05.2019 / Prüfbericht Nr. 54173-001			

SENTINEL HOLDING
INSTITUT

Product:
MEHABIT

SHI Product Passport no.:
2900-10-1002

MEHA Dämmstoffe
Qualität seit 1957

LEED v4.1

LEED (Leadership in Energy and Environmental Design) is an internationally recognised building certification system developed by the U.S. Green Building Council. It is one of the most widely used sustainability standards for buildings worldwide and is particularly applied in internationally oriented projects. LEED assesses buildings holistically across categories such as energy efficiency, resource conservation, material selection, indoor environmental quality and site sustainability. Depending on the number of points achieved, projects are awarded one of the certification levels: LEED Certified, Silver, Gold or Platinum.

Criteria	Product category	Assessment
EQ Credit: Low-Emitting Materials	Wand- und Deckenelemente	compliant
Verification: Prüfbericht des Instituts eco-INSTITUT Germany GmbH vom 13.05.2019 / Prüfbericht Nr. 54173-001		

SENTINEL HOLDING
INSTITUT

Product:
MEHABIT

SHI Product Passport no.:
2900-10-1002

MEHA Dämmstoffe
Qualität seit 1957

Product labels

In the construction industry, high-quality materials are crucial for a building's indoor air quality and sustainability. Product labels and certificates offer guidance to meet these requirements. However, the evaluation criteria of these labels vary, and it is important to carefully assess them to ensure products align with the specific needs of a construction project.

The *Blue Angel* ("Blauer Engel") ecolabel, awarded by the German Federal Environment Agency, is one of the oldest and most widely used ecolabels in Germany. It exists in several variants for many different product groups. Since the test criteria, such as threshold values, differ between these variants, it is important to consider each one individually when assessing indoor air quality.

This product is SHI Indoor Air Quality certified and recommended by Sentinel Holding Institut. Indoor-air-focused construction, renovation, and operation of buildings is made possible by transparent and verifiable criteria thanks to the Sentinel Holding concept.

Products bearing the Sentinel Holding Institute QNG-ready seal are suitable for projects aiming to achieve the "Qualitätssiegel Nachhaltiges Gebäude" (Quality Seal for Sustainable Buildings). QNG-ready products meet the requirements of QNG Appendix Document 3.1.3, "Avoidance of Harmful Substances in Building Materials." The KfW loan program Climate-Friendly New Construction with QNG may allow for additional funding.

Product:
MEHABIT

SHI Product Passport no.:
2900-10-1002

MEHA Dämmstoffe
Qualität seit 1957

Legal notices

(*) These criteria apply to the construction project as a whole. While individual products can positively contribute to the overall building score through proper planning, the evaluation is always conducted at the building level. The information was provided entirely by the manufacturer.

Find our criteria here: https://www.sentinel-holding.eu/de/Themenwelten/Pr%C3%BCfkriterien%20f%C3%BCr%20Produkte

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar

SGS TÜV SAAR

Publisher

Sentinel Holding Institut GmbH
Bötzinger Str. 38
79111 Freiburg im Breisgau
Germany
Tel.: +49 761 590 481-70
info@sentinel-holding.eu
www.sentinel-holding.eu

MEHA Dämmstoffe

Qualität seit 1957

Produktdatenblatt (Stand 08/2023)

MEHABIT

Dämm- und Ausgleichsschüttung mit Klebeeffekt in gebundener Form nach DIN 18560-2

Produktbeschreibung



Universell einsetzbare, bauaufsichtlich zugelassene Dämm- und Ausgleichsschüttung, bestehend aus Hanfschäben mit lösungsmittelfreiem Bitumen. Die Bituminierung garantiert die Verklebung zur „gebundenen Form".
MEHABIT erfüllt die Anforderungen der aktualisierten **DIN 18560-2:2022-08**.

Anwendungsgebiet

Höhenausgleich auf Beton- oder Holzbalkendecken mit hoher Druckbelastbarkeit, als Unterkonstruktion unter Trocken-, Nass- und Gussasphalt-Estrichen. Stabile Auffüllung und Überdeckung von Zwischenräumen und Rohrleitungsbündeln.

Empfohlene Einbaustärke
- von 10 mm (kleinflächig) bis 200 mm – punktuell auf Null auslaufend
- auf glatten Untergründen (z.B. Folie) Mindesthöhe von ca. 10 mm

Vorteile

- Bildung einer gebundenen fugenlosen Dämm- und Ausgleichsschicht
- auch für hohe Belastungen geeignet, da sich die Schüttung nicht zerreibt
- geringes Gewicht und damit kaum Auswirkungen auf die Statik
- staubfrei
- Bauaufsichtliche Zulassung: DIBt [Z-23.11-1185]
- erfüllt die Anforderungen einer „gebundenen Schüttung" nach BEB-Bundesverband Estrich und Belag e.V. (2015)[1]

GEPRÜFT GESÜNDERE PRODUKTE – QNG READY – SENTINEL HAUS INSTITUT

BLAUER ENGEL – DAS UMWELTZEICHEN

www.blauer-engel.de/uz132

Verarbeitungs- und Verlege-Richtlinien

MEHABIT nur auf trockenem Untergrund einbauen. Auf ausreichend Schutz vor Feuchtigkeit ist zu achten. Abdichtungen gegen Bodenfeuchte und nicht drückendes Wasser sind vom Bauwerksplaner festzulegen und vor Einbau der Schüttung herzustellen. Bei erdberührten Bauteilen (z.B. Bodenplatten) Abdichtung gemäß DIN ausführen.

Beim Einbau der Schüttung in Bereichen, in denen mit höheren, insbesondere dynamischen Lasten gerechnet werden muss, ist auf eine ausreichende Druckverteilung (Lastverteilerplatte z.B. MEHASOL) zu achten, damit eine gleichmäßige Verdichtung der eingebauten Schüttung gewährleistet wird.

Die allgemeinen Verarbeitungs- und Verlege-Richtlinien, die Aufbauempfehlungen sowie die Verlegehinweise sind zu beachten.

Technische Daten	Wert	Einheit (Norm)
Wärmeleitfähigkeit	0,060	W/(m·K) (DIN EN 12667)
Druckspannung bei 10% Stauchung im eingebauten Zustand	≥ 0,1	N/mm² (DIN EN 826)
Kornfestigkeit	2,5	kN (DIN 4226-3)
Trittschallverbesserung (Rohbetondecke)	19-26	dB (Musterprüfung, Werte können je nach Aufbau abweichen)
Brandverhalten	B2	(DIN 4102-1)
Schüttdichte ca.	140	kg/m³
Wasserdampfdiffusionswiderstand	9	(DIN EN 12806)

[1] BEB-Bundesverband Estrich und Belag e.V. (2015); Hinweise zur Planung und Ausführung von Fußbodenkonstruktionen bei Rohren, Leitungen und Einbauteilen auf Rohdecken, Sammelmappe-Nr. 4.6. Herausgegeben von: Bundesverband Estrich und Belag e.V. Troisdorf-Oberlar, Bundesfachgruppe Estrich und Belag im Zentralverband des Deutschen Baugewerbes e.V. Berlin

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

MEHABIT

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture:
Building and construction preparations not covered elsewhere

Relevant identified uses:

Sector of uses [SU]
SU 19: Building and construction work
Product Categories [PC]
PC 10: Building and construction preparations not covered elsewhere
Environmental release categories [ERC]
ERC 9a: Wide dispersive indoor use of substances in closed systems
Article categories [AC]
AC 0: Other Articles:

1.3. Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor):
MEHA Dämmstoff und Handels GmbH
Böhlerweg 6-10
67105 Schifferstadt
Germany
Telephone: 06235 92550
E-mail: info@meha.de
Website: www.meha.de

1.4. Emergency telephone number

+49 (0) 6235 - 92550 (Only available during office hours.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]:
This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP].

Classification according to Directive 67/548/EEC or 1999/45/EC:
This mixture is classified as not hazardous according to 1999/45/EC.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

According to EC directives or the corresponding national regulations the product does not have to be labelled.

Hazard statements: -

Supplemental Hazard information (EU): -

Precautionary statements: -

Labelling (67/548/EEC or 1999/45/EC)

According to EC directives or the corresponding national regulations the product does not have to be labelled.

2.3. Other hazards

Adverse physicochemical effects:
No known significant effects or critical hazards.

Adverse human health effects and symptoms:
No known significant effects or critical hazards.

Adverse environmental effects:
No known significant effects or critical hazards.
The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

Other adverse effects:
No known significant effects or critical hazards.

SECTION 3: Composition / information on ingredients

3.2. Mixtures

Description:
This mixture does not contain any substances presenting a health or environmental hazard within the meaning of the Dangerous Substances Directive 67/548/EEC or Regulation (EC) No. 1272/2008, assigned a Community workplace exposure limit, classified as PBT/vPvB or included in the Candidate List.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:
When in doubt or if symptoms are observed, get medical advice.

Following inhalation:
Provide fresh air.

In case of skin contact:
After contact with skin, wash immediately with plenty of water and soap.

After eye contact:
Rinse immediately carefully and thoroughly with eye-bath or water.
In case of eye irritation consult an ophthalmologist.

After ingestion:
not applicable

Self-protection of the first aider:
No special measures are necessary.

4.2. Most important symptoms and effects, both acute and delayed

No known symptoms to date.

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:
Water, Foam, Extinguishing powder, Water spray

Unsuitable extinguishing media:
no restriction

5.2. Special hazards arising from the substance or mixture

No known significant effects or critical hazards.

Hazardous combustion products:
Carbon dioxide (CO2), Carbon monoxide.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

5.4. Additional information

Co-ordinate fire-fighting measures to the fire surroundings.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:
Avoid generation of dust.

Emergency procedures:
Remove persons to safety.
Provide adequate ventilation.

6.1.2. For emergency responders

Personal protection equipment:
Use appropriate respiratory protection.

6.2. Environmental precautions
Ensure waste is collected and contained.

6.3. Methods and material for containment and cleaning up
For containment:
No special measures are necessary.

For cleaning up:
Take up mechanically.

6.4. Reference to other sections
Safe handling: see section 7

6.5. Additional information
Clear spills immediately.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures
Advices on safe handling:
It is recommended to design all work processes always so that the following is excluded:
Generation/formation of dust

Fire prevent measures:
Flammable.
Usual measures for fire prevention.

Measures to prevent aerosol and dust generation:
Open windows to ensure natural ventilation.

Environmental precautions:
No special measures are necessary.

Advices on general occupational hygiene
Wash hands and face before breaks and after work and take a shower if necessary.

7.2. Conditions for safe storage, including any incompatibilities
Technical measures and storage conditions:
No special measures are necessary.

Packaging materials:
no restriction

Storage class: 11

Further information on storage conditions:
Protect from moisture.

7.3. Specific end use(s)
Recommendation:
Observe technical data sheet.
Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters
No data available

8.2. Exposure controls

8.2.1. Appropriate engineering controls
No data available

8.2.2. Personal protection equipment
Eye/face protection:
Eye protection: not required.

Skin protection:
Recommended material:
dust-tight, Chromate-free leather

Respiratory protection:
Respiratory protection necessary at: dust formation, insufficient ventilation

Thermal hazards:
No known significant effects or critical hazards.

8.2.3. Environmental exposure controls
See section 7. No additional measures necessary.

8.3. Additional information
Further information: see technical data sheet.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: solid
Colour: black
Odour: odourless
Odour threshold: not applicable

Safety relevant basis data

		at °C	Method	remark
pH	*not applicable*			
Melting point/freezing point	*not applicable*			
Freezing point	*not applicable*			
Initial boiling point and boiling range	*not applicable*			
Decomposition temperature (°C):	*not applicable*			
Flash point	*not applicable*			
Evaporation rate	*not applicable*			
Ignition temperature in °C	*not applicable*			
Upper/lower flammability or explosive limits	*not applicable*			
Vapour pressure	*not applicable*			
Vapour density	*not applicable*			
Density	*not determined*			
Bulk density	≈ 150 kg/m³			
Water solubility (g/L)	*not applicable*			
Partition coefficient: n-octanol/water	*not applicable*			
Dynamic viscosity	*not applicable*			
Kinematic viscosity	*not applicable*	40 °C		

9.2. Other information
No data available

SECTION 10: Stability and reactivity

10.1. Reactivity
No known hazardous reactions.

10.2. Chemical stability
The substance is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions
No known hazardous reactions.

10.4. Conditions to avoid
Protect from moisture.

10.5. Incompatible materials
none

10.6. Hazardous decomposition products
No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute oral toxicity:
none

Acute dermal toxicity:
none

Acute inhalation toxicity:
none

Skin corrosion/irritation:
none

Eye damage/irritation:
none

Respiratory or skin sensitisation:
not sensitising.

Germ cell mutagenicity:
none

Carcinogenicity:
none

Reproductive toxicity:
none

STOT-single exposure:
none

STOT-repeated exposure:
none

Aspiration hazard:
none

SECTION 12: Ecological information

12.1. Toxicity

Aquatic toxicity:
not applicable

12.2. Persistence and degradability

Biodegradation:
not applicable

Additional information:
Due to its low solubility in water the product is almost completely mechanically separated in biological sewage plants.

12.3. Bioaccumulative potential

Partition coefficient: n-octanol/water:
not applicable

Accumulation / Evaluation:
not applicable

12.4. Mobility in soil

not applicable

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Waste code product:

17 03 02	bituminous mixtures other than those mentioned in 17 03 01

Waste code packaging:

20 03 99	Municipal wastes not otherwise specified

Waste treatment options

Appropriate disposal / Product:
Dispose of waste according to "Kreislaufwirtschaftsgesetz (KrWG)".

Appropriate disposal / Package:
Completely emptied packages can be recycled.

13.2. Additional information
No data available

SECTION 14: Transport information

No dangerous good in sense of these transport regulations.

14.1. UN-No.
not relevant
14.2. UN proper shipping name
not relevant
14.3. Transport hazard class(es)
not relevant
14.4. Packing group
not relevant
14.5. Environmental hazards
not relevant
14.6. Special precautions for user
not relevant

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
not relevant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation
No data available

15.1.2. National regulations

[DE] National regulations

Water hazard class (WGK)
WGK:
nwg - nicht wassergefährdend

15.2. Chemical Safety Assessment
Chemical safety assessments for substances in this mixture were not carried out.

15.3. Additional information
No data available

SECTION 16: Other information

16.1. Indication of changes
No data available

16.2. Abbreviations and acronyms
See overview table at www.euphrac.eu

16.3. Key literature references and sources for data
No data available

16.4. Classification for mixtures and used evaluation method according to regulation (EC) 1272/2008 [CLP]
Classification according to Regulation (EC) No. 1272/2008 [CLP]:
This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP].

16.5. Relevant R-, H- and EUH-phrases (Number and full text)
No data available

16.6. Training advice

No data available

16.7. Additional information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

This Safety Data Sheet was drawn up by TÜV SÜD Industrie Service GmbH (see below), based on data from the supplier, who is named in section 1 and who is responsible for this document.
TÜV SÜD Industrie Service GmbH
Department Environmental Service
Westendstraße 199
80686 Munich - Germany

MEHA Dämmstoff und Handels GmbH • Böhler Weg 6-10 • 67105 Schifferstadt

www.meha.de

Stand: März 2024

Herstellererklärung

Die MEHA Dämmstoff und Handels GmbH bescheinigt für die von ihr hergestellten Produkte MEHABIT und MEHASPORT folgende Eigenschaften:

REACH-Erklärung (SVHC):

Die MEHA Dämmstoff und Handels GmbH bestätigt, dass in den folgenden von uns gelieferten Produkten:

- MEHABIT
- MEHAPOR
- MEHASPORT

keine SVHC-Kandidaten (Substances of Very High Concern – SVHC, Stand Kandidatenliste vom 17. Januar 2023) nach Art. 33(2) der Verordnung (EG) Nr. 1907/2006 (REACH) über 0,1 Massen-% enthalten sind.

Reproduktionstoxische Borverbindungen

Die MEHA Dämmstoff und Handels GmbH bestätigt, dass in den folgenden von uns gelieferten Produkten:

- MEHABIT
- MEHAPOR
- MEHASPORT

keine reproduktionstoxische Borverbindungen über 0,1 Mass-% enthalten sind.

VOC-Emissionen nach AgBB-Schema:

MEHABIT und MEHASPORT erfüllen die Anforderungen des AgBB-Schemas (Ausschuss zur gesundheitlichen Bewertung von Bauprodukten) für die Verwendung von Bauprodukten in Innenräumen. Es werden die vorgegebenen Grenzwerte deutlich unterschritten. Gerne senden wir Ihnen die Prüfberichte auf Anfrage zu (info@meha.de).

MEHA Dämmstoff und Handels GmbH
Anwendungstechnik

MEHA Dämmstoff und Handels GmbH
Industriegebiet Nord
Böhler Weg 6-10
67105 Schifferstadt

Telefon: 06235/9255-0
Telefax: 06235/9255-20
Email: info@meha.de
Internet: www.meha.de

Geschäftsführung:
Dipl. Ing. Peter Kahanek
Marc Beutnagel, B.Sc.
Amtsgericht: Ludwigshafen Rh. - HRB 61418
USt-Idt Nr. DE263582715

Sparkasse Heidelberg
IBAN DE97 6725 0020 0009 0584 51
BIC: SOLADES1HDB
Vereinigte VR Bank Kur- und Rheinpfalz
IBAN DE53 5479 0000 0001 3223 20
BIC: GENODE61SPE

URKUNDE

MEHA Dämmstoff und Handels GmbH
67105 Schifferstadt, Deutschland

wird aufgrund des Zeichenbenutzungsvertrages Nr. 37620 zur DE-UZ 132 Ausgabe 2020 das Recht verliehen, für das Produkt

MEHABIT - Dämm- und Ausgleichsschüttung mit Klebeeffekt in gebundener Form (Anwendungstyp nach DIN 4108-10: DEO)

das nachstehend abgebildete Umweltzeichen als Ausweis für die besondere Umweltfreundlichkeit zu führen.

Bonn, den 07. Februar 2022

Geschäftsführer
RAL gGmbH

Bundesministerium für Umwelt, Naturschutz und nukleare Sicherheit

Umwelt Bundesamt

Jury Umweltzeichen

RAL gGmbH