SENTINEL HOLDING
INSTITUT

SHI PRODUCT PASSPORT

Find products. Certify buildings.

SHI Product Passport No.:

12012-10-1097

DASAPLANO 0,01 connect

Product group: Waterproofing membranes - Vapor barriers / vapor retarders - Roof and facade

pro clima®

pro clima - MOLL bauökologische Produkte GmbH
Rheintalstraße 35-43
68723 Schwetzingen

Product qualities:

- SHI Product Assessment 2024
- QNG Qualitätssiegel Nachhaltiges Gebäude
- DGNB NEW CONSTRUCTION 2023.2
- DGNB NEW CONSTRUCTION 2023
- DGNB NEW CONSTRUCTION 2018
- BNB-BN NEUBAU V2015
- EU TAXONOMY
- BREEAM DE NEUBAU 2018
- LEED v4.1 (outside US)

CERTIFIED SUSTAINABLE PRODUCT
SHI PRODUCT PASSPORT
SENTINEL HOLDING INSTITUT
www.sentinel-holding.eu

Köttner

Helmut Köttner
Scientific Director
Freiburg, 26 August 2026

SENTINEL HOLDING
INSTITUT

Product:
DASAPLANO 0,01 connect

SHI Product Passport no.:
12012-10-1097

pro clima®

Contents

SHI Product Assessment 2024	1
QNG - Qualitätssiegel Nachhaltiges Gebäude	2
DGNB New Construction 2023.2	3
DGNB New Construction 2023	4
DGNB New Construction 2018	6
BNB-BN Neubau V2015	7
EU taxonomy	8
BREEAM DE Neubau 2018	9
LEED v4.1	10
Product labels	11
Legal notices	12
Technical data sheet/attachments	12

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar

SGS

SGS TÜV SAAR

SENTINEL HOLDING
INSTITUT

Product:
DASAPLANO 0,01 connect

SHI Product Passport no.:
12012-10-1097

pro clima®

SHI Product Assessment 2024

Since 2008, Sentinel Holding Institut GmbH (SHI) has been establishing a unique standard for products that support healthy indoor air. Experts carry out independent product assessments based on clear and transparent criteria. In addition, the independent testing company SGS regularly audits the processes and data accuracy.

Criteria	Product category	Harmful substance limit	Assessment
SHI Product Assessment	Other products	TVOC ≤ 300 µg/m^3 Formaldehyd ≤ 24 µg/m^3	Indoor Air Quality Certified
Valid untill: 23 October 2026			

SENTINEL HOLDING
INSTITUT

Product:
DASAPLANO 0,01 connect

SHI Product Passport no.:
12012-10-1097

pro clima®

QNG - Qualitätssiegel Nachhaltiges Gebäude

The Qualitätssiegel Nachhaltiges Gebäude (Quality Seal for Sustainable Buildings), developed by the German Federal Ministry for Housing, Urban Development and Building (BMWSB), defines requirements for the ecological, socio-cultural, and economic quality of buildings. The Sentinel Holding Institut evaluates construction products in accordance with QNG requirements for certification and awards the QNG ready label. Compliance with the QNG standard is a prerequisite for eligibility for the KfW funding programme. For certain product groups, the QNG currently has no specific requirements defined. Although classified as not assessment-relevant, these products remain suitable for QNG-certified projects.

Criteria	Pos. / product group	Considered substances	QNG assessment
3.1.3 Schadstoffvermeidung in Baumaterialien			QNG ready - Not relevant for assessment

SENTINEL HOLDING
INSTITUT

Product:
DASAPLANO 0,01 connect

SHI Product Passport no.:
12012-10-1097

pro clima®

DGNB New Construction 2023.2

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact			Not relevant for assessment

SENTINEL HOLDING
INSTITUT

Product:
DASAPLANO 0,01 connect

SHI Product Passport no.:
12012-10-1097

pro clima®

DGNB New Construction 2023

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings. The 2023 version sets high standards for ecological, economic, socio-cultural, and functional aspects throughout the entire life cycle of a building.

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 03.05.2024 (3rd edition)			Not relevant for assessment

Criteria	Assessment
TEC1.3 Quality of the building envelope (*)	May positively contribute to the overall building score
Verification: Luftdichtheit	

Criteria	Assessment
SOC1.1 Thermal comfort (*)	May positively contribute to the overall building score
Verification: Luftdichtheit	

Criteria	Assessment
SOC1.2 Indoor air quality (*)	May positively contribute to the overall building score
Verification: SHI-Schadstoffgeprüft	

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 29.05.2025 (4th edition)	not applicable		Not relevant for assessment

SENTINEL HOLDING
INSTITUT

Product:
DASAPLANO 0,01 connect

SHI Product Passport no.:
12012-10-1097

pro clima®

DGNB New Construction 2018

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings.

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact	not applicable	not applicable	Not relevant for assessment

SENTINEL HOLDING
INSTITUT

Product:
DASAPLANO 0,01 connect

SHI Product Passport no.:
12012-10-1097

pro clima®

BNB-BN Neubau V2015

The Bewertungssystem Nachhaltiges Bauen (Assessment System for Sustainable Building) is a tool for evaluating public office and administrative buildings, educational facilities, laboratory buildings, and outdoor areas in Germany. The BNB was developed by the former Federal Ministry for the Environment, Nature Conservation, Building and Nuclear Safety (BMUB) and is now overseen by the Federal Ministry for Housing, Urban Development and Building (BMWSB).

Criteria	Pos. / product type	Considered substance group	Quality level
1.1.6 Risiken für die lokale Umwelt			Not relevant for assessment

SENTINEL HOLDING
INSTITUT

Product:
DASAPLANO 0,01 connect

SHI Product Passport no.:
12012-10-1097

pro clima®

EU taxonomy

The EU Taxonomy classifies economic activities and products according to their environmental impact. At the product level, the EU regulation defines clear requirements for harmful substances, formaldehyde and volatile organic compounds (VOCs). The Sentinel Holding Institut GmbH labels qualified products that meet this standard.

Criteria	Product type	Considered substances	Assessment
DNSH - Pollution prevention and control	Sonstige	Stoffe nach Anlage C	compliant
Verification: Herstellererklärung vom 01.07.2025			

SENTINEL HOLDING
INSTITUT

Product:
DASAPLANO 0,01 connect

SHI Product Passport no.:
12012-10-1097

pro clima®

BREEAM DE Neubau 2018

BREEAM (Building Research Establishment Environmental Assessment Methodology) is a UK-based building assessment system that evaluates the sustainability of new constructions, refurbishments, and conversions. Developed by the Building Research Establishment (BRE), the system aims to assess and improve the environmental, economic, and social performance of buildings.

Criteria	Product category	Considered substances	Quality level
Hea 02 Indoor Air Quality			Not relevant for assessment

SENTINEL HOLDING
INSTITUT

Product:
DASAPLANO 0,01 connect

SHI Product Passport no.:
12012-10-1097

pro clima®

LEED v4.1

LEED (Leadership in Energy and Environmental Design) is an internationally recognised building certification system developed by the U.S. Green Building Council. It is one of the most widely used sustainability standards for buildings worldwide and is particularly applied in internationally oriented projects. LEED assesses buildings holistically across categories such as energy efficiency, resource conservation, material selection, indoor environmental quality and site sustainability. Depending on the number of points achieved, projects are awarded one of the certification levels: LEED Certified, Silver, Gold or Platinum.

Criteria	Product category	Considered substances	Assessment
EQ Credit: Low-Emitting Materials			Not relevant for assessment

SENTINEL HOLDING
INSTITUT

Product:
DASAPLANO 0,01 connect

SHI Product Passport no.:
12012-10-1097

pro clima®

Product labels

In the construction industry, high-quality materials are crucial for a building's indoor air quality and sustainability. Product labels and certificates offer guidance to meet these requirements. However, the evaluation criteria of these labels vary, and it is important to carefully assess them to ensure products align with the specific needs of a construction project.

Products bearing the Sentinel Holding Institute QNG-ready seal are suitable for projects aiming to achieve the "Qualitätssiegel Nachhaltiges Gebäude" (Quality Seal for Sustainable Buildings). QNG-ready products meet the requirements of QNG Appendix Document 3.1.3, "Avoidance of Harmful Substances in Building Materials." The KfW loan program Climate-Friendly New Construction with QNG may allow for additional funding.

This product is SHI Indoor Air Quality certified and recommended by Sentinel Holding Institut. Indoor-air-focused construction, renovation, and operation of buildings is made possible by transparent and verifiable criteria thanks to the Sentinel Holding concept.

SENTINEL HOLDING
INSTITUT

Product:
DASAPLANO 0,01 connect

SHI Product Passport no.:
12012-10-1097

Legal notices

(*) These criteria apply to the construction project as a whole. While individual products can positively contribute to the overall building score through proper planning, the evaluation is always conducted at the building level. The information was provided entirely by the manufacturer.

Find our criteria here: https://www.sentinel-holding.eu/de/Themenwelten/Pr%C3%BCfkriterien%20f%C3%BCr%20Produkte

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar

Publisher

Sentinel Holding Institut GmbH
Bötzinger Str. 38
79111 Freiburg im Breisgau
Germany
Tel.: +49 761 590 481-70
info@sentinel-holding.eu
www.sentinel-holding.eu

DASAPLANO 0,01 connect

Luftdichtungsbahn für die Dachsanierung von außen und Unterdeck- / Unterspannbahn, mit Selbstklebezonen



Technische Daten

	Stoff
Schutz- und Deckvlies	Polypropylen-Mikrofaser
Membran	monolithische Polymermischung
Selbstklebezonen	wasserfester SOLID-Kleber

Eigenschaft	Regelwerk	Wert
Farbe		hellblau
Flächengewicht	DIN EN 1849-2	145 g/m²
Dicke	DIN EN 1849-2	0,50 mm
Dampfdiffusionswiderstandszahl µ	DIN EN ISO 12572	20
sd-Wert feuchtevariabel	DIN EN ISO 12572	0,01 m
Brandverhalten	DIN EN 13501-1	E
Brandkennziffer (CH)	VKF / AEAI	5.2
Freibewitterung Steildach ab 14° DN		3 Monate
Freibewitterung bei Sanierung zw. 2 Dämmebenen		14 Tage; 7 Tage bei ≤10 °C
Wasserdichtheit Nähte mit connect Verbindungen oder bei Verklebung mit TESCON VANA	DIN EN 13859-1	W1
Unterspannbahn / Unterdeckbahn	ZVDH-Produktdatenblatt 2024	USB / UDB
Behelfsdeckung; geeignet als ...	ZVDH	ja
Widerstand Wasserdurchgang	DIN EN 1928	W1
Wassersäule	DIN EN ISO 811	> 2.500 mm
Luftdichtheit	DIN EN 12114	durchgeführt
Höchstzugkraft längs/quer	DIN EN 12311-2	270 N/5 cm / 200 N/5 cm
Dehnung längs/quer	DIN EN 12311-2	55 % / 70 %
Weiterreißwiderstand längs/quer	DIN EN 12310-1	150 N / 150 N
Dauerhaftigkeit nach künstl. Alterung	DIN EN 1297 / DIN EN 1296	bestanden
Temperaturbeständigkeit		dauerhaft -40 °C bis +100 °C
Wärmeleitzahl		0,04 W/(m·K)
QNG Anforderungen	Anhangdokument 3.1.3	erfüllt
CE-Kennzeichnung	DIN EN 13984 / DIN EN 13859-1	vorhanden

Anwendung

Einsatz als bewitterbare Luftdichtungsbahn für die Dachsanierung von außen bei Volldämmung des bestehenden Sparrengefachs. Verlegung über den Sparren unter einer zusätzlichen Aufsparrendämmung aus Holzfaserunterdeckplatten im Rahmen der Sanierungslösungen von pro clima, sowie für die freigegebenen Sanierungslösungen von Holzfaserplattenherstellern.

Lieferformen

Art.-Nr.	GTIN	Länge	Breite	Inhalt	Gewicht	VE	Gebinde
14086	4026639140869	50 m	1,5 m	75 m²	12 kg	1	20

Die dargestellten Sachverhalte beziehen sich auf den Stand der aktuellen Forschung und der praktischen Erfahrung. Wir behalten uns Änderungen der empfohlenen Konstruktionen und der Verarbeitung sowie die Weiterentwicklung und die damit verbundene Qualitätsänderung der einzelnen Produkte vor. Wir informieren Sie gern über den aktuellen technischen Kenntnisstand zum Zeitpunkt der Verlegung.

Weitere Informationen über die Verarbeitung und Konstruktionsdetails enthalten die pro clima Planungs- und Anwendungsempfehlungen. Bei Fragen erreichen Sie die technische Hotline von pro clima unter 0 62 02 - 27 82.45.

MOLL
bauökologische Produkte GmbH
Rheintalstraße 35 - 43
D-68723 Schwetzingen
Fon: +49 (0) 62 02 - 27 82.0
eMail: info@proclima.de

pro clima®

Vorteile

- ✔ Einfache Herstellung der luftdichten Ebene: Verlegung flächig über Sparren und Dämmung
- ✔ Auch als Unterdeck- und Unterspannbahn einsetzbar
- ✔ Trockene und sichere Bauteile durch aktiven Feuchtetransport
- ✔ Schutz während der Bauphase: geeignet als Behelfsdeckung
- ✔ Schnelle und sichere Verklebung durch integrierte connect-Selbstklebezonen in Bahnenlängsrichtung
- ✔ Beste Werte im Schadstofftest, Prüfung nach AgBB / ISO 16000 durchgeführt

Rahmenbedingungen

DASAPLANO 0,01 connect soll mit der bedruckten Seite zum Verarbeiter hin zeigend verlegt werden. Sie wird straff, waagerecht (parallel zur Traufe) und flächig auf der Gefachdämmung verlegt.

Wird die DASAPLANO 0,01 connect freibewittert bzw. beregnet müssen die Bahnen quer zur Wasserlaufrichtung verlegt werden. Dadurch ist das Bauteil besser vor Feuchteeintrag geschützt.
Um Tauwasserbildung zu vermeiden, sollte der Einbau der Überdämmung unmittelbar nach der luftdichten Verklebung der DASAPLANO 0,01 connect erfolgen. Dies gilt besonders bei Arbeiten im Winter.

Luftdichte Verklebungen können nur auf faltenfrei verlegten Dampfbremsen erreicht werden.

Während der gesamten Sanierungsmaßnahme herrscht innen ein normales Wohnraumklima.

Mit Gipsbauplatten innen: 2:1-Lösung
D.h. 2/3 der Gesamtdämmschichtdicke eines beliebigen Faserdämmstoffes zwischen den Sparren, dann die DASAPLANO 0,01 connect, abschließend mind. 1/3 als Holzfaserunterdeckplatte.
Zusätzlich kann eine der SOLITEX Unterdeckbahnen verlegt werden.

Mit Profilbretter bzw. Putz auf Leistenschalung innen: 3:1-Lösung
D.h. 3/4 der Gesamtdämmschichtdicke eines beliebigen Faserdämmstoffes zwischen den Sparren, dann die DASAPLANO 0,01 connect, abschließend mind. 1/4 als Holzfaserunterdeckplatte.

Empfehlungen von Holzfaserdämmplatten-Herstellern können abweichen. Es gelten dann die Empfehlungen des Herstellers.

Schadstoffgeprüft nach AgBB

ÉMISSIONS DANS L'AIR INTÉRIEUR* A+ (A+ A B C)

*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes missions)

CE 12 EN 13984

CE 12 EN 13859-1

Die dargestellten Sachverhalte beziehen sich auf den Stand der aktuellen Forschung und der praktischen Erfahrung. Wir behalten uns Änderungen der empfohlenen Konstruktionen und der Verarbeitung sowie die Weiterentwicklung und die damit verbundene Qualitätsänderung der einzelnen Produkte vor. Wir informieren Sie gern über den aktuellen technischen Kenntnisstand zum Zeitpunkt der Verlegung.

Weitere Informationen über die Verarbeitung und Konstruktionsdetails enthalten die pro clima Planungs- und Anwendungsempfehlungen. Bei Fragen erreichen Sie die technische Hotline von pro clima unter
0 62 02 - 27 82.45.

MOLL
bauökologische Produkte GmbH
Rheintalstraße 35 - 43
D-68723 Schwetzingen
Fon: +49 (0) 62 02 - 27 82.0
eMail: info@proclima.de

pro clima®

MOLL bauökologische Produkte GmbH
Rheintalstraße 35-43 D-68723 Schwetzingen

Sentinel Holding Institut GmbH
Frau Natalie Szczyglowski
Merzhauser Str. 76
79100 FREIBURG
DEUTSCHLAND

MOLL
bauökologische Produkte GmbH
Rheintalstraße 35-43
D-68723 Schwetzingen

Tel: 06202 27 82 0

info@proclima.de
www.proclima.de

Unser Zeichen:
Michael Förster

Fon: 06202 278245
eMail: michael.foerster@proclima.de

1. Juli 2025

Herstellererklärung SVHC & CMR-Stoffe

Sehr geehrte Frau Szczyglowski,

gerne bestätige ich Ihnen, dass die folgenden auf dem Sentinel Portal gelisteten pro clima Produkte die Anforderungen SVHC < 0,1% (gemäß REACH-Kandidatenliste, Stand 25.05.2025), sowie CMR-Stoffe mit der Einstufung CMR 1A/1B < 0,1% erfüllen:

- AEROSANA VISCONN, AEROSANA VISCONN FIBRE
- CONTEGA IQ, CONTEGA PV, CONTEGA SL
- CONTEGA SOLIDO SL, CONTEGA SOLIDO EXO-D, CONTEGA SOLIDO IQ-D
- TESCON VANA, TESCON No.1, TESCON PROFECT
- UNI TAPE, UNI TAPE XL
- DUPLEX
- EXTOSEAL ENCORS
- ORCON F, ORCON MULTIBOND
- TESCON NAIDECK, TESCON NAIDECK mono
- TESCON PRIMER RP
- KAFLEX mono, KAFLEX duo, ROFLEX 20, ROFLEX 30-300
- INTELLO, INTELLO X, INTELLO PLUS, INTELLO X PLUS
- DA
- DASAPLANO 0,01 connect
- DB+
- SOLITEX ADHERO 3000, SOLITEX ADHERO VISTO
- SOLITEX FRONTA WA
- SOLITEX MENTO 1000-5000 (connect)
- SOLITEX QUANTHO 3000 connect
- SOLITEX ADHERO SENSIS, SENSIS COLL, SENSIS TAPE

Für weitere Fragen erreichen Sie die technische Hotline von pro clima unter der Nummer 06202 - 2782.45.

Mit freundlichen Grüßen
MOLL bauökologische Produkte GmbH



i.V. Michael Förster
Dipl.-Ing.
Bereichsleitung Technik