SENTINEL HOLDING
INSTITUT

SHI PRODUCT PASSPORT

Find products. Certify buildings.

SHI Product Passport No.:

15148-10-1007

Oneflor LVT Designbelag zum Kleben (Dryback)

Product group: Vinyl

ONE FLOR EUROPE

Oneflor Europe B.V.
Wittestraat 10
8501 Heule

Product qualities:

- **SHI** Product Assessment 2024
- **QNG** Qualitätssiegel Nachhaltiges Gebäude
- **DGNB** NEW CONSTRUCTION 2023.2
- **DGNB** NEW CONSTRUCTION 2023
- **DGNB** NEW CONSTRUCTION 2018
- **BNB-BN** NEUBAU V2015
- **EU** TAXONOMY
- **BREEAM** DE NEUBAU 2018
- **LEED** v4.1 (outside US)

CERTIFIED SUSTAINABLE PRODUCT
SHI PRODUCT PASSPORT
SENTINEL HOLDING INSTITUT
www.sentinel-holding.eu

Köttner

Helmut Köttner
Scientific Director
Freiburg, 17 August 2026

SENTINEL HOLDING
INSTITUT

Product:
Oneflor LVT Designbelag zum Kleben (Dryback)

SHI Product Passport no.:
15148-10-1007

ONE FLOR EUROPE

Contents

SHI Product Assessment 2024	1
QNG - Qualitätssiegel Nachhaltiges Gebäude	2
DGNB New Construction 2023.2	3
DGNB New Construction 2023	4
DGNB New Construction 2018	6
BNB-BN Neubau V2015	7
EU taxonomy	8
BREEAM DE Neubau 2018	9
LEED v4.1	10
Product labels	11
Legal notices	12
Technical data sheet/attachments	12

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar

SGS

SGS TÜV SAAR

SENTINEL HOLDING
INSTITUT

Product:
Oneflor LVT Designbelag zum Kleben (Dryback)

SHI Product Passport no.:
15148-10-1007

ONE FLOR EUROPE

SHI Product Assessment 2024

Since 2008, Sentinel Holding Institut GmbH (SHI) has been establishing a unique standard for products that support healthy indoor air. Experts carry out independent product assessments based on clear and transparent criteria. In addition, the independent testing company SGS regularly audits the processes and data accuracy.

Criteria	Product category	Harmful substance limit	Assessment
SHI Product Assessment	Other products	TVOC ≤ 300 µg/m^3 Formaldehyd ≤ 24 µg/m^3	Indoor Air Quality Certified
Valid untill: 28 June 2027			

SENTINEL HOLDING
INSTITUT

Product:
Oneflor LVT Designbelag zum Kleben (Dryback)

SHI Product Passport no.:
15148-10-1007

ONE FLOR EUROPE

QNG - Qualitätssiegel Nachhaltiges Gebäude

The Qualitätssiegel Nachhaltiges Gebäude (Quality Seal for Sustainable Buildings), developed by the German Federal Ministry for Housing, Urban Development and Building (BMWSB), defines requirements for the ecological, socio-cultural, and economic quality of buildings. The Sentinel Holding Institut evaluates construction products in accordance with QNG requirements for certification and awards the QNG ready label. Compliance with the QNG standard is a prerequisite for eligibility for the KfW funding programme. For certain product groups, the QNG currently has no specific requirements defined. Although classified as not assessment-relevant, these products remain suitable for QNG-certified projects.

Criteria	Pos. / product group	Considered substances	QNG assessment
3.1.3 Schadstoffvermeidung in Baumaterialien	2.2 Resilient floor coverings – including multilayer systems	VOC / Emissions / hazardous substances / polycyclic aromatic hydrocarbons (PAH) / SVHC / heavy metals	QNG ready
Verification: Prüfbericht des Instituts Normec Product Testing vom 28.06.2023. Herstellererklärung vom 13.11.2025			

SENTINEL HOLDING
INSTITUT

Product:
Oneflor LVT Designbelag zum Kleben (Dryback)

SHI Product Passport no.:
15148-10-1007

ONE FLOR EUROPE

DGNB New Construction 2023.2

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact			Not relevant for assessment

SENTINEL HOLDING
INSTITUT

Product:
Oneflor LVT Designbelag zum Kleben (Dryback)

SHI Product Passport no.:
15148-10-1007

ONE FLOR EUROPE

DGNB New Construction 2023

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings. The 2023 version sets high standards for ecological, economic, socio-cultural, and functional aspects throughout the entire life cycle of a building.

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 03.05.2024 (3rd edition)	7 Floor coverings (Resilient floor coverings)	VVOCs, VOC, SVOC emissions and content of hazardous substances	Quality level 3
Verification: Prüfbericht des Instituts Normec Product Testing vom 28.06.2023. Herstellererklärung vom 13.11.2025			

Criteria	Assessment
SOC1.2 Indoor air quality (*)	May positively contribute to the overall building score
Verification: SHI Schadstoffgeprüft	

Criteria	Assessment
SOC1.3 Sound insulation and acoustic comfort (*)	May positively contribute to the overall building score
Verification: TDB	

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 29.05.2025 (4th edition)	7 Floor coverings for indoor use (elastic floor coverings)	VVOCs, VOC, SVOC emissions and content of hazardous substances	Quality level 3
Verification: Prüfbericht des Instituts Normec Product Testing vom 28.06.2023. Herstellererklärung vom 13.11.2025			

SENTINEL HOLDING
INSTITUT

Product:
Oneflor LVT Designbelag zum Kleben (Dryback)

SHI Product Passport no.:
15148-10-1007

ONE FLOR EUROPE

DGNB New Construction 2018

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings.

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact	7 Floor coverings (Resilient floor coverings)	VOC / SVOC / hazardous substances	Quality level 4
Verification: Prüfbericht des Instituts Normec Product Testing vom 28.06.2023. Herstellererklärung vom 13.11.2025			

SENTINEL HOLDING
INSTITUT

Product:
Oneflor LVT Designbelag zum Kleben (Dryback)

SHI Product Passport no.:
15148-10-1007

ONE FLOR EUROPE

BNB-BN Neubau V2015

The Bewertungssystem Nachhaltiges Bauen (Assessment System for Sustainable Building) is a tool for evaluating public office and administrative buildings, educational facilities, laboratory buildings, and outdoor areas in Germany. The BNB was developed by the former Federal Ministry for the Environment, Nature Conservation, Building and Nuclear Safety (BMUB) and is now overseen by the Federal Ministry for Housing, Urban Development and Building (BMWSB).

Criteria	Pos. / product type	Considered substance group	Quality level
1.1.6 Risiken für die lokale Umwelt	2a Elastic floor coverings – with and without bonded underlay or insulation layer	VOC / hazardous substances / heavy metals	Quality level 3
Verification: Prüfbericht des Instituts Normec Product Testing vom 28.06.2023. Herstellererklärung vom 13.11.2025			

SENTINEL HOLDING
INSTITUT

Product:
Oneflor LVT Designbelag zum Kleben (Dryback)

SHI Product Passport no.:
15148-10-1007

ONE FLOR EUROPE

EU taxonomy

The EU Taxonomy classifies economic activities and products according to their environmental impact. At the product level, the EU regulation defines clear requirements for harmful substances, formaldehyde and volatile organic compounds (VOCs). The Sentinel Holding Institut GmbH labels qualified products that meet this standard.

Criteria	Product type	Considered substances	Assessment
DNSH - Pollution prevention and control	Floor coverings (including associated adhesives and sealants)	Stoffe nach Anlage C, Formaldehyd, Karzinogene VOC Kategorie 1A/1B	compliant
Verification: Prüfbericht des Instituts Normec Product Testing vom 28.06.2023. Herstellererklärung vom 13.11.2025			

SENTINEL HOLDING
INSTITUT

Product:
Oneflor LVT Designbelag zum Kleben (Dryback)

SHI Product Passport no.:
15148-10-1007

ONE FLOR EUROPE

BREEAM DE Neubau 2018

BREEAM (Building Research Establishment Environmental Assessment Methodology) is a UK-based building assessment system that evaluates the sustainability of new constructions, refurbishments, and conversions. Developed by the Building Research Establishment (BRE), the system aims to assess and improve the environmental, economic, and social performance of buildings.

Criteria	Product category	Considered substances	Quality level
Hea 02 Indoor Air Quality	Flooring materials (including floor levelling compounds and resin flooring)	Emissions: Formaldehyde, TVOC, TSVOC, carcinogens	Exemplary quality
Verification: Prüfbericht des Instituts Normec Product Testing vom 28.06.2023.			

SENTINEL HOLDING
INSTITUT

Product:
Oneflor LVT Designbelag zum Kleben (Dryback)

SHI Product Passport no.:
15148-10-1007

ONE FLOR EUROPE

LEED v4.1

LEED (Leadership in Energy and Environmental Design) is an internationally recognised building certification system developed by the U.S. Green Building Council. It is one of the most widely used sustainability standards for buildings worldwide and is particularly applied in internationally oriented projects. LEED assesses buildings holistically across categories such as energy efficiency, resource conservation, material selection, indoor environmental quality and site sustainability. Depending on the number of points achieved, projects are awarded one of the certification levels: LEED Certified, Silver, Gold or Platinum.

Criteria	Product category	Considered substances	Assessment
EQ Credit: Low-Emitting Materials	Bodenbeläge	Emissionen: Formaldehyd, VOC, Krebserregende Stoffe	compliant
Verification: Prüfbericht des Instituts Normec Product Testing vom 28.06.2023			

SENTINEL HOLDING
INSTITUT

Product:
Oneflor LVT Designbelag zum Kleben (Dryback)

SHI Product Passport no.:
15148-10-1007

ONE FLOR EUROPE

Product labels

In the construction industry, high-quality materials are crucial for a building's indoor air quality and sustainability. Product labels and certificates offer guidance to meet these requirements. However, the evaluation criteria of these labels vary, and it is important to carefully assess them to ensure products align with the specific needs of a construction project.



This product is SHI Indoor Air Quality certified and recommended by Sentinel Holding Institut. Indoor-air-focused construction, renovation, and operation of buildings is made possible by transparent and verifiable criteria thanks to the Sentinel Holding concept.



Products bearing the Sentinel Holding Institute QNG-ready seal are suitable for projects aiming to achieve the "Qualitätssiegel Nachhaltiges Gebäude" (Quality Seal for Sustainable Buildings). QNG-ready products meet the requirements of QNG Appendix Document 3.1.3, "Avoidance of Harmful Substances in Building Materials." The KfW loan program Climate-Friendly New Construction with QNG may allow for additional funding.

Product:
Oneflor LVT Designbelag zum Kleben (Dryback)

SHI Product Passport no.:
15148-10-1007

ONE FLOR EUROPE

Legal notices

(*) These criteria apply to the construction project as a whole. While individual products can positively contribute to the overall building score through proper planning, the evaluation is always conducted at the building level. The information was provided entirely by the manufacturer.

Find our criteria here: https://www.sentinel-holding.eu/de/Themenwelten/Pr%C3%BCfkriterien%20f%C3%BCr%20Produkte

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar

SGS TÜV SAAR

Publisher

Sentinel Holding Institut GmbH
Bötzinger Str. 38
79111 Freiburg im Breisgau
Germany
Tel.: +49 761 590 481-70
info@sentinel-holding.eu
www.sentinel-holding.eu

TECHNICAL DATASHEET ECO 30 (HOME 30)

Update: March 2020

ONE FLOR EUROPE

PRODUCT SPECIFICATIONS	STANDARD	ECO 30 (HOME 30)
Product standard / Belagsart / Standard produit	-	EN ISO 10582
Product standard / Belagsart / Standard produit	-	Heterogeneous resilient floorcovering Heterogener elastischer Designbodenbelag Revêtements de sol résilients hétérogènes
Total thickness / Gesamtstärke / Epaisseur totale	EN ISO 24346	2,0 mm
Wear layer thickness / Nutzschichtdicke / Epaisseur couche d'usure	EN ISO 24340	0,30 mm
Classification / Nutzungsklasse / Classe d'usage	EN ISO 10874	Domestic: 23 Commercial: 31 -
Total weight / Gesamtgewicht / Poids total	EN ISO 23997	3.605 g/m²
Wear layer binder content / Bindemittelgehalt / Teneur en agent liant (couche d'usure)	EN ISO 10582	Type I / Typ I / Type I
Abrasion group / Verschleißprüfung / Groupe d'abrasion	EN 660-2	Group T: ≤ 2,00 mm³
Dimensions / Dielengröße / Dimensions	EN ISO 24342	Planks / Dielen / Lames: 185 x 1219,2 mm 21 planks/box = 4,74m² 60 boxes/pallet = 284,4m² Tiles / Fliesen / Dalles: 457,2 x 914,4 mm 12 tiles/box = 5,02m² 58 boxes/pallet = 291,16m² Tiles / Fliesen / Dalles: 304,8 x 609,6 mm 24 tiles/box = 4,46m² 68 boxes/pallet = 294,36m²
Surface treatment / Oberflächenvergütung / Traitement de surface	-	PUR Ecoprotec™
Locking system / Klick System / Type de clic	-	Dry back / Zum kleben / A coller
Bevelled edges / Gefaste Kanten (Füge) / Chanfrein	-	Yes / Ja / Oui (Micro bevel)


PRODUCT PERFORMANCES	STANDARD	ECO 30 (HOME 30)
Dimensional stability / Dimensionsstabilität / Stabilité dimensionnelle	EN ISO 23999	≤ 0,10 %
Castor chair / Schreibtischstuhl / Chaise à roulettes	ISO 4918	No damage / Keine Schäden / Aucun dommage (Type W)
Furniture leg / Möbelfüße / Pied de meuble	EN ISO 16581	No damage / Keine Schäden / Aucun dommage
Squareness & straightness / Rechtwinklichkeit & Geradheit / Equerrage	EN ISO 24342	≤ 0,25 mm
Residual indentation / Eindruckverhalten / Poinçonnement statique rémanent	EN ISO 24343-1	≤ 0,10 mm
Impact sound reduction / Trittschalldämmung / Isolation acoustique	EN ISO 717-2	ΔLw = 6 dB
Light fastness / Lichtechtheit / Solidité lumière	EN ISO 105-B02	≥ 6
Slip resistance / Rutschhemmung / Glissance	DIN 51130 EN 13893	R10 DS
Resistance to chemicals / Chemikalienbeständigkeit / Résistance aux produits chimiques	EN ISO 26987	Not affected (0) / Nicht verändert (0) / Non affecté (0)
Thermal resistance / Wärmewiderstand / Conductivité thermique	EN ISO 10456	0,02 m² K/W
Curl after exposure to heat / Curling nach Wärmeeinwirkung / Incurvation après exposition à la chaleur	EN ISO 23999	≤ 2 mm
Fire resistance / Brandverhalten / Classement feu	EN 13501-1	Bfl-s1
Electrical properties / Elektrostatische Eigenschaften / Charges électrostatiques	EN 1815	≤ 2kV
Resistance against staining / Bestimmung der Fleckenempfindlichkeit / Résistance aux tâches	EN 26987	Passed / Bestanden / Haute résistance
Underfloor heating suitability / Fußbodenheizung / Compatibilité chauffage par le sol	EN 12524	Suitable / Geeignet / Compatible - max. 27°c

ENVIRONMENT	STANDARD	ECO 30 (HOME 30)
TVOC after 28 days (AgBB test) - Indoor air quality / Raumluftqualität / Qualité de l'air intérieur	ISO 16000-9	≤ 100µg/m³
VOC emission class (French regulation) - Indoor air quality / Raumluftqualität / Qualité de l'air intérieur	ISO 16000-9	A+
Floorscore VOC test - Indoor air quality / Raumluftqualität / Qualité de l'air intérieur	ISO 16000-9	Passed / Bestanden / Passé
Plasticizer / Weichmacher / Plastifiant	-	Phthalate-free / Phthatalfrei / Sans phtalate
Formaldehyde group / Formaldehyde Gruppe / Groupe formaldéhyde	EN 717-1	E1
Recyclability / Recyclingfähigkeit / Recyclabilité	-	100%

WARRANTIES	-	ECO 30 (HOME 30)
Residential warranty / Garantie im Wohnbereich / Garantie en usage résidentiel	-	25 years / Jahre / ans
Commercial warranty / Garantie im Objektbereich / Garantie en usage commercial	-	5 years / Jahre / ans

CE MARKING	-	ECO 30 (HOME 30)
DoP number / DoP Nummer / Numéro de DoP	-	No. 001-520











TECHNICAL DATASHEET CLASSIC30 XL

Update: January 2020

ONE FLOR EUROPE

PRODUCT SPECIFICATIONS	STANDARD	CLASSIC 30 XL
Product standard / Belagsart / Standard produit	-	EN ISO 10582
Product standard / Belagsart / Standard produit	-	Heterogeneous resilient floorcovering Heterogener elastischer Designbodenbelag Revêtements de sol résilients hétérogènes
Total thickness / Gesamtstärke / Epaisseur totale	EN ISO 24346	2,0 mm
Wear layer thickness / Nutzschichtdicke / Epaisseur couche d'usure	EN ISO 24340	0,30 mm
Classification / Nutzungsklasse / Classe d'usage	EN ISO 10874	Domestic: 23 Commercial: 31 -
Total weight / Gesamtgewicht / Poids total	EN ISO 23997	4.000 g/m²
Wear layer binder content / Bindemittelgehalt / Teneur en agent liant (couche d'usure)	EN ISO 10582	Type I / Typ I / Type I
Abrasion group / Verschleißprüfung / Groupe d'abrasion	EN 660-2	Group T: ≤ 2,00 mm³
Dimensions / Dielengröße / Dimensions	EN ISO 24342	Planks / Dielen / Lames: 228,6 x 1524 mm 14 planks/box = 4,87m² 48 boxes/pallet = 233,76m²
Surface treatment / Oberflächenvergütung / Traitement de surface	-	PUR EcoprotecTM
Locking system / Klick System / Type de clic	-	Dry back / Zum kleben / A coller
Bevelled edges / Gefaste Kanten (Füge) / Chanfrein	-	Yes / Ja / Oui (Micro bevel)

PRODUCT PERFORMANCES	STANDARD	CLASSIC 30 XL
Dimensional stability / Dimensionsstabilität / Stabilité dimensionnelle	EN ISO 23999	≤ 0,10 %
Castor chair / Schreibtischstuhl / Chaise à roulettes	ISO 4918	No damage / Keine Schäden / Aucun dommage (Type W)
Furniture leg / Möbelfüße / Pied de meuble	EN ISO 16581	No damage / Keine Schäden / Aucun dommage
Squareness & straightness / Rechtwinklichkeit & Geradheit / Equerrage	EN ISO 24342	≤ 0,25 mm
Residual indentation / Eindruckverhalten / Poinçonnement statique rémanent	EN ISO 24343-1	≤ 0,10 mm
Impact sound reduction / Trittschalldämmung / Isolation acoustique	EN ISO 717-2	ΔLw = 6 dB
Light fastness / Lichtechtheit / Solidité lumière	EN ISO 105-B02	≥ 6
Slip resistance / Rutschhemmung / Glissance	DIN 51130 EN 13893	R10 DS
Resistance to chemicals / Chemikalienbeständigkeit / Résistance aux produits chimiques	EN ISO 26987	Not affected (0) / Nicht verändert (0) / Non affecté (0)
Thermal resistance / Wärmewiderstand / Conductivité thermique	EN ISO 10456	0,02 m² K/W
Curl after exposure to heat / Curling nach Wärmeeinwirkung / Incurvation après exposition à la chaleur	EN ISO 23999	≤ 2 mm
Fire resistance / Brandverhalten / Classement feu	EN 13501-1	Bfl-s1
Electrical properties / Elektrostatische Eigenschaften / Charges électrostatiques	EN 1815	≤ 2kV
Resistance against staining / Bestimmung der Fleckenempfindlichkeit / Résistance aux tâches	EN 26987	Passed / Bestanden / Haute résistance
Underfloor heating suitability / Fußbodenheizung / Compatibilité chauffage par le sol	EN 12524	Suitable / Geeignet / Compatible - max. 27°c

ENVIRONMENT	STANDARD	CLASSIC 30 XL
TVOC after 28 days (AgBB test) - Indoor air quality / Raumluftqualität / Qualité de l'air intérieur	ISO 16000-9	≤ 100µg/m³
VOC emission class (French regulation) - Indoor air quality / Raumluftqualität / Qualité de l'air intérieur	ISO 16000-9	A+
Floorscore VOC test - Indoor air quality / Raumluftqualität / Qualité de l'air intérieur	ISO 16000-9	Passed / Bestanden / Passé
Plasticizer / Weichmacher / Plastifiant	-	Phthalate-free / Phthatalfrei / Sans phtalate
Formaldehyde group / Formaldehyde Gruppe / Groupe formaldéhyde	EN 717-1	E1
Recyclability / Recyclingfähigkeit / Recyclabilité	-	100%

WARRANTIES	-	CLASSIC 30 XL
Residential warranty / Garantie im Wohnbereich / Garantie en usage résidentiel	-	25 years / Jahre / ans
Commercial warranty / Garantie im Objektbereich / Garantie en usage commercial	-	5 years / Jahre / ans

CE MARKING	-	CLASSIC 30 XL
DoP number / DoP Nummer / Numéro de DoP	-	No. 20-KS-001



TECHNICAL DATASHEET ECO55 (WORKSHOP 55 ^{EIR})

Update: June 2021

ONE FLOR EUROPE

PRODUCT SPECIFICATIONS	STANDARD	ECO 55 (WORKSHOP 55)
Product standard / Belagsart / Standard produit	-	EN ISO 10582
Product standard / Belagsart / Standard produit	-	Heterogeneous resilient floorcovering Heterogener elastischer Designbodenbelag Revêtements de sol résilients hétérogènes
Total thickness / Gesamtstärke / Epaisseur totale	EN ISO 24346	2,5 mm
Wear layer thickness / Nutzschichtdicke / Epaisseur couche d'usure	EN ISO 24340	0,55 mm
Classification / Nutzungsklasse / Classe d'usage	EN ISO 10874	Domestic: 23 Commercial: 33 Industrial: 42 Conçu pour usage en Locaux classés U3P3
Total weight / Gesamtgewicht / Poids total	EN ISO 23997	4.750 g/m²
Wear layer binder content / Bindemittelgehalt / Teneur en agent liant (couche d'usure)	EN ISO 10582	Type I / Typ I / Type I
Abrasion group / Verschleißprüfung / Groupe d'abrasion	EN 660-2	Group T: ≤ 2,00 mm³
Dimensions / Dielengröße / Dimensions	EN ISO 24342	Planks / Dielen / Lames: 184,1 x 1219,2 mm 20 planks/box = 4,49m² 40 boxes/pallet = 179,60m²
		Tiles / Fliesen / Dalles: 457,2 x 914,4 mm 10 tiles/box = 4,18m² 42 boxes/pallet = 175,56m²
		Planks / Dielen / Lames (Herringbones): 120 x 600 mm 32 planks/box = 2,30m² 80 boxes/pallet = 184m²
		Planks / Dielen / Lames (Chevrons): 152,4 x 1066,8 mm 16 planks/box = 2,60m² 66 boxes/pallet = 171,60m²
Surface treatment / Oberflächenvergütung / Traitement de surface	-	PUR Ecoprotec™
Locking system / Klick System / Type de clic	-	Dry back / Zum kleben / A coller
Bevelled edges / Gefaste Kanten (Füge) / Chanfrein	-	Yes / Ja / Oui (except Chevrons)

PRODUCT PERFORMANCES	STANDARD	ECO 55 (WORKSHOP 55)
Dimensional stability / Dimensionsstabilität / Stabilité dimensionnelle	EN ISO 23999	≤ 0,10 %
Castor chair / Schreibtischstuhl / Chaise à roulettes	ISO 4918	No damage / Keine Schäden / Aucun dommage (Type W)
Furniture leg / Möbelfüße / Pied de meuble	EN ISO 16581	No damage / Keine Schäden / Aucun dommage
Squareness & straightness / Rechtwinklichkeit & Geradheit / Equerrage	EN ISO 24342	≤ 0,25 mm
Residual indentation / Eindruckverhalten / Poinçonnement statique rémanent	EN ISO 24343-1	≤ 0,10 mm
Impact sound reduction / Trittschalldämmung / Isolation acoustique	EN ISO 717-2	ΔLw = 6 dB
Light fastness / Lichtechtheit / Solidité lumière	EN ISO 105-B02	≥ 6
Slip resistance / Rutschhemmung / Glissance	DIN 51130 EN 13893	R10 DS
Resistance to chemicals / Chemikalienbeständigkeit / Résistance aux produits chimiques	EN ISO 26987	Not affected (0) / Nicht verändert (0) / Non affecté (0)
Thermal resistance / Wärmewiderstand / Conductivité thermique	EN ISO 10456	0,02 m² K/W
Curl after exposure to heat / Curling nach Wärmeeinwirkung / Incurvation après exposition à la chaleur	EN ISO 23999	≤ 2 mm
Fire resistance / Brandverhalten / Classement feu	EN 13501-1	Bfl-s1
Electrical properties / Elektrostatische Eigenschaften / Charges électrostatiques	EN 1815	≤ 2kV
Resistance against staining / Bestimmung der Fleckenempfindlichkeit / Résistance aux tâches	EN 26987	Passed / Bestanden / Haute résistance
Underfloor heating suitability / Fußbodenheizung / Compatibilité chauffage par le sol	EN 12524	Suitable / Geeignet / Compatible - max. 27°c

ENVIRONMENT	STANDARD	ECO 55 (WORKSHOP 55)
TVOC after 28 days (AgBB test) - Indoor air quality / Raumluftqualität / Qualité de l'air intérieur	ISO 16000-9	≤ 100µg/m³
VOC emission class (French regulation) - Indoor air quality / Raumluftqualität / Qualité de l'air intérieur	ISO 16000-9	A+
Floorscore VOC test - Indoor air quality / Raumluftqualität / Qualité de l'air intérieur	ISO 16000-9	Passed / Bestanden / Passé
Plasticizer / Weichmacher / Plastifiant	-	Phthalate-free / Phthatalfrei / Sans phtalate
Formaldehyde group / Formaldehyde Gruppe / Groupe formaldéhyde	EN 717-1	E1
Recyclability / Recyclingfähigkeit / Recyclabilité	-	100%

WARRANTIES	-	ECO 55 (WORKSHOP 55)
Residential warranty / Garantie im Wohnbereich / Garantie en usage résidentiel	-	25 years / Jahre / ans
Commercial warranty / Garantie im Objektbereich / Garantie en usage commercial	-	10 years / Jahre / ans

CE MARKING	-	ECO 55 (WORKSHOP 55)
DoP number / DoP Nummer / Numéro de DoP	-	No. 21-SW-001

23 33 42

CE EN 14041:2004 DOP:21-SW-001 Resilient Flooring to be used within a building.

KSA ISO 9001 KSA ISO14001

floor score

ÉMISSIONS DANS L'AIR INTÉRIEUR A+ A B C

TECHNICAL DATASHEET CLASSIC55 XL (EIR)

ONE FLOR EUROPE

PRODUCT SPECIFICATIONS	STANDARD	CLASSIC 55 XL (EIR)
Product standard / Belagsart / Standard produit / Product standaard	-	EN ISO 10582
Product standard / Belagsart / Standard produit / Product standaard	-	Heterogeneous resilient floorcovering Heterogener elastischer Designbodenbelag Revêtements de sol résilients hétérogènes Heterogene veerkrachtige vloerbedekking
Total thickness / Gesamtstärke / Epaisseur totale / Totale dikte	EN ISO 24346	2,5 mm
Wear layer thickness / Nutzschichtdicke / Epaisseur couche d'usure / Slijtlaagdikte	EN ISO 24340	0,55 mm
Classification / Nutzungsklasse / Classe d'usage / Classificatie	EN ISO 10874	Domestic: 23 Commercial: 33 Industrial: 42
Total weight / Gesamtgewicht / Poids total / Totale gewicht	EN ISO 23997	4.750 g/m²
Wear layer binder content / Bindemittelgehalt / Teneur en agent liant / Inhoud van het bindmiddel	EN ISO 10582	Type I / Typ I / Type I / Typ I
Abrasion group / Verschleißprüfung / Groupe d'abrasion / Slijtage groep	EN 660-2	Group T: ≤ 2,00 mm³
Dimensions / Dielengröße / Dimensions / Afmetingen	EN ISO 24342	Planks / Dielen / Lames / Planken: 228,6 x 1524 mm 12 planks/box = 4,18m² 40 boxes/pallet = 167,20m²
Surface treatment / Oberflächenvergütung / Traitement de surface / Oppervlakte behandeling	-	PUR Ecoprotec™
Locking system / Klick System / Type de clic / Vergrendelingssysteem	-	Dry back / Zum kleben / A coller / Te lijmen
Bevelled edges / Gefaste Kanten (Füge) / Chanfrein / Schuine randen	-	Yes / Ja / Oui / Ja (Micro bevel)

PRODUCT PERFORMANCES	STANDARD	CLASSIC 55 XL (EIR)
Dimensional stability / Dimensionsstabilität / Stabilité dimensionnelle / Dimensionale stabiliteit	EN ISO 23999	≤ 0,10 %
Castor chair / Schreibtischstuhl / Chaise à roulettes / Rolstoeltest	ISO 4918	No damage / Keine Schäden / Aucun dommage / Geen schade (Type W)
Furniture leg / Möbelfüße / Pied de meuble / Meubelpoottest	EN ISO 16581	No damage / Keine Schäden / Aucun dommage / Geen schade
Squareness & straightness / Rechtwinklichkeit & Geradheit / Equerrage et rectitude / Verandering in vierkant & rechtheid	EN ISO 24342	≤ 0,25 mm
Residual indentation / Eindruckverhalten / Poinçonnement statique rémanent / Resterende inkeping	EN ISO 24343-1	≤ 0,10 mm
Impact sound reduction / Trittschalldämmung / Isolation acoustique / Effect geluidsreductie	EN ISO 717-2	ΔLw = 6 dB
Light fastness / Lichtechtheit / Solidité lumière / Lichtvastheid	EN ISO 105-B02	≥ 6
Slip resistance / Rutschhemmung / Glissance / Slipweerstand	DIN 51130 EN 13893	R10 DS
Resistance to chemicals / Chemikalienbeständigkeit / Résistance aux produits chimiques / Weerstand tegen chemicalien	EN ISO 26987	Not affected (0) / Nicht verändert (0) / Non affecté / Niet aangetast (0)
Thermal resistance / Wärmewiderstand / Conductivité thermique / Warmteweerstand	EN ISO 10456	0,02 m² K/W
Curl after exposure to heat / Curling nach Wärmeeinwirkung / Incurvation après exposition à la chaleur / Krul na blootstelling aan hitte	EN ISO 23999	≤ 2 mm
Fire resistance / Brandverhalten / Classement feu / Brandveiligheid	EN 13501-1	Bfl-s1
Electrical properties / Elektrostatische Eigenschaften / Charges électrostatiques / Elektrische weerstand	EN 1815	≤ 2kV
Resistance against staining / Bestimmung der Fleckenempfindlichkeit / Résistance aux taches / Bestendigheid tegen vlekken	EN 26987	Passed / Bestanden / Haute résistance / Geslaagd
Underfloor heating suitability / Fußbodenheizung / Compatibilité chauffage par le sol / Geschikt voor vloerverwarming	EN 12524	Suitable / Geeignet / Compatible / Geschikt - max. 27°c

ENVIRONMENT	STANDARD	CLASSIC 55 XL (EIR)
TVOC after 28 days (AgBB test) - Indoor air quality / Raumluftqualität / Qualité de l'air intérieur / Luchtkwaliteit binnenshuis	ISO 16000-9	≤ 100µg/m³
VOC emission class (French regulation) - Indoor air quality / Raumluftqualität / Qualité de l'air intérieur / Luchtkwaliteit binnenshuis	ISO 16000-9	A+
Plasticizer / Weichmacher / Plastifiant / Weekmaker	-	Phthalate-free / Phthatalfrei / Sans phtalate / Phthalaat-vrij
Formaldehyde group / Formaldehyde Gruppe / Groupe formaldéhyde / Formaldehyde groep	EN 717-1	E1
Recyclability / Recyclingfähigkeit / Recyclabilité / Recycleerbaarheid	-	100%

WARRANTIES	-	CLASSIC 55 XL (EIR)
Residential warranty / Garantie im Wohnbereich / Garantie en usage résidentiel / Woongarantie	-	25 years / Jahre / ans / jaar
Commercial warranty / Garantie im Objektbereich / Garantie en usage commercial / Commerciële garantie	-	10 years / Jahre / ans / jaar

CE MARKING	-	CLASSIC 55 XL (EIR)
DoP number / DoP Nummer / Numéro de DoP / DoP nummer	-	No. 23-SW-002

VOC emission Attestation

ONEFLOR EUROPE bv
Wittestraat 10
8501 Heule
Belgium

Product group **Dryback LVT**

Applicable products: ECO30 / CLASSIC30XL (2mm 0.30WL), ECO55 / CLASSIC55XL (2.5mm 0.55WL), ECOLAY70 (5mm 0.70WL) and ECOLOCK70 (5mm 0.70WL)

Attestation date: 30-06-2023

Testing was performed according to the latest version of EN 16516 by ISO/IEC 17025 accredited test laboratory Normec Product Testing. This attestation confirms compliance with the following VOC requirements on low emitting regulations, standards or protocols:

Regulation or protocol	Conclusion	Version of regulation of protocol
French VOC regulations		Arrêté du 28 mai 2009 modifiant l'arrêté du 30 avril 2009, Arrêté du 20 février 2012 modifiant l'arrêté du 19 avril 2011, Décret no 2011-321 du 23 mars 2011
German AgBB (2021)/ABG (2022)	Pass	AgBB - Evaluation procedure for VOC emissions from building products, June 2021
Belgian legislation	Pass	Royal Decree: 8 MEI 2014
Italian regulation (public procurement)	Pass	Decree 11 October 2017 (GAZZETTA UFFICIALE DELLA REPUBBLICA n.259 - 6-11-2017)
BREEAM International	Pass/Exemplary	BREEAM International New Construction 2021 v6.0
BREEAM Norway	Pass/Exemplary	BREEAM-NOR 2022 v6.0: New Construction
BREEAM NL	Pass/Exemplary	BREEAM-NL Nieuwbouw 2020
BREEAM UK	Pass/Exemplary	BREEAM UK New Construction 2022 v6.0
WELL (EU)	Pass	WELL v2 2021 - Concept Materials X06 VOC restrictions
LEED (EU) 4.1	Pass	LEED v4.1 Building design and construction April 2023 – section EQ Credit: Low-Emitting Materials
M1	Pass/M1	M1 Emission Classification of Building Materials: Protocol for Chemical and Sensory Testing of Building Materials - Version 15.11.2017 + CMR update January 2019
DICL	Pass/Emission class 1	Danish Indoor Climate Labelling, General test and labelling criteria, 7th Edition, May 2021
ECOproduct	Pass/very low emitting	ECOproduct Method description version 5.1, 29-10-2020
SINTEF	Pass	SINTEF Environmental certificate v09/05/2022
Nordic Swan	Pass	Nordic Ecolabelling of Floor coverings: Version 6.8 - 18 November 2014 - 30 June 2023
Byggvarubedömningen	Pass	SWEDISH BUILDING MATERIALS ASSESSMENT Version 5.0
Austrian Ecolabel	Pass	UZ 42: Elastic floor coverings, 2019

Full details on the testing and direct comparison with limit values are available in test reports SPT2023-R200 and SPT2023-R181 For reporting statements of conformity (decision rule) the measurement uncertainty is not taken into account.

SPT2023-R181

M. Lor
Managing Director Normec Product Testing

Normec Product Testing

Test results are only valid for the tested sample(s), as received from the client. Test report may only be copied or reprinted in this entity, parts of it only with a written acceptance by Normec Product Testing.

Honderdweg 13
9230 Wetteren
Belgium

ONE FLOR EUROPE

Oneflor Europe
Wittestraat 10 B-8501 Heule
Tel. +32 56 41 06 04
info@oneflor-europe.com
www.oneflor-europe.com

Heule,13.11.2025

Manufacturer's declaration

We hereby declare that our LVT floor coverings **Eco 30, Linea 30, Solid Click 30, Classic 30 XL, Rigid Click 30, Eco 55, Solid Click 55, Mercury 2.0 Classic, Mercury 2.0 Rigid, Classic 55 XL, Rigid 55 XL, Eco Acoustic 55, Ecolay 55 and Ultra Lock Pro** are free of harmful substances in accordance with the REACH Regulation and therefore fulfill the following product requirements:

- SVHC < 0.1%
- Chlorinated paraffins (SCCPs + MCCPs + LCCPs) < 0.1%
- Phthalates toxic to reproduction < 0.1%
- CMR substances of category 1A and 1B < 0.1%
- No tin, cadmium and lead stabilizers

This declaration is made to ensure compliance with applicable regulations and to guarantee the safety of our products for consumers and the environment.

Alban Parisse
- Product & Marketing Manager-

ONE FLOR EUROPE

ONEFLOR EUROPE BVBA
Wittestraat 10 – 8501 Heule
BELGIUM
tel.: +32 56 41 06 04
VAT: BE0645736720
info@oneflor-europe.com

ONE FLOR EUROPE
www.oneflor-europe.com