SENTINEL HOLDING
INSTITUT

SHI PRODUCT PASSPORT

Find products. Certify buildings.

SHI Product Passport No.:

1548-10-1004

btf Flexibel New

Product group: Vapor barriers / vapor retarders

btf Innovationen für den Bau GmbH
Fahrenheitstraße 3
86899 Landsberg

Product qualities:

- SHI Product Assessment 2024
- QNG Qualitätssiegel Nachhaltiges Gebäude
- DGNB NEW CONSTRUCTION 2023
- DGNB NEW CONSTRUCTION 2018
- BNB-BN NEUBAU V2015
- EU taxonomy
- BREEAM DE NEUBAU 2018
- LEED v4.1 (outside US)

CERTIFIED SUSTAINABLE PRODUCT
SHI PRODUCT PASSPORT
SENTINEL HOLDING INSTITUT
www.sentinel-holding.eu

Köttner

Helmut Köttner
Scientific Director
Freiburg, 04 April 2026

SENTINEL HOLDING
INSTITUT

Product:
btf Flexibel New

SHI Product Passport no.:
1548-10-1004

Contents

SHI Product Assessment 2024	1
QNG - Qualitätssiegel Nachhaltiges Gebäude	2
DGNB New Construction 2023	3
DGNB New Construction 2018	4
BNB-BN Neubau V2015	5
EU taxonomy	6
BREEAM DE Neubau 2018	7
LEED v4.1	8
Product labels	9
Legal notices	10
Technical data sheet/attachments	11

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar

SENTINEL HOLDING
INSTITUT

Product:
btf Flexibel New

SHI Product Passport no.:
1548-10-1004

SHI Product Assessment 2024

Since 2008, Sentinel Holding Institut GmbH (SHI) has been establishing a unique standard for products that support healthy indoor air. Experts carry out independent product assessments based on clear and transparent criteria. In addition, the independent testing company SGS regularly audits the processes and data accuracy.

Criteria	Product category	Harmful substance limit	Assessment
SHI Product Assessment	Other products	TVOC ≤ 300 µg/m^3 Formaldehyd ≤ 24 µg/m^3	Indoor Air Quality Certified
Valid untill: 17 December 2027			

SENTINEL HOLDING
INSTITUT

Product:
btf Flexibel New

SHI Product Passport no.:
1548-10-1004

QNG - Qualitätssiegel Nachhaltiges Gebäude

The Qualitätssiegel Nachhaltiges Gebäude (Quality Seal for Sustainable Buildings), developed by the German Federal Ministry for Housing, Urban Development and Building (BMWSB), defines requirements for the ecological, socio-cultural, and economic quality of buildings. The Sentinel Holding Institut evaluates construction products in accordance with QNG requirements for certification and awards the QNG ready label. Compliance with the QNG standard is a prerequisite for eligibility for the KfW funding programme. For certain product groups, the QNG currently has no specific requirements defined. Although classified as not assessment-relevant, these products remain suitable for QNG-certified projects.

Criteria	Pos. / product group	Considered substances	QNG assessment
3.1.3 Schadstoffvermeidung in Baumaterialien			QNG ready - Not relevant for assessment

SENTINEL HOLDING
INSTITUT

Product:
btf Flexibel New

SHI Product Passport no.:
1548-10-1004

DGNB New Construction 2023

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings. The 2023 version sets high standards for ecological, economic, socio-cultural, and functional aspects throughout the entire life cycle of a building.

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 03.05.2024 (3rd edition)	not applicable		Not relevant for assessment

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 29.05.2025 (4th edition)	not applicable		Not relevant for assessment

SENTINEL HOLDING
INSTITUT

Product:
btf Flexibel New

SHI Product Passport no.:
1548-10-1004

DGNB New Construction 2018

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings.

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact	not applicable	not applicable	Not relevant for assessment

SENTINEL HOLDING
INSTITUT

Product:
btf Flexibel New

SHI Product Passport no.:
1548-10-1004

BNB-BN Neubau V2015

The Bewertungssystem Nachhaltiges Bauen (Assessment System for Sustainable Building) is a tool for evaluating public office and administrative buildings, educational facilities, laboratory buildings, and outdoor areas in Germany. The BNB was developed by the former Federal Ministry for the Environment, Nature Conservation, Building and Nuclear Safety (BMUB) and is now overseen by the Federal Ministry for Housing, Urban Development and Building (BMWSB).

Criteria	Pos. / product type	Considered substance group	Quality level
1.1.6 Risiken für die lokale Umwelt			Not relevant for assessment

SENTINEL HOLDING
INSTITUT

Product:
btf Flexibel New

SHI Product Passport no.:
1548-10-1004

EU taxonomy

The EU Taxonomy classifies economic activities and products according to their environmental impact. At the product level, the EU regulation defines clear requirements for harmful substances, formaldehyde and volatile organic compounds (VOCs). The Sentinel Holding Institut GmbH labels qualified products that meet this standard.

Criteria	Product type	Considered substances	Assessment
DNSH - Pollution prevention and control		Substances according to Annex C	EU taxonomy compliant
Verification: Herstellererklärung vom 28.08.2025			

SENTINEL HOLDING
INSTITUT

Product:
btf Flexibel New

SHI Product Passport no.:
1548-10-1004

BREEAM DE Neubau 2018

BREEAM (Building Research Establishment Environmental Assessment Methodology) is a UK-based building assessment system that evaluates the sustainability of new constructions, refurbishments, and conversions. Developed by the Building Research Establishment (BRE), the system aims to assess and improve the environmental, economic, and social performance of buildings.

Criteria	Product category	Considered substances	Quality level
Hea 02 Indoor Air Quality			Not relevant for assessment

SENTINEL HOLDING
INSTITUT

Product:
btf Flexibel New

SHI Product Passport no.:
1548-10-1004

LEED v4.1

LEED (Leadership in Energy and Environmental Design) is an internationally recognised building certification system developed by the U.S. Green Building Council. It is one of the most widely used sustainability standards for buildings worldwide and is particularly applied in internationally oriented projects. LEED assesses buildings holistically across categories such as energy efficiency, resource conservation, material selection, indoor environmental quality and site sustainability. Depending on the number of points achieved, projects are awarded one of the certification levels: LEED Certified, Silver, Gold or Platinum.

Criteria	Product category	Assessment
EQ Credit: Low-Emitting Materials		Not relevant for assessment

SENTINEL HOLDING
INSTITUT

Product:
btf Flexibel New

SHI Product Passport no.:
1548-10-1004

Product labels

In the construction industry, high-quality materials are crucial for a building's indoor air quality and sustainability. Product labels and certificates offer guidance to meet these requirements. However, the evaluation criteria of these labels vary, and it is important to carefully assess them to ensure products align with the specific needs of a construction project.

This product is SHI Indoor Air Quality certified and recommended by Sentinel Holding Institut. Indoor-air-focused construction, renovation, and operation of buildings is made possible by transparent and verifiable criteria thanks to the Sentinel Holding concept.

Products bearing the Sentinel Holding Institute QNG-ready seal are suitable for projects aiming to achieve the "Qualitätssiegel Nachhaltiges Gebäude" (Quality Seal for Sustainable Buildings). QNG-ready products meet the requirements of QNG Appendix Document 3.1.3, “Avoidance of Harmful Substances in Building Materials.” The KfW loan program Climate-Friendly New Construction with QNG may allow for additional funding.

SENTINEL HOLDING
INSTITUT

Product:
btf Flexibel New

SHI Product Passport no.:
1548-10-1004

Legal notices

(*) These criteria apply to the construction project as a whole. While individual products can positively contribute to the overall building score through proper planning, the evaluation is always conducted at the building level. The information was provided entirely by the manufacturer.

Find our criteria here: https://www.sentinel-holding.eu/de/Themenwelten/Pr%C3%BCfkriterien%20f%C3%BCr%20Produkte

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar

Publisher

Sentinel Holding Institut GmbH
Bötzinger Str. 38
79111 Freiburg im Breisgau
Germany
Tel.: +49 761 590 481-70
info@sentinel-holding.eu
www.sentinel-holding.eu

BTF FLEXIBEL NEW

FEUCHTIGKEITSSPERRBAHN UND DAMPFSPERRE

Mehrlagige, weiche, flexible und mit Spinnvlies kaschierte Aluminiumverbund-Abdichtungsbahn

EIGENSCHAFTEN

+ Bis -5 °C einsatzbereit
+ Extrem reißfest und extrem robust
+ Flexibel und weich
+ Extrem trittfest
+ Leicht im Gewicht
+ Schnell und einfach zu verlegen
+ PVC- / bitumenbeständig
+ PVC- / bitumenfrei
+ Dampfdicht (S_D-Wert: ≥ 1.500 m)
+ Radondicht
+ Allgemeine Bauartgenehmigung
+ Emissionsgeprüft
+ Passt sich optimal an die Gegebenheiten auf der Baustelle an



PRODUKTBESCHREIBUNG

Die BTF FLEXIBEL NEW ist eine mehrlagige, weiche und flexible mit Spinnvlies kaschierte Aluminiumverbund-Abdichtungsbahn. Als Feuchtigkeitssperre und Dampfsperre besitzt die Bahn einen zweiseitenversetzten Klebestreifen, die Verwendbarkeit wird durch die Einhaltung der Anforderungen der DIN EN 13967 erfüllt.Ohne Klebestreifen wird die Bahn als Mauerwerkssperrbahn eingesetzt. Sie ist geprüft nach den Anforderungen der DIN EN 14909 als Mauerwerkssperrbahn.Das technische Merkblatt für die BTF FLEXIBEL NEW Mauerwerkssperrbahn finden Sie im Bereich Boden unter Mauerwerkssperrbahnen.

ANWENDUNGSBEREICHE

+ Geeignet zur Abdichtung gegen Bodenfeuchte und nicht drückendes Wasser - erdberührte Bodenplatte - gemäß DIN 18533 Teil 1 und 2: W1-E (DIN EN 13967, siehe Allgemeine Bauartgenehmigung).
+ Geeignet zur Abdichtung gegen Kapillarwasser in und unter Wänden gemäß DIN 18533 Teil 1 und 2: W4-E (DIN EN 13967, siehe Allgemeine Bauartgenehmigung).
+ Geeignet zur Abdichtung in den Anwendungsbereich am spritzwasserbeanspruchten Wandsockel gemäß DIN 18533 Teil 1 und 2: W4-E. (DIN EN 13967, siehe gutachterliche Stellungnahme).
+ Geeignet zur Abdichtung gegen Radongas (Nachweis der Radondichtheit der Bahn gemäß Prüfbericht).
+ Zum Einsatz im Sockelbereich (L- und Z-Isolierung) geeignet.

btf Innovationen für den Bau GmbH
Fahrenheitstr. 3 • 86899 Landsberg am Lech • T + 49 (0) 81 91/ 9 40 40 – 0 • F + 49 (0) 81 91/ 9 40 40 – 40 • info@btf-innovationen.de • www.btf-innovationen.de

Technisches Merkblatt

VERARBEITUNG

Untergrund:

+ Der Untergrund muss druckfest, eben, frei von Nestern, Graten und frei von für die Bahn schädlichen Verunreinigungen sein.

Abdichtung von Bodenplatten:

+ Bei waagerechter Anwendung auf der Bodenplatte muss die Abdichtungsbahn immer geschützt zwischen Bodenplatte und direkt aufgebrachtem Estrich, zwischen Bodenplatte und direkt aufgebrachter Dämmung (schwimmender Estrich) oder zwischen Höhenausgleich (z.B. Ausgleichsestrich, gebundene Schüttung) und aufliegender Dämmung (schwimmender Estrich) oder zwischen der Dämmung und dem direkt aufgebrachten Estrich mindestens einlagig eingebaut werden.
+ Die Abdichtungsbahn ist lose auf dem Untergrund mit einer Bahnenüberdeckung von mind. 5 cm zu verlegen. Die Abdichtung der längsseitigen Überdeckung erfolgt über das integrierte Selbstklebeband.
+ Kopfstöße bzw. Quernähte und An- und Abschlüsse an Durchdringungen bzw. aufgehende Bauteile sind unter Verwendung eines 10 cm bzw. 20 cm breiten ,,BTF SYSTEMANSCHLUSSSTREIFEN ALU" (Aluminium-Verbundfolie mit kaltselbstklebender Butyl- bzw. HotMeltschicht) bei mittig liegender Naht auszuführen.
+ Zum Anschluss an aufgehende Bauteile kann die Bahn auch am Bauteil hochgeführt werden (ggf. unter Verwendung eines Primers als Montagehilfe).
+ Die „BTF FLEXIBEL NEW" Abdichtungsbahn ist so an die Mauersperrbahn heranzuführen oder mit ihr zu verkleben, dass keine Feuchtigkeitsbrücken, insbesondere im Bereich von Putzflächen, entstehen können.

Abdichtung von Wandsockeln:

+ Die Sockelfläche ist zuvor mit dem „BTF SYSTEM SPEZIALPRIMER/KLEBER" nach Herstellerangabe zu grundieren.
+ Die Verlegung der Abdichtungsbahn erfolgt wie bei der zuvor beschriebenen Abdichtung von Bodenplatten.
+ Der obere und untere Abschluss ist entweder mit dem BTF SYSTEMANSCHLUSSSTREIFEN ALU oder dem BTF K+D Kleber und Dichtstoff auszuführen.
+ Es dürfen keine Feuchtigkeitsbrücken entstehen.

Sichtprüfung:

+ Vor dem weiteren Schichtaufbau ist an der „BTF FLEXIBEL NEW" Abdichtungsbahn eine gründliche Sichtprüfung durchzuführen und ggf. vorhandene Schäden gemäß Herstellerempfehlungen zu beseitigen. Der Einbau weiterer Schichten hat unmittelbar nach der Freigabe zu erfolgen.

Radonsperre:

+ Um die Radondichtheit bei Anschlüssen und Überlappungen zu gewährleisten, ist hier unser BTF SYSTEMANSCHLUSSSTREIFEN ALU erforderlich.

Hinweis:

+ Der BTF SYSTEM SPZIALPRIMER/KLEBER und der BTF SYSTEM SPEZIALPRIMER/KLEBER LF NEW müssen vor der Anwendung kräftig aufgerührt werden. Bei der Anwendung von Porenbeton-/Gasbetonstein, muss vorher der Stein mit einem Tiefengrund vorbehandelt werden. Dabei den Tiefengrund satt auftragen.

LIEFEREINHEITEN

ABMESSUNGEN	VERKAUFSEINHEIT	VERKAUFSEINHEIT PRO PALETTE	ART.-NR.
1,00 m × 50 lfm	1 Rolle	28 Rollen	2009 NEW/1000
1,50 m x 50 lfm	1 Rolle	28 Rollen	2009 NEW/1500

TECHNISCHE DATEN

Eigenschaft	Wert
Brandverhalten	Klasse E
Breite	1,00 m ± 2 %, 1,50 m ± 2 %
Flächenbezogene Masse	245 g/m^2 ± 10 %
Länge	50 m ± 2 %
Stärke	0,65 mm ± 0,15 mm
Verarbeitungstemperatur	Bis -5 °C
Wasserdampfdurchlässigkeit	S_D ≥ 1.500 m

btf Innovationen für den Bau GmbH
Fahrenheitstr. 3 • 86899 Landsberg am Lech • T + 49 (0) 81 91/ 9 40 40 – 0 • F + 49 (0) 81 91/ 9 40 40 – 40 • info@btf-innovationen.de • www.btf-innovationen.de

Stand: 11.10.2024

Technisches Merkblatt

PRODUKTZUBEHÖR

Bezeichnung	Verkaufseinheit	Verkaufseinheit pro Palette	Art.-Nr.
BTF SYSTEM SPEZIALPRIMER/ KLEBER LF NEW	1 Eimer à 4,5 kg	60 Eimer	3107
BTF SYSTEM SPEZIALPRIMER/ KLEBER LF NEW	1 Eimer à 12,0 kg	24 Eimer	3108
BTF SYSTEM SPEZIALPRIMER/ DÄMMPLATTENKLEBER	1 Eimer à 4,5 kg	60 Eimer	3101
BTF SYSTEM SPEZIALPRIMER/ DÄMMPLATTENKLEBER	1 Eimer à 10 kg	42 Eimer	3100/10
BTF SYSTEMANSCHLUSSSTREIFEN ALU	1 Karton à 6 Rollen	34 Kartons	2012
BTF SYSTEMANSCHLUSSSTREIFEN ALU	1 Karton à 4 Rollen	35 Kartons	2014
BTF SYSTEMANSCHLUSSSTREIFEN ALU	1 Karton à 4 Rollen	35 Kartons	2015
BTF FUSSPUNKTABDICHTUNGSMANSCHETTE	1 Karton à 1 Set à 4 Stück (2x rechts und 2x links)	28 Kartons	LM3004
BTF INNEN- UND AUSSENECKE ALU BUTYL	1 Karton à 25 Stück		LM2006
BTF INNEN- UND AUSSENECKE ALU BUTYL	1 Karton à 25 Stück		LM2008
BTF INNEN- UND AUSSENECKE ALU BUTYL	1 Karton à 25 Stück		LM2007
BTF INNEN- UND AUSSENECKE ALU BUTYL	1 Karton à 25 Stück		LM2009

LAGERUNG

Die Rollen sind stehend auf Paletten zu transportieren. Bis zur Verarbeitung müssen die Bahnen gegenüber Wärme, vor direkter Sonnenbestrahlung und Feuchtigkeit geschützt werden. Eine Beanspruchung durch punkt- und linienförmige Lasteinwirkung sowie durch Lösemitteldämpfe ist zu vermeiden. In geschlossenen Räumen können die Bahnen bei einer Raumtemperatur von max. +30 °C, 12 Monate nach Datum der Herstellung gelagert werden. Eine Lagerung über +30 °C kann zu erschwertem Abziehen des Abdeckstreifens vom Kleber führen.

SICHERHEITSHINWEISE

Die allgemeinen Hinweise, Verarbeitungsanleitung und das allgemeine bauaufsichtliche Prüfzeugnis des Herstellers sind zu beachten.

Zur besonderen Beachtung: Bei den aufgeführten Eigenschaften und Leistungsmerkmalen handelt es sich um circa-Werte. Wegen den außerhalb unseres Einflusses liegenden Verarbeitungs- und Anwendungsbedingungen und der Vielzahl unterschiedlicher Materialien empfehlen wir, in jedem Fall zunächst ausreichende Eigenversuche durchzuführen. Eine Haftung für konkrete Anwendungsergebnisse kann daher aus den Angaben und Hinweisen in diesem Merkblatt nicht abgeleitet werden. Eine Gewährleistung wird im Rahmen unserer Verkaufsbedingungen allein für die stets gleichbleibend hohe Qualität unserer Erzeugnisse übernommen. Mit Erscheinen dieser Ausgabe verlieren alle vorhergehenden technischen Merkblätter ihre Gültigkeit.

btf Innovationen für den Bau GmbH
Fahrenheitstr. 3 • 86899 Landsberg am Lech • T + 49 (0) 81 91/ 9 40 40 – 0 • F + 49 (0) 81 91/ 9 40 40 – 40 • info@btf-innovationen.de • www.btf-innovationen.de

Stand: 11.10.2024

btf Innovationen für den Bau GmbH + Fahrenheitstraße 3 + 86899 Landsberg am Lech

Sentinel Holding Institut GmbH
Natalie Szczyglowski
Bötzinger Straße38
79111 Freiburg im Breisgau

btf Innovationen für den Bau GmbH
Fahrenheitstraße 3
86899 Landsberg am Lech
T +49 (0) 8191/94040-0
F +49 (0) 8191/94040-40
info@btf-innovationen.de
www.btf-innovationen.de

Landsberg, den 28.08.2025

Herstellererklärung

Sehr geehrte Frau Szczyglowski,

hiermit bestätigen wir Ihnen als Hersteller, dass in unsere Produkte keine Stoffe der Kategorien SVHC gemäß REACH-Verordnung und CMR Stoffe der Kategorie 1A / 1B gemäß CLP-Verordnung in einer Konzentration von mehr als 0,1 % enthalten sind.

Die genaue Zusammensetzung und die Einhaltung aller relevanten Verordnungen wurden von uns gründlich überprüft und bestätigt.

Sollten Sie weitere Fragen haben oder zusätzliche Informationen benötigen, stehen wir Ihnen gerne zur Verfügung.

Mit freundlichen Grüßen
btf Innovationen für den Bau

btf - Innovationen
für den Bau GmbH
Fahrenheitstraße 3
86899 Landsberg am Lech
Tel: 08191/94040-0 Fax: 08191/94040-40
Dominik Turtenwald