SENTINEL HOLDING
INSTITUT

SHI PRODUCT PASSPORT

Find products. Certify buildings.

SHI Product Passport No.:

2765-10-1030

PU-Schäume - 1K Adapterschäume

Product group: Construction Foam - PU foam - Construction chemicals - Polyurethane (PU)

fischer

fischerwerke GmbH & Co. KG
Klaus-Fischer-Straße 1
72178 Waldachtal

Product qualities:

- SHI Product Assessment 2024
- QNG Qualitätssiegel Nachhaltiges Gebäude
- DGNB NEW CONSTRUCTION 2023.2
- DGNB NEW CONSTRUCTION 2023
- DGNB NEW CONSTRUCTION 2018
- BNB-BN NEUBAU V2015
- EU TAXONOMY
- BREEAM DE NEUBAU 2018
- LEED v4.1 (outside US)

CERTIFIED SUSTAINABLE PRODUCT
SHI PRODUCT PASSPORT
SENTINEL HOLDING INSTITUT
www.sentinel-holding.eu

Köttner

Helmut Köttner
Scientific Director
Freiburg, 17 August 2026

SENTINEL HOLDING
INSTITUT

Product:
PU-Schäume - 1K Adapterschäume

SHI Product Passport no.:
2765-10-1030

fischer

Contents

SHI Product Assessment 2024	1
QNG - Qualitätssiegel Nachhaltiges Gebäude	2
DGNB New Construction 2023.2	3
DGNB New Construction 2023	4
DGNB New Construction 2018	5
BNB-BN Neubau V2015	6
EU taxonomy	7
BREEAM DE Neubau 2018	8
LEED v4.1	9
Product labels	10
Legal notices	11
Technical data sheet/attachments	12

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar

SGS TÜV SAAR

SENTINEL HOLDING
INSTITUT

Product:
PU-Schäume - 1K Adapterschäume

SHI Product Passport no.:
2765-10-1030

fischer

SHI Product Assessment 2024

Since 2008, Sentinel Holding Institut GmbH (SHI) has been establishing a unique standard for products that support healthy indoor air. Experts carry out independent product assessments based on clear and transparent criteria. In addition, the independent testing company SGS regularly audits the processes and data accuracy.

Criteria	Product category	Harmful substance limit	Assessment
SHI Product Assessment	Sealants and adhesives	TVOC ≤ 300 µg/m^3 Formaldehyd ≤ 24 µg/m^3	Indoor Air Quality Certified (Advisory Note)
Valid untill: 24 July 2027			

SENTINEL HOLDING
INSTITUT

Product:
PU-Schäume - 1K Adapterschäume

SHI Product Passport no.:
2765-10-1030

fischer

QNG - Qualitätssiegel Nachhaltiges Gebäude

The Qualitätssiegel Nachhaltiges Gebäude (Quality Seal for Sustainable Buildings), developed by the German Federal Ministry for Housing, Urban Development and Building (BMWSB), defines requirements for the ecological, socio-cultural, and economic quality of buildings. The Sentinel Holding Institut evaluates construction products in accordance with QNG requirements for certification and awards the QNG ready label. Compliance with the QNG standard is a prerequisite for eligibility for the KfW funding programme. For certain product groups, the QNG currently has no specific requirements defined. Although classified as not assessment-relevant, these products remain suitable for QNG-certified projects.

Criteria	Pos. / product group	Considered substances	QNG assessment
3.1.3 Schadstoffvermeidung in Baumaterialien	12.5 In-situ foams (PUR, UF) for interior spaces and the building envelope	Halogenated propellants / SVHC / formaldehyde / emissions / chlorinated paraffins	QNG ready
Verification: Herstellererklärung vom 17.12.2025			

SENTINEL HOLDING
INSTITUT

Product:
PU-Schäume - 1K Adapterschäume

SHI Product Passport no.:
2765-10-1030

fischer

DGNB New Construction 2023.2

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact	38 Montageschäume (innen und Gebäudehülle)	VVOC, VOC, SVOC Emissionen und Gehalt an gefährlichen Stoffen	Quality level 1
Verification: Herstellererklärung vom 17.12.2025			

SENTINEL HOLDING
INSTITUT

Product:
PU-Schäume - 1K Adapterschäume

SHI Product Passport no.:
2765-10-1030

fischer

DGNB New Construction 2023

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings. The 2023 version sets high standards for ecological, economic, socio-cultural, and functional aspects throughout the entire life cycle of a building.

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 03.05.2024 (3rd edition)	38 Installation foams that do not have to meet the requirements8	VVOCs, VOCs, SVOC emissions, halogenated propellants, chlorinated paraffins, plasticisers, flame retardants	Quality level 2
Verification: Herstellererklärung vom 17.12.2025			

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 29.05.2025 (4th edition)	38 Installation foams	VVOCs, VOCs, SVOC emissions, halogenated propellants, chlorinated paraffins, plasticisers, flame retardants	Quality level 2
Verification: Herstellererklärung vom 17.12.2025			

SENTINEL HOLDING
INSTITUT

Product:
PU-Schäume - 1K Adapterschäume

SHI Product Passport no.:
2765-10-1030

fischer

DGNB New Construction 2018

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings.

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact	38 Installation foams that do not have to meet the requirements of class B1	Halogenated and other propellants solvents, plasticisers and flame retardants	Quality level 2
Verification: Herstellererklärung vom 17.12.2025			

SENTINEL HOLDING
INSTITUT

Product:
PU-Schäume - 1K Adapterschäume

SHI Product Passport no.:
2765-10-1030

fischer

BNB-BN Neubau V2015

The Bewertungssystem Nachhaltiges Bauen (Assessment System for Sustainable Building) is a tool for evaluating public office and administrative buildings, educational facilities, laboratory buildings, and outdoor areas in Germany. The BNB was developed by the former Federal Ministry for the Environment, Nature Conservation, Building and Nuclear Safety (BMUB) and is now overseen by the Federal Ministry for Housing, Urban Development and Building (BMWSB).

Criteria	Pos. / product type	Considered substance group	Quality level
1.1.6 Risiken für die lokale Umwelt	33 Spray and mounting foams	Halogenated refrigerants / individual hazardous substances (formaldehyde)	Quality level 3
Verification: Herstellererklärung vom 17.12.2025			

SENTINEL HOLDING
INSTITUT

Product:
PU-Schäume - 1K Adapterschäume

SHI Product Passport no.:
2765-10-1030

fischer

EU taxonomy

The EU Taxonomy classifies economic activities and products according to their environmental impact. At the product level, the EU regulation defines clear requirements for harmful substances, formaldehyde and volatile organic compounds (VOCs). The Sentinel Holding Institut GmbH labels qualified products that meet this standard.

Criteria	Product type	Considered substances	Assessment
DNSH - Pollution prevention and control	Sonstige	Stoffe nach Anlage C	compliant
Verification: Sicherheitsdatenblätter siehe Downloadbereich			

SENTINEL HOLDING
INSTITUT

Product:
PU-Schäume - 1K Adapterschäume

SHI Product Passport no.:
2765-10-1030

fischer

BREEAM DE Neubau 2018

BREEAM (Building Research Establishment Environmental Assessment Methodology) is a UK-based building assessment system that evaluates the sustainability of new constructions, refurbishments, and conversions. Developed by the Building Research Establishment (BRE), the system aims to assess and improve the environmental, economic, and social performance of buildings.

Criteria	Product category	Considered substances	Quality level
Hea 02 Indoor Air Quality	Interior adhesives and sealants (including flooring adhesives)	Emissions: Formaldehyde, TVOC, TSVOC, carcinogens	Exemplary quality
Verification: EMICODE EC1+-Zertifikate siehe Downloadbereich			

SENTINEL HOLDING
INSTITUT

Product:
PU-Schäume - 1K Adapterschäume

SHI Product Passport no.:
2765-10-1030

fischer

LEED v4.1

LEED (Leadership in Energy and Environmental Design) is an internationally recognised building certification system developed by the U.S. Green Building Council. It is one of the most widely used sustainability standards for buildings worldwide and is particularly applied in internationally oriented projects. LEED assesses buildings holistically across categories such as energy efficiency, resource conservation, material selection, indoor environmental quality and site sustainability. Depending on the number of points achieved, projects are awarded one of the certification levels: LEED Certified, Silver, Gold or Platinum.

Criteria	Product category	Considered substances	Assessment
EQ Credit: Low-Emitting Materials	Kleb- und Dichtstoffe	Emissionen: Formaldehyd, VOC, Krebserregende Stoffe	compliant

Product:
PU-Schäume - 1K Adapterschäume

SHI Product Passport no.:
2765-10-1030

fischer

Product labels

In the construction industry, high-quality materials are crucial for a building's indoor air quality and sustainability. Product labels and certificates offer guidance to meet these requirements. However, the evaluation criteria of these labels vary, and it is important to carefully assess them to ensure products align with the specific needs of a construction project.

The EMICODE® label, awarded by the German manufacturers' association "GEV – Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e. V.", is primarily relevant for flooring installation materials. The EMICODE® EC1^{PLUS} label, as the premium class, sets significantly stricter emission limits than the other label variants.

Products bearing the Sentinel Holding Institute QNG-ready seal are suitable for projects aiming to achieve the "Qualitätssiegel Nachhaltiges Gebäude" (Quality Seal for Sustainable Buildings). QNG-ready products meet the requirements of QNG Appendix Document 3.1.3, "Avoidance of Harmful Substances in Building Materials." The KfW loan program Climate-Friendly New Construction with QNG may allow for additional funding.

This product is SHI Indoor Air Quality certified and recommended by Sentinel Holding Institut. Indoor-air-focused construction, renovation, and operation of buildings is made possible by transparent and verifiable criteria thanks to the Sentinel Holding concept.

Product:
PU-Schäume - 1K Adapterschäume

SHI Product Passport no.:
2765-10-1030

fischer

Legal notices

(*) These criteria apply to the construction project as a whole. While individual products can positively contribute to the overall building score through proper planning, the evaluation is always conducted at the building level. The information was provided entirely by the manufacturer.

Find our criteria here: https://www.sentinel-holding.eu/de/Themenwelten/Pr%C3%BCfkriterien%20f%C3%BCr%20Produkte

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar

SGS TÜV SAAR

Publisher

Sentinel Holding Institut GmbH
Bötzinger Str. 38
79111 Freiburg im Breisgau
Germany
Tel.: +49 761 590 481-70
info@sentinel-holding.eu
www.sentinel-holding.eu

PU Pro 500 B2 (#50426)

Merkmal	Wert	Einheit	Prüfvorschrift / Bemerk.
Chemische Basis	1K Polyurethan		
Farbe	gelblich		
Inhalt	500	ml	
Klebfreizeit	10 - 15	min	EN 17333-3
Schneidzeit	60 - 80	min	EN 17333-3
Brandklasse	B2		DIN 4102-1
Gesamtschaumausbeute	24	l	EN 17333-1
Rohdichte	25 bis 35	kg/m^3	fugengeschäumt
Standfestigkeit im Spalt	standfest		
Lagerhaltbarkeit	18	Monate	bei + 5 bis + 25 °C
Verarbeitungstemperatur	+ 5 bis + 35	°C	
Optimale Verarbeitungstemperatur	+ 20	°C	
Temperaturbeständigkeit	- 40 bis + 90	°C	ausgehärteter Schaum
Wärmeleitfähigkeit (λ)	30 - 35	mW/(m*K)	DIN 52612
Bewertetes Fugenschalldämm-Maß $R_{s,w}$:)	63 (-1;-4)	dB	10 mm und 20 mm Fugenbreite
Wasserdichtheit	0.50 24	bar h	Prüfdruck Prüfdauer (siehe Prüfbericht)
Treibmittelbasis	HFKW-frei		
Aushärtung	chemisch durch Reaktion mit Luftfeuchtigkeit		
Normen und Prüfungen	DIN 4102-1 EN ISO 717-1 Fugenschalldämmung VOC emissions ISO 16000 Emicode EC1 Plus		

Anwendungshinweise

Dieser Montageschaum haftet auf allen üblichen Baumaterialien, ausgenommen Polyethylen, Polypropylen, Silikon, Teflon, Öle und Fette, o. ä.. Der ausgehärtete Schaum ist halbhart, elastisch, verrottungsfest, feuchtigkeitsbeständig und alterungsbeständig (vor UV-Strahlung schützen). Die Untergründe müssen fest, sauber, staub- und fettfrei sein.

Vor der Verarbeitung die Untergründe ausreichend mit Wasser befeuchten. Schichtdicken von mehr als 50 mm in mehreren Lagen schäumen und zwischenfeuchten. Zu kalte Dosen vorsichtig im lauwarmen Wasserbad erwärmen. Niemals über 50 °C erhitzen, da sonst Berstgefahr. Zu heiße Dosen im Wasserbad abkühlen.

Gelegentliches Schütteln unterstützt den Temperaturausgleich. Soweit nicht anders angegeben gelten die Angaben bei Standardbedingungen von 23 °C und 50 % r. F. und nicht gealtertem Schaum. Für die Prüfungen Ausbeute und Reaktivität sind mind. 85% r. F. erforderlich (gut vorfeuchten). Bei gealtertem Schaum sinkt die Ausbeute um bis zu 30%. Hierbei verkürzt sich auch die Klebfrei- und Schneidzeit. **Dose vor Gebrauch gut schütteln!**

Weitere Informationen zum Umgang entnehmen Sie bitte dem Sicherheitsdatenblatt; dieses enthält wichtige Hinweise.

Die Anwendungshinweise in diesem technischen Datenblatt sowie unsere anwendungstechnische Beratung in Wort und Schrift erfolgen nach bestem Wissen, beinhalten aber weder Zusagen an die Beschaffenheit oder Verwendbarkeit der Produkte noch selbständige oder unselbständige Garantiezusagen jeglicher Art.
Wir empfehlen vor Verwendung unserer Produkte stets die Eignung für den vorgesehenen Verwendungszweck konkret zu prüfen.
Aufgrund der Vielfalt der Anwendungsmöglichkeiten des einzelnen Produkts und den nicht einschätzbaren Gegebenheiten am Ort der Verarbeitung empfehlen wir darüber hinaus vor Verwendung die Funktion auf den Substraten vor Verwendung zu erproben.

PU Pro 750 B2 (#53080)

Merkmal	Wert	Einheit	Prüfvorschrift / Bemerk.
Chemische Basis	1K Polyurethan		
Farbe	gelblich		
Inhalt	750	ml	
Klebfreizeit	10 - 15	min	EN 17333-3
Schneidzeit	60 - 80	min	EN 17333-3
Brandklasse	B2		DIN 4102-1
Gesamtschaumausbeute	bis zu 35	l	EN 17333-1
Rohdichte	25 bis 35	kg/m^3	fugengeschäumt
Standfestigkeit im Spalt	standfest		
Lagerhaltbarkeit	18	Monate	bei + 5 bis + 25 °C
Verarbeitungstemperatur	+ 5 bis + 35	°C	
Optimale Verarbeitungstemperatur	+ 20	°C	
Temperaturbeständigkeit	- 40 bis + 90	°C	ausgehärteter Schaum
Wärmeleitfähigkeit (λ)	30 - 35	W/(m*K)	DIN 52612
Bewertetes Fugenschalldämm-Maß $R_{s,w}$:)	63 (-1;-4)	dB	10 mm und 20 mm Fugenbreite
Wasserdichtheit	0.50 24	0.50 24	Prüfdruck Prüfdauer (siehe Prüfbericht)
Treibmittelbasis	HFKW-frei		
Aushärtung	chemisch durch Reaktion mit Luftfeuchtigkeit		
Normen und Prüfungen	DIN 4102-1 EN ISO 717-1 Fugenschalldämmung VOC emissions ISO 16000 Emicode EC1 Plus		

Anwendungshinweise

Dieser Montageschaum haftet auf allen üblichen Baumaterialien, ausgenommen Polyethylen, Polypropylen, Silikon, Teflon, Öle und Fette, o. ä.. Der ausgehärtete Schaum ist halbhart, elastisch, verrottungsfest, feuchtigkeitsbeständig und alterungsbeständig (vor UV-Strahlung schützen). Die Untergründe müssen fest, sauber, staub- und fettfrei sein.

Vor der Verarbeitung die Untergründe ausreichend mit Wasser befeuchten. Schichtdicken von mehr als 50 mm in mehreren Lagen schäumen und zwischenfeuchten. Zu kalte Dosen vorsichtig im lauwarmen Wasserbad erwärmen. Niemals über 50 °C erhitzen, da sonst Berstgefahr. Zu heiße Dosen im Wasserbad abkühlen.

Gelegentliches Schütteln unterstützt den Temperaturausgleich. Soweit nicht anders angegeben gelten die Angaben bei Standardbedingungen von 23 °C und 50 % r. F. und nicht gealtertem Schaum. Für die Prüfungen Ausbeute und Reaktivität sind mind. 85% r. F. erforderlich (gut vorfeuchten). Bei gealtertem Schaum sinkt die Ausbeute um bis zu 30%. Hierbei verkürzt sich auch die Klebfrei- und Schneidzeit. **Dose vor Gebrauch gut schütteln!**

Weitere Informationen zum Umgang entnehmen Sie bitte dem Sicherheitsdatenblatt.

Die Informationen in diesem technischen Datenblatt und unsere anwendungstechnische Beratung in Wort und Schrift erfolgen nach bestem Wissen, sind jedoch nur unverbindliche Hinweise und keine Garantie im Sinne von § 443 BGB. Wir empfehlen vor Verwendung unserer Produkte die Eignung für den vorgesehenen Verwendungszweck zu prüfen. Aufgrund der Vielfalt der Anwendungsmöglichkeiten des einzelnen Produkts und den nicht einschätzbaren Gegebenheiten am Ort der Verarbeitung empfehlen wir darüber hinaus vor Verwendung die Verklebung zu erproben.

PU S 750 B2 SCHNELLMONTAGESCHAUM #40301

Merkmal	Wert	Einheit	Prüfvorschrift / Bemerk.
Chemische Basis	1K Polyurethan		
Farbe	beige		
Inhalt	750	ml	
Klebfreizeit	10-15	min	EN 17333-3
Schneidzeit	60-80	min	EN 17333-3
Brandklasse	B2		DIN 4102-1
Gesamtschaumausbeute	ca. 35	l	EN 17333-1
Rohdichte	25 bis 35	kg/m^3	
Standfestigkeit im Spalt	standfest		
Lagerhaltbarkeit	18	Monate	bei + 20 °C
Verarbeitungstemperatur	+ 5 bis + 35	°C	
Optimale Verarbeitungstemperatur	+ 20	°C	
Temperaturbeständigkeit	- 40 bis + 90	°C	ausgehärteter Schaum
Wärmeleitfähigkeit (λ)	0,035	W/(m*K)	DIN 52612
Bewertetes Fugenschalldämmmaß	63	dB	
Treibmittelbasis	HFKW-frei		
Normen / Prüfungen	A+ Emicode EC 1 Plus		
Aushärtung	chemisch durch Reaktion mit Luftfeuchtigkeit		

Anwendungshinweise

Dieser Montageschaum haftet auf allen üblichen Baumaterialien, ausgenommen Polyethylen, Polypropylen, Silikon, Teflon, Öle und Fette, o. ä.. Der ausgehärtete Schaum ist halbhart, elastisch, verrottungsfest, feuchtigkeitsbeständig und alterungsbeständig (vor UV-Strahlung schützen). Die Untergründe müssen fest, sauber, staub- und fettfrei sein.

Vor der Verarbeitung die Untergründe ausreichend mit Wasser befeuchten. Schichtdicken von mehr als 50 mm in mehreren Lagen schäumen und zwischenfeuchten. Zu kalte Dosen vorsichtig im lauwarmen Wasserbad erwärmen. Niemals über 50 °C erhitzen, da sonst Berstgefahr. Zu heiße Dosen im Wasserbad abkühlen.

Gelegentliches Schütteln unterstützt den Temperaturausgleich. Soweit nicht anders angegeben gelten die Angaben bei Standardbedingungen von 23 °C und 50 % r. F. und nicht gealtertem Schaum. Für die Prüfungen Ausbeute und Reaktivität sind mind. 85% r. F. erforderlich (gut vorfeuchten). Bei gealtertem Schaum sinkt die Ausbeute um bis zu 30%. Hierbei verkürzt sich auch die Klebfrei- und Schneidzeit. **Dose vor Gebrauch gut schütteln!**

Weitere Informationen zum Umgang entnehmen Sie bitte dem Sicherheitsdatenblatt; dieses enthält wichtige Hinweise.
Die Anwendungshinweise in diesem technischen Datenblatt sowie unsere anwendungstechnische Beratung in Wort und Schrift erfolgen nach bestem Wissen, beinhalten aber weder Zusagen an die Beschaffenheit oder Verwendbarkeit der Produkte noch selbständige oder unselbständige Garantiezusagen jeglicher Art.
Wir empfehlen vor Verwendung unserer Produkte stets die Eignung für den vorgesehenen Verwendungszweck konkret zu prüfen.
Aufgrund der Vielfalt der Anwendungsmöglichkeiten des einzelnen Produkts und den nicht einschätzbaren Gegebenheiten am Ort der Verarbeitung empfehlen wir darüber hinaus vor Verwendung die Funktion auf den Substraten vor Verwendung zu erproben.

PU S 500 B2 #40300

Merkmal	Wert	Einheit	Prüfvorschrift / Bemerk.
Chemische Basis	1K Polyurethan		
Farbe	gelblich		
Inhalt	500	ml	
Klebfreizeit	ca. 20	min	EN 17333-3
Schneidzeit	ca. 40	min	EN 17333-3
Brandklasse	B2		DIN 4102-1
Gesamtschaumausbeute	bis zu 24	l	EN 17333-1
Rohdichte	25 bis 35	kg/m^3	fugengeschäumt
Druckspannung bei 10 % Stauchung	5	N/cm^2	DIN 53421
Standfestigkeit im Spalt	standfest		
Lagerhaltbarkeit	18	Monate	bei + 18 bis + 20 °C
Verarbeitungstemperatur	+ 5 bis + 35	°C	
Optimale Verarbeitungstemperatur	+ 20	°C	
Temperaturbeständigkeit	- 40 bis + 90	°C	ausgehärteter Schaum
Wärmeleitfähigkeit (λ)	0,0345	W/(m*K)	DIN 52612
Bewertetes Fugenschalldämmmaß	63	dB	
Normen / Prüfungen	Emicode EC 1 Plus		
Treibmittelbasis	HFCKW-frei		
Aushärtung	chemisch durch Reaktion mit Luftfeuchtigkeit		

Anwendungshinweise

Dieser Montageschaum haftet auf allen üblichen Baumaterialien, ausgenommen Polyethylen, Polypropylen, Silikon, Teflon, Öle und Fette, o.ä.. Der ausgehärtete Schaum ist halbhart, elastisch, verrottungsfest, feuchtigkeitsbeständig und alterungsbeständig (vor UV-Strahlung schützen). Die Untergründe müssen fest, sauber, staub- und fettfrei sein.

Vor der Verarbeitung die Untergründe ausreichend mit Wasser befeuchten. Schichtdicken von mehr als 50 mm in mehreren Lagen schäumen und zwischenfeuchten. Zu kalte Dosen vorsichtig im lauwarmen Wasserbad erwärmen. Niemals über 50 °C erhitzen, da sonst Berstgefahr. Zu heiße Dosen im Wasserbad abkühlen.

Gelegentliches Schütteln unterstützt den Temperaturausgleich. Soweit nicht anders angegeben gelten die Angaben bei Standardbedingungen von 23 °C und 50 % r. F. und nicht gealtertem Schaum. Für die Prüfungen Ausbeute und Reaktivität sind mind. 85% r. F. erforderlich (gut vorfeuchten). Bei gealtertem Schaum sinkt die Ausbeute um bis zu 30%. Hierbei verkürzt sich auch die Klebfrei- und Schneidzeit. **Dose vor Gebrauch gut schütteln!**

Weitere Informationen zum Umgang entnehmen Sie bitte dem Sicherheitsdatenblatt; dieses enthält wichtige Hinweise.
Die Anwendungshinweise in diesem technischen Datenblatt sowie unsere anwendungstechnische Beratung in Wort und Schrift erfolgen nach bestem Wissen, beinhalten aber weder Zusagen an die Beschaffenheit oder Verwendbarkeit der Produkte noch selbständige oder unselbständige Garantiezusagen jeglicher Art.
Wir empfehlen vor Verwendung unserer Produkte stets die Eignung für den vorgesehenen Verwendungszweck konkret zu prüfen.
Aufgrund der Vielfalt der Anwendungsmöglichkeiten des einzelnen Produkts und den nicht einschätzbaren Gegebenheiten am Ort der Verarbeitung empfehlen wir darüber hinaus vor Verwendung die Funktion auf den Substraten vor Verwendung zu erproben.

fischerwerke GmbH & Co. KG – Otto-Hahn-Straße 15 – 79211 Denzlingen

Denzlingen, 17. Dezember 2025

Bestätigung fischer Polyurethanschäume

Sehr geehrte Damen und Herren,

hiermit bestätigen wir, dass die unten genannten Polyurethanschäume dem Anforderungskatalog des Qualitätssiegel Nachhaltiges Gebäude (QNG) entsprechen. Diese Produkte sind frei von halogenierten Treibmitteln und Formaldehyd, ebenfalls liegt der Gehalt an TCEP und Chlorparaffinen < 0,1 %. Alle genannten Produkte besitzen Emicode EC1 Plus.

Freundliche Grüße

fischerwerke GmbH & Co. KG
EIN UNTERNEHMEN DER UNTERNEHMENSGRUPPE FISCHER
Abt. Chemisches Labor

i.V. M. Vogel i. A. Y. Herbstritt

Dr. Martin Vogel Yvonne Herbstritt

Firmendaten
Telefon +49 7666 902-0
Telefax +49 7666 902-2929
Website www.fischer.de
GLN 40 06209 00000 7
USt-IDNr. DE 144252337
Anschrift:
Otto-Hahn-Str. 15, 79211 Denzlingen

Sitz
Klaus-Fischer-Straße 1, 72178 Waldachtal, Deutschland
Registergericht Stuttgart HRA440255
Komplementär:
fischerinternational Beteiligungs GmbH, Wiener Straße 95, 2514 Traiskirchen, Österreich
Landesgericht Wiener Neustadt FN 319271 t

Geschäftsführer
Professor E. h. Senator E. h. E. h. Dipl.-Ing. (FH) Klaus Fischer
Andreas Voll (Vorsitzender)
Maximilian Bronner, Dr. Oliver Geibig, Jürgen Grün, Christian Hasenest
Marc-Sven Mengis, Claudia Rothe, Matthias Schneider, Holger Thrun

Bankverbindung
Baden-Württembergische Bank
BLZ 600 501 01, Kto. 4 903 000
IBAN DE98 6005 0101 0004 9030 00
SWIFT SOLADEST600

Art. Nr.	Neue Bezeichnung	Bild
563227	Monomerarmer PU-Schaum PU-P EVO 750 B2	
543453	Flexibler Pistoilenschaum PUP Flex 750 B2	
53084	Premium Pistolenschaum PUP Pro 825 B2	
503259	Premium Pistolenschaum PUP Pro 500 B2	
539197	Pistolenschaum Profi PUP S 750 B2	
40302	Pistolenschaum PUP S 750 B2	
539163	Pistolenschaum Profi PUP S 500 B2	
45300	Pistolenschaum schwer entflammbar PUP HF 750 B1	
513763	Brunnenschaum PUP BS 750 B2	
53080	Premium Schnellmontage- & Brunnenschaum PU Pro 750 B2	
50426	Premium Schnellmontage- & Brunnenschaum PU Pro 500 B2	
40301	Schnellmontageschaum Profi PU S 750 B2	
40300	Schnellmontageschaum PU S 500 B2	
506671	Perimeterklebeschaum PUP P 750 B2	
539164	WDVS Klebeschaum PUP WDVS 750	
53081	Schnellschaum Türzarge & Wanne PU 2K 400 B2	

Materialprüfanstalt Hannover
Bauwesen und Produktionstechnik

Allgemeines bauaufsichtliches Prüfzeugnis

Prüfzeugnisnummer: P - NDS04 - 136

Gegenstand: Montageschäume „PU S 500 B2“, „PU S 750 B2“, „PU 500 B2“ und „PU 750 B2“
gemäß der
Niedersächsischen Verwaltungsvorschrift Technische Baubestimmungen (VV TB) - Fassung März 2022 - Lfd. Nr. C 3.2
als normalentflammbarer Baustoff (Baustoffklasse B2)
nach DIN 4102-1: 1998-05

Antragsteller: fischerwerke GmbH & Co. KG
Klaus-Fischer-Straße 1
72178 Waldachtal
DEUTSCHLAND

Ausstellungsdatum: 17.08.2022
Geltungsdauer von: 01.07.2022
Geltungsdauer bis: 31.05.2027

Aufgrund dieses allgemeinen bauaufsichtlichen Prüfzeugnisses ist der oben genannte Gegenstand im Sinne der Landesbauordnungen verwendbar*).

Dieses allgemeine bauaufsichtliche Prüfzeugnis umfasst 4 Seiten.

Auftragsnummer: 224424

*) Dieses allgemeine bauaufsichtliche Prüfzeugnis ersetzt das allgemeine bauaufsichtliche Prüfzeugnis Nr. P-NDS04-136 vom 12.10.2017. Dem Gegenstand ist erstmals am 30.08.1999 eine Prüfzeugnisnummer zugeteilt worden.

Materialprüfanstalt für das Bauwesen und Produktionstechnik
Nienburger Straße 3 · 30167 Hannover
Bearbeiterin L. Wagner, M. Sc.
Direkt +49 511 762-2586
E-Mail wagner@mpa-hannover.de
Internet www.mpa-hannover.de

Niedersachsen
Notifizierte Stelle 0764

A Allgemeine Bestimmungen

Mit dem allgemeinen bauaufsichtlichen Prüfzeugnis ist die Verwendbarkeit der Bauprodukte im Sinne der Landesbauordnungen nachgewiesen.

Das allgemeine bauaufsichtliche Prüfzeugnis ersetzt nicht die für die Durchführung von Bauvorhaben gesetzlich vorgeschriebenen Genehmigungen, Zustimmungen und Bescheinigungen.

Das allgemeine bauaufsichtliche Prüfzeugnis wird unbeschadet der Rechte Dritter, insbesondere privater Schutzrechte, erteilt.

Hersteller und Vertreiber der Bauprodukte haben, unbeschadet weitergehender Regelungen, dem Verwender der Bauprodukte Kopien des allgemeinen bauaufsichtlichen Prüfzeugnisses zur Verfügung zu stellen und darauf hinzuweisen, dass das allgemeine bauaufsichtliche Prüfzeugnis an der Verwendungsstelle vorliegen muss. Auf Anforderung sind den beteiligten Behörden Kopien des allgemeinen bauaufsichtlichen Prüfzeugnisses zur Verfügung zu stellen.

Das allgemeine bauaufsichtliche Prüfzeugnis darf nur vollständig vervielfältigt werden. Eine auszugsweise Veröffentlichung bedarf der Zustimmung der Materialprüfanstalt für das Bauwesen und Produktionstechnik Hannover (MPA HANNOVER). Texte und Zeichnungen von Werbeschriften dürfen dem allgemeinen bauaufsichtlichen Prüfzeugnis nicht widersprechen. Übersetzungen des allgemeinen bauaufsichtlichen Prüfzeugnisses müssen den Hinweis „Von der Materialprüfanstalt für das Bauwesen und Produktionstechnik Hannover nicht geprüfte Übersetzung der deutschen Originalfassung“ enthalten.

Das allgemeine bauaufsichtliche Prüfzeugnis wird widerruflich erteilt. Die Bestimmungen des allgemeinen bauaufsichtlichen Prüfzeugnisses können nachträglich ergänzt und geändert werden, insbesondere, wenn technische Erkenntnisse dies erfordern.

B Besondere Bestimmungen

1 Gegenstand und Verwendungsbereich

1.1 Gegenstand

Montageschäume „PU S 500 B2“, „PU S 750 B2“, „PU 500 B2“ und „PU 750 B2“ als normalentflammbare Baustoffe (Baustoffklasse DIN 4102-B2) nach DIN 4102-1: 1998-05 gemäß VV TB - Fassung März 2022 - Lfd. Nr. C 3.2.

1.2 Verwendungsbereich

1.2.1 Die Bauprodukte sind zur Montage und technischen Isolierung von Bauteilen sowie zum Füllen von Fugen und Hohlräumen zu verwenden.

1.2.2 Dieses allgemeine bauaufsichtliche Prüfzeugnis gilt nur, soweit Anforderungen gemäß VV TB - Fassung März 2022 - Lfd. Nr. C 3.2 zu erfüllen sind. Der Nachweis weiterer bauaufsichtlicher Anforderungen ist nicht Gegenstand dieses allgemeinen bauaufsichtlichen Prüfzeugnisses. Gegebenenfalls sind hierfür weitere / andere Nachweise erforderlich.



2 Bestimmungen für die Bauprodukte

2.1 Eigenschaften und Zusammensetzung

2.1.1 Die 1-komponentigen Adapterschäume müssen aus Polyurethan hergestellt werden. Die Rohdichte muss ca. 21 kg/m^3 betragen.

2.1.2 Die Bauprodukte müssen im eingebauten Zustand die Anforderungen an normalentflammbare Baustoffe (Baustoffklasse DIN 4102-B2) nach DIN 4102-1: 1998-05 erfüllen.

2.1.3 Die Zusammensetzung der Bauprodukte muss den bei der Materialprüfanstalt für das Bauwesen und Produktionstechnik Hannover hinterlegten Angaben entsprechen.

2.1.4 Die für die Erteilung des allgemeinen bauaufsichtlichen Prüfzeugnisses verwendeten Nachweise des Brandverhaltens sind bei der MPA HANNOVER hinterlegt.

2.2 Herstellung und Kennzeichnung

2.2.1 Herstellung

Bei der Herstellung der Bauprodukte sind die Bestimmungen der Abschnitte 2.1.1 bis 2.1.3 einzuhalten.

2.2.2 Kennzeichnung

Die Bauprodukte müssen vom Hersteller mit dem Übereinstimmungszeichen (Ü-Zeichen) nach den Übereinstimmungszeichen-Verordnungen der Länder gekennzeichnet werden. Die Kennzeichnung darf nur erfolgen, wenn die Voraussetzungen nach Abschnitt 3 erfüllt sind.

Folgende Angaben müssen auf dem Bauprodukt, der Verpackung oder dem Beipackzettel enthalten sein:

- Produktname
- Name des Herstellers
- Übereinstimmungszeichen (Ü-Zeichen) mit
  - Herstellwerk
  - Prüfzeugnisnummer
- Baustoffklasse normalentflammbar (DIN 4102-B2)

3 Übereinstimmungsnachweis

3.1 Allgemeines

Die Bestätigung der Übereinstimmung der Bauprodukte mit den Bestimmungen des allgemeinen bauaufsichtlichen Prüfzeugnisses muss für jedes Herstellwerk mit einer Übereinstimmungserklärung des Herstellers auf der Grundlage einer Erstprüfung und einer werkseigenen Produktionskontrolle erfolgen.



3.2 Werkseigene Produktionskontrolle

In jedem Herstellwerk ist eine werkseigene Produktionskontrolle nach DIN 18200: 2018-09 einzurichten und durchzuführen, bei welcher durch eine vom Hersteller vorzunehmende kontinuierliche Überwachung der Produktion sichergestellt wird, dass die Bauprodukte den Bestimmungen des allgemeinen bauaufsichtlichen Prüfzeugnisses entsprechen.

Die Ergebnisse der werkseigenen Produktionskontrolle sind aufzuzeichnen und auszuwerten. Die Aufzeichnungen müssen mindestens folgende Angaben enthalten:
- Bezeichnung des Bauprodukts
- Art der Kontrolle
- Datum der Herstellung und der Kontrolle des Bauprodukts
- Ergebnis der Kontrollen und, soweit zutreffend, Vergleich mit den Anforderungen
- Unterschrift des für die werkseigene Produktionskontrolle Verantwortlichen.

Die Aufzeichnungen über die werkseigene Produktionskontrolle müssen mindestens fünf Jahre aufbewahrt und der für die Fremdüberwachung eingeschalteten Überwachungsstelle vorgelegt werden. Bei ungenügendem Kontrollergebnis sind vom Hersteller unverzüglich die erforderlichen Maßnahmen zur Abstellung des Mangels zu treffen und die betroffenen Produkte auszusondern. Im Rahmen der werkseigenen Produktionskontrolle ist sicherzustellen, dass Bauprodukte, die nicht den Anforderungen entsprechen, nicht mit dem Ü-Zeichen gekennzeichnet werden und Verwechselungen mit Übereinstimmenden ausgeschlossen sind. Nach Abstellung des Mangels ist die betreffende Kontrolle unverzüglich zu wiederholen.

4 Rechtsgrundlage

Dieses allgemeine bauaufsichtliche Prüfzeugnis wird aufgrund des § 19 der Niedersächsischen Bauordnung (NBauO) in der Fassung vom 03.04.2012 (Nds. GVBl. Nr. 5/2012, S. 46-73) zuletzt geändert durch das Gesetz zur Änderung der Niedersächsischen Bauordnung vom 10.11.2020 (Nds. GVBl. S. 384) in Verbindung mit der Verwaltungsvorschrift Technische Baubestimmungen (VV TB) gemäß RdErl. d. MU vom 01.04.2022 (Nds. MBl. Nr. 14/2022, S. 508-553) erteilt.

5 Rechtsbehelfsbelehrung

Gegen dieses allgemeine bauaufsichtliche Prüfzeugnis kann innerhalb eines Monats nach Ausstellung Widerspruch erhoben werden. Der Widerspruch ist schriftlich oder zur Niederschrift bei der Materialprüfanstalt für das Bauwesen und Produktionstechnik Hannover einzulegen.

Hannover, 17.08.2022

Leitung der Prüfstelle nach LBO

(Dipl.-Ing. S. Suhr)

Materialprüfanstalt für das Bauwesen und Produktionstechnik · Hannover ·

Sachbearbeitung

(L. Wagner, M. Sc.)

Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e.V.
Association for the Control of Emissions from Products for Flooring Installation, Adhesives and Building Materials

GEV EMICODE®

Awarding of licence for the use of EMICODE

Licence Number:	15385/25.04.13
For the product	Fischer PU 750 B2
Due to application date	22.07.2022

With reference to the classification in accordance with the directives as stipulated in § 10 of the GEV trademark constitution

on behalf of the GEV for the above mentioned product as per § 5, section 4 of the GEV trademark constitution is awarded the licence for the use of the GEV trademark



This product meets with the guidelines for the criteria of use listed reverse.
The company is ordinary member of the GEV.

OM094 25.07.2022
valid until 25.07.2027

The Secretary General
Association for the Control of Emissions in Products for Flooring Installation, Adhesives and Building Materials (GEV)
Völklinger Straße 4 · D-40219 Düsseldorf

Requirement guidelines for the awarding of the EMICODE licence

The product mentioned on the front side of the licence has to fulfil among others the following criteria in accordance with the Constitution and the guidelines of the Technical Advisory Board of the GEV:

- The product meets all the legal requirements, especially the chemical laws and their specifications.
- The product is solvent free as specified in clause 2.4 of the “GEV Classification Criteria”, except if it is a surface treatment product. If the product is assigned to a GISCODE product group then this can be labelled.
- A safety data sheet (SDS) according to local law in its respectively valid version is issued for the product.
- Carcinogenic, mutagenic, reprotoxic substances of the categories 1A or 1B are not added during the manufacture of the product.
- The testing of the product is performed in accordance with the GEV Testing Method. VOC determination is performed in a test chamber followed by the Tenax / thermal desorption procedures with subsequent GC/MS analysis.
- The assignment of an EMICODE class is performed according to the following criteria and TVOC/TSVOC concentration levels. The corresponding EMICODE class shall be used to label the product:

1) Installation products, adhesives and construction products

Parameter	EC 1 PLUS	EC 1	EC 2
	max. allowed concentration [µg/m³]		
TVOC after 3 days	≤ 750	≤ 1000	≤ 3000
TVOC after 28 days	≤ 60	≤ 100	≤ 300
TSVOC after 28 days	≤ 40	≤ 50	≤ 100
R value based on German AgBB LCI (NIK) after 28 days	1	-	-
Sum of non-assessable VOC	≤ 40	-	-
Formaldehyde after 3 days	≤ 50	≤ 50	≤ 50
Acetaldehyde after 3 days	≤ 50	≤ 50	≤ 50
Sum of form- and acetaldehyde	≤ 0.05 ppm	≤ 0.05 ppm	≤ 0.05 ppm
Sum of volatile C1A/C1B after 3 days	≤ 10	≤ 10	≤ 10
Any volatile C1A/C1B after 28 days	≤ 1	≤ 1	≤ 1

2) Products for floor surface treatments for parquet, mineral floors and resilient floorings

Parameter	EC 1 PLUS	EC 1	EC 2
	max. allowed concentration [µg/m³]		
Sum TVOC + TSVOC after 28 days	≤ 100 thereof max. 40 SVOC	≤ 150 thereof max. 50 SVOC	≤ 450 thereof max. 100 SVOC
Formaldehyde after 3 days	≤ 50	≤ 50	≤ 50
Acetaldehyde after 3 days	≤ 50	≤ 50	≤ 50
Any volatile C1A/C1B after 3 days	≤ 10	≤ 10	≤ 10
Any volatile C1A/C1B after 28 days	≤ 1	≤ 1	≤ 1

Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e.V.
Association for the Control of Emissions from Products for Flooring Installation, Adhesives and Building Materials

GEV EMICODE®

Awarding of licence for the use of EMICODE

Licence Number:	15383/25.04.13
For the product	Fischer PU S 750 B2
Due to application date	22.07.2022

With reference to the classification in accordance with the directives as stipulated in § 10 of the GEV trademark constitution

on behalf of the GEV for the above mentioned product as per § 5, section 4 of the GEV trademark constitution is awarded the licence for the use of the GEV trademark



This product meets with the guidelines for the criteria of use listed reverse.
The company is ordinary member of the GEV.

OM094 25.07.2022
valid until 25.07.2027

The Secretary General
Association for the Control of Emissions in Products for Flooring Installation, Adhesives and Building Materials (GEV)
Völklinger Straße 4 · D-40219 Düsseldorf

Requirement guidelines for the awarding of the EMICODE licence

The product mentioned on the front side of the licence has to fulfil among others the following criteria in accordance with the Constitution and the guidelines of the Technical Advisory Board of the GEV:

- The product meets all the legal requirements, especially the chemical laws and their specifications.
- The product is solvent free as specified in clause 2.4 of the “GEV Classification Criteria”, except if it is a surface treatment product. If the product is assigned to a GISCODE product group then this can be labelled.
- A safety data sheet (SDS) according to local law in its respectively valid version is issued for the product.
- Carcinogenic, mutagenic, reprotoxic substances of the categories 1A or 1B are not added during the manufacture of the product.
- The testing of the product is performed in accordance with the GEV Testing Method. VOC determination is performed in a test chamber followed by the Tenax / thermal desorption procedures with subsequent GC/MS analysis.
- The assignment of an EMICODE class is performed according to the following criteria and TVOC/TSVOC concentration levels. The corresponding EMICODE class shall be used to label the product:

1) Installation products, adhesives and construction products

Parameter	EC 1 PLUS	EC 1	EC 2
	max. allowed concentration [µg/m³]		
TVOC after 3 days	≤ 750	≤ 1000	≤ 3000
TVOC after 28 days	≤ 60	≤ 100	≤ 300
TSVOC after 28 days	≤ 40	≤ 50	≤ 100
R value based on German AgBB LCI (NIK) after 28 days	1	-	-
Sum of non-assessable VOC	≤ 40	-	-
Formaldehyde after 3 days	≤ 50	≤ 50	≤ 50
Acetaldehyde after 3 days	≤ 50	≤ 50	≤ 50
Sum of form- and acetaldehyde	≤ 0.05 ppm	≤ 0.05 ppm	≤ 0.05 ppm
Sum of volatile C1A/C1B after 3 days	≤ 10	≤ 10	≤ 10
Any volatile C1A/C1B after 28 days	≤ 1	≤ 1	≤ 1

2) Products for floor surface treatments for parquet, mineral floors and resilient floorings

Parameter	EC 1 PLUS	EC 1	EC 2
	max. allowed concentration [µg/m³]		
Sum TVOC + TSVOC after 28 days	≤ 100 thereof max. 40 SVOC	≤ 150 thereof max. 50 SVOC	≤ 450 thereof max. 100 SVOC
Formaldehyde after 3 days	≤ 50	≤ 50	≤ 50
Acetaldehyde after 3 days	≤ 50	≤ 50	≤ 50
Any volatile C1A/C1B after 3 days	≤ 10	≤ 10	≤ 10
Any volatile C1A/C1B after 28 days	≤ 1	≤ 1	≤ 1

Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e.V.
Association for the Control of Emissions from Products for Flooring Installation, Adhesives and Building Materials

GEV EMICODE®

Awarding of licence for the use of EMICODE

Licence Number:	15384/25.04.13
For the product	Fischer PU S 500 B2
Due to application date	22.07.2022

With reference to the classification in accordance with the directives as stipulated in § 10 of the GEV trademark constitution

on behalf of the GEV for the above mentioned product as per § 5, section 4 of the GEV trademark constitution is awarded the licence for the use of the GEV trademark



This product meets with the guidelines for the criteria of use listed reverse.
The company is ordinary member of the GEV.

OM094 25.07.2022
valid until 25.07.2027

The Secretary General
Association for the Control of Emissions in Products for Flooring Installation, Adhesives and Building Materials (GEV)
Völklinger Straße 4 · D-40219 Düsseldorf

Requirement guidelines for the awarding of the EMICODE licence

The product mentioned on the front side of the licence has to fulfil among others the following criteria in accordance with the Constitution and the guidelines of the Technical Advisory Board of the GEV:

- The product meets all the legal requirements, especially the chemical laws and their specifications.
- The product is solvent free as specified in clause 2.4 of the “GEV Classification Criteria”, except if it is a surface treatment product. If the product is assigned to a GISCODE product group then this can be labelled.
- A safety data sheet (SDS) according to local law in its respectively valid version is issued for the product.
- Carcinogenic, mutagenic, reprotoxic substances of the categories 1A or 1B are not added during the manufacture of the product.
- The testing of the product is performed in accordance with the GEV Testing Method. VOC determination is performed in a test chamber followed by the Tenax / thermal desorption procedures with subsequent GC/MS analysis.
- The assignment of an EMICODE class is performed according to the following criteria and TVOC/TSVOC concentration levels. The corresponding EMICODE class shall be used to label the product:

1) Installation products, adhesives and construction products

Parameter	EC 1 PLUS	EC 1	EC 2
	max. allowed concentration [µg/m³]		
TVOC after 3 days	≤ 750	≤ 1000	≤ 3000
TVOC after 28 days	≤ 60	≤ 100	≤ 300
TSVOC after 28 days	≤ 40	≤ 50	≤ 100
R value based on German AgBB LCI (NIK) after 28 days	1	-	-
Sum of non-assessable VOC	≤ 40	-	-
Formaldehyde after 3 days	≤ 50	≤ 50	≤ 50
Acetaldehyde after 3 days	≤ 50	≤ 50	≤ 50
Sum of form- and acetaldehyde	≤ 0.05 ppm	≤ 0.05 ppm	≤ 0.05 ppm
Sum of volatile C1A/C1B after 3 days	≤ 10	≤ 10	≤ 10
Any volatile C1A/C1B after 28 days	≤ 1	≤ 1	≤ 1

2) Products for floor surface treatments for parquet, mineral floors and resilient floorings

Parameter	EC 1 PLUS	EC 1	EC 2
	max. allowed concentration [µg/m³]		
Sum TVOC + TSVOC after 28 days	≤ 100 thereof max. 40 SVOC	≤ 150 thereof max. 50 SVOC	≤ 450 thereof max. 100 SVOC
Formaldehyde after 3 days	≤ 50	≤ 50	≤ 50
Acetaldehyde after 3 days	≤ 50	≤ 50	≤ 50
Any volatile C1A/C1B after 3 days	≤ 10	≤ 10	≤ 10
Any volatile C1A/C1B after 28 days	≤ 1	≤ 1	≤ 1

Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e.V.
Association for the Control of Emissions from Products for Flooring Installation, Adhesives and Building Materials

GEV EMICODE®

Awarding of licence for the use of EMICODE

Licence Number:	15386/25.04.13
For the product	Fischer PU 500 B2
Due to application date	22.07.2022

With reference to the classification in accordance with the directives as stipulated in § 10 of the GEV trademark constitution

on behalf of the GEV for the above mentioned product as per § 5, section 4 of the GEV trademark constitution is awarded the licence for the use of the GEV trademark



This product meets with the guidelines for the criteria of use listed reverse.
The company is ordinary member of the GEV.

OM094 25.07.2022
valid until 25.07.2027

The Secretary General
Association for the Control of Emissions in Products for Flooring Installation, Adhesives and Building Materials (GEV)
Völklinger Straße 4 · D-40219 Düsseldorf

Requirement guidelines for the awarding of the EMICODE licence

The product mentioned on the front side of the licence has to fulfil among others the following criteria in accordance with the Constitution and the guidelines of the Technical Advisory Board of the GEV:

- The product meets all the legal requirements, especially the chemical laws and their specifications.
- The product is solvent free as specified in clause 2.4 of the “GEV Classification Criteria”, except if it is a surface treatment product. If the product is assigned to a GISCODE product group then this can be labelled.
- A safety data sheet (SDS) according to local law in its respectively valid version is issued for the product.
- Carcinogenic, mutagenic, reprotoxic substances of the categories 1A or 1B are not added during the manufacture of the product.
- The testing of the product is performed in accordance with the GEV Testing Method. VOC determination is performed in a test chamber followed by the Tenax / thermal desorption procedures with subsequent GC/MS analysis.
- The assignment of an EMICODE class is performed according to the following criteria and TVOC/TSVOC concentration levels. The corresponding EMICODE class shall be used to label the product:

1) Installation products, adhesives and construction products

Parameter	EC 1 PLUS	EC 1	EC 2
	max. allowed concentration [µg/m³]		
TVOC after 3 days	≤ 750	≤ 1000	≤ 3000
TVOC after 28 days	≤ 60	≤ 100	≤ 300
TSVOC after 28 days	≤ 40	≤ 50	≤ 100
R value based on German AgBB LCI (NIK) after 28 days	1	-	-
Sum of non-assessable VOC	≤ 40	-	-
Formaldehyde after 3 days	≤ 50	≤ 50	≤ 50
Acetaldehyde after 3 days	≤ 50	≤ 50	≤ 50
Sum of form- and acetaldehyde	≤ 0.05 ppm	≤ 0.05 ppm	≤ 0.05 ppm
Sum of volatile C1A/C1B after 3 days	≤ 10	≤ 10	≤ 10
Any volatile C1A/C1B after 28 days	≤ 1	≤ 1	≤ 1

2) Products for floor surface treatments for parquet, mineral floors and resilient floorings

Parameter	EC 1 PLUS	EC 1	EC 2
	max. allowed concentration [µg/m³]		
Sum TVOC + TSVOC after 28 days	≤ 100 thereof max. 40 SVOC	≤ 150 thereof max. 50 SVOC	≤ 450 thereof max. 100 SVOC
Formaldehyde after 3 days	≤ 50	≤ 50	≤ 50
Acetaldehyde after 3 days	≤ 50	≤ 50	≤ 50
Any volatile C1A/C1B after 3 days	≤ 10	≤ 10	≤ 10
Any volatile C1A/C1B after 28 days	≤ 1	≤ 1	≤ 1