Product Information



tesa® Powerstrips Strips Transparent Large

BNR 58810

Product Features

• Transparent for unobtrusive fixation * Maximum hold of up to 1 kg on smooth surfaces* * Removable without trace thanks to the Powerstrips® technology * Limited UV-resistance (e.g. seasonal decoration) *Not suitable for use on styrofoam, foamed material, surfaces with non-sticking coating, porous materials

Product Description

tesa Powerstrips Transparent Large are self-adhesive double-sided strips perfectly suited for the unobtrusive fixation of transparent objects.

Application Fields

How to apply - Step by step:

- 1. Clean the surface with alcohol or silicone-free glass cleaner
- 2. Apply the tesa Powerstrips® Transparent DECO Large strip on the surface press for 5 seconds minimum
- 3. Fix object onto surface press for 5 seconds minimum
- 4. Make sure the tab can be accessed for removal

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

Type of adhesiveHolding power of strip up to	synthetic rubber 1 Kg	Total thickness	650 μm
Properties/Performance Values			
Ageing resistance (UV)Application temperatureApplicationfield	yes 15 °C Kitchen, Living room, Children's room, Office, Hall	Residue free removalSolvent freeSuitable surfaces	yes yes Even wood, Tiles, Most plastics, Glass, Acrylic glass, Steel
Area of useChemical resistanceHazard materialHumidity resistance	Indoor no no no	Temperature resistance max.Temperature resistance min.UV resistantWater resistance	35 °C 5 °C yes no
 Oil and grease resistance 	no	 Waterproof 	no

Ozone resistance yes

For latest information on this product please visit http://l.tesa.com/?ip=NaN **Product Information**



tesa® Powerstrips Strips Transparent Large

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

